

Московский Авиационный Институт
(Национальный Исследовательский Университет)

Кафедра 806 «Вычислительная информатика и программирование»
Факультет: «Информационные технологии и прикладная математика»

Лабораторная работа
Дисциплина: «Объектно-ориентированное программирование»
I I семестр
Задание 3: «Наследование, полиморфизм»

Группа:	М8О-208Б-18, №3
Студент:	Анисимов Валерий Алексеевич
Преподаватель:	Журавлёв Андрей Андреевич
Оценка:	
Дата:	27.10.2019

Москва, 2019

1. **Тема:** Наследование, полиморфизм

2. **Цель работы:** Изучение механизмов работы с наследованием в C++

3. **Задание (вариант № 3):**

Разработать классы согласно варианту задания. Классы должны наследоваться от базового класса Figure. Фигуры являются фигурами вращения. Все классы должны поддерживать общий набор методов:

- Вычисление геометрического центра фигуры
- Вывод в стандартный поток std::cout координат вершин фигуры
- Вычисление площади фигуры

Создать программу, которая позволяет:

- Вводить из стандартного ввода std::cin фигуры, согласно варианту задания
- Сохранять созданные фигуры в динамический массив std::vector<Figure*>
- Вызывать для всего массива общие функции (1 — 3)
- Необходимо уметь вычислять общую площадь фигур в массиве
- Удалять из массива фигуру по индексу

Фигуры (Вариант 3):

Прямоугольник, трапеция, ромб.

4. **Адрес репозитория на GitHub** https://github.com/wAlienUFOx/oop_exercise_03

5. **Код программы на C++**

main.cpp

```
#include <iostream>
#include "figure.h"
#include "rhombus.h"
#include "trapeze.h"
#include "rectangle.h"
#include <vector>
#include <string>
```

```
void read_fig(std::vector<Figure*>& fig)
```

```
{
    int figt;
    Trapeze *t = nullptr;
    Rhombus *rh = nullptr;
    Rectangle *re = nullptr;
```

```
    std::cout << "Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle\n";
```

```
    std::cin >> figt;
```

```
    switch (figt) {
```

```
    case 1:
```

```
        try{
```

```
            t = new Trapeze(std::cin);
```

```
        } catch(std::logic_error& err){
```

```
            std::cout << err.what() << std::endl;
```

```
            break;
```

```
        }
```

```
        fig.push_back(dynamic_cast<Figure*>(t));
```

```
        break;
```

```
    case 2:
```

```
        try{
```

```
            rh = new Rhombus(std::cin);
```

```
        } catch(std::logic_error& err){
```

```

        std::cout << err.what() << std::endl;
        break;
    }
    fig.push_back(dynamic_cast<Figure*>(rh));
    break;
case 3:
    try {
        re = new Rectangle(std::cin);
    } catch(std::logic_error& err){
        std::cout << err.what() << std::endl;
        break;
    }
    fig.push_back(dynamic_cast<Figure*>(re));
    break;
default:
    std::cout << "Wrong. Try 1 - trapeze, 2 - rhombus or 3 - rectangle\n";
}
}

```

```

void Tut(){
    std::cout << "      2      3      2      2 3\n";
    std::cout << "      *          *      *\n";
    std::cout << "      *          ***      *\n";
    std::cout << "      *          1*          3 *\n";
    std::cout << "      *          ***      *\n";
    std::cout << "      *          *      *\n";
    std::cout << " 1          4 4      1 4\n";
}

```

```

int main(){
    unsigned int index;
    double Tarea = 0;
    std::string operation;
    std::vector<Figure*> fig;
    Tut();
    std::cout << "Operations: add / delete / out / quit\n";

```

```

    while (std::cin >> operation) {
        if (operation == "add") {
            read_fig(fig);
        }
        else if (operation == "delete") {
            std::cin >> index;
            delete fig[index];
            for (; index < fig.size() - 1; ++index) {
                fig[index] = fig[index + 1];
            }
            fig.pop_back();
        }
        else if (operation == "out") {
            Tarea = 0;
            for (unsigned int i = 0; i < fig.size(); i++) {

```

```

std::cout << i << "\n";
std::cout << "Area: " << fig[i]->area() << std::endl;
std::cout << "Center: " << fig[i]->center() << std::endl;
std::cout << "Coordinates: ";
fig[i]->print(std::cout);
std::cout << std::endl;
Tarea += fig[i]->area();
}
std::cout << "Total area: " << Tarea << std::endl;
}
else if (operation == "quit"){
    for (unsigned int i = 0; i < fig.size(); ++i) {
        delete fig[i];
    }
    return 0;
}
else {
    std::cout << "Wrong. Operations: add / delete / out / quit\n";
}
}
}

```

point.h

```

#ifndef POINT_H
#define POINT_H

#include <iostream>

class Point {
public:
    Point();
    Point(double x, double y);
    double X() const;
    double Y() const;
    friend std::ostream& operator<< (std::ostream& out, const Point& p);
    friend std::istream& operator>> (std::istream& in, Point& p);
private:
    double x;
    double y;
};

```

#endif

point.cpp

```

#include "point.h"
#include <cmath>

Point::Point() : x{0}, y{0}

```

```

{}

Point::Point(double x, double y) : x{x}, y{y}
{}

double Point::X() const
{
    return x;
}

double Point::Y() const
{
    return y;
}

std::ostream& operator<< (std::ostream& out, const Point& p)
{
    out << "(" << p.X() << ";" << p.Y() << ")";
    return out;
}

std::istream& operator>> (std::istream& in, Point& p)
{
    in >> p.x >> p.y;
    return in;
}

```

figure.h

```

#ifndef FIGURE_H
#define FIGURE_H

#include <iostream>
#include "point.h"

class Figure {
public:
    virtual double area() const = 0;
    virtual Point center() const = 0;
    virtual std::ostream& print(std::ostream& out) const = 0;
    virtual ~Figure() = default;
};

#endif

```

figure.cpp

```

#include "figure.h"

```

rhombus.h

```
#ifndef RHOMBUS_H
#define RHOMBUS_H

#include "figure.h"
#include "point.h"

class Rhombus : public Figure {
public:
    Rhombus();
    Rhombus(std::istream& in);
    double area() const override;
    Point center() const override;
    std::ostream& print(std::ostream& out) const override;
private:
    Point A;
    Point B;
    Point C;
    Point D;
};

#endif

#endif
```

rhombus.cpp

```
#include "rhombus.h"
#include <cmath>

Rhombus::Rhombus() : A{0, 0}, B{0, 0}, C{0, 0}, D{0,0} {}
Rhombus::Rhombus(std::istream& in) {
    in >> A >> B >> C >> D;
    double a, b, c, d;
    a = sqrt((B.X() - A.X()) * (B.X() - A.X()) + (B.Y() - A.Y()) * (B.Y() - A.Y()));
    b = sqrt((C.X() - B.X()) * (C.X() - B.X()) + (C.Y() - B.Y()) * (C.Y() - B.Y()));
    c = sqrt((C.X() - D.X()) * (C.X() - D.X()) + (C.Y() - D.Y()) * (C.Y() - D.Y()));
    d = sqrt((D.X() - A.X()) * (D.X() - A.X()) + (D.Y() - A.Y()) * (D.Y() - A.Y()));
    if(a != b || a != c || a != d)
        throw std::logic_error("It`s not a rhombus");
}

double Rhombus::area() const{
    double d1 = sqrt((C.X() - A.X()) * (C.X() - A.X()) + (C.Y() - A.Y()) * (C.Y() - A.Y()));
    double d2 = sqrt((B.X() - D.X()) * (B.X() - D.X()) + (B.Y() - D.Y()) * (B.Y() - D.Y()));
    return d1 * d2 / 2;
}

Point Rhombus::center() const
{
```

```

    return Point{(A.X() + B.X() + C.X() + D.X()) / 4, (A.Y() + B.Y() + C.Y() + D.Y()) / 4};
}

std::ostream& Rhombus::print(std::ostream& out) const
{
    out << A << " " << B << " " << C << " " << D;
    return out;
}

```

rectangle.h

```

#ifndef RECTNAGLE_H
#define RECTNAGLE_H

```

```

#include "figure.h"
#include "point.h"

```

```

class Rectangle : public Figure {
public:
    Rectangle();
    Rectangle(std::istream& in);
    double area() const override;
    Point center() const override;
    std::ostream& print(std::ostream& out) const override;
private:
    Point A;
    Point B;
    Point C;
    Point D;
};

```

```

#endif
rectangle.cpp

```

```

#include "rectangle.h"
#include <cmath>

```

```

Rectangle::Rectangle() : A{0, 0}, B{0, 0}, C{0,0}, D{0,0} {}

```

```

Rectangle::Rectangle(std::istream& in) {
    in >> A >> B >> C >> D;
    double a, b, c, d, d1, d2, ABC, BCD, CDA, DAB;
    a = sqrt((B.X() - A.X()) * (B.X() - A.X()) + (B.Y() - A.Y()) * (B.Y() - A.Y()));
    b = sqrt((C.X() - B.X()) * (C.X() - B.X()) + (C.Y() - B.Y()) * (C.Y() - B.Y()));
    c = sqrt((C.X() - D.X()) * (C.X() - D.X()) + (C.Y() - D.Y()) * (C.Y() - D.Y()));
    d = sqrt((D.X() - A.X()) * (D.X() - A.X()) + (D.Y() - A.Y()) * (D.Y() - A.Y()));
    d1 = sqrt((B.X() - D.X()) * (B.X() - D.X()) + (B.Y() - D.Y()) * (B.Y() - D.Y()));
    d2 = sqrt((C.X() - A.X()) * (C.X() - A.X()) + (C.Y() - A.Y()) * (C.Y() - A.Y()));
    ABC = (a * a + b * b - d2 * d2) / 2 * a * b;
    BCD = (b * b + c * c - d1 * d1) / 2 * b * c;
    CDA = (d * d + c * c - d2 * d2) / 2 * d * c;
    DAB = (a * a + d * d - d1 * d1) / 2 * a * d;
}

```

```

    if(ABC != BCD || ABC != CDA || ABC != DAB)
        throw std::logic_error("It`s not a rectangle");
}

double Rectangle::area() const{
    double a = sqrt((B.X() - A.X()) * (B.X() - A.X()) + (B.Y() - A.Y()) * (B.Y() - A.Y()));
    double b = sqrt((C.X() - B.X()) * (C.X() - B.X()) + (C.Y() - B.Y()) * (C.Y() - B.Y()));
    return a * b;
}

Point Rectangle::center() const{
    return Point{(A.X() + B.X() + C.X() + D.X()) / 4, (A.Y() + B.Y() + C.Y() + D.Y()) / 4};
}

std::ostream& Rectangle::print(std::ostream& out) const{
    out << A << " " << B << " " << C << " " << D;
    return out;
}

```

trapeze.h

```

#ifndef TRAPEZE_H
#define TRAPEZE_H

#include "figure.h"
#include "point.h"

class Trapeze : public Figure {
public:
    Trapeze();
    Trapeze(std::istream& in);
    double area() const override;
    Point center() const override;
    std::ostream& print(std::ostream& out) const override;
private:
    Point A;
    Point B;
    Point C;
    Point D;
};
#endif

```

trapeze.cpp

```

#include "trapeze.h"
#include <cmath>

Trapeze::Trapeze() : A{0, 0}, B{0, 0}, C{0, 0}, D{0,0} {}

Trapeze::Trapeze(std::istream& in) {
    in >> A >> B >> C >> D;
    double a, b, c, d;
}

```



```

a = sqrt((B.X() - A.X()) * (B.X() - A.X()) + (B.Y() - A.Y()) * (B.Y() - A.Y()));
c = sqrt((C.X() - D.X()) * (C.X() - D.X()) + (C.Y() - D.Y()) * (C.Y() - D.Y()));
if(a != c || (C.Y() - B.Y()) / (C.X() - B.X()) != (D.Y() - A.Y()) / (D.X() - A.X()))
    throw std::logic_error("It's not a isosceles trapeze");
}

double Trapeze::area() const{
    double a = sqrt((C.X() - B.X()) * (C.X() - B.X()) + (B.Y() - C.Y()) * (B.Y() - C.Y()));
    double b = sqrt((B.X() - A.X()) * (B.X() - A.X()) + (B.Y() - A.Y()) * (B.Y() - A.Y()));
    double l = sqrt((D.X() - A.X()) * (D.X() - A.X()) + (A.Y() - D.Y()) * (A.Y() - D.Y()));
    double c = (l - a) / 2;
    double h = sqrt((b * b) - (c * c));
    return 0.5 * h * (a + l);
}

Point Trapeze::center() const
{
    double a = sqrt((C.X() - B.X()) * (C.X() - B.X()) + (B.Y() - C.Y()) * (B.Y() - C.Y()));
    double b = sqrt((B.X() - A.X()) * (B.X() - A.X()) + (B.Y() - A.Y()) * (B.Y() - A.Y()));
    double l = sqrt((D.X() - A.X()) * (D.X() - A.X()) + (A.Y() - D.Y()) * (A.Y() - D.Y()));
    double c = (l - a) / 2;
    double h = sqrt((b * b) - (c * c));
    double y_ = (2 * l + a) * h / (a + l) / 3;
    if (B.X() == C.X() && D.X() < C.X())
        return Point{D.X() + h - y_, (A.Y() + B.Y() + C.Y() + D.Y()) / 4};
    if (B.X() == C.X() && C.X() < D.X())
        return Point{C.X() + h - y_, (A.Y() + B.Y() + C.Y() + D.Y()) / 4};
    return Point{(A.X() + B.X() + C.X() + D.X()) / 4, (B.Y() + C.Y()) / 2 - ((B.Y() + C.Y()) / 2 -
(D.Y() + A.Y()) / 2) * y_ / h};
}

std::ostream& Trapeze::print(std::ostream& out) const
{
    out << A << " " << B << " " << C << " " << D;
    return out;
}

```

CMakeLists.txt

```
cmake_minimum_required (VERSION 3.5)
```

```
project(lab3)
```

```
add_executable(oop_exercise_03
```

```
    main.cpp
```

```
    figure.cpp
```

```
    rhombus.cpp
```

```
    point.cpp
```

```
rectangle.cpp
trapeze.cpp)
```

```
set(CMAKE_CXX_FLAGS "${CMAKE_CXX_FLAGS} -Wall -Wextra")
```

```
set_target_properties(oop_exercise_03 PROPERTIES CXX_STANDARD 14
CXX_STANDARD_REQUIRED ON)
```

6. Набор testcases

test_01.txt результат	Координаты вершин		Ожидаемый
--------------------------	-------------------	--	-----------

Трапеция	(0;0) (1;1) (2;1) (3;0)	Площадь	2
0		Центр	(1.5; 0.41)
0			
1			
1			
2			
1			
3			
0			

Ромб	(0;2)(1;4)(2;2)(1;0)	Площадь	4
0		Центр	(1;2)
2			
1			
4			
2			
2			
1			
0			

Прямоугольник	(-4;0)(-4;5)(0;5)(0;0)	Площадь	20
-4		Центр	(-2;2.5)
0			
-4			
5			
0			
5			
0			
0			
out			
delete 1			
out			

test_02.txt результат	Координаты вершин		Ожидаемый
--------------------------	-------------------	--	-----------

Трапеция	(0;-2) (1;0) (4;0) (5;-2)	Площадь	8
0		Центр	(2.5; -1.08)
-2			
1			
0			
4			
0			
5			
-2			
Ромб	(0;-2)(-1;0)(0;2)(1;0)	Площадь	4
0		Центр	(0;0)
-2			
-1			
0			
0			
2			
1			
0			
Прямоугольник	(-2;-2)(-2;-1)(2;-1)(2;-2)	Площадь	4
-2		Центр	(0;-1.5)
-2			
-2			
-1			
2			
-1			
2			
-2			
out			
delete 1			
delete 1			
out			
delete 0			
out			
test_03.txt	Координаты вершин	Ожидаемый	
результат			
Трапеция	(0;4) (2;3) (2;1) (0;0)	Площадь	6
0		Центр	(0.89;2)
4			
2			
3			
2			
1			
0			
0			
Ромб	(0;1)(3;2)(6;1)(3;0)	Площадь	6

0
1
3
2
6
1
3
0

Центр (3;1)

Прямоугольник (-4;0)(-4;5)(0;5)(0;0)

Площадь 8
Центр (2;1)

0
2
4
2
4
0
0
0
out
delete 0
out

7. Результаты выполнения тестов

walien@PC-name:~/2kurs/CPP/lab3/tmp\$./oop_exercise_03 < ~/2kurs/CPP/lab3/test_01.txt

```

 2  3    2  2 3
*****      *      *****
*****      ***      *****
*****1 *****3 *****
*****      ***      *****
*****      *      *****
1      4  4    1 4

```

Operations: add / delete / out / quit

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

0:

Area: 2

Center: (1.5;0.416667)

Coordinates: (0;0) (1;1) (2;1) (3;0)

1:

Area: 4

Center: (1;2)

Coordinates: (0;2) (1;4) (2;2) (1;0)

2:

Area: 20

Center: (-2;2.5)

Coordinates: (-4;0) (-4;5) (0;5) (0;0)

Total area: 26

0:

Area: 2

Center: (1.5;0.416667)

Coordinates: (0;0) (1;1) (2;1) (3;0)

1:

Area: 20

Center: (-2;2.5)

Coordinates: (-4;0) (-4;5) (0;5) (0;0)

Total area: 22

walien@PC-name:~/2kurs/CPP/lab3/tmp\$./oop_exercise_03 < ~/2kurs/CPP/lab3/test_02.txt

```
  2  3    2  2 3
  *****      *      *****
  *****      ***      *****
  ***** 1 *****3 *****
  *****      ***      *****
  *****      *      *****
1          4  4    1 4
```

Operations: add / delete / out / quit

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

0:

Area: 8

Center: (2.5;-1.08333)

Coordinates: (0;-2) (1;0) (4;0) (5;-2)

1:

Area: 4

Center: (0;0)

Coordinates: (0;-2) (-1;0) (0;2) (1;0)

2:

Area: 4

Center: (0;-1.5)

Coordinates: (-2;-2) (-2;-1) (2;-1) (2;-2)

Total area: 16

0:

Area: 8

Center: (2.5;-1.08333)

Coordinates: (0;-2) (1;0) (4;0) (5;-2)

Total area: 8

Total area: 0

walien@PC-name:~/2kurs/CPP/lab3/tmp\$./oop_exercise_03 < ~/2kurs/CPP/lab3/test_03.txt

```
  2  3    2  2 3
  *****      *      *****
  *****      ***      *****
  ***** 1 *****3 *****
  *****      ***      *****
  *****      *      *****
1          4  4    1 4
```

Operations: add / delete / out / quit

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

Fig types: 1 - trapeze; 2 - rhombus; 3 - rectangle

0:

Area: 6

Center: (0.888889;2)

Coordinates: (0;4) (2;3) (2;1) (0;0)
1:
Area: 6
Center: (3;1)
Coordinates: (0;1) (3;2) (6;1) (3;0)
2:
Area: 8
Center: (2;1)
Coordinates: (0;2) (4;2) (4;0) (0;0)
Total area: 20
0:
Area: 6
Center: (3;1)
Coordinates: (0;1) (3;2) (6;1) (3;0)
1:
Area: 8
Center: (2;1)
Coordinates: (0;2) (4;2) (4;0) (0;0)
Total area: 14

8. Объяснение результатов работы программы - вывод

в figure.h задаётся базовый класс Figure задающий общий принцип структуры для классов — наследников — Rectangle, Trapeze и Rhombus.
Наследование позволяет избежать дублирования лишнего кода при написании классов, т. к. класс может использовать переменные и методы другого класса как свои собственные. В данном случае класс Figure является абстрактным — он определяет интерфейс для переопределения методов классами Rectangle, Trapeze и Rhombus.
Полиморфизм позволяет использовать одно и то же имя для различных действий, похожих, но технически отличающихся. В данной лабораторной работе он осуществляется посредством виртуальных функций.