


Kidputer Control

A parental-control system for Windows 11 PCs. You set a bedtime schedule from a web dashboard. The child's PC shows a countdown and then locks, and it keeps enforcing the schedule even when it's offline. From any browser or phone, a parent can lock the PC right away, grant extra time, or send an on-screen message. Everything that happens is recorded in one central activity log.



What it does

- **Bedtime schedule:** a lock window for each night of the week, in the PC's own time zone. A countdown (5 minutes by default) warns the child before the PC locks.
- **Lock now:** an immediate lock that applies even during extra time.
- **Extra time:** +30 minutes, +1 hour, +2 hours, or until a chosen time.
- **On-screen messages:** either *closable* by the child, or *persistent* until a parent removes them.
- **Lock-screen PIN:** a parent standing at the PC can type the PIN to unlock it. Too many wrong attempts lock PIN entry for a while.
- **Tamper resistance:**
  - The enforcement process runs as SYSTEM, so a standard user can't stop or remove it.
  - If the child closes the lock screen, it comes back within about a second.
  - The installed files are checked against a fingerprint every minute.
- **Central activity log:** locks, unlocks, wrong PINs, messages, tamper alerts, and parent actions. You can filter by PC, importance, and source.
- **Offline-safe:** the PC enforces from its last-synced copy of the settings. Only remote actions need a connection.
- **Secure dashboard:** password plus mandatory two-factor sign-in with an authenticator app. Sessions use secure cookies, and repeated failed sign-ins lock the account temporarily.
- **Reversible:** locking always uses the Windows lock (`LockWorkStation`). Nothing is ever shut down, so no work is lost.

Device page	On a phone
	

How it fits together

```
Parent's browser / phone ──HTTPS──►  Render: FastAPI + React dashboard ──► Postgres
                                                  ▲
Child's PC:  SYSTEM watchdog ──HTTPS (device token)┘
                  │ launches into the child's session
                  ▼
             Lock screen / countdown / messages (WinForms)
```

- **Cloud (`server/`, `web/`):**
  - One Docker image on Render runs both the dashboard and the API, on the same web address.
  - Postgres stores the schedule, overrides, messages, lock requests, and the activity log.
- **PC agent (`agent/`):** PowerShell 5.1, which is built into Windows, so there's nothing to install first.
  - A **SYSTEM watchdog**, run as a scheduled task, decides when to lock, checks PINs, syncs with the cloud, and watches for tampering.
  - A **UI agent** runs in the child's session and shows the countdown, the lock screen, and messages.
  - The UI agent never sees the PIN hash; the watchdog checks every attempt.

Repository layout

Path	What
`server/`	FastAPI + Postgres API: schema and migrations, dashboard sign-in (password + TOTP), device management, and the agent sync protocol
`web/`	Parent dashboard: React + TypeScript (Vite)
`agent/`	Windows agent: SYSTEM watchdog, UI agent, installer and uninstaller, tests
`Dockerfile`, `render.yaml`	Single-image build and Render Blueprint (web service + Postgres)
`docs/DEPLOY-RENDER.md`	Step-by-step deployment and first sign-in
`docs/ARCHITECTURE.md`	Design decisions, data model, agent protocol
`agent/README.md`	Installing on the child's PC, plus a first-run checklist

Getting started

1. **Deploy the cloud side to Render:** New → Blueprint → pick this repo. Enter your email and a first password when asked. Full steps are in docs/DEPLOY-RENDER.md.
2. **Sign in** and set up two-factor sign-in (scan the QR code). Then remove the bootstrap password from Render's environment settings.
3. **Add a PC** in the dashboard. It shows a one-time enrollment code and the exact install command.
4. **Install on the child's PC:** in an administrator PowerShell, in the `agent` folder, run:

   ```
   .\Install.ps1 -ApiUrl https://<your-app>.onrender.com -EnrollmentCode ABCD-EFGH-JKMN -ChildUser Sam
   ```

   The child should use a **standard** (non-administrator) Windows account.
5. Set the **schedule** and a **lock-screen PIN** on the device's page. Then walk through the first-run checklist in agent/README.md once.

Running locally:

```
KC_BOOTSTRAP_ADMIN_EMAIL=you@example.com KC_BOOTSTRAP_ADMIN_PASSWORD='a long local password'
\
  docker compose up --build      # dashboard + API on http://localhost:8000
```

For dashboard development with hot reload, run `cd web && npm install && npm run dev`.

Testing

Suite	What it covers
`server/tests` (pytest, real Postgres)	API, auth and 2FA, lockouts, the agent protocol, UTC lock windows, serving the dashboard
`server/tests/test_agent_integration.py`	The agent's PowerShell code against a live API (enroll, sync, events, PIN unlock)
`server/tests/test_dashboard_e2e.py`	The whole parent journey in Chromium, including a phone-width layout check
`web` (Vitest)	Status, time, and schedule helpers
`agent/tests`	Decision logic, countdown, PIN lockout, queue, inbox, tamper check, script parsing, interop compile

CI runs all of these. The agent tests run on Windows under both PowerShell 5.1 and 7.

Status

Version 1.0.0. All four build steps are complete: the cloud API, the agent syncing through it, the SYSTEM watchdog, and the web dashboard.

Not yet verified on a real PC: the parts that need an interactive Windows session. These are the lock-screen windows, launching into the child's session, the scheduled task, and the folder permissions. Before relying on the agent, run through the checklist in `agent/README.md` once.

Roadmap

- **App and process management** (next version): control which apps the child can run, and when.
- Also planned: usage quotas, weekly reports, and bonus time.

Recent changes

- **Renamed to Kidputer Control, version 1.0.0:**
  - The product was renamed from Session Monitor, and the version reset to 1.0.0.
  - Install paths on the PC are now `%ProgramFiles%\KidputerControl` and `%ProgramData%\KidputerControl`, and the scheduled task is `\KidputerControl\Watchdog`.
  - Settings use the `KC_` prefix, and the Render service is named `kidputer-control`.
- **Dashboard polish:**
  - At phone width, the extra-time row and the schedule table no longer overflow their card. The browser test now checks for this.
  - Times show with two-digit hours (03:15 rather than 3:15).
  - Activity entries use plain-English labels.
- **Step 4, web dashboard and Render hosting:**
  - React + TypeScript dashboard: sign-in with mandatory 2FA, devices overview, device page (lock now, extra time, messages, schedule, settings, PIN, enrollment), activity log, and

account page. It works on phones and supports light and dark themes.
    - The server serves the dashboard with a strict Content-Security-Policy.
    - The first admin can be created from environment variables, because Render's free tier has no shell.
    - A single-image `Dockerfile`, the `render.yaml` Blueprint, and a deployment guide.
- **Steps 2–3, Windows agent:**
    - SYSTEM watchdog, lock-screen UI agent, installer and uninstaller.
    - Offline-safe enforcement from a local cache, with an idempotent event upload queue.
    - PBKDF2 PIN checks and lockout, handled by the watchdog.
    - The countdown deadline survives reboots.
    - Tamper detection, and relaunching of the UI if it's closed.
- **Server additions:**
    - Lock windows are precomputed in UTC for the next 14 days, which keeps them correct across daylight saving and stops the child dodging them by changing time zones.
    - A lock-screen PIN unlock shows up in the dashboard, and it ends an immediate lock.
- **Step 1, cloud API:**
    - FastAPI + Postgres schema.
    - Password and TOTP sign-in with CSRF protection and lockouts.
    - Device enrollment codes and tokens.
    - Central activity log.