# Strings

`stringr` is a versatile package for working with strings in R. It provides functions for string manipulation, pattern matching, and cleaning. These functions make it easier to perform various text-related tasks when working with data.

Detect Matches

- `str_detect()`: Detects Patterns - checks if a string contains a specific pattern. Output: TRUE/FALSE.

Example 1: Detect whether the word fox is in the string or not.

```
my_string <- "The quick brown fox jumps over the lazy dog."
str_detect(my_string, "fox")
```

Output:

All these examples are illustrated with a vector, but they can be used in dataframes, typically with mutate. For example:

illustration_data

Example
"the quick brown fox jumps over the lazy dog."
"hello, world!"
"fox and cat"

Example 2: Use str_detect in illustration data above to detect whether on each sentence there is the word fox.

```
example_2 <- illustration_data %>%
  mutate(fox_check = str_detect(Example, "fox"))
```

Example	
"the quick brown fox jumps over the lazy dog."	
"hello, world!"	
"fox and cat"	

Manage Length

- str_length(): Finds the length (the number of characters) in a string.

Example 3: Count how many characters are in the following string.

```
my_string <- "Hello, World!"
str_length(my_string)
```

Output:

- `str_trim():` Trims white space - removes leading and trailing white space from a string.

Example 4: Remove the white space from the beginning and the end of the string.

```
my_string <- "  Trim me!    "
str_trim(my_string)
```

Output:

- `str_squish():` Removes extra white space withing a string, as well as the beginning, and the end.

Example 5: Remove all whitespace from the string.

```
my_string <- "   Hello   world    from    R!    "
str_squish(my_string)
```

Output:

Mutating Strings

- `str_sub():` extracts substrings from a string:

Example 6: Extract the string from position 8 to position 13.

```
my_string <- "Extract this part"
str_sub(my_string, start = 9, end = 13)
```

Output:

- `str_replace()`: replaces a pattern with another string:

Example 7: Substitute the word fox with the word cat.

```
my_string <- "The quick brown fox jumps over the lazy dog."
str_replace(my_string, "fox", "cat")
```

Output:

- `str_to_lower()`: Changes the case to all lower case of a string.
- `str_to_upper()`: Changes the case to all upper case of a string.

Example 8: Change the following string to all lower case and then to all upper.

```
my_string <- "Hello, World!"
str_to_lower(my_string)
str_to_upper(my_string)
```

Output:

Output:

Join & Split

- `str_c()`: Combining Strings - concatenates strings together.

Example 9: combine the following two strings. Separate them by "-".

```
first_name <- "John"
last_name <- "Doe"
str_c(first_name, "-", last_name)
```

Output:

- `str_split():` splits a string into a character vector using a specified delimiter.

Example 10: Separate the following string by ",".

```
my_string <- "apple,banana,cherry"
str_split(my_string, ",")
```

Output:

Subset Strings

- `str_extract():` extracts the first occurrence of a pattern from a string.

Example 11: Extract the phone number from the following string.

```
my_string <- "Email me at john@example.com or call at 555-123-4567."
str_extract(my_string, "\\d{3}-\\d{3}-\\d{4}")
```

Output: