

Thunar Custom Actions

 help.ubuntu.com/community/ThunarCustomActions

- [Partners](#)
- [Support](#)
- [Community](#)
- [Ubuntu.com](#)

[ThunarCustomActions](#)

Contents

1. [Thunar Custom Actions](#)

1. [Delete/Bypass Recycle Bin](#)
2. [Create Symlink](#)
3. [Permanently Remove](#)
4. [Join](#)
5. [View](#)
6. [Play 15 seconds](#)
7. [Copy Current Path](#)
8. [Open Terminal Here](#)
9. [Extract Archive Here](#)
10. [Extract Passworded Archive](#)
11. [Estimated Space Usage](#)
12. [Create Archive Here](#)
13. [Sign Using GnuPG](#)
14. [Encrypt Using GnuPG](#)
15. [Decrypt GnuPG File](#)
16. [Shred and Delete File\(s\)](#)
17. [Add to iPod](#)
18. [Open Folder As Root](#)
19. [Open Text as Root](#)
20. [Search Including Hidden Files/Folders](#)
21. [Mount ISO](#)
22. [Convert To AVI](#)
23. [Add Progress Bar To Copy](#)
24. [Change Multiple File Permissions](#)
25. [Move Files From Subfolders To Parent Folder](#)
26. [Delete All Empty Folders](#)
27. [Encrypt/Decrypt using BCrypt](#)
28. [Grab Metadata From Media File](#)
29. [Edit Filesystem Metadata](#)
30. [Open anything as Superuser](#)

Discussion of this wiki can be found [here](#)

If you like the Thunar file manager (default in Xubuntu), you will probably love custom actions. These are user-defined commands that act upon selected files in Thunar. Either on their own, or combined with a simple dialog app such as Zenity, these can be very powerful and useful.

Thunar > Edit > Configure custom actions will take you to the dialog for creating and organising your custom actions. However, because this is GUI-oriented, the easiest way to

install someone else's custom action is through a bash command. This is a list of a number of custom actions contributed by the Ubuntu community.

```
ffmpeg -i %f 2>&1 | grep -e Stream -e Duration -e Input | zenity --width=800 --height=240 --text-info --title %n
```

Delete/Bypass Recycle Bin

Command:

```
rm -r
```

Description: Removes the selected file(s) from the disk, bypassing any local Recycle bin. Useful when in samba shares. Requires confirmation for reasons of safety.

Requires: zenity

```
CONTENT='<action><icon>stock_delete</icon><name>Remove...</name><command>zenity --question --title="Remove..." --window-icon="/usr/share/icons/Tango/16x16/actions/edit-delete.png" --text="Do you wish to permanently\nremove the selected file(s)?" ; if [ $? = 0 ] ; then rm -r %F ; fi</command><description>Permanently remove the selected file(s)</description><patterns>*</patterns><directories/><audio-files/><image-files/><other-files/><text-files/><video-files/></action>'
cat $HOME/.config/Thunar/uca.xml >> newtmp
sed 's/<\n/actions>/' <newtmp >newfile
echo $CONTENT >> newfile
mv $HOME/.config/Thunar/uca.xml $HOME/.config/Thunar/uca.xml.bak
mv newfile $HOME/.config/Thunar/uca.xml
rm newtmp
```

Create Symlink

Command:

```
ln -s
```

Description: Creates an absolute symbolic link to the selected file in the same folder, which can then be moved or renamed as desired. man ln for more info.

Requires:

```
CONTENT='<action><icon>emblem-symbolic-link</icon><name>Create Symlink</name><command>ln -s %f %n.symlink</command><description>Creates a symbolic link to the selected object</description><patterns>*</patterns><directories/><audio-files/><image-files/><other-files/><text-files/><video-files/></action>'
cat $HOME/.config/Thunar/uca.xml >> newtmp
sed 's/<\n/actions>/' <newtmp >newfile
```

```
echo $CONTENT >> newfile
mv $HOME/.config/Thunar/uca.xml $HOME/.config/Thunar/uca.xml.bak
mv newfile $HOME/.config/Thunar/uca.xml
rm newtmp
```

Permanently Remove

Command:

```
Xdialog --title "Remove..." --yesno "Do you wish to permanently remove \n %N?" 10 45
&& rm -r %F
```

Description: Permanently remove selected files. Appears if selection contains any files.

Requires: Xdialog

```
<action><icon></icon><name>Permanently remove...</name><command>Xdialog --title
&quot;Remove...&quot; --yesno &quot;Do you wish to permanently remove n %N?&quot; 10
45 && rm -r %F</command><description>Permanently remove selected
files</description><patterns>*</patterns><directories/><audio-files/><image-files/>
<other-files/><text-files/><video-files/></action>
```

Join

Command:

```
cat %F &gt; joined.txt
```

Description: Join selected text files. Appears if selection contains text files.

Requires:

```
<action><icon></icon><name>Join</name><command>cat %F &gt; joined.txt</command>
<description>Join selected text files</description><patterns>*</patterns><text-files/>
</action>
```

View

Command:

```
feh %F
```

Description: View selected images in a slideshow. Appears if selection contains image files.

Requires: feh

```
<action><icon></icon><name>View</name><command>feh %F</command><description>View
selected images in a slideshow</description><patterns>*</patterns><image-files/>
</action>
```

Play 15 seconds

Command:

```
mplayer %f -really-quiet -endpos 15
```

Description: Play a 15 seconds clip of a media file. Appears if selection contains: audio files, video files

Requires: mplayer

```
<action><icon></icon><name>Play 15 seconds</name><command>mplayer %f -really-quiet -endpos 15</command><description>Play a 15 seconds clip of a media file</description><patterns>*</patterns><audio-files/><video-files/></action>
```

Copy Current Path

Command:

```
echo -n %f | xclip -selection "clipboard"
```

Description: Copies \$PATH to clipboard.

Requires:

xclip program to be installed on your system

Open Terminal Here

Command:

```
urxvtc -cd %f
```

Description: Opens terminal in current directory.

Requires: urxvt client

```
urxvtc -cd %f
```

Extract Archive Here

Command:

```
squeeze -x . %N
```

Description: Extracts archive to current directory.

Requires: squeeze

```
squeeze -x . %N
```

Extract Passworded Archive

Command:

```
xarchiver -e %N
```

Description: Extracts passworded archive to current directory.

Requires: xarchiver

```
xarchiver -e %N
```

Estimated Space Usage

Command:

```
du -chs --apparent-size %N | zenity --text-info
```

Description: Estimates disk space usage.

Requires: zenity

```
du -chs --apparent-size %N | zenity --text-info
```

Create Archive Here

Command:

```
squeeze -n %N
```

Description: Creates archive in current directory.

Requires: squeeze

```
squeeze -n %N
```

Sign Using GnuPG

Command:

```
terminal -e "gpg -a -u [user] -b %f"
```

Description: Signs a file with the user's GPG key.

Requires: gpg

```
terminal -e "gpg -a -u [user] -b %f"
```

Encrypt Using GnuPG

Command:

```
terminal -e "gpg -e -r [recipient] %f"
```

Description: Encrypts a file using GPG.

Requires: gpg

```
terminal -e "gpg -e -r [recipient] %f"
```

Decrypt GnuPG File

Command:

```
terminal -e "gpg -o %n.decrypted -d %f"
```

Description: Decrypts GnuPG file, appending ".decrypted" to the decrypted filename.

Requires: gpg

```
terminal -e "gpg -o %n.decrypted -d %f"
```

Shred and Delete File(s)

Command:

```
zenity --question;if [$? = 0];then shred -fuz %F;fi
```

Description: Shreds and deletes file.

Requires: zenity

```
zenity --question;if [$? = 0];then shred -fuz %F;fi
```

Add to iPod

Command:

```
gnupod_addsong.pl %F | Xdialog --title "GNUpod - Add song" --no-cancel --tailbox - 24 64
```

Description: Adds songs to iPod. Appears if selection contains audio or video files.

Requires: gnupod, Xdialog

```
<action><icon></icon><name>Add to Ipod</name><command>gnupod_addsong.pl %F | Xdialog -  
-title &quot;GNUpod - Add song&quot; --no-cancel --tailbox - 24 64</command>  
<description>Add songs to Ipod</description><patterns>*.mp3;*.m4a;*.mp4</patterns>  
<audio-files/><video-files/></action>
```

Open Folder As Root

Command:

```
pkexec thunar %f
```

Description: Opens current folder with root permissions.

Requires:

```
pkexec thunar %f
```

Open Text as Root

Command:

```
pkexec mousepad %f
```

Description: Opens selected text file with root permissions. Substitute the name of your editor of choice for "gedit".

Requires: text editor

```
pkexec mousepad %f
```

Search Including Hidden Files/Folders

Command:

```
catfish --fileman=thunar --hidden --path=%f
```

Description: Searches entire filesystem.

Requires: catfish

```
catfish --fileman=thunar --hidden --path=%f
```

Mount ISO

Command:

```
udisksctl loop-setup -f %f
```

Description: Mounts .iso files.

Requires:

```
udisksctl loop-setup -f %f
```


Convert To AVI

Command:

```
xfce4-terminal -x ffmpeg -i %f -b 798k -ab 128k %f.avi
```

Description: Converts video file to .avi.

Requires: ffmpeg

```
xfce4-terminal -x ffmpeg -i %f -b 798k -ab 128k %f.avi
```

Add Progress Bar To Copy

Command:

```
(for I in $(seq 2); do echo $I; sleep 1; done; cp %F "/destination/folder") | zenity -  
-progress --pulsate --auto-close
```

Description: Adds progress bar to copy/paste.

Requires: zenity

```
(for I in $(seq 2); do echo $I; sleep 1; done; cp %F "/destination/folder") | zenity -  
-progress --pulsate --auto-close
```

Change Multiple File Permissions

Command:

Description: Allows user to change file permissions of one or multiple files with small GUI.

Requires: zenity

```
ans=$(zenity --height=350 --list --text "change files permissions" --checklist --  
column "pick" --column "options" TRUE "user-read" TRUE "user-write" FALSE "user-exec"  
FALSE "group-read" FALSE "group-write" FALSE "group-exec" FALSE "all-read" FALSE "all-  
write" FALSE "all-exec" --separator=":"); if [ "$ans" != "" ]; then  
searchuserread="user-read"; searchuserwrite="user-write"; searchuserexec="user-exec";  
user1="0" ; user2="0" ; user3="0" ; searchgroupread="group-read";  
searchgroupwrite="group-write"; searchgroupexec="group-exec"; group1="0" ; group2="0"  
; group3="0" ; searchallread="all-read"; searchallwrite="all-write";  
searchallexec="all-exec"; all1="0" ; all2="0" ; all3="0" ; case $ans in  
*"${searchuserread}*) user1="4" ;; esac ; case $ans in *"${searchuserwrite}*) user2="2"  
;; esac ; case $ans in *"${searchuserexec}*) user3="1" ;; esac ; case $ans in  
*"${searchgroupread}*) group1="4" ;; esac ; case $ans in *"${searchgroupwrite}*)  
group2="2" ;; esac ; case $ans in *"${searchgroupexec}*) group3="1" ;; esac ; case  
$ans in *"${searchallread}*) all1="4" ;; esac ; case $ans in *"${searchallwrite}*)  
all2="2" ;; esac ; case $ans in *"${searchallexec}*) all3="1" ;; esac ; u=$((user1 +
```

```
$user2 + $user3)) ; g=$(( $group1 + $group2 + $group3 )) ; a=$(( $all1 + $all2 + $all3 ))  
; result="$u$g$a" ; chmod $result %F || { zenity --error --text="an error  
occurred!\ncheck if you are allowed\nto change permissions\nof the selected files"; }  
; fi
```

Move Files From Subfolders To Parent Folder

Command:

```
find . -mindepth 2 -type f -exec mv "{}" . \;
```

Description: Moves files from subfolders to parent (current) folder.

Requires:

```
find . -mindepth 2 -type f -exec mv "{}" . \;
```

Delete All Empty Folders

Command:

```
find . -type d -empty -delete
```

Description: Deletes all empty folders in current directory.

Requires:

```
find . -type d -empty -delete
```

Encrypt/Decrypt using BCrypt

Command:

Description: Uses bcrypt to encrypt/decrypt files.

Requires: zenity, bcrypt

```
zenity --info --title="Impending Bcrypt Operation" --window-  
icon="/usr/share/pixmaps/keybox.png" --text="There is a bcrypt operation impending.  
Watch inside the File Manager window to verify that said operation is successful." ; :  
; while [ "$?" = "0" ] ; do xterm -e bcrypt %F ; sleep 2 ; zenity --question --  
title="Success?" --window-icon="/usr/share/pixmaps/keybox.png" --text="Was the bcrypt  
operation successful?" ; if [ "$?" = "0" ] ; then exit ; fi ; zenity --question --  
title="Try again?" --window-icon="/usr/share/pixmaps/keybox.png" --text="Would you  
like to try again?" ; if [ "$?" != "0" ] ; then exit ; fi ; done
```

Grab Metadata From Media File

Command:

```
ffmpeg -i %f 2>&1 | grep -e Stream -e Duration -e Input | zenity --width=800 --height=240 --text-info --title %n
```

Description: Grabs info from a media (audio/video) file using ffmpeg.

Requires: ffmpeg, zenity

```
ffmpeg -i %f 2>&1 | grep -e Stream -e Duration -e Input | zenity --width=800 --height=240 --text-info --title %n
```

Edit Filesystem Metadata

Command:

```
eiciel %f
```

Description: Edit file or folder extended attributes and access control lists

Requires: eiciel

```
<action>
  <icon>document-properties</icon>
  <name>Extended attributes</name>
  <command>eiciel %f</command>
  <description>Edit extended attributes and permissions</description>
  <patterns>*</patterns>
  <directories/>
  <audio-files/>
  <image-files/>
  <other-files/>
  <text-files/>
  <video-files/>
</action>
```

Open anything as Superuser

Command:

```
gksudo exo-open %f
```

Description: Launch any file or folder with superuser privileges

```
<action>
  <icon>category-show-all</icon>
  <name>Open as superuser</name>
  <command>gksudo exo-open %f</command>
  <description>Open file/folder with full privileges</description>
  <patterns>*</patterns>
```

```
<startup-notify/>
<directories/>
<audio-files/>
<image-files/>
<other-files/>
<text-files/>
<video-files/>
</action>
```

Another good source of custom actions can be found in the [Thunar wiki](#).

Originally posted [The Ubuntu Forums \(ubuntuforums.org\)](#)

ThunarCustomActions (last edited 2020-11-26 12:49:36 by [serhii-gipsy](#))