

Conventional Commits Cheatsheet

 gist.github.com/qoomon/5dfcdf8eec66a051ecd85625518cfd13

262588213843476



Conventional Commits Cheatsheet

Conventional Commit Messages



See how [a minor change](#) to your commit message style can make a difference.

```
git commit -m"<type>(<optional scope>): <description>" \
-m"<optional body>" \
-m"<optional footer>"
```

Note

This cheatsheet is opinionated, however it does not violate the specification of [conventional commits](#)

Tip

Take a look at [git-conventional-commits](#) a CLI util to ensure these conventions, determine version and generate changelogs.

Commit Message Formats

General Commit

`<type>(<optional scope>): <description>`
empty line as separator
`<optional body>`
empty line as separator
`<optional footer>`

Initial Commit

chore: init

Merge Commit

Merge branch '<branch name>'

Follows default git merge message

Revert Commit

Revert "<reverted commit subject line>"

Follows default git revert message

Types

- Changes relevant to the API or UI:
 - **feat** Commits that add, adjust or remove a feature to/of/from the API or UI
 - **fix** Commits that fix an API or UI bug of a preceded **feat** commit
- **refactor** Commits that rewrite or restructure code without altering API or UI behavior
 - perf** Commits are special type of **refactor** commits that specifically improve performance
- **style** Commits that address code style (e.g., white-space, formatting, missing semi-colons) and do not affect application behavior
- **test** Commits that add missing tests or correct existing ones
- **docs** Commits that exclusively affect documentation
- **build** Commits that affect build-related components such as build tools, dependencies, project version, ...
- **ops** Commits that affect operational aspects like infrastructure (IaC), deployment scripts, CI/CD pipelines, backups, monitoring, or recovery procedures, ...
- **chore** Commits that represent tasks like initial commit, modifying **.gitignore**, ...

Scopes

The **scope** provides additional contextual information.

- The scope is an **optional** part
- Allowed scopes vary and are typically defined by the specific project
- **Do not** use issue identifiers as scopes

Breaking Changes Indicator

- A commit that introduce breaking changes **must** be indicated by an **!** before the **:** in the subject line e.g. `feat(api)!: remove status endpoint`
- Breaking changes **should** be described in the [commit footer section](#), if the [commit description](#) isn't sufficiently informative

Description

The **description** contains a concise description of the change.

- The description is a **mandatory** part
- Use the imperative, present tense: "change" not "changed" nor "changes"
Think of `This commit will...` or `This commit should...`
- **Do not** capitalize the first letter
- **Do not** end the description with a period (.)
- In case of breaking changes also see [breaking changes indicator](#)

Body

The **body** should include the motivation for the change and contrast this with previous behavior.

- The body is an **optional** part
- Use the imperative, present tense: "change" not "changed" nor "changes"

Footer

The **footer** should contain issue references and informations about **Breaking Changes**

- The footer is an **optional** part, except if the commit introduce breaking changes
- *Optionally* reference issue identifiers (e.g., `Closes #123`, `Fixes JIRA-456`)
- **Breaking Changes must** start with the word `BREAKING CHANGE:`
 - For a single line description just add a space after `BREAKING CHANGE:`
 - For a multi line description add two new lines after `BREAKING CHANGE:`

Versioning

- If your next release contains commit with...
 - **Breaking Changes** incremented the **major version**
 - **API relevant changes** (**feat** or **fix**) incremented the **minor version**
- **Else** increment the **patch version**

Examples

- feat: add email notifications on new direct messages
- feat(shopping cart): add the amazing button
- feat!: remove ticket list endpoint

refers to JIRA-1337

BREAKING CHANGE: ticket endpoints no longer supports list all entities.
- fix(shopping-cart): prevent order an empty shopping cart
- fix(api): fix wrong calculation of request body checksum
- fix: add missing parameter to service call

The error occurred due to <reasons>.
- perf: decrease memory footprint for determine unique visitors by using HyperLogLog
- build: update dependencies
- build(release): bump version to 1.0.0
- refactor: implement fibonacci number calculation as recursion
- style: remove empty line

Git Hook Scripts to ensure commit message header format

► Click to expand

References

- <https://www.conventionalcommits.org/>
- <https://github.com/angular/angular/blob/master/CONTRIBUTING.md>
- <http://karma-runner.github.io/1.0/dev/git-commit-msg.html>

- <https://github.com/github/platform-samples/tree/master/pre-receive-hooks>
- <https://github.community/t5/GitHub-Enterprise-Best-Practices/Using-pre-receive-hooks-in-GitHub-Enterprise/ba-p/13863>