© PNN 2025

Lecture 6: Message Digest and Digital Signatures

a) Message Digest: Hashing Cryptographic Algorithms

Hashing is a fundamental concept in cryptography used to convert an input (or message) into a fixed-length string of characters, which represents the original data. Unlike encryption, hashing is a one-way process - meaning once the data is hashed, it cannot be reversed to retrieve the original input.

Hashing cryptographic algorithms, also known as cryptographic hash functions, are referred to by several names depending on their specific characteristics or applications. One common alternative name is **message digest algorithms**, which emphasizes their role in producing a fixed-size output (the "digest") from an input message of arbitrary length. Another term is **one-way functions / Trap door functions**, highlighting the property that these algorithms are designed to be computationally infeasible to reverse - given a hash value, it is practically impossible to determine the original input. Additionally, they are sometimes called **fingerprinting algorithms**, as the hash output serves as a unique "fingerprint" of the input data, ensuring its integrity and uniqueness. In certain contexts, especially when used for security purposes like password storage or digital signatures, they may be referred to as **secure hash algorithms** (e.g., SHA-256), emphasizing their robustness against attacks such as collisions or preimage resistance. The terms **"checksum algorithm"** and **"hashing cryptographic algorithm"** are related but not exactly the same. These various names reflect the diverse roles and properties of hashing algorithms in ensuring data integrity, authentication, and security in modern cryptographic systems.

Hashing plays a critical role in ensuring data integrity, authentication, and secure password storage. It is commonly used in applications such as digital signatures, blockchain, and message authentication codes (MACs).

How Hashing Works

i) Input Data (Message): Any size data, such as a password or file.
ii) Hashing Algorithm: Processes the data to produce a hash value or digest of fixed length.
iii) Hash Value: A unique, fixed-length string that serves as a digital fingerprint of the input data. Even a small change in the input results in a completely different hash value, a property known as the avalanche effect.

Common Cryptographic Hashing Algorithms

i) MD5 (Message Digest 5)
Produces a 128-bit hash value.
Once widely used for verifying data integrity but now considered insecure due to vulnerabilities.

ii) SHA-1 (Secure Hash Algorithm 1)
Produces a 160-bit hash value.
More secure than MD5 but also vulnerable to certain attacks.

iii) SHA-256 (Secure Hash Algorithm 256-bit)
Part of the SHA-2 family, it generates a 256-bit hash value.

Widely used for securing blockchain, digital signatures, and password storage.

iv) SHA-3
Designed as an improvement over SHA-2 with enhanced security.

Applications of Hashing


i) Password Storage: Hashing ensures passwords are stored securely. Even if the database is compromised, the original passwords cannot be retrieved from the hash values.
ii) Data Integrity Verification: Hash values help verify that files or messages have not been tampered with during transmission.
iii) Blockchain Technology: Hashing is a key component of blockchain, ensuring data immutability and secure transaction verification.
iv) Digital Signatures: Used to create unique fingerprints of documents, ensuring authenticity and preventing forgery.
v) Message Authentication Codes (MACs): Provide both data integrity and authentication.

Properties of Cryptographic Hash Functions

i) Deterministic: The same input always produces the same hash value.
ii) Fast Computation: Hashing should be efficient and quick.
iii) Preimage Resistance: It should be computationally infeasible to reverse a hash and retrieve the original input.
iv) Collision Resistance: Two different inputs should not produce the same hash value.
v) Avalanche Effect: A small change in the input should produce a completely different hash.

Diagram Explanation

The diagram illustrates how an input message is passed through a hashing algorithm to generate a fixed-length hash value. Any change to the input results in a completely different hash value, emphasizing the one-way and unique nature of hashing.



b) Cryptographic Digital Signatures

A cryptographic digital signature is a mathematical technique used to ensure the authenticity, integrity, and non-repudiation of digital messages or documents. Digital signatures are analogous to handwritten signatures or wax seals, but they are far more secure due to their cryptographic foundations. They rely on asymmetric cryptography, where a private key is used to generate the signature, and a corresponding public key is used to verify it. This process ensures that only the person holding the private key could have created the signature, making it a reliable method for verifying the sender's identity.

How Digital Signatures Work

The process of generating and verifying a digital signature involves three main steps: hashing, signing, and verification. First, the message or document is processed through a cryptographic hash function (e.g., SHA-256) to create a fixed-length hash value that uniquely represents the content. The sender then encrypts the hash value using their private key, creating the digital signature. This signature is appended to the message and sent to the recipient. Upon receiving the message, the recipient recalculates the hash value from the message content and decrypts the digital signature using the sender's public key. If the two hash values match, the message is verified as authentic and unchanged.

Applications of Digital Signatures

Digital signatures are used in various fields to ensure secure communication and data integrity. In email encryption (S/MIME), digital signatures validate the authenticity of the sender and prevent tampering. In software distribution, they guarantee that software packages have not been altered by verifying the publisher's signature. Digital signatures are also critical in blockchain technology, where they are used to authenticate transactions. In legal and financial sectors, digital signatures replace handwritten signatures for signing contracts and documents, offering greater security and verifiability.

Advantages and Security Features

Digital signatures offer several benefits, including data integrity, authentication, and non-repudiation. They protect against message tampering, ensuring that the data remains unchanged during transmission. By verifying the sender's identity, they prevent impersonation and unauthorized access. Non-repudiation ensures that the signer cannot deny creating the signature, which is essential for legal and financial transactions. Digital signatures also enhance public trust in secure communication protocols such as HTTPS and VPNs.

c) Post-Quantum Cryptography Algorithms

Post-Quantum Cryptography (PQC) refers to cryptographic algorithms designed to be secure against attacks from quantum computers. Unlike classical computers, which rely on bits (0s and

1s), quantum computers use quantum bits (qubits) that can represent multiple states simultaneously, enabling them to solve certain mathematical problems exponentially faster. This poses a serious threat to existing cryptographic systems—particularly asymmetric algorithms like RSA, ECC, and Diffie-Hellman, which rely on problems such as integer factorization and discrete logarithms. Once powerful quantum computers become available, they could potentially break these systems, compromising the security of encrypted data.

How Post-Quantum Cryptography Works

Post-Quantum Cryptography focuses on developing algorithms that are resistant to both classical and quantum attacks. Unlike current cryptographic methods that rely on number-theoretic problems, PQC algorithms are built on different mathematical foundations, such as lattice-based cryptography, hash-based cryptography, multivariate polynomial cryptography, and code-based cryptography. For example, lattice-based cryptography relies on solving hard problems in high-dimensional lattices, which are believed to be infeasible for quantum computers to solve in a reasonable timeframe. These algorithms can be used for key exchange, digital signatures, and encryption without sacrificing the security that quantum computing threatens to undermine.

Implementation and Importance of PQC

The transition to Post-Quantum Cryptography is crucial for future-proofing data security, especially for industries that require long-term confidentiality, such as banking, healthcare, and government communications. Many organizations are already working on hybrid encryption systems, combining classical and post-quantum algorithms to ensure secure communication during the transition period. Standards bodies like the US National Institute of Standards and Technology (NIST) are in the process of evaluating and standardizing post-quantum algorithms. Implementing PQC, however, presents challenges related to key sizes, computational efficiency, and compatibility with existing infrastructure. Despite these challenges, PQC remains essential for preparing cryptographic systems for the quantum era and safeguarding sensitive data against future threats.