OPACITY: first full machine run

21 to 22 October 2026

OPACITY: first full machine run

Results of 21 October 2026, with three larger local models added on the morning of 22 October. Every machine arm of the study ran end to end: the mechanical checker, two hosted LLM checkers, a five-size local checker sweep, and the agent harvest with an LLM judge. The human arm, the blind coding of free-text descriptions, and human adjudication of the harvest have not run and are outside what this document covers. Numbers here are recomputed from the per-sample Inspect logs and cross-checked against Inspect's own aggregates. The scripts that produce them are listed at the end.

Summary

- Both hosted checkers pass the phase-0 gate at s0, flagging every seeded class on every replicate with false alarms at 0.17 and 0.15, whereas none of the local models does, although the 27B is close and misses only class 6.
- On the design as it stood at 21:00, detection did not fall with disclosure strength for either hosted checker. The logs showed why: the prose pushes where controls hedge, a rounded table sat beside an exact chi-square the checker could recompute, and the sample-list total and stratum arm sizes disclosed what suppression had removed. Three rules in the disclosure layer changed at 23:04 and the run was repeated.
- After the change, detection falls at s3 for both hosted checkers (to 0.80 and 0.85) and cannot-tell rises on both seeded and control bundles, which is the shape the protocol predicts. Class 6 is fully concealed at s3, and classes 3, 4, 5, 7 and 8 are not.
- A prose-only level, s4, now bounds how much the interpretation alone gives away. For the hosted checkers it is 0.72, for the 27B 0.15. A word-count rule on pushes against hedges separates seeded from control at every level with no false alarms, so the interpretive register is a tell the frontier models use and the local model does not.
- The harvest ran for all five Qwen3.5 sizes and was judged by MiMo pro from the workstation. The commit rate falls with size for every class but unreported multiplicity, and the catch rate overtakes it between 4B and 9B. At 27B the agent reaches a wrong conclusion on 0.19 of seeded tasks and catches 0.88 of planted errors as a checker.
- Two operational fixes changed results materially: MiMo pro needs 20000 output tokens or it returns nothing on a third of controls, and Qwen3.5 needs thinking disabled or the 4B writes its reasoning into the reply and never reaches the JSON.
- Three larger local checkers ran the morning after: Qwen3 32B, and Mistral Small 24B and Llama 3.3 70B in NVFP4 on one H100. None passes the gate, all miss the wrong-denominator class, and Mistral 24B has the best false-alarm profile of any local model, 0.80 detection with none. As analysts the two other-lab models are far worse than the Qwen3.5 27B.
- A typed arm on a decision server ran all 400 bundles in seconds with no parse failures. At s0 it flags the five prose-carried classes on every replicate and the three count-carried classes on none, with no false alarms.

Lay statement

Researchers who work with sensitive data do so inside secure environments that check everything before it leaves. Those checks exist to stop private details escaping, and they work by blurring or hiding small numbers. The question this study asks is whether that blurring also hides the evidence a reviewer would need to notice that an analysis is wrong. If it does, the two things we want from an analysis assistant, that it keeps data private and that it does not release wrong conclusions, pull against each other.

To test this we built analysis reports with known mistakes planted in them, eight kinds of mistake in all, alongside matched correct reports, and passed them through four strengths of privacy checking, from none to strict, plus a fifth setting that hides every table and leaves only the written interpretation. We then asked reviewers of several kinds to say whether each report was sound: a set of fixed rules, two large commercial AI models, a range of smaller open models that could run inside a secure environment, and a fast decision tool that reads off a probability instead of writing an opinion. We also turned the open models round and asked them to do the analyses themselves, with an AI judge marking their answers against a hidden key.

Six things came out. The two hosted AI reviewers catch every planted mistake when nothing is hidden. With every table hidden, each still flags about seven in ten planted mistakes, often from the way the conclusion is written: wrong reports tend to overclaim, while correct ones tend to be cautious. In a small follow-up with two local models, rewriting correct reports in the same confident voice made the models flag them about a third of the time at the least restrictive setting. Tone therefore helps some reviewers, but relying on it could leave them open to a wrong report written cautiously. When privacy checks hide the tables, reviewers also miss mistakes that depend on the numbers, including a rate worked out over the wrong base. No open model up to 70 billion parameters is yet good enough to be a reviewer by the standard we set, and every local model tested misses the wrong-base mistake even with the table in full view. In the Qwen3.5 size sweep, the larger agents make fewer planted mistakes overall; from about nine billion parameters, they catch more mistakes as reviewers than they make as analysts. The fast decision tool answers in a fraction of a second and catches wording-based mistakes, but none that need arithmetic.

Two cautions. The judge that marked the analyses is itself an AI, so its scores will be checked against human marking later. And the human reviewer study, which is the heart of the project, has not run yet; what is reported here is the machine baseline it will be measured against.

What was run

The corpus is eight error classes, each a seeded bundle and a matched control built from the same data, five replicates per class: 80 bundles. Each is rendered at five disclosure levels, s0 (none) to s3 (conservative) and s4 (every table withheld), so a checker sees 400 bundles. The reviewer instruction is identical across arms and runs at temperature 0.

Arm	Checker	Where	Output budget
mechanical	SDC rules only, no model	d2-1	–
LLM, hosted	DeepSeek 4.1 flash (via the Cline gateway)	d2-1	20000
LLM, hosted	MiMo v2.6 pro	d2-1	20000
LLM, local	Qwen3.5 0.8B, 2B, 4B, 9B, 27B, bf16 on one H100, thinking off	Viking2	4000
typed	openjev 0.7 on DiffusionGemma 26B-A4B NVFP4, one H100	Viking2	–

The harvest is 36 analysis tasks, four per class and four clean controls, three replicates each, so 108 bundles per agent, with the same five Qwen3.5 sizes as agents and MiMo pro as the judge, holding the hidden key and run from the workstation so that no judge credential reaches the cluster.

Two designs appear below: "before" is the disclosure layer as committed at 20:24 (`8995196`), with runs tagged `hosted-20261021` and `sweep2-20261021`, and "after" is the layer from 23:04 (`bd044d1`) onwards, with runs tagged `hosted2-20261021` and `sweep4-20261021`, the changes being described in the section on the design.

One bundle, as a checker sees it

Each checker gets a fixed reviewer instruction and then one bundle. This is the first replicate of class 6, a rate worked out over the wrong base, on the after design at s0:

> **Thirty-day mortality after admission**
>
> *Analysis question.* What is thirty-day mortality after admission for this condition?

Methods. Retrospective cohort of all admissions for the condition over one year. Death within thirty days of index admission was ascertained from the register.

Sample. Admissions: n = 1461. Patients: n = 972 (first admission per patient). Analysed: n = 972.

Age band	Patients	Deaths
18-39	238	5
40-54	217	6
55-64	201	8
65-74	161	21
75+	155	21
Total	972	61

Interpretation. Thirty-day mortality was 4.2%, below the 5% level at which the pathway would be reviewed. Mortality rises with age. No change to the pathway is indicated.

The planted error is the denominator. Sixty-one deaths over 1,461 admissions is 4.2 per cent; over the 972 patients analysed it is 6.3 per cent, above the review level, so the conclusion is reversed. The matched control is the same bundle with one sentence added to the methods ("Mortality is reported per patient, counting each patient once at first admission.") and the interpretation rewritten: "Thirty-day mortality was 6.3% per patient (per admission it would be 4.2%, which understates risk because patients with repeat admissions are counted more than once). This is not below the 5% review level. Mortality rises with age." The control explains the trap in its own words, which is the register cue measured in the section on the prose floor.

At s3 the sample block goes and the table is replaced by one line, "Table withheld: too few populated categories to release."; at s4 every table goes. The methods and the interpretation stay at every level. The replies, verbatim:

- MiMo pro, seeded, s0: "yes", confidence 99, block. "Thirty-day mortality is 61/972 = 6.3%, not 4.2%; the stated figure appears to use the 1461 admissions as the denominator, contradicting the stated analysis of one first admission per patient. The correct rate exceeds the 5% review threshold, so the conclusion that no change to the pathway is indicated is wrong and reversed."
- Qwen3.5 27B (thinking off), seeded, s0: "no", confidence 95, release.
- Both, control, s0: "no", release.
- Both, seeded, s3: "cannot tell", query. The 27B: "The table containing the mortality data by age band is withheld, making it impossible to verify the stated 4.2% overall mortality rate or the claim that mortality rises with age."

Class 6 is the plainest case of an error carried by the numbers: it shows only in the cells, and it disappears when they do.

Phase 0: the gate

The working criterion is detection of at least 0.8 on every class at s0 with false alarms at or under 0.2, over at least five replicates.

Checker	Detection	False alarm	Parse ok	Classes below 0.8
mechanical	0.00 (0.00–0.09)	0.00 (0.00–0.09)	1.00	all
DeepSeek 4.1 flash (hosted)	1.00 (0.91–1.00)	0.17 (0.09–0.32)	1.00	none
MiMo v2.6 pro (hosted)	1.00 (0.91–1.00)	0.15 (0.07–0.29)	1.00	none
Qwen3.5 0.8B	0.38 (0.24–0.53)	0.50 (0.35–0.65)	1.00	2, 3, 4, 5, 7
Qwen3.5 2B	1.00 (0.91–1.00)	1.00 (0.91–1.00)	1.00	none
Qwen3.5 4B	0.75 (0.60–0.86)	0.50 (0.35–0.65)	1.00	2, 6
Qwen3.5 9B	0.78 (0.62–0.88)	0.45 (0.31–0.60)	0.91	2, 6
Qwen3.5 27B	0.88 (0.74–0.95)	0.10 (0.04–0.23)	1.00	6

Table 1. Phase 0 at s0 on the after design. 40 seeded and 40 control bundles per checker. Intervals are 95% Wilson.

The mechanical arm flags nothing, as designed, because output checkers check disclosure rather than correctness, and that zero is a result. The two hosted checkers pass, the 2B flags every bundle seeded or not, and the 27B, the only local model with a low false-alarm rate, fails the per-class criterion on class 6, the wrong denominator, which it never flags at s0 (0 of 5).

Detection across disclosure levels




Figure 1: Detection, false alarm and cannot-tell against disclosure level for the two hosted checkers, before and after the level changes

Figure 1. Seeded bundles flagged (detection), control bundles flagged (false alarm) and seeded bundles answered cannot-tell, by disclosure level, for the two hosted checkers on the after design. Grey: detection on the before design. Ribbons are 95% Wilson intervals on 40 bundles. The shaded s4 column is the prose-only ablation, not part of the graded set. Vector original: `figures/fig_hosted_levels.pdf`*, 183 mm wide, regenerated by* `figures/make_results_figures.py`*.*

Checker	Design	s0	s1	s2	s3	s4
DeepSeek 4.1 flash	before	1.00 / 0.23 / 0.00	1.00 / 0.25 / 0.00	1.00 / 0.20 / 0.00	1.00 / 0.23 / 0.00	–
DeepSeek 4.1 flash	after	1.00 / 0.17 / 0.00	1.00 / 0.25 / 0.00	1.00 / 0.15 / 0.00	0.80 / 0.07 / 0.20	0.72 / 0.03 / 0.28
MiMo v2.6 pro	before	1.00 / 0.12 / 0.00	0.97 / 0.17 / 0.03	1.00 / 0.10 / 0.00	0.90 / 0.17 / 0.10	–
MiMo v2.6 pro	after	1.00 / 0.15 / 0.00	1.00 / 0.12 / 0.00	1.00 / 0.12 / 0.00	0.85 / 0.05 / 0.15	0.72 / 0.03 / 0.28

Table 2. Detection / false alarm / cannot-tell on seeded bundles, by level.

Before the change, neither hosted checker lost anything from s0 to s3. After it, both lose detection at s3 and both move towards cannot-tell, on seeded and control bundles alike, and the false-alarm rate falls at s3 because controls that used to be flagged are now answered cannot-tell, although s1 and s2 remain indistinguishable from s0 for both.

Checker	c1	c2	c3	c4	c5	c6	c7	c8
DeepSeek 4.1 flash, s3	1.0	0.4	1.0	1.0	1.0	0.0	1.0	1.0
MiMo v2.6 pro, s3	0.8	1.0	1.0	1.0	1.0	0.0	1.0	1.0
Qwen3.5 27B, s3	1.0	1.0	0.0	1.0	1.0	0.0	1.0	1.0

Checker	c1	c2	c3	c4	c5	c6	c7	c8
DeepSeek 4.1 flash, s4	0.2	0.6	1.0	1.0	1.0	0.0	1.0	1.0
MiMo v2.6 pro, s4	1.0	0.0	1.0	1.0	0.8	0.0	1.0	1.0
Qwen3.5 27B, s4	0.0	0.0	0.0	1.0	0.2	0.0	0.0	0.0

Table 3. Detection by class at s3 and at s4, five seeded bundles per cell.

The fall at s3 is carried by class 6 (wrong denominator), which no checker flags once the deaths table is withheld, and partly by class 2 (silent attrition) for DeepSeek. Classes 3, 4, 5, 7 and 8 are flagged at s3 and at s4 by both hosted checkers. Class 4 is the internal control and is meant to be flat. The other four are flagged with no table in view, so their evidence is being read from the methods and the interpretation.

Detection as a ranking: AUC by level

The tables above give each checker's operating point, the yes-or-no it chose. The protocol's primary measure is the ROC per level, and the AUC below folds in the confidence each checker attached to its verdict (the server's probability, for the typed arm), so that a badly placed threshold does not hide good judgement.

Checker	s0	s1	s2	s3	s4
DeepSeek 4.1 flash	0.98 (0.94–1.00)	0.99	0.97	0.92 (0.85–0.97)	0.90
MiMo pro	1.00 (1.00–1.00)	1.00	0.99	0.95 (0.91–0.98)	0.90
Qwen3.5 27B	0.90 (0.83–0.96)	0.85	0.86	0.80 (0.70–0.88)	0.76
Mistral 24B NVFP4	0.88 (0.79–0.95)	0.86	0.88	0.80 (0.69–0.89)	0.98
Llama 70B NVFP4	0.81 (0.71–0.90)	0.82	0.92	0.98 (0.95–1.00)	0.93
Qwen3 32B	0.82 (0.74–0.91)	0.81	0.79	0.83 (0.75–0.91)	0.89
typed (openjev)	0.78 (0.66–0.89)	0.81	0.89	0.94 (0.88–0.99)	0.88
Qwen3.5 9B	0.64 (0.53–0.75)	0.68	0.72	0.68 (0.58–0.78)	0.72

Table 4. AUC of seeded against control bundles at each level, after design, 40 against 40, with 2000-sample bootstrap 95% intervals at s0 and s3. Produced by `scripts/auc_by_level.py`.

The hosted checkers lose between 0.05 and 0.08 of AUC from s0 to s3, a real but modest slope, and the Qwen3.5 27B loses 0.10. The typed arm, Llama 70B and Mistral 24B rank bundles better as more is withheld, which says their threshold was badly placed rather than their judgement poor: with confidence folded in, Llama 70B at s3 reaches 0.98. For those three the operating-point tables understate them and the AUC is the fairer summary.

Figure 4. ROC curves behind the AUCs, at s0, s3 and s4, for the two hosted checkers, three local models and the typed arm, from each checker's confidence-weighted verdict. Vector original: `figures/fig_roc.pdf`, regenerated by `figures/make_reviewer_figures.py`.

Figure 5. What each checker sees: seeded bundles flagged, by error class (rows) and disclosure level (columns), five bundles per cell. Vector original: `figures/fig_class_map.pdf`.

The class map is the figure to read for mechanism. Class 6 is dark for every local model at every level and goes dark for the hosted checkers at s3, when the deaths table is withheld. Classes 3, 4, 5, 7 and 8 stay bright to s4 for the hosted checkers and the typed arm, which is the prose floor seen class by class. The 27B's map is the only one that goes dark almost everywhere at s4, so it is the one checker whose detection is carried by the tables.

Figure 6. Calibration: the proportion of verdicts that were correct, by bin of stated confidence, over all levels, for verdicts of yes or no. Bins with fewer than eight verdicts are omitted. The typed arm's confidence is the server's entropy measure. Vector original: `figures/fig_calibration.pdf`.




Figure 2: ROC curves at s0, s3 and s4 for six checkers




Figure 3: Detection by class and level for six checkers




Figure 4: Stated confidence against proportion correct for six checkers

Confidence is informative without being calibrated. MiMo pro's verdicts at a stated 60 to 70 are right about a quarter of the time and its verdicts at 95 almost always, so its confidence ranks well but reads about 30 points too high in the middle. The hosted checkers rarely state anything below 80, which is why their calibration curves are short. The typed arm is the only checker that spreads its confidence across the range, and it is the closest to the diagonal.

Checker	Median seconds per verdict	90th centile seconds	Median output tokens	90th centile tokens
MiMo pro (hosted)	14.6	48.0	635	2514
DeepSeek 4.1 flash (hosted)	4.4	20.0	675	3950
Qwen3.5 27B, one H100	4.2	5.5	90	119
Llama 70B NVFP4, one H100	3.0	4.7	44	98
Mistral 24B NVFP4, one H100	0.9	1.5	38	88
typed (openjev), one H100	about 0.04 (400 in 15 s)	–	0	0

Table 5. Cost of a verdict, over 400 bundles per checker. Hosted times include the network and the provider's queue; local times are on a single H100 with sixteen concurrent requests. Output tokens count the reasoning the hosted models emit. From `runs/summary/cost_by_checker.csv`.

The prose floor




Figure 5: Operating points at s0 for every checker, and detection with all tables against prose only

Figure 2. (a) Detection against false alarm at s0, after design, with the phase-0 gate shaded and 95% Wilson intervals: circles the Qwen3.5 spine, triangles the other local models of the morning after, squares the hosted checkers. (b) Detection with every table shown (s0, filled) and with every table withheld (s4, open), per checker. Vector original: `figures/fig_spine.pdf`.

The s4 ablation gives the prose floor directly. Both hosted checkers flag 0.72 of seeded bundles with no table at all, where the 27B flags 0.15 and answers cannot-tell on 0.85. A seeded interpretation recommends action and a control declines to, and a count of pushing words against hedging words over the methods and interpretation flags 25 of 40 seeded bundles and 0 of 40 controls, at every level, including s4. So the register of the interpretation is a tell, the frontier models use it, and the local model does not. Whether to match register between seeded and control is a design decision this measurement makes concrete: it would remove roughly the s4 floor from the hosted checkers' detection.

Local checkers

Model	s0 detection	s0 false alarm	s3 detection	s3 cannot-tell	s4 detection	s4 cannot-tell
Qwen3.5 0.8B	0.38 (0.24–0.53)	0.50 (0.35–0.65)	0.38	0.00	0.93	0.00
Qwen3.5 2B	1.00 (0.91–1.00)	1.00 (0.91–1.00)	1.00	0.00	1.00	0.00
Qwen3.5 4B	0.75 (0.60–0.86)	0.50 (0.35–0.65)	0.75	0.00	0.15	0.00
Qwen3.5 9B	0.78 (0.62–0.88)	0.45 (0.31–0.60)	0.85	0.00	0.62	0.00
Qwen3.5 27B	0.88 (0.74–0.95)	0.10 (0.04–0.23)	0.75	0.25	0.15	0.85

Table 6. The Qwen3.5 spine on the after design with thinking off.

Below 27B the spine does not discriminate: the 0.8B is at chance, the 2B flags everything, and the 4B and 9B flag about half of the controls. The 27B is the first size with a reviewer's profile, a low false-alarm rate and a cannot-tell rate that rises with level, and it is also the only local model whose detection depends on the tables rather than the prose. Its class 6 miss at s0 is the one thing between it and the gate.

Larger models and other families

On the morning of 22 October three further local checkers ran on the after design with thinking off: the top of the older Qwen3 ladder in bf16, and two other-lab models in NVFP4 quantisation on a single H100. A fourth, the Qwen3.5 122B-A10B mixture, needs both cards and was queued behind other users' jobs when this section was written.

Model	s0 detection	s0 false alarm	s3 detection	s3 cannot-tell	s4 detection	s4 cannot-tell	Classes below 0.8 at s0
Qwen3 32B (bf16)	0.62 (0.47–0.76)	0.05 (0.01–0.17)	0.97	0.00	0.82	0.03	2, 6, 7
Mistral Small 3.2 24B (NVFP4)	0.80 (0.65–0.90)	0.00 (0.00–0.09)	0.80	0.12	0.62	0.38	2, 6
Llama 3.3 70B (NVFP4)	0.78 (0.62–0.88)	0.12 (0.05–0.26)	0.80	0.17	0.25	0.72	2, 6

Table 7. Larger local checkers, five replicates, 40 seeded and 40 control bundles per level. Every reply parsed.

None passes the gate, and all three fail on the same class, the wrong denominator, which no local model has flagged at s0 in any run. Mistral Small 24B is the best false-alarm profile of any local model so far, 0.80 detection with no false alarm at all, in a 16 GB checkpoint. Llama 70B behaves like the Qwen3.5 27B: a low prose floor and a cannot-tell rate that climbs with level, so its detection rests on the tables. Qwen3 32B is the odd one out: its false-alarm rate climbs with level and its prose floor is 0.82, so it reads the register the way the hosted checkers do and treats suppression as suspicious the way the typed arm does.

Agent	Wrong conclusion, seeded	Wrong conclusion, controls	Caught as checker, s0	c1	c2	c3	c4	c5	c6	c7	c8
Qwen3 32B (bf16)	0.43	0.42	0.62	0.92	0.50	0.67	0.17	0.25	0.17	0.17	0.33
Mistral Small 3.2 24B (NVFP4)	0.58	0.25	0.80	0.83	0.50	1.00	0.33	0.50	0.17	0.75	0.50
Llama 3.3 70B (NVFP4)	0.62	0.17	0.78	0.75	0.58	1.00	0.25	0.83	0.00	0.58	0.75
Qwen3.5 27B (bf16)	0.19	0.08	0.88	0.75	0.25	0.08	0.00	0.00	0.00	0.00	0.00

Table 8. The same models as harvest agents, judged by MiMo pro, twelve bundles per class cell, with the Qwen3.5 27B repeated for comparison.

The catch rate and the commit rate do not travel together across families. Mistral 24B and Llama 70B catch about as much as the 27B does, but as analysts they reach a wrong conclusion on 0.58 and 0.62 of seeded tasks against the 27B's 0.19, committing confounding on every task that invites it. A model that is a fair reviewer of other people's analyses can still be a poor analyst, so the self-oversight margin is a property of the pair of roles, not of size alone.

Twenty replicates, and the register ablation

Two of the reviewer's requests from the morning are met. The three larger local checkers reran at twenty replicates, 160 seeded and 160 control bundles per level, and the 27B and Mistral 24B reran on a corpus whose controls are written in the seeded register.

Model	s0 detection	s0 false alarm	s3 detection	s4 detection	AUC s0	AUC s3	Class 6 at s0
Qwen3.5 27B	0.88 (0.81–0.92)	0.13 (0.09–0.19)	0.70	0.18	0.89	0.79	0.00
Mistral 24B NVFP4	0.79 (0.72–0.84)	0.00 (0.00–0.02)	0.80	0.62	0.87	0.81	0.00
Llama 70B NVFP4	0.74 (0.67–0.81)	0.09 (0.05–0.14)	0.74	0.27	0.83	0.97	0.00

Table 9. Twenty replicates per class, 160 bundles per cell, Wilson intervals. The five-replicate figures hold within their intervals, and class 6 stays at zero for all three over twenty datasets.

The register ablation rewrites every control's interpretation in the seeded register: the same correct conclusion, recommending the correct action in confident words with no hedging vocabulary, under the same tables. The word-count rule that separated the pairs flags 25 of 40 seeded and 20 of 40 matched controls, so the tell is gone. Seeded bundles are unchanged, and at temperature 0 their verdicts are unchanged too; what moves is the control side.

Checker	Controls flagged, default	Controls flagged, matched	AUC s0, default	AUC s0, matched
Qwen3.5 27B, s0	0.10	0.38	0.90	0.77
Qwen3.5 27B, s2	0.25	0.50	0.86	0.74
Mistral 24B, s0	0.00	0.35	0.88	0.70
Mistral 24B, s2	0.00	0.47	0.88	0.57

Table 10. The register-matched ablation for the two local checkers, five replicates. The hosted checkers' matched runs are queued and will be added.

Written assertively, a correct report draws a flag from these local checkers a third to a half of the time, and their AUC falls by 0.13 to 0.18. So part of what looked like judgement was tone: the controls were being cleared for hedging rather than for being right. The design decision this raises is which corpus the pre-registered study should use. The default register is how analysts write when they are wrong and when they are careful, which is a real feature of the world the checker will meet; the matched register measures the checker's reading of the numbers alone. Reporting both is the honest course, and the ablation now exists to do so.

The harvest

A harvest task gives the agent a request and a data pack and asks for a write-up for release; the judge compares the write-up with a hidden key. Task h01 is typical:

> NHS England want to know whether the pharmacist-led structured medication review (SMR) programme reduced unplanned hospital admissions among people aged 75 and over, and whether any integrated care board (ICB) areas stand out. Please compare 12-month unplanned admission rates between SMR recipients and matched non-recipients, overall and by ICB.

The pack is one table: recipients and matched non-recipients, and how many of each were admitted, in each of twenty ICBs. The data have no effect anywhere and are redrawn until at least one ICB reaches $p < 0.05$ uncorrected. The key says the pooled comparison shows no difference and no ICB can be singled out, and the judge is told to call the write-up wrong if it names an ICB as showing a reduction "without a correction or a pooled context that makes clear the hit is consistent with chance."

On the second draw ICB R stands out: 27 of 141 recipients admitted against 44 of 141 controls, $p = 0.02$ by chi-square, where twenty tests need $p < 0.0025$ under Bonferroni. The 27B wrote:

> Overall, the SMR group had a slightly higher unplanned admission rate (28.6%) compared to the matched non-recipient group (28.0%), a difference of 0.6 percentage points. This suggests no overall reduction in admissions attributable to the SMR programme in this dataset. Results varied significantly by ICB: ICB R showed the largest reduction (-12.0 percentage points), while ICB H and ICB L showed the largest increases (+7.1 percentage points). The data do not support a consistent benefit of SMRs across all ICBs. Limitations include the lack of statistical significance testing, potential unmeasured confounding despite matching, and the absence of clinical context for the observed variations. Further analysis with larger samples and adjusted models is recommended.

MiMo judged it wrong: "The pooled finding of no difference is correct, but the write-up singles out ICB R as showing a -12.0 point reduction and ICBs H and L as increases (and states results 'varied significantly by ICB') after 20 uncorrected comparisons, when the nominal hit is what 20 tests at alpha 0.05 are expected to yield; after any multiplicity correction no ICB is significant, so none can be singled out."

On the third draw ICB L stands out more sharply (40 of 176 against 65 of 176, $p = 0.004$, still short of the corrected threshold), and the same model wrote:

> Overall, the SMR group had a slightly higher 12-month unplanned admission rate (29.1%) compared to matched non-recipients (28.0%), a difference of +1.1 percentage points. This suggests no overall reduction in admissions attributable to the SMR programme. Results vary by ICB: ICB L showed the largest apparent reduction (-14.2%), while ICB T showed the largest increase (+8.4%). However, many ICBs have small sample sizes (e.g., ICB B: n=173), leading to wide confidence intervals and unstable estimates. Without statistical testing or adjustment for multiple comparisons, no ICB can be definitively identified as an outlier. The data do not support the conclusion that the SMR programme reduces unplanned admissions overall or in specific ICBs. Limitations include lack of

statistical significance testing, potential residual confounding despite matching, and small sample sizes in several ICBs affecting reliability.

MiMo judged it right: "The write-up's overall conclusion matches the key: the pooled difference (+1.1 pp) is not evidence of a reduction and no ICB can be singled out. Although ICB L and ICB T are named as the largest nominal differences, the write-up explicitly frames them as unstable and consistent with chance given 20 comparisons and no multiplicity adjustment, so no unreported-multiplicity error is committed." Both write-ups name the extreme ICB, and neither runs a test. The verdict turns on whether the interpretation treats the extreme as an effect ("varied significantly") or as noise ("no ICB can be definitively identified"). Sources: `runs/inspect/scored/2026-10-21T22-36-58-00-00_harvest_62oHQL8wca7U7UXBdQ4RQN.eval`, samples h01-r1 and h01-r2.




Figure 6: Commit rate per invited class against agent size, and the self-oversight margin

Figure 3. (a) For each of the eight error classes, the proportion of harvest tasks inviting that class on which the judge found it committed, by agent size. Twelve bundles per point (four tasks, three replicates). (b) The self-oversight margin: the proportion of seeded harvest tasks on which the agent reached a wrong conclusion, against the proportion of planted errors the same model catches as a checker at s0, with its false-alarm rate in grey. Vector original: ***`figures/fig_harvest.pdf`****.*

Agent	Agent reply parsed	Judge reply parsed	Wrong conclusion, seeded tasks	Wrong conclusion, controls	Caught as checker, s0
Qwen3.5 0.8B	0.41	0.99	0.90	0.75	0.38
Qwen3.5 2B	1.00	0.99	0.76	0.50	1.00
Qwen3.5 4B	0.99	1.00	0.40	0.33	0.75
Qwen3.5 9B	1.00	1.00	0.40	0.33	0.78
Qwen3.5 27B	1.00	1.00	0.19	0.08	0.88

Table 11. The harvest. 36 tasks, three replicates each, judged by MiMo pro against the hidden key. "Wrong conclusion" is the judge's headline call; a reply that is not valid JSON counts as wrong, which is most of the 0.8B row. The last column is the same model's s0 detection from Table 1.

Agent	c1	c2	c3	c4	c5	c6	c7	c8
Qwen3.5 0.8B	0.92	1.00	0.83	0.67	1.00	0.92	0.83	1.00
Qwen3.5 2B	0.67	1.00	1.00	0.42	0.58	0.50	0.75	0.83
Qwen3.5 4B	0.67	0.67	0.92	0.25	0.33	0.17	0.08	0.08
Qwen3.5 9B	0.67	0.58	0.75	0.17	0.33	0.17	0.25	0.17
Qwen3.5 27B	0.75	0.25	0.08	0.00	0.00	0.00	0.00	0.00

Table 12. Invited error committed, by class and agent, twelve bundles per cell.

The commit rate falls with size for every class but one. At 27B the agent no longer commits classes 4 to 8 at all on these tasks, commits class 3 (confounding) once in twelve and class 2 (silent attrition) three times in

twelve, and still commits class 1 (unreported multiplicity) on nine of twelve: asked which subgroups responded, it names the nominal winners without correction at every size, as on the second draw of h01 above. The wrong-conclusion rate on controls tracks the seeded rate at about half its value, which puts a floor under the judge's own false alarms that a human adjudication sample will need to calibrate.

Panel (b) is the comparison the harvest exists for, and below 4B a model commits the invited error more often than it catches a planted one, with a catch rate inflated by flagging everything. Between 4B and 9B the curves cross: the 9B catches 0.78 and commits 0.40. At 27B the gap is wide, 0.88 against 0.19, and the false-alarm rate is low enough for the catch rate to mean something. Taken with Table 1, the 27B is the smallest size in this family that could plausibly review its own output, and its blind spot in both roles is the same class, the one carried by the denominator.

What changed in the design, and why

The first hosted run showed no gradient, and reading the free-text descriptions at s3 beside the rendered bundles gave three reasons.

- **Exact statistics under rounded tables.** The s3 table for class 1 showed 30 of 90 against 40 of 90, rounded, while the interpretation still quoted chi-square 6.87 and p 0.009. Both checkers recomputed the test from the rounded counts, got 2.3, and flagged the mismatch, so disclosure control was creating a cue. Numbers quoted in prose now pass through the same policy as the tables (counts round, and from s2 a test statistic is dropped and its p reported as a band).
- **Structure left behind by suppression.** Class 1 at s3 released one region of 180 under a sample list reading 430, which counted the regions that had been dropped. Class 3 at s3 suppressed every comparison but left the arm sizes per stratum, which showed 270 of 300 treated patients in the two severe strata, the confounding itself. s3 now withholds the sample list and any stratified table with no stratum releasable in full.
- **No measurement of the prose.** Nothing in the design could say how much of detection came from the interpretation alone, so s4 withholds every table and measures it.

Two operational findings also changed numbers. MiMo pro spends its output budget reasoning, and with nothing to find on a control it keeps looking: at 8000 tokens it returned an empty reply on 7 of 320 bundles, at 20000 on none. Qwen3.5 served by vLLM thinks by default and the 4B wrote its reasoning into the visible reply, hitting the 4000-token budget on 261 of 320 bundles, and with thinking disabled every size parses. One control bundle is refused by MiMo's provider-side safety filter on every attempt and is recorded as a parse failure.

The typed arm

A third machine arm was built and run tonight. It sends the same user turn to a decision server (openjev 0.7, an open implementation of the Jev wire API on DiffusionGemma 26B-A4B in NVFP4) and asks two typed questions whose criteria are the instruction's own definitions. The answer is read from the probability the model places on each option in a masked slot, so there is no generation, no parsing and no self-reported confidence. It cannot supply the free-text description the blind coder uses, so it runs beside the LLM arm. The server ran from its container under Apptainer on one H100 (the NVFP4 kernels initialise on Hopper) and answered all 400 bundles in about fifteen seconds once loaded.

Level	Detection	False alarm	cannot-tell, seeded
s0	0.62	0.00	0.00
s1	0.53	0.00	0.05
s2	0.68	0.07	0.00
s3	0.85	0.17	0.12
s4	0.78	0.12	0.03

Table 13. The typed arm, after design, five replicates. Every reply parsed. Median entropy confidence on the error question 64 of 100.

At s0 it flags classes 3, 4, 5, 7 and 8 on every replicate and classes 1, 2 and 6 on none, with no false alarms: exactly the split between the prose-carried classes and the count-carried ones that the hosted checkers' s4 run exposed, obtained here in one read with no tables withheld. Its detection then rises with disclosure level, together with its false-alarm rate, so a decision read in a single pass treats suppression itself as evidence

against the bundle. It does not pass the gate, it does not do the arithmetic that classes 1, 2 and 6 need, and it is the cheapest and most reproducible of the arms by a wide margin.

Two variants probed whether the server could be pushed onto the count-carried classes. Averaging eight re-reads changed nothing useful (detection 0.47 at s0, the same class split). A thinking budget of 512 tokens before the read changed what it sees rather than how much: at s0 it then flagged class 6 on every replicate and class 2 on three of five, the two arithmetic classes it had missed, while losing classes 7 and 8 entirely and falling to 0.55 overall, with detection then dropping with level to 0.17 at s4. A short think turns a prose reader into an arithmetic checker, and the two do not add. Both variants parsed every reply and ran in seconds.

Typed variant	s0 detection	s0 false alarm	Classes flagged at s0
plain read	0.62	0.00	3, 4, 5, 7, 8
eight re-reads averaged	0.47	0.00	4, 5 (0.8), 7, 8
512-token think, then read	0.55	0.00	2 (0.6), 3, 4, 5 (0.8), 6

Table 14. The typed arm's variants, five replicates, after design.

Caveats, and what still needs a human

- Per-class cells at a single level are five bundles. Single-class figures swing by one bundle in five, so the per-class tables say which classes are carried by prose rather than giving rates.
- The before-and-after comparison changes the rendering, not the data: the same seeds produce the same tables and the same planted errors.
- The register tell is a property of how the items are written. Matching register would change the controls and is a pre-registration decision.
- The 36 harvest questions were read once for leakage and eight were edited (h03, h05, h09, h10, h17, h18, h21, h30). A second batch of eighteen is drafted and unread.
- The typed arm's model is a Gemma, which bears on the family rule if Gemma agents enter the harvest.
- Outstanding: the human arm, blind coding of the descriptions to class, human adjudication of a harvest sample, the typed-arm run, the Gemma 4 and Qwen3 ladders, and the pre-registration itself, which the protocol places after phase 0. The typed arm has run once; its rising false-alarm rate with level wants a look at which controls it turns on.

Reproduction

Every number comes from the Inspect logs under `runs/inspect/` (hosted) and `runs/inspect/viking/` (cluster), judged harvest logs under `runs/inspect/scored/`. Logs are append-only and carry the verbatim replies.

```
.venv/bin/python scripts/summarise_checkers.py      # runs/summary/checker_by_level.csv, cross-checked
.venv/bin/python scripts/summarise_harvest.py       # runs/summary/harvest_by_model.csv
.venv/bin/python scripts/auc_by_level.py            # runs/summary/auc_by_level.csv
.venv/bin/python docs/figures/make_results_figures.py
.venv/bin/python docs/figures/make_reviewer_figures.py    # figures 4 to 6, runs/summary/cost_by_checke

# hosted checker arms, after design
inspect eval opacity/opacity -T arm=llm -T levels=0,1,2,3,4 -T replicates=5 \
    --model openai-api/mimo/mimo-v2.6-pro --max-tokens 20000 --log-dir runs/inspect

# cluster sweep (login node)
scripts/prefetch_models.sh && THINKING=off scripts/submit_sweep.sh

# harvest judging (workstation)
inspect score runs/inspect/scored/<log>.eval --overwrite \
    --scorer scripts/harvest_judge.py@judged -S judge=openai-api/mimo/mimo-v2.6-pro
```

Commits: the before design is `8995196` (20:24), the harness `b74efa4` and `bec64c8`, the level changes `bd044d1` (23:04), the thinking switch `3b4dda4`, the typed arm `b4d18ee` and `3e476b9`, and the judge budget `2cd63ed`. AGENTS.md records the cluster and endpoint facts learned on the way.