PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Index

A

Accumulation, 53
Accuracy:
  numerical integration, 83–84
  sensor, 383, 772–773
Adaptive tuning:
  expert system, 528
  gain scheduling, 518, 529, 709, 715
  input conversion, 519
  reasons for, 512–517
  relay auto-tuning, 527
  selection of method, 529
  valve characteristic, 520–525
Alarms, 795, 890
Aliasing:
  antialiasing filter, 393
  due to sampling, 362, 989
Amplitude:
  amplitude ratio, 121–123, 316, 412, 988-989
  response to sine, 121
  (*See also* Frequency response)
Analog:
  computation, 257
  signals, 212–215, 358–359
Anti–reset windup, 399–402, 604–605, 715
Array (*see* Relative gain array)
Averaging filter, 394
Averaging level control, 563–564, 569–570

B

Bandwidth, 419
Benefits, control, 28–35, 423–425
Blending:
  controllability, 627, 637
  gasoline, 866
  interaction, 632
  loop pairing, 663
  model, 621
  operating window, 625

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Blending—*Cont.*
optimum, 866–870
tuning for, 646–648
Block diagrams:
algebra, 116, 118, 143, 244
cascade, 463
definition of, 115
feed forward, 489
multiloop, 630
IMC, 592, 994
reduction to transfer function, 116, 244
series, 143
single-loop, 243, 974
Smith predictor, 600
Bode:
cascade, 468
closed-loop, 412–415
generalized plots, 323–326
key aspects of plots, 328
plot, 123
stability criterion, 313–317
limitations of, 316
Boiler:
control of, 27, 474
efficiency of, 32–34
optimization of, 861–865
(*See also* Steam system)
Bounded input-output stability, 304, 307–308

C

Cascade:
block diagram, 463
degrees of freedom, 460–461
design criteria for, 461
examples:
chemical reactor, 471–473
distillation, 690–691
fired heater, 473
heat exchanger, 458–460
levels of, 473
performance, 462–468
primary variable, 460
secondary variable, 460
terminology, 460
transfer functions, 462
tuning, 469
Cause-effect relationship, 6–7, 114, 651
Centralized control, 617, 727
Characteristic, valve:
examples, 520–525
inherent, 520
specifying for linearizing loopgain, 524
Characteristic equation:
definition, 309, 630
relation to stability, 309–310, 316, 643, 987
Characteristic polynomial:
definition of, 108, 932
relation to stability, 109
roots of, 109, 932
Checklist, for design, 820–822
Chemical reactor, packed bed:
cascade, 471–473
feedforward, 495–497
inferential, 549–552
variable structure, 713–714
Chemical reactor, stirred tank, 62, 72, 84–86
isothermal, 62, 72
nonisothermal:
cascade design, 475–476
control design, 835
control performance, 438–440
linearized, 900
model for, 85, 897–901
multiple input-output, 163–165
operating window, 781–783
recycle, with, 785
selecting variables, 216–218
signal select, 710–712
transfer function, 902
series:
block diagram, 944
inverse response, 944–945
model, 64–67, 943–944
transfer function, 944
stability, without control, 902–906
steady-states:
calculating, 902–904
multiple, 905
stabilizing via control, 905
Combustion:
benefits for, 32–34
excess oxygen control, 27
fuel control, 500–501
(*See also* Fired heater)
Complex numbers:
magnitude, 122, 316–317, 936–937
phase angle, 122, 316–317, 936–937
polar form, 122, 316–317, 936–937

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Composition control:
blending and mixing, 270, 282, 512–519, 646–648
chemical reactor, 37, 216, 438, 475, 835
flash, 23, 537–544, 768, 802–803
(*See also* Distillation)
Computation:
analog, 257–258
digital, 358–362
Computer:
analog, 257–258
digital, 358–362
control implementation, 365–367, 974, 983–989
simulation, 82–84, 422–425
(*See also* Digital control)
Computer-aided calculations, 82–84, 421–422
Conservation
component, 53
energy, 53, 898
material, 53
Constitutive relationships, 54
Constraints, 26
control, 715–720
hard or soft, 767–770
valve position control, 718–719
(*See also* Operating window)
Continual improvement, 859
Continuous cycling, 342–343
Continuous-flow stirred tank (CST):
chemical reactor:
heat-integrated, 785
with recycle, 155–157
(*See also*, Chemical reactor, stirred tank)
heater, 76–80, 253–257, 458–461, 483–486
mixer, 186–187, 223–225, 270, 512
Continuous-time variables, 98, 212
Control:
algorithms:
DMC, 735–748
IMC, 590–600
lead/lag, 485–486
PID, 252
Smith predictor, 600–603
approaches, 228
automated vs. manual, 228–231
benefits, 28–35, 425
definition, 6
design, 216–218, 823, 834
feedback, 6–7, 212, 243
Control—*Cont.*
feedforward, 488
objectives, seven categories, 20–25, 768, 838
(*See also* Model predictive control)
Control design form, 768, 838
Control objectives, 20, 216, 269, 768
Control performance:
best possible, 426–427, 490
control system factors, 433–440
economic analysis, (*see* Benefits, control)
faction dead time, 279, 426–429
factors affecting, 444
by frequency response, 412–415
measures, 219–223, 240–241
multivariable systems:
disturbance type, 667, 677–679
interaction, 616
(*See also* Relative disturbance gain)
process factors, 425–432
robust, 268–269, 411
by simulation, 422
Control system:
hierarchy, 829
layout, 9–10, 212–213, 359–361
Control valve:
characteristic, 520
dynamics, 776
failure position, 777
range, 776
selection, 217
Controlled variable:
selection of, 7–8, 225, 536, 771–773, 775, 787, 840
Controller:
dimensionless gain, 397
error, 242–243
execution frequency, 370, 373
flowchart, 403
frequency response of, 325–326
location, 9–10
manipulated variable, 217
measured variable, 216
nonlinear, 517, 567
performance (*see* Control performance)
sense switch, 396–397
tuning:
Ciacone, 278–286
comparison, 347
dynamic matrix, 750
fine, 289–293
goals, 268–269

PDF-XChange Editor Click to BUY NOW! www.tracker-software.com

Controller—*Cont.*
tuning—*Cont.*
IMC, 598
Lopez, 287
multiloop, 638–646
robustness, 268–269, 338–341
Ziegler-Nichols, 329–330, 347
Corner frequency, 323
Critical frequency, 315
Crossover frequency, 315
CST (*see* Continuous-flow stirred tank)

D

Damping:
coefficient, 138–139
critically, 139
overdamped, 139
underdamped, 139
Dead time:
Bode plot, 324
compensation, 600
computer programming, 922
definition, 103
discrete, 977
effect on performance, 426–427
effect on stability, 334–337
frequency response, 318
Padé approximation, 913
Decay ratio, 220
Decentralized control, 616–617
Decoupling:
application criteria, 690
designs:
calculated controlled variables, 685–686
calculated manipulated variables, 684–685
explicit controller calculations, 686–689
performance, 689–690
sensitivity to errors, 689–690
(*See also* Interaction)
Degrees of freedom:
in control design, 217, 460–461, 708, 711, 778
effect of control, 254, 778
in modelling, 54–55
Derivative:
approximation, 366
definition of, 56
filter, 402
Derivative—*Cont.*
Laplace transform of, 101
mode:
behavior, 249–252
frequency response, 326
noise transmission, 252, 292–293
time, 250
z-transform, 978
Design, control:
control design form (CDF), 768–769, 838–839
controllability, 780–781
degrees of freedom, 778
dynamics:
disturbance, 444
feedback, 444
loop pairing, 695
operating window, 624–626, 681, 781, 788–789
procedure, integrated, 834
process decomposition, 831
sequence of steps, 823
temporal hierarchy, 825
Detuning factor, 678
Deviation variables, 71, 111
Diagnostic:
model, 183
tuning, 290
Difference equations:
controllers, 367, 493, 595, 994–995
discrete models:
approximate, 923
empirical, 188
exact, 923, 986
Differential equations:
discrete form, 188, 923, 986
linearization of, 70–72
numerical solution:
error control, 84
Euler, 83, 423
Runge-Kutta, 84
solution by:
integrating factor, 895
Laplace transforms, 102
Digital control:
computing network, 359
dynamic matrix control, 735
internal model control, 595
lead/lag, 493
performance of PID, 367–369
ringing, 370–371, 982, 992
sampling:
hold, types of, 364–366
period selection, 369

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Digit[illegible]ontrol—*Cont.*
[illegible]pling—*Cont.*
simulation, 423
tuning modifications for, 370
Dimensional analysis, tuning, 278–286
Direct-acting feedback, 396
Distillation:
cascade control, 690
composition control of:
inferential, 545–549
interaction in, 637
operating window, 625–626
relative disturbance gain (RDG), 679–680
tuning for, 648
decoupling control, 689
dynamic matrix control of, 746–747, 754–756
feedforward control of, 500–501
industrial case study, 949–960
modelling of:
empirical, 62, 622–623
fundamental, 157–163
regulatory control of:
energy balance, 664
material balance, 665
Distributed control system:
advantages of, 361
structure of, 359
Disturbance:
causes, 7
interaction effects (*see* Relative disturbance gain)
models, 220, 224, 415, 444, 496, 666
response, closed-loop:
frequency response, 412–418
simulation, 422–425
Dominant variable, 779, 827
Draining tank, 75–77, 106–107
Drawings, 12–13
instrument symbols, 889–892
process equipment, 892–894
valve symbols, 892
Dynamic compensation, 551
Dynamic matrix control (DMC):
approximate inverse for, 729
controller formulation, 737–738
discrete step process model, 730–734
feedback signal, 740–742
future prediction, 735
horizon, 737
model, step-weight, 730
move suppression, 743
Dynamic matrix control (DMC)—*Cont.*
multivariable formulation, 744–748
predictive structure, 728
single-variable formulation, 738
tuning, 750
Dynamics:
dead time, 103, 140, 324, 328
first-order systems, 57, 137, 323, 328
integrating process, 140–141, 564–566, 325, 328
recycle systems, 155, 840
second-order systems, 138–140, 324, 328
series systems, 143, 328
staged systems, 157
(*See also* Modelling procedure)

E

Economic value of control, 28–35
Electrical circuit, 137, 138
Emergency control systems, 20, 230–231, 794–799
Empirical modelling:
dead time, 144, 179–181, 190
diagnostics, 61, 183, 194
experimental design for, 181, 188
multivariable systems:
open-loop, 197, 622
partial closed-loop, 629, 670
process reaction curve, 179
signal-to-noise, 182
six-step procedure, 176
statistical method, 188
use in control analysis, 280, 338–343
Energy balance:
in modelling, 53–54, 898
strategy in distillation, 664
Energy reduction, control systems for, 23, 716–717, 791, 861–866
Environmental protection, 21, 768, 797
Equal-percentage characteristic, 521
Equilibrium, ideal stage, 159
Equilibrium, phase, 159, 538
Error:
measures of control performance, 219
in sensor measurement, 383, 773
variable used by controller:
model predictive, 585, 741
proportional-integral-derivative, 242–243

PDF-XChange Editor Click to BUY NOW! www.tracker-software.com

Euler:
identity, 934
numerical integration, 83
Evaporator, 676
Evolutionary operation, 871
Experimental modelling (*see* Empirical modelling)
Exponential filter:
analog, 390, 393
digital, 392, 988
predictive control, 593
principle, 389
External feedback, 399
External variable, 54,

F

Factor, partial fractions, 107, 931
Factorization, model, 590
Feasible region (*see* Operating window)
Feedback control:
block diagram for, 243, 463, 586, 630
components of loop, 212–213
compared with feedforward, 488
definition, 6
negative, 6
performance (*see* Control performance)
pluses and minuses, 229
positive, 142
selecting variables in, 216–218, 438, 536, 775, 779, 828
(*See also* PID; IMC; DMC)
Feedforward control:
algorithms for:
digital, 492–493
general derivation, 485
lead/lag, 485–486
transfer function, 488
block diagram for, 489
design criteria for, 487
goal, 484
digital implementation, 492
examples:
chemical reactor, 495
distillation, 501
fired heater, 499–500
heat exchanger, 497–498
feedback:
combined with, 486, 497
comparison with, 488
Feedforward control—*Cont.*
perfect, 484
performance guidelines:
dynamic behavior, 491
model error, 490
stability, effect on, 488, 502
tuning, 493
Fieldbus, 375
Filtering:
algorithms:
continuous, 390
discrete, 392, 988
aliasing in, 393
low-pass, 390
perfect, 390
performance, effect on, 391
reasons for, 389
z-transform, 979
Final control element, 5, 10, 212–213, 226, 438, 776–777
Final value theorem, 104, 979
Fine tuning, 289–293
Finite difference, 366–367, 493, 923
Fired heater:
cascade control, 494
feedforward, 522–524
industrial case study, 961–972
loop pairing, 694–695
outlet temperature control, 29
First-order system:
continuous, 137
discrete approximation, 922
dynamic behavior, 59, 137–138
Bode diagram, 323
example systems, 137
frequency response, 328
time-domain responses, 136
series of:
interacting, 145–148
noninteracting, 143–145
transfer function for, 144
Flash process:
alarms for, 795–796
control design for, 802
control objectives for, 20–25, 768–769
controllability of, 787–788
degrees of freedom, 787–788
dynamic response of, 803
inferential control of, 537–541
operating window, 788–789
safety control, 794–799

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Flo
ntrol, 13
measurement, 387
ratio, 499, 684
value, 80
Forcing function, 895
Frequency distribution, 31–35
Frequency response, 121
amplitude ratio, 121–122
of basic systems, 323–326, 328
Bode plot, 123
closed-loop control performance, 412–420
computer program for, 317, 421
direct evaluation, 122
phase angle, 121, 123
of series systems, 144, 316–317
shortcut from transfer function, 122
in stability analysis:
Bode stability, 314–316
transient, complete, 119–120
Furnace (*see* Fired heater)

G

Gain:
controller:
feedback, 245, 587
feedforward, 485
nonlinear, 567
frequency dependent, 315
margin, 338
process, 87
disturbance, 224
feedback, 224, 254
multivariable process, 627
steady-state, 58
Gain scheduling, 518, 529

H

Heat exchanger:
with bypass:
feedback control, 784
model, 76–80, 939–942
numerator zero, 941
recycle systems, 785
transient response, 942
Heat exchanger—*Cont.*
cascade, 458
dynamic model, 76–80
feedback control transient, 256
feedforward, 486
linearizing characteristic, 523–524
refrigeration, 475, 884–885
steam condensing, 777
stirred tank, 76–80
Heaviside, 932
Hierarchy, 476, 826, 829
High signal select, 713
Histogram, 29–31
Hold:
first order, 364
zero-order, 364
Holdup time, 562
Horizon:
input, 749
output, 749
Hydrocracker control, 753

I

Identification (*see* Empirical modelling)
IMC (*see* Internal model control)
Impulse function, 101
Inferential control:
block diagram, 537
design criteria, 542
design procedure, 543
examples:
chemical reactor, 549–552
combustion, 552–554
distillation, 545–549
flash process, 537–541
goal, 536
multiple correlated measurements, 554
Initialization:
controller, 245, 402
filtering, 392
Input:
terminology for control, 6
terminology for modelling, 53
typical time functions, 220–222
Input-output (*see* Cause-effect relationship)
Input processing:
conversion, 212–213, 387
filtering, 389

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Input processing—*Cont.*
units, 388
validity, 387
Integral:
Laplace transform of, 102
numerical approximation, 366
z-transform, 978
Integral stabilizability, 692
Integral error measures:
IAE, integral of absolute value, 219
IE, integral of error, 219, 677
ISE, integral of squared, 219
ITAE, integral of product of time and absolute, 219
Integral mode:
advantage/disadvantage, 249
equation for explicit mode, 248
implicit (*see* Model predictive control)
tuning constant, 248
(*See also* Anti–reset windup)
Integral windup (*see* Anti–reset windup)
Integrating factor, 58, 895
Integrating process:
dynamic behavior, 136
general form, 140–141
levels, 564
stability, 307–308
(*See also* Level control)
Integrity, 637, 672, 692
Interacting series, 145–148
Interaction:
block diagram, 624
controllability, effect on, 627, 651
(*See also* Decoupling)
definition, 620
integrity, effect on, 672–674, 692, 850
measure of (*see* Relative gain array)
modelling:
empirical, 622
fundamental, 621
operating window, effect on, 624–626, 789
performance, feedback control:
loop pairing, 671–681
tuning, 682–683
stability, effect on, 638
transfer function, 629–630
tuning, 641–646
(*See also* DMC)
Internal model control (IMC):
digital form, 595, 994
filter for, 593
model inverse, approximate, 590, 994
performance, 597
Internal model control (IMC)—*Cont.*
structure, 592
tuning:
for IMC controller, 598
for PID controller, 609
Inventories:
control of (*see* Level)
models for, 564–565
reasons for and against, 562–563
sizing, 562, 572–574
Inverse:
approximate, 590
exact model, 588, 729–730
feedback as, 588
Inverse Laplace transform, 99
Inverse response:
control performance, 430–431, 444, 996–1000
multivariable systems, 669–671
open-loop, 152–155, 943–946
ISE (*see* Integral error measures)
ITAE (*see* Integral error measures)

J

Jacketed reactor, 476

L

Lag (*see* First-order system)
Laplace transform:
applications:
solving ODE, 102
transfer function, 111
of common functions, 100
definition of, 98
of derivatives, 101
of integrals, 102
partial fractions, 107, 931–935
properties, 98–99
Lead:
lead/lag algorithm, 485–486, 595, 687, 923
time constant, 152
Least squares:
as approximate inverse, 737
assumptions in, 191

PDF-XChange Editor Click to BUY NOW! www.tracker-software.com

Le... squares—*Cont.*
... design of dynamic matrix control, 737–738
empirical modelling, 188-190
solution of linear problem, 191
Level:
control of:
linear PI, 566
nonlinear PI, 567
control objectives, averaging and tight, 563–564
controller tuning, 568
draining tank, 75–77
inventory size, 572
process model for:
non-self-regulating, 140, 565
self-regulating, 75–77
sensors, 577
series processes, 574–576
Limit cycle, 906
Linear operator, 70
Linear programming, 866–868
Linearity, definition of, 70
Linearization, 71–72
control loop, 517–529
effect on stability analysis, 275, 284, 513–517
Taylor's series, 71
Load (*see* Disturbance)
Long-time behavior, 109, 119–121, 306, 936–937
Low-pass filter, 390
Low signal select, 710–713
Lumped-parameter model, 47, 53

M

Manipulated variable, 207, 212, 218, 226, 243, 276
Manual operation, 228
Mass, conservation of, 53
Master controller (*see* Cascade)
Material, conservation of, 53
Maximum deviation, 221
Maximum overshoot, 220
Measured variable:
accuracy, 383 (*See also* Filtering)
linearity, 387
range, 383–384
reproducibility, 383
sensor dynamics, 212–216, 773
MIMO (*see* Interaction, Multiloop control; Multivariable control)
Mixing process, with dead time:
control of, 270–277, 413–415
model of, 271
Mixing process, three-tank:
adaptive tuning for, 517–519
control of:
derivative-only, 249–251
integral-only, 248
internal model, 595
proportional-integral-derivative, 282–285, 330–332
proportional-only, 245–248
mismatch from true process:
due to nonlinearity, 283–285, 512–517
effect on control performance, 431–432
effect on stability, 345–346
model of:
empirical, 186
fundamental, 223–224
input-output, 223
Model predictive control (MPC):
for cascade control, 606
dead time, 606
error, feedback, 585
with feedforward control, 607
filter for robustness, 592–593
internal model control (IMC), 590
perfect control, 587–588
process inverse:
approximate, 590
exact, 587–588
saturation of final element, 604
Smith predictors, 600
structure, 586
transfer function, 592
two-degree-of-freedom, 594
zero-offset requirements, 587, 593, 601
(*See also* DMC)
Modelling procedure, 50
approximate, 909
empirical, 175
fundamental, 53
linearized, 71
Moments:
definition, 909
for impulse response, 910
use in correlations, 281, 286–287, 336, 598
use in modelling, 912
Monitoring, 23, 799

PDF-XChange Editor Click to BUY NOW! www.tracker-software.com

Move suppression factor, 743, 749
Multiloop control:
  block diagram for, 624, 630
  comparison with single-loop, 616
  control performance:
    input forcing, 663–669
    interaction, 628
    interactive dynamics, 669–671
    operating condition, 663
  controllability, 626, 651, 780–781
  decoupling:
    lead/lag, 687
    model sensitivity, 689
  loop pairing, 671
  relative disturbance gain (RDG), 677–681
  tuning, 646–649, 682
  (*See also* Control design, Interaction)
Multivariable control:
  centralized:
    model inverse for, 729, 738
    structure, 728
  (*See also* Dynamic matrix control; Multiloop control)

N

Negative feedback, 6, 141–142, 207, 242
Niederlinski criterion, 692, 694–695
Noise:
  effect on tuning, 275–276, 292, 915–920
  frequency content, 423–425
  signal-to-noise ratio, 182
  (*See also* Filtering)
Noninteracting series systems, 143
Nonlinear:
  control, 517, 520, 570
  process, effect on operating window, 625–626, 782, 789
  process, effect on performance, 283–285, 512
  saturation, 399–402, 604, 707, 717
  (*See also* Linearization)
Normal distribution, 30
Numerical solution methods:
  for algebraic equations, 902–903
  for differential equations, 82–84
Numerical solution methods—*Cont.*
  frequency response, 317, 421
  for integrals, 366, 917
Nyquist, 314

O

Objective function, 271, 736, 743, 864, 866, 917
Objectives, control, 20, 268, 768, 838
Offset, steady-state:
  definition, 218, 240
  with feedback control, 246, 249, 251
  with feedforward control, 488
  integral mode, 249, 587
  level control, 571
On-off control:
  heating, 5, 230
  model, 67–69
One-way decoupling, 690
One-way interaction, 631, 636–637
Open-loop operation, 228
Open-loop transfer function:
  $G_{OL}(s)$, 316
  terminology, 328
Operability, 778
Operating window, 26–27, 226, 440, 625–626, 720–721, 789
Optimization:
  constraints, 868
  control methods for:
    control design, 861
    direct search, 870
    model-based, 866
  in controller tuning:
    control objectives, 268, 917
    correlations from, 281, 284, 598
  plant economics:
    effect of variance, 31, 33
    profit contours, 31, 43
Order of system, 112
Ordinary differential equations, 47, 56, 102
Output:
  meaning for control, 6
  meaning for modelling, 53
Overdamped, 138–139
Overshoot, 219–220

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Packed bed:
cascade control, 471–473
empirical model, 202
feedforward control, 495–497
Padé approximation, 913
Pairing, loop, 671
Partial control, 779, 827
Partial fraction expansion, 107, 932–935, 980
Performance, (*see* Control performance)
Period of oscillation, 121, 222, 315, 330, 343
Periodic behavior, 5, 67, 343, 906
pH control, 527, 776
Phase angle, 121–123
Phase equilibrium:
in distillation, 159
in flash process, 538
K values for, 538
relative volatility, 159
Phase margin, 340
Physical realizability, 496, 588
PI, PID (*see* Proportional-integral-derivative controller)
Pneumatic:
control valve, 213
controller, 257
signal transmission, 212–213, 891
Polar form:
complex numbers, 122, 316–318, 421
frequency response for series systems, 317
Poles:
definition of, 113
effect of control on, 247, 254–256, 259, 313
effect on dynamic response, 109, 113, 310
effect of process design on, 141–142, 151, 155, 157, 425, 440, 564, 785, 902, 906
effect on stability, 109, 310
Position (full) form of digital controller, 367
Predictive control (*see* Model-predictive control)
Primary controller (*see* Cascade control)
Process dynamics:
effect on control performance, 415, 426, 438, 440, 663, 694
effect on stability, 334
effect of zeros, 152, 939
empirical modelling of, 196
fundamental modelling of, 53
linearized models, 74
recycle process structures, 155
series process structures, 152, 939
staged process structures, 157
Process examples, guide, 925–929
Process reaction curve, 179, 187
Product quality, 23, 768
Profit function (*see* Objective function)
Proportional:
controller mode, 245
tuning constant, 245
Proportional band, 398
Proportional-integral-derivative (PID) controller:
in adaptive control, 517
in cascade control, 458, 468–469
derivative mode, 250
effect on offset, 251
effect on stability, 326
digital form of controller, 367–369
frequency response, of controller, 366–367
initialization, 245, 402
integral mode:
effect on dynamic response, 249
effect on offset, 249
effect on stability, 325, 336–337
windup, 399
mode selection, 436
output limits, 403
proportional mode:
effect of dynamic response, 245, 272
effect on offset, 245
effect on stability, 246
tuning:
Ciancone, 281, 286
IMC, 609
Lopez, 287
multiloop, 641–646
selection, 347
Ziegler-Nichols, 329, 347
Proportional-only control, 245, 571
Pulse, input function, 64, 101

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Q

Quadratic dynamic matrix control, 751
Quick-opening valve, 521

R

Ramp:
  input function, 93
  output response, 93
Random variable, normal distribution, 30
Ratio control:
  effect on stability, 519
  as feedforward, 499
  flow ratio, 499
  reset by feedback, 519, 684
Reactor (*see* Chemical reactor)
Realizable, 496, 588
Real-time operating system, 360
Real-time optimization (*see* Optimization)
Reconstruction of signal, 362
Recycle:
  advantages of, 155–157, 785
  alternative source/sink, 832
  control of systems with, 785, 832, 845–846
  effect of dynamic response, 156–157
  effect on stability, 156
Refrigeration, 475, 885
Regression (*see* Least squares)
Relative disturbance gain (RDG):
  integral error measure, 677
  loop pairing, 678–679
  tuning factor, 678
Relative gain array (RGA):
  calculation, 634
  control integrity, 637, 672
  definition:
    dynamic, 637
    steady-state, 633–634
  interpretations, 636
  loop pairing, 672–674, 695
  properties, 633–636
  stability, 637
Relative volatility, 159
Reproducibility, sensor, 383, 773
Reset (*see* Integral)
Reset time, 398
Reset windup (*see* Anti–reset windup)
Resonant frequency, 414
Reverse-acting feedback, 396
Ringing controller, 368, 992
Rise time, 219
Robustness:
  importance, 241, 512
  performance, 268–269, 919
  stability, 338, 345
  tuning, 268, 919
Root locus, 312
Runge-Kutta numerical integration, 83

S

Safety, 20–21
  alarms, 795
  basic process control, 794
  failure position of final elements, 386
  good practices, 797
  safety interlock system (SIS), 796
  safety valves, 797
Sampling (*see* Digital control)
Saturation of controller output, 398, 604, 707, 717
Second-order system, 138–139
Secondary controller (*see* Cascade)
Select, signal:
  degrees of freedom, 710
  design criteria, 715
  tuning, 714
  (*See also* Constraints, control)
Selection of variables:
  controlled variables, 216, 773, 827–828
  manipulated variables, 216, 226, 438
  measured disturbances, 487
  secondary cascade, 461
Self-regulation, 141
Sense (*see* Controller sense switch)
Sensor:
  accuracy, 383
  cost, 772–773
  dynamics, 215, 773
  flow, 387
  identification symbols, 889
  level, 892
  noise, 276, 389, 424, 879
  range or span, 383
  reliability, 387

PDF-XChange Editor
Click to BUY NOW!
www.tracker-software.com

Sensor—*Cont.*
reproducibility, 383, 773
signal transmission, 890
temperature, 388, 536
Separable differential equation, 58, 895
Set point, 218, 242–243, 458, 586
Settling time, 220
Shannon's sampling theorem, 362
Signal:
conversion, 212
analog to digital (A/D), 359
digital to analog (D/A), 359
electronic to pneumatic, 212
digital transmission, 373
dynamics, 213
electrical transmission, 212
pneumatic transmission, 212
ranges, 213
Signal-to-noise, 182
Signal select, 710
Simulation:
closed-loop system, 423, 916
performance measures, 917
process dynamics, 83–84
(*See also* Digital control)
Sine input:
amplitude ratio, 121–123
first order, 123
flow attenuation, 572
typical input forcing, 136
(*See also* Frequency response)
Single-input single-output (SISO) (*see* Single-loop control)
Single-loop control, 5–6, 208, 218, 243
SIS (*see* Safety)
Slave controller, 460
Smith predictor:
system structure, 600
tuning, 602
zero offset, 601
(*See also* Model predictive control)
Snowball effect, 847
Split range:
degrees of freedom, 706
design criteria, 709
tuning, 708
(*See also* Constraints, control)
Spring and dashpot, 137–138
Stability:
analysis:
Bode, 314–317
complex plane plots (*see* Root locus)
Stability—*Cont.*
analysis—*Cont.*
Nyquist, 314
pole calculation, 308–313
root locus, 312–313
simulation, 248
chemical reactor, 902–906
definition, bounded input-output, 303–304
effect of controller tuning, 312
effect of process dynamics, 334
effect of sampling period, 367–370
feedforward, 488
of linearized system, 305–308
margin, 338–340
multiloop, 630, 638
Staged systems (*see* Distillation)
Standard deviation:
of averages, 394
of data set, 30
from set point, 221, 466
Statistical modelling, 189
Statistical process control:
capability index, 880–881
goal of preventing disturbances, 876
Shewart chart, 876
specification limit, 881
Steady state:
error (offset), 240
feedforward control, 488
operating window, 625–626
Steam heat exchanger:
bypass, 784
condensing, 777
Steam system:
boiler, 27, 862
header, 862
turbines, 885
Steam trap, 777
Step:
input function, 58, 136–138, 162
Laplace transform, 99
test (*see* Process reaction curve)
Stiffness, 84
Stirred tank (CST):
chemical reactor, 62, 72, 85, 438, 835, 897
heat exchanger, 76–80, 458, 486, 523, 939–943
mixer:
one-tank, 52, 270, 415

PDF-XChange Editor Click to BUY NOW! www.tracker-software.com

Stirred tank (CST)—*Cont.*
mixer—*Cont.*
three-tank, 186, 223, 282, 422–424, 512, 595–596
series reactors, 64, 430, 943
typical assumptions, 52, 899
Stochastic control performance, 293, 424, 879
Superposition, 70
Surge tank, 119, 562, 572
System definition, 52
Systems analysis, 135

T

Target, 585–586
Taylor series approximation, 71
Temperature control:
distillation, 545
fired heater, 26, 31, 473, 500, 552, 961
flash drum, 21, 538, 802
stirred tank, 252–523
Three-mode controller (*see* Proportional-integral-derivative controller)
Time constant:
empirical estimation, 179–180
relation to process, 74, 137, 271, 900, 942, 944
series of, 143–145
Time delay (*see* Dead time)
Thermocouple, 388, 526
Thermowell, 940
Transfer function:
closed-loop, 244, 462, 488, 586, 629–630
controller, 252–253
definition, 111, 118, 983
disturbance process, 224, 415, 666
feedback process, 224, 270–271, 622, 666
instrument, 213
matrix of, 624
poles of, 113, 255, 259, 312–313
zeros of, 113, 152
Transient (*see* Dynamics)
Transmission interaction, 629
Transportation delay, 103–104
Tray, distillation, general balances, 159
Tuning, feedback controller:
digital PID control, 370
dynamic matrix control, 750
effect of process on, 281, 334, 564–566, 645
internal model control, 598
multiloop PID, 645, 682
objectives (*see* Control, objectives)
Smith predictor, 602
stability margin:
gain margin, 338
phase margin, 340
(*See also* Proportional-integral-derivative, tuning)
Tuning, feedforward controller, 496

U

Ultimate controller gain, 330, 993
Ultimate period, 330
Underdamped process, 85, 138–139, 253–256, 899–903
Unstable systems:
closed-loop system, 308–317
process without control, 307–308, 899–907
Unsteady-state (*see* Dynamics)
Utility systems:
fuel gas system, 501, 810–811
hot oil, 885
steam system, 862
(*See also* Refrigeration)

V

Validation, model, 60–61
Valve:
automated control:
capacity, 217, 226, 385, 438–441, 625–626
characteristic, 520
dynamic response, 213
failure position, 386
pneumatic power, 212–213
range, 385
manual, 228, 892
positioner, 474

PDF-XChange Editor Click to BUY NOW! www.tracker-software.com

Valve, *cont.*
y relief, 797
stem, 81, 213, 474, 520
Valve position controller, 718
Variable:
continuous, 98
dependent, 56, 254
deviation, 71, 111
discrete, 188–189, 365, 973
external, 56, 254
manipulated, 5, 208, 213, 217
Variable structure:
constraint control, 715
multiple controllers, 716
signal select, 710
split range, 706
valve position control, 718
Variance:
definition, 30
measure of performance, 221–222
Velocity form, controller, 367

W

Weir, 159
Wild stream, 499, 684
Windup, reset (*see* Anti–reset windup)

Z

z-transform, 973–975
table, 975
Zero, sensor signal, 388
Zero-order hold, 364, 985
Zeros of transfer function:
cancellation of pole and zero, 113
effect on dynamic response, 152, 943
effect on stability, 113
Ziegler-Nichols:
closed-loop tuning, 329, 342–343
open-loop tuning, 347
process reaction curve, 179–180