

Creating a Sentiment Analysis Web App

Using PyTorch and SageMaker

Deep Learning Nanodegree Program | Deployment

Now that we have a basic understanding of how SageMaker works we will try to use it to construct a complete project from end to end. Our goal will be to have a simple web page which a user can use to enter a movie review. The web page will then send the review off to our deployed model which will predict the sentiment of the entered review.

Instructions

Some template code has already been provided for you, and you will need to implement additional functionality to successfully complete this notebook. You will not need to modify the included code beyond what is requested. Sections that begin with **'TODO'** in the header indicate that you need to complete or implement some portion within them. Instructions will be provided for each section and the specifics of the implementation are marked in the code block with a `# TODO: ... comment`. Please be sure to read the instructions carefully!

In addition to implementing code, there will be questions for you to answer which relate to the task and your implementation. Each section where you will answer a question is preceded by a **'Question:'** header. Carefully read each question and provide your answer below the **'Answer:'** header by editing the Markdown cell.

Note: Code and Markdown cells can be executed using the **Shift+Enter** keyboard shortcut. In addition, a cell can be edited by typically clicking it (double-click for Markdown cells) or by pressing **Enter** while it is highlighted.

General Outline

Recall the general outline for SageMaker projects using a notebook instance.

1. Download or otherwise retrieve the data.
2. Process / Prepare the data.
3. Upload the processed data to S3.
4. Train a chosen model.
5. Test the trained model (typically using a batch transform job).
6. Deploy the trained model.
7. Use the deployed model.

For this project, you will be following the steps in the general outline with some modifications.

First, you will not be testing the model in its own step. You will still be testing the model, however, you will do it by deploying your model and then using the deployed model by sending the test data to it. One of the reasons for doing this is so that you can make sure that your deployed model is working correctly before moving forward.

In addition, you will deploy and use your trained model a second time. In the second iteration you will customize the way that your trained model is deployed by including some of your own code. In addition, your newly

Step 1: Downloading the data

As in the XGBoost in SageMaker notebook, we will be using the [IMDb dataset](http://ai.stanford.edu/~amaas/data/sentiment/) (<http://ai.stanford.edu/~amaas/data/sentiment/>)

Maas, Andrew L., et al. [Learning Word Vectors for Sentiment Analysis](http://ai.stanford.edu/~amaas/data/sentiment/) (<http://ai.stanford.edu/~amaas/data/sentiment/>). In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*. Association for Computational Linguistics, 2011.

```
In [1]: %mkdir ../data
!wget -O ../data/aclImdb_v1.tar.gz http://ai.stanford.edu/~amaas/data/sentiment/aclImdb_v1.tar.gz
!tar -zxf ../data/aclImdb_v1.tar.gz -C ../data

mkdir: cannot create directory '../data': File exists
--2019-03-24 13:51:17-- http://ai.stanford.edu/~amaas/data/sentiment/aclImdb_v1.tar.gz
Resolving ai.stanford.edu (ai.stanford.edu)... 171.64.68.10
Connecting to ai.stanford.edu (ai.stanford.edu)|171.64.68.10|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 84125825 (80M) [application/x-gzip]
Saving to: '../data/aclImdb_v1.tar.gz'

../data/aclImdb_v1. 100%[=====>] 80.23M 19.8MB/s in 7.7s

2019-03-24 13:51:25 (10.4 MB/s) - '../data/aclImdb_v1.tar.gz' saved [84125825/84125825]
```

Step 2: Preparing and Processing the data

Also, as in the XGBoost notebook, we will be doing some initial data processing. The first few steps are the same as in the XGBoost example. To begin with, we will read in each of the reviews and combine them into a single input structure. Then, we will split the dataset into a training set and a testing set.

```

In [2]: import os
import glob

def read_imdb_data(data_dir='../data/aclImdb'):
    data = {}
    labels = {}

    for data_type in ['train', 'test']:
        data[data_type] = {}
        labels[data_type] = {}

        for sentiment in ['pos', 'neg']:
            data[data_type][sentiment] = []
            labels[data_type][sentiment] = []

        path = os.path.join(data_dir, data_type, sentiment, '*.txt')
        files = glob.glob(path)

        for f in files:
            with open(f) as review:
                data[data_type][sentiment].append(review.read())
                # Here we represent a positive review by '1' and a negative
                # review by '0'
                labels[data_type][sentiment].append(1 if sentiment == 'pos' else 0)

        assert len(data[data_type][sentiment]) == len(labels[data_type][sentiment]), \
            "{} / {} data size does not match labels size".format(data_type, sentiment)

    return data, labels

```

```

In [3]: data, labels = read_imdb_data()
print("IMDB reviews: train = {} pos / {} neg, test = {} pos / {} neg".format(
    len(data['train']['pos']), len(data['train']['neg']),
    len(data['test']['pos']), len(data['test']['neg'])))

```

IMDB reviews: train = 12500 pos / 12500 neg, test = 12500 pos / 12500 neg

Now that we've read the raw training and testing data from the downloaded dataset, we will combine the positive and negative reviews and shuffle the resulting records.

```
In [4]: from sklearn.utils import shuffle

def prepare_imdb_data(data, labels):
    """Prepare training and test sets from IMDB movie reviews."""

    #Combine positive and negative reviews and labels
    data_train = data['train']['pos'] + data['train']['neg']
    data_test = data['test']['pos'] + data['test']['neg']
    labels_train = labels['train']['pos'] + labels['train']['neg']
    labels_test = labels['test']['pos'] + labels['test']['neg']

    #Shuffle reviews and corresponding labels within training and test sets
    data_train, labels_train = shuffle(data_train, labels_train)
    data_test, labels_test = shuffle(data_test, labels_test)

    # Return a unified training data, test data, training labels, test labels
    return data_train, data_test, labels_train, labels_test
```

```
In [5]: train_X, test_X, train_y, test_y = prepare_imdb_data(data, labels)
print("IMDb reviews (combined): train = {}, test = {}".format(len(train_X), len(test_X)))
```

IMDb reviews (combined): train = 25000, test = 25000

Now that we have our training and testing sets unified and prepared, we should do a quick check and see an example of the data our model will be trained on. This is generally a good idea as it allows you to see how each of the further processing steps affects the reviews and it also ensures that the data has been loaded correctly.

```
In [6]: print(train_X[100])
print(train_y[100])
```

Bunny Comes Home 'This Man's Navy' deserves more credit than it gets, a clever script by Borden Chase, directed by 'Wild Bill' Wellman, the film has just the right feel for early post WW11 euphoria and goodwill, and none of the blind terror that came into play few years later. Produced in 1944, the Japanese defeated, the battle scenes a little déjà vu, Tom Drake's melancholy attraction for radiant young Jan Clayton has solid chemistry, plays real and validates Drake's career at Metro. The following year Jan opened on Broadway in 'Carousel.' Wally Beery, a little bleary-eyed, boasts to an always incredulous Jimmy Gleason his memories an improvement over reality, and give Beery a Ulysses-like shadow to play against. The Navy LTA (Lighter Than Air) shots are authentic, photographed at Tustin and Lakehurst, and the P-38 squadron is out of March AFB. Lot 3 doubled for India, and Bunny's U-turn Bunny Comes Home gives back to Beery an authentic slice of his past, something he had wanted to believe was true then, the future we spin into again is fantastical now on a grander scale, a newly designed Navy LTA with launch capabilities for a reconnaissance plane how expensive, blissfully optimistic still, "You got to believe in it, that's the way you make things come true"

1

The first step in processing the reviews is to make sure that any html tags that appear should be removed. In addition we wish to tokenize our input, that way words such as *entertained* and *entertaining* are considered the same with regard to sentiment analysis.

```
In [7]: import nltk
from nltk.corpus import stopwords
from nltk.stem.porter import *

import re
from bs4 import BeautifulSoup

def review_to_words(review):
    nltk.download("stopwords", quiet=True)
    stemmer = PorterStemmer()

    text = BeautifulSoup(review, "html.parser").get_text() # Remove HTML tags
    text = re.sub(r"^[^a-zA-Z0-9]", " ", text.lower()) # Convert to lower case
    words = text.split() # Split string into words
    words = [w for w in words if w not in stopwords.words("english")] # Remove stopwords
    words = [PorterStemmer().stem(w) for w in words] # stem

    return words
```

The `review_to_words` method defined above uses `BeautifulSoup` to remove any html tags that appear and uses the `nltk` package to tokenize the reviews. As a check to ensure we know how everything is working, try applying `review_to_words` to one of the reviews in the training set.

```
In [8]: # TODO: Apply review_to_words to a review (train_X[100] or any other review)

print(review_to_words(train_X[100]))

['bunni', 'come', 'home', 'man', 'navi', 'deserv', 'credit', 'get', 'clever',
'script', 'borden', 'chase', 'direct', 'wild', 'bill', 'wellman', 'film', 'ri
ght', 'feel', 'earli', 'post', 'ww11', 'euphoria', 'goodwil', 'none', 'blin
d', 'terror', 'came', 'play', 'year', 'later', 'produc', '1944', 'japanes',
'defeat', 'battl', 'scene', 'littl', 'j', 'vu', 'tom', 'drake', 'melancholi',
'attract', 'radiant', 'young', 'jan', 'clayton', 'solid', 'chemistri', 'pla
y', 'real', 'valid', 'drake', 'career', 'metro', 'follow', 'year', 'jan', 'op
en', 'broadway', 'carousel', 'walli', 'beeri', 'littl', 'bleari', 'eye', 'boa
st', 'alway', 'incredul', 'jimmi', 'gleason', 'memori', 'improv', 'realiti',
'give', 'beeri', 'ulyss', 'like', 'shadow', 'play', 'navi', 'lta', 'lighter',
'air', 'shot', 'authent', 'photograph', 'tustin', 'lakehurst', 'p', '38', 'sq
uadron', 'march', 'afb', 'lot', '3', 'doubl', 'india', 'bunni', 'u', 'turn',
'bunni', 'come', 'home', 'give', 'back', 'beeri', 'authent', 'slice', 'past',
'someth', 'want', 'believ', 'true', 'futur', 'spin', 'fantast', 'grander', 's
cale', 'newli', 'design', 'navi', 'lta', 'launch', 'capabl', 'reconnaiss', 'p
lane', 'expens', 'bliss', 'optimist', 'still', 'got', 'believ', 'way', 'mak
e', 'thing', 'come', 'true']
```

Question: Above we mentioned that `review_to_words` method removes html formatting and allows us to tokenize the words found in a review, for example, converting *entertained* and *entertaining* into *entertain* so that they are treated as though they are the same word. What else, if anything, does this method do to the input?

Answer:

The method does the followings in addition to what mentioned above:

- Converts all uppercase characters to thier lowercases.
- Replaces non-alphanumeric characters with a space or " "
- Splits the string into words
- Removes stopwords, such as "the", "a", "an", "in", etc.
- Removes all punctuations.

The method below applies the `review_to_words` method to each of the reviews in the training and testing datasets. In addition it caches the results. This is because performing this processing step can take a long time. This way if you are unable to complete the notebook in the current session, you can come back without needing to process the data a second time.

```

In [9]: import pickle

cache_dir = os.path.join("../cache", "sentiment_analysis") # where to store c
ache files
os.makedirs(cache_dir, exist_ok=True) # ensure cache directory exists

def preprocess_data(data_train, data_test, labels_train, labels_test,
                    cache_dir=cache_dir, cache_file="preprocessed_data.pkl"):
    """Convert each review to words; read from cache if available."""

    # If cache_file is not None, try to read from it first
    cache_data = None
    if cache_file is not None:
        try:
            with open(os.path.join(cache_dir, cache_file), "rb") as f:
                cache_data = pickle.load(f)
            print("Read preprocessed data from cache file:", cache_file)
        except:
            pass # unable to read from cache, but that's okay

    # If cache is missing, then do the heavy lifting
    if cache_data is None:
        # Preprocess training and test data to obtain words for each review
        # words_train = list(map(review_to_words, data_train))
        # words_test = list(map(review_to_words, data_test))
        words_train = [review_to_words(review) for review in data_train]
        words_test = [review_to_words(review) for review in data_test]

        # Write to cache file for future runs
        if cache_file is not None:
            cache_data = dict(words_train=words_train, words_test=words_test,
                               labels_train=labels_train, labels_test=labels_te
st)

            with open(os.path.join(cache_dir, cache_file), "wb") as f:
                pickle.dump(cache_data, f)
            print("Wrote preprocessed data to cache file:", cache_file)
        else:
            # Unpack data loaded from cache file
            words_train, words_test, labels_train, labels_test = (cache_data['word
s_train'],
                                                                    cache_data['words_test'], cache_data['labels_train'], cache_da
ta['labels_test'])

    return words_train, words_test, labels_train, labels_test

```

```

In [10]: # Preprocess data
train_X, test_X, train_y, test_y = preprocess_data(train_X, test_X, train_y, t
est_y)

```

Read preprocessed data from cache file: preprocessed_data.pkl

Transform the data

In the XGBoost notebook we transformed the data from its word representation to a bag-of-words feature representation. For the model we are going to construct in this notebook we will construct a feature representation which is very similar. To start, we will represent each word as an integer. Of course, some of the words that appear in the reviews occur very infrequently and so likely don't contain much information for the purposes of sentiment analysis. The way we will deal with this problem is that we will fix the size of our working vocabulary and we will only include the words that appear most frequently. We will then combine all of the infrequent words into a single category and, in our case, we will label it as `1`.

Since we will be using a recurrent neural network, it will be convenient if the length of each review is the same. To do this, we will fix a size for our reviews and then pad short reviews with the category 'no word' (which we will label `0`) and truncate long reviews.

(TODO) Create a word dictionary

To begin with, we need to construct a way to map words that appear in the reviews to integers. Here we fix the size of our vocabulary (including the 'no word' and 'infrequent' categories) to be `5000` but you may wish to change this to see how it affects the model.

TODO: Complete the implementation for the `build_dict()` method below. Note that even though the `vocab_size` is set to `5000`, we only want to construct a mapping for the most frequently appearing `4998` words. This is because we want to reserve the special labels `0` for 'no word' and `1` for 'infrequent word'.

```

In [11]: import numpy as np
import operator
#from collections import Counter

def build_dict(data, vocab_size = 5000):
    """Construct and return a dictionary mapping each of the most frequently a
    ppearing words to a unique integer."""

    # TODO: Determine how often each word appears in `data`. Note that `data`
    is a list of sentences and that a
    #         sentence is a list of words.

    word_count = {} # A dict storing the words that appear in the reviews along
    with how often they occur

    for sentence in data:
        for word_item in sentence:
            if word_item in word_count:
                word_count[word_item] += 1
            else:
                word_count[word_item] = 1

    # TODO: Sort the words found in `data` so that sorted_words[0] is the most
    frequently appearing word and
    #         sorted_words[-1] is the least frequently appearing word.

    sorted_words = [record[0] for record in sorted(word_count.items(), key=operator.itemgetter(1), reverse=True)]

    word_dict = {} # This is what we are building, a dictionary that translates
    words into integers
    for idx, word in enumerate(sorted_words[:vocab_size - 2]): # The -2 is so
    that we save room for the 'no word'                                # 'infrequent'
    labels
        word_dict[word] = idx + 2

    return word_dict

```

```

In [12]: word_dict = build_dict(train_X)

```

```

In [13]: print(len(word_dict))

```

4998

Question: What are the five most frequently appearing (tokenized) words in the training set? Does it make sense that these words appear frequently in the training set?

Answer: The six most frequent words are: movi, film, one, like, time, good. This makes sense as they are very common words used in movie reviews. Also the word "one" some times is used as "this" or "that" in english language besides being a number, therefore, it is a very common word in english in general.

```
In [72]: # TODO: Use this space to determine the five most frequently appearing words i  
n the training set.  
  
sorted_words = sorted(word_dict.items(), key=operator.itemgetter(1))  
  
print("The six most frequent words are: \n")  
  
for i in range(6):  
    print(sorted_words[i][0])
```

The six most frequent words are:

movi
film
one
like
time
good

Save word_dict

Later on when we construct an endpoint which processes a submitted review we will need to make use of the `word_dict` which we have created. As such, we will save it to a file now for future use.

```
In [15]: data_dir = '../data/pytorch' # The folder we will use for storing data  
if not os.path.exists(data_dir): # Make sure that the folder exists  
    os.makedirs(data_dir)
```

```
In [16]: with open(os.path.join(data_dir, 'word_dict.pkl'), "wb") as f:  
    pickle.dump(word_dict, f)
```

Transform the reviews

Now that we have our word dictionary which allows us to transform the words appearing in the reviews into integers, it is time to make use of it and convert our reviews to their integer sequence representation, making sure to pad or truncate to a fixed length, which in our case is 500 .

```
In [17]: def convert_and_pad(word_dict, sentence, pad=500):  
    NOWORD = 0 # We will use 0 to represent the 'no word' category  
    INFREQ = 1 # and we use 1 to represent the infrequent words, i.e., words not  
    appearing in word_dict  
  
    working_sentence = [NOWORD] * pad  
  
    for word_index, word in enumerate(sentence[:pad]):  
        if word in word_dict:  
            working_sentence[word_index] = word_dict[word]  
        else:  
            working_sentence[word_index] = INFREQ  
  
    return working_sentence, min(len(sentence), pad)  
  
def convert_and_pad_data(word_dict, data, pad=500):  
    result = []  
    lengths = []  
  
    for sentence in data:  
        converted, leng = convert_and_pad(word_dict, sentence, pad)  
        result.append(converted)  
        lengths.append(leng)  
  
    return np.array(result), np.array(lengths)
```

```
In [18]: train_X, train_X_len = convert_and_pad_data(word_dict, train_X)  
test_X, test_X_len = convert_and_pad_data(word_dict, test_X)
```

As a quick check to make sure that things are working as intended, check to see what one of the reviews in the training set looks like after having been processed. Does this look reasonable? What is the length of a review in the training set?

```
In [19]: # Use this cell to examine one of the processed reviews to make sure everything is working as intended.
record_No = 12
print(train_X[record_No], "\n", train_X_len[record_No])
```

```
[ 54 1999 153 156 353 573 27 1232 47 28 2 141 37 258
  1 156 8 196 41 2 891 179 253 1151 2811 3668 277 10
 430 575 1 416 960 3296 807 370 2064 114 1072 1 4020 734
3311 3181 468 136 2 159 668 419 516 70 2104 2 2051 39
 5 573 59 1500 2051 820 1293 2 171 1 1589 623 1037 746
1589 623 29 1 369 27 746 1 220 1664 1037 1664 27 746
491 807 365 746 531 35 746 15 25 21 643 1 1 251
1444 381 4817 746 152 2606 2155 232 5 2132 682 3311 1128 10
 22 136 2 159 323 4 261 190 1037 65 1297 1874 4777 104
1974 6 5 25 315 1138 189 2 3585 852 2662 405 661 2907
 90 124 231 1293 153 38 1 678 404 3311 59 54 461 2226
 19 882 54 319 220 1 3937 25 1 2 106 21 504 136
 4 245 104 1501 337 104 1 4912 3486 581 866 63 2 1080
 21 1501 337 1 710 1987 1 453 741 221 112 347 65 1590
179 214 128 16 3759 1299 2 132 1 2662 688 184 104 344
187 1073 257 487 15 2 114 2065 554 672 4586 104 123 22
104 344 297 219 50 2863 124 146 1259 1044 1304 257 18 1009
4777 271 344 1495 2581 28 2 71 196 904 104 196 257 881
 19 7 1167 30 371 1 448 247 4778 25 12 3114 772 1258
1992 2 620 7 257 344 1834 1068 2226 967 23 1 1081 68
1081 28 2 3028 4779 601 1 221 112 3707 93 52 35 201
 828 1 2108 46 326 2362 1 1 1974 6 1 330 2105 1220
1806 4058 2198 200 757 2 237 757 71 1 2032 2795 36 16
163 28 2 382 783 3906 470 303 324 98 9 338 404 264
233 338 1151 312 2811 1 43 16 324 70 954 9 125 97
3992 9 1392 179 214 3378 3312 179 6 303 2925 1993 3708 9
 1 32 60 2852 53 1 7 32 585 3 8 466 277 20
1175 3311 1 263 922 3332 54 8 1 207 1 1228 1729 557
 853 412 125 561 8 2607 277 27 263 922 1 94 297 19
 888 131 21 5 1 1084 188 1013 18 1017 17 119 1 764
 793 196 1161 1346 698 125 228 68 61 69 9 684 235 350
 8 1059 554 1214 257 18 2 651 287 7 148 390 510 2
278 568 59 396 11 2226 850 141 11 77 1 3709 69 180
 7 104 84 117 119 4059 1506 1 791 592 1 376 1051 16
189 1806 4058 57 98 58 365 3467 2237 1098 70 189 245 3
 0 0 0 0 0 0 0 0 0 0]
490
```

Question: In the cells above we use the `preprocess_data` and `convert_and_pad_data` methods to process both the training and testing set. Why or why not might this be a problem?

Answer: There are some issues with the current implementation of the preprocessing data functions, that need to be more deeply addressed in the future as potential improvements:

- Limiting the review to a certain size may make us lose important information in long reviews that are usually deeper and convey better evaluation of the movie.
- Treating long and short reviews in the same way and with the same weight is not an accurate practice as this may skew the overall results. Usually long reviews have more depth and short ones are superficial.
- Padding the short reviews with zeros is a huge waste of memory and computational resources.
- However, treating both the training and testing datasets with the same preprocessing pipeline is a good practice to avoid any bias.

Step 3: Upload the data to S3

As in the XGBoost notebook, we will need to upload the training dataset to S3 in order for our training code to access it. For now we will save it locally and we will upload to S3 later on.

Save the processed training dataset locally

It is important to note the format of the data that we are saving as we will need to know it when we write the training code. In our case, each row of the dataset has the form `label, length, review[500]` where `review[500]` is a sequence of 500 integers representing the words in the review.

```
In [20]: import pandas as pd

pd.concat([pd.DataFrame(train_y), pd.DataFrame(train_X_len), pd.DataFrame(train_X)], axis=1) \
        .to_csv(os.path.join(data_dir, 'train.csv'), header=False, index=False
        )
```

Uploading the training data

Next, we need to upload the training data to the SageMaker default S3 bucket so that we can provide access to it while training our model.

```
In [21]: import sagemaker

sagemaker_session = sagemaker.Session()

bucket = sagemaker_session.default_bucket()
prefix = 'sagemaker/sentiment_rnn'

role = sagemaker.get_execution_role()
```

INFO:sagemaker:Created S3 bucket: sagemaker-us-east-1-538652065034

```
In [22]: input_data = sagemaker_session.upload_data(path=data_dir, bucket=bucket, key_prefix=prefix)
```

NOTE: The cell above uploads the entire contents of our data directory. This includes the `word_dict.pkl` file. This is fortunate as we will need this later on when we create an endpoint that accepts an arbitrary review. For now, we will just take note of the fact that it resides in the data directory (and so also in the S3 training bucket) and that we will need to make sure it gets saved in the model directory.

Step 4: Build and Train the PyTorch Model

In the XGBoost notebook we discussed what a model is in the SageMaker framework. In particular, a model comprises three objects

- Model Artifacts,
- Training Code, and
- Inference Code,

each of which interact with one another. In the XGBoost example we used training and inference code that was provided by Amazon. Here we will still be using containers provided by Amazon with the added benefit of being able to include our own custom code.

We will start by implementing our own neural network in PyTorch along with a training script. For the purposes of this project we have provided the necessary model object in the `model.py` file, inside of the `train` folder. You can see the provided implementation by running the cell below.

```

In [23]: !pygmentize train/model.py

import torch.nn as nn

class LSTMClassifier(nn.Module):
    """
    This is the simple RNN model we will be using to perform Sentiment Analysis.
    """

    def __init__(self, embedding_dim, hidden_dim, vocab_size):
        """
        Initialize the model by setting up the various layers.
        """
        super(LSTMClassifier, self).__init__()

        self.embedding = nn.Embedding(vocab_size, embedding_dim, padding_idx=0)

        self.lstm = nn.LSTM(embedding_dim, hidden_dim)
        self.dense = nn.Linear(in_features=hidden_dim, out_features=1)
        self.sig = nn.Sigmoid()

        self.word_dict = None

    def forward(self, x):
        """
        Perform a forward pass of our model on some input.
        """
        x = x.t()
        lengths = x[0,:]
        reviews = x[1:,:]
        embeds = self.embedding(reviews)
        lstm_out, _ = self.lstm(embeds)
        out = self.dense(lstm_out)
        out = out[lengths - 1, range(len(lengths))]
        return self.sig(out.squeeze())

```

The important takeaway from the implementation provided is that there are three parameters that we may wish to tweak to improve the performance of our model. These are the embedding dimension, the hidden dimension and the size of the vocabulary. We will likely want to make these parameters configurable in the training script so that if we wish to modify them we do not need to modify the script itself. We will see how to do this later on. To start we will write some of the training code in the notebook so that we can more easily diagnose any issues that arise.

First we will load a small portion of the training data set to use as a sample. It would be very time consuming to try and train the model completely in the notebook as we do not have access to a gpu and the compute instance that we are using is not particularly powerful. However, we can work on a small bit of the data to get a feel for how our training script is behaving.


```
In [24]: import torch
import torch.utils.data

# Read in only the first 250 rows
train_sample = pd.read_csv(os.path.join(data_dir, 'train.csv'), header=None, names=None, nrows=250)

# Turn the input pandas dataframe into tensors
train_sample_y = torch.from_numpy(train_sample[[0]].values).float().squeeze()
train_sample_X = torch.from_numpy(train_sample.drop([0], axis=1).values).long()

# Build the dataset
train_sample_ds = torch.utils.data.TensorDataset(train_sample_X, train_sample_y)
# Build the dataloader
train_sample_dl = torch.utils.data.DataLoader(train_sample_ds, batch_size=50)
```

(TODO) Writing the training method

Next we need to write the training code itself. This should be very similar to training methods that you have written before to train PyTorch models. We will leave any difficult aspects such as model saving / loading and parameter loading until a little later.

```
In [25]: def train(model, train_loader, epochs, optimizer, loss_fn, device):
    for epoch in range(1, epochs + 1):
        model.train()
        total_loss = 0
        for batch in train_loader:
            batch_X, batch_y = batch

            batch_X = batch_X.to(device)
            batch_y = batch_y.to(device)

            # TODO: Complete this train method to train the model provided.
            optimizer.zero_grad()
            predicted_output = model(batch_X)
            loss = loss_fn(predicted_output, batch_y)
            loss.backward()
            optimizer.step()

            total_loss += loss.data.item()
        print("Epoch: {}, BCELoss: {}".format(epoch, total_loss / len(train_loader)))
```

Supposing we have the training method above, we will test that it is working by writing a bit of code in the notebook that executes our training method on the small sample training set that we loaded earlier. The reason for doing this in the notebook is so that we have an opportunity to fix any errors that arise early when they are easier to diagnose.

```
In [28]: import torch.optim as optim
from train.model import LSTMClassifier

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
model = LSTMClassifier(32, 100, 5000).to(device)
optimizer = optim.Adam(model.parameters())
loss_fn = torch.nn.BCELoss()

train(model, train_sample_dl, 5, optimizer, loss_fn, device)

Epoch: 1, BCELoss: 0.6917103290557861
Epoch: 2, BCELoss: 0.6821335077285766
Epoch: 3, BCELoss: 0.6735182285308838
Epoch: 4, BCELoss: 0.6635008215904236
Epoch: 5, BCELoss: 0.6504418849945068
```

```
In [29]: print(device)
```

cpu

In order to construct a PyTorch model using SageMaker we must provide SageMaker with a training script. We may optionally include a directory which will be copied to the container and from which our training code will be run. When the training container is executed it will check the uploaded directory (if there is one) for a `requirements.txt` file and install any required Python libraries, after which the training script will be run.

(TODO) Training the model

When a PyTorch model is constructed in SageMaker, an entry point must be specified. This is the Python file which will be executed when the model is trained. Inside of the `train` directory is a file called `train.py` which has been provided and which contains most of the necessary code to train our model. The only thing that is missing is the implementation of the `train()` method which you wrote earlier in this notebook.

TODO: Copy the `train()` method written above and paste it into the `train/train.py` file where required.

The way that SageMaker passes hyperparameters to the training script is by way of arguments. These arguments can then be parsed and used in the training script. To see how this is done take a look at the provided `train/train.py` file.

```
In [30]: from sagemaker.pytorch import PyTorch

estimator = PyTorch(entry_point="train.py",
                    source_dir="train",
                    role=role,
                    framework_version='0.4.0',
                    train_instance_count=1,
                    train_instance_type='ml.p2.xlarge',
                    hyperparameters={
                        'epochs': 30,
                        'hidden_dim': 200,
                    })
```

```
In [31]: estimator.fit({'training': input_data})
```

INFO:sagemaker:Created S3 bucket: sagemaker-us-east-1-538652065034

INFO:sagemaker:Creating training-job with name: sagemaker-pytorch-2019-03-24-13-55-33-537

```

2019-03-24 13:55:33 Starting - Starting the training job...
2019-03-24 13:55:35 Starting - Launching requested ML instances.....
2019-03-24 13:56:41 Starting - Preparing the instances for training.....
2019-03-24 13:58:00 Downloading - Downloading input data
2019-03-24 13:58:00 Training - Downloading the training image.....
2019-03-24 13:58:58 Training - Training image download completed. Training in
progress..
bash: cannot set terminal process group (-1): Inappropriate ioctl for device
bash: no job control in this shell
2019-03-24 13:58:59,358 sagemaker-containers INFO      Imported framework sage
maker_pytorch_container.training
2019-03-24 13:58:59,385 sagemaker_pytorch_container.training INFO      Block u
ntil all host DNS lookups succeed.
2019-03-24 13:58:59,393 sagemaker_pytorch_container.training INFO      Invokin
g user training script.
2019-03-24 13:58:59,706 sagemaker-containers INFO      Module train does not p
rovide a setup.py.
Generating setup.py
2019-03-24 13:58:59,706 sagemaker-containers INFO      Generating setup.cfg
2019-03-24 13:58:59,706 sagemaker-containers INFO      Generating MANIFEST.in
2019-03-24 13:58:59,707 sagemaker-containers INFO      Installing module with
the following command:
/usr/bin/python -m pip install -U . -r requirements.txt
Processing /opt/ml/code
Collecting pandas (from -r requirements.txt (line 1))
  Downloading https://files.pythonhosted.org/packages/74/24/0cdbf8907e1e3bc5a
8da03345c23cbcd7044330bb8f73bb12e711a640a00/pandas-0.24.2-cp35-cp35m-manylinu
x1_x86_64.whl (10.0MB)
Collecting numpy (from -r requirements.txt (line 2))
  Downloading https://files.pythonhosted.org/packages/e3/18/4f013c3c3051f4e0f
fbaa4bf247050d6d5e527fe9cb1907f5975b172f23f/numpy-1.16.2-cp35-cp35m-manylinux
1_x86_64.whl (17.2MB)
Collecting nltk (from -r requirements.txt (line 3))
  Downloading https://files.pythonhosted.org/packages/6f/ed/9c755d357d33bc193
1e157f537721efb5b88d2c583fe593cc09603076cc3/nltk-3.4.zip (1.4MB)
Collecting beautifulsoup4 (from -r requirements.txt (line 4))
  Downloading https://files.pythonhosted.org/packages/1d/5d/3260694a59df0ec52
f8b4883f5d23b130bc237602a1411fa670eae12351e/beautifulsoup4-4.7.1-py3-none-an
y.whl (94kB)
Collecting html5lib (from -r requirements.txt (line 5))
  Downloading https://files.pythonhosted.org/packages/a5/62/bbd2be0e7943ec850
4b517e62bab011b4946e1258842bc159e5dfde15b96/html5lib-1.0.1-py2.py3-none-any.w
hl (117kB)
Collecting pytz>=2011k (from pandas->-r requirements.txt (line 1))
  Downloading https://files.pythonhosted.org/packages/61/28/1d3920e4d1d50b19b
c5d24398a7cd85cc7b9a75a490570d5a30c57622d34/pytz-2018.9-py2.py3-none-any.whl
(510kB)
Requirement already satisfied, skipping upgrade: python-dateutil>=2.5.0 in /u
sr/local/lib/python3.5/dist-packages (from pandas->-r requirements.txt (line
1)) (2.7.5)
Requirement already satisfied, skipping upgrade: six in /usr/local/lib/python
3.5/dist-packages (from nltk->-r requirements.txt (line 3)) (1.11.0)
Collecting singledispatch (from nltk->-r requirements.txt (line 3))
  Downloading https://files.pythonhosted.org/packages/c5/10/369f50bcd4621b263
927b0a1519987a04383d4a98fb10438042ad410cf88/singledispatch-3.4.0.3-py2.py3-no
ne-any.whl
Collecting soupsieve>=1.2 (from beautifulsoup4->-r requirements.txt (line 4))

```

```

Downloading https://files.pythonhosted.org/packages/77/78/bca00cc9fa70bba12
26ee70a42bf375c4e048fe69066a0d9b5e69bc2a79a/soupsieve-1.8-py2.py3-none-any.wh
l (88kB)
Collecting webencodings (from html5lib->-r requirements.txt (line 5))
  Downloading https://files.pythonhosted.org/packages/f4/24/2a3e3df732393fed8
b3ebf2ec078f05546de641fe1b667ee316ec1dcf3b7/webencodings-0.5.1-py2.py3-none-a
ny.whl
Building wheels for collected packages: nltk, train
  Running setup.py bdist_wheel for nltk: started
  Running setup.py bdist_wheel for nltk: finished with status 'done'
  Stored in directory: /root/.cache/pip/wheels/4b/c8/24/b2343664bcceb7147efeb
21c0b23703a05b23fcfeaceaa2a1e
  Running setup.py bdist_wheel for train: started
  Running setup.py bdist_wheel for train: finished with status 'done'
  Stored in directory: /tmp/pip-ephem-wheel-cache-4kp5e2kp/wheels/35/24/16/37
574d11bf9bde50616c67372a334f94fa8356bc7164af8ca3
Successfully built nltk train
Installing collected packages: numpy, pytz, pandas, singledispatch, nltk, sou
psieve, beautifulsoup4, webencodings, html5lib, train
  Found existing installation: numpy 1.15.4
  Uninstalling numpy-1.15.4:
    Successfully uninstalled numpy-1.15.4
Successfully installed beautifulsoup4-4.7.1 html5lib-1.0.1 nltk-3.4 numpy-1.1
6.2 pandas-0.24.2 pytz-2018.9 singledispatch-3.4.0.3 soupsieve-1.8 train-1.0.
0 webencodings-0.5.1
You are using pip version 18.1, however version 19.0.3 is available.
You should consider upgrading via the 'pip install --upgrade pip' command.
2019-03-24 13:59:12,428 sagemaker-containers INFO      Invoking user script

```

Training Env:

```

{
  "input_config_dir": "/opt/ml/input/config",
  "model_dir": "/opt/ml/model",
  "module_name": "train",
  "module_dir": "s3://sagemaker-us-east-1-538652065034/sagemaker-pytorch-20
19-03-24-13-55-33-537/source/sourcedir.tar.gz",
  "framework_module": "sagemaker_pytorch_container.training:main",
  "channel_input_dirs": {
    "training": "/opt/ml/input/data/training"
  },
  "hosts": [
    "algo-1"
  ],
  "input_data_config": {
    "training": {
      "S3DistributionType": "FullyReplicated",
      "TrainingInputMode": "File",
      "RecordWrapperType": "None"
    }
  },
  "input_dir": "/opt/ml/input",
  "additional_framework_parameters": {},
  "resource_config": {
    "network_interface_name": "ethwe",
    "current_host": "algo-1",
    "hosts": [

```

```

        "algo-1"
    ]
},
"user_entry_point": "train.py",
"output_intermediate_dir": "/opt/ml/output/intermediate",
"current_host": "algo-1",
"output_dir": "/opt/ml/output",
"network_interface_name": "ethwe",
"num_cpus": 4,
"hyperparameters": {
    "epochs": 30,
    "hidden_dim": 200
},
"num_gpus": 1,
"log_level": 20,
"output_data_dir": "/opt/ml/output/data",
"job_name": "sagemaker-pytorch-2019-03-24-13-55-33-537"
}

```

Environment variables:

```

SM_CURRENT_HOST=algo-1
SM_TRAINING_ENV={"additional_framework_parameters":{}, "channel_input_dirs":
{"training": "/opt/ml/input/data/training"}, "current_host": "algo-1", "framework
_module": "sagemaker_pytorch_container.training:main", "hosts": ["algo-1"], "hype
rparameters": {"epochs": 30, "hidden_dim": 200}, "input_config_dir": "/opt/ml/inpu
t/config", "input_data_config": {"training": {"RecordWrapperType": "None", "S3Dist
ributionType": "FullyReplicated", "TrainingInputMode": "File"}}, "input_dir": "/op
t/ml/input", "job_name": "sagemaker-pytorch-2019-03-24-13-55-33-537", "log_leve
l": 20, "model_dir": "/opt/ml/model", "module_dir": "s3://sagemaker-us-east-1-5386
52065034/sagemaker-pytorch-2019-03-24-13-55-33-537/source/sourcedir.tar.g
z", "module_name": "train", "network_interface_name": "ethwe", "num_cpus": 4, "num_g
pus": 1, "output_data_dir": "/opt/ml/output/data", "output_dir": "/opt/ml/outpu
t", "output_intermediate_dir": "/opt/ml/output/intermediate", "resource_config":
{"current_host": "algo-1", "hosts": ["algo-1"], "network_interface_name": "ethw
e"}, "user_entry_point": "train.py"}
SM_FRAMEWORK_MODULE=sagemaker_pytorch_container.training:main
SM_INPUT_DATA_CONFIG={"training": {"RecordWrapperType": "None", "S3DistributionT
ype": "FullyReplicated", "TrainingInputMode": "File"}}
SM_HPS={"epochs": 30, "hidden_dim": 200}
SM_RESOURCE_CONFIG={"current_host": "algo-1", "hosts": ["algo-1"], "network_inter
face_name": "ethwe"}
SM_LOG_LEVEL=20
SM_NUM_GPUS=1
SM_CHANNEL_TRAINING=/opt/ml/input/data/training
SM_MODULE_NAME=train
SM_INPUT_DIR=/opt/ml/input
SM_OUTPUT_DIR=/opt/ml/output
SM_OUTPUT_DATA_DIR=/opt/ml/output/data
SM_FRAMEWORK_PARAMS={}
SM_OUTPUT_INTERMEDIATE_DIR=/opt/ml/output/intermediate
SM_NETWORK_INTERFACE_NAME=ethwe
SM_CHANNELS=["training"]
SM_USER_ENTRY_POINT=train.py
SM_USER_ARGS=["--epochs", "30", "--hidden_dim", "200"]
SM_HOSTS=["algo-1"]
PYTHONPATH=/usr/local/bin:/usr/lib/python3.5:/usr/lib/p

```



```
python3.5/plat-x86_64-linux-gnu:/usr/lib/python3.5/lib-dynload:/usr/local/lib/
python3.5/dist-packages:/usr/lib/python3/dist-packages
SM_MODEL_DIR=/opt/ml/model
SM_HP_HIDDEN_DIM=200
SM_MODULE_DIR=s3://sagemaker-us-east-1-538652065034/sagemaker-pytorch-2019-03
-24-13-55-33-537/source/sourcedir.tar.gz
SM_NUM_CPUS=4
SM_INPUT_CONFIG_DIR=/opt/ml/input/config
SM_HP_EPOCHS=30
```

Invoking script with the following command:

```
/usr/bin/python -m train --epochs 30 --hidden_dim 200
```

Using device cuda.

Get train data loader.

Model loaded with embedding_dim 32, hidden_dim 200, vocab_size 5000.

```
Epoch: 1, BCELoss: 0.6744139583743348
Epoch: 2, BCELoss: 0.5986390868011786
Epoch: 3, BCELoss: 0.5005764462509934
Epoch: 4, BCELoss: 0.4211335528870018
Epoch: 5, BCELoss: 0.36465318105658706
Epoch: 6, BCELoss: 0.33002998147692
Epoch: 7, BCELoss: 0.3563659969641238
Epoch: 8, BCELoss: 0.31212027705445583
Epoch: 9, BCELoss: 0.29185319281354244
Epoch: 10, BCELoss: 0.28123952843705
Epoch: 11, BCELoss: 0.265179662376034
Epoch: 12, BCELoss: 0.27453278734975933
Epoch: 13, BCELoss: 0.25752870951380047
Epoch: 14, BCELoss: 0.2320846583770246
Epoch: 15, BCELoss: 0.24524896211770117
Epoch: 16, BCELoss: 0.2236068066285581
Epoch: 17, BCELoss: 0.3993566912047717
Epoch: 18, BCELoss: 0.45077754709185386
Epoch: 19, BCELoss: 0.29468271227515475
Epoch: 20, BCELoss: 0.24662774557970008
Epoch: 21, BCELoss: 0.24226544006746642
Epoch: 22, BCELoss: 0.22338763001013776
Epoch: 23, BCELoss: 0.21355382763609596
Epoch: 24, BCELoss: 0.19338506004031825
Epoch: 25, BCELoss: 0.17303257146660161
Epoch: 26, BCELoss: 0.171290573873082
Epoch: 27, BCELoss: 0.16691533856245935
Epoch: 28, BCELoss: 0.16003402246504414
Epoch: 29, BCELoss: 0.14540520234375584
Epoch: 30, BCELoss: 0.13376906194857188
```

```
2019-03-24 14:07:52,902 sagemaker-containers INFO      Reporting training SUCCESS
```

```
2019-03-24 14:08:01 Uploading - Uploading generated training model
```

```
2019-03-24 14:08:01 Completed - Training job completed
```

```
Billable seconds: 610
```

Step 5: Testing the model

As mentioned at the top of this notebook, we will be testing this model by first deploying it and then sending the testing data to the deployed endpoint. We will do this so that we can make sure that the deployed model is working correctly.

Step 6: Deploy the model for testing

Now that we have trained our model, we would like to test it to see how it performs. Currently our model takes input of the form `review_length, review[500]` where `review[500]` is a sequence of 500 integers which describe the words present in the review, encoded using `word_dict`. Fortunately for us, SageMaker provides built-in inference code for models with simple inputs such as this.

There is one thing that we need to provide, however, and that is a function which loads the saved model. This function must be called `model_fn()` and takes as its only parameter a path to the directory where the model artifacts are stored. This function must also be present in the python file which we specified as the entry point. In our case the model loading function has been provided and so no changes need to be made.

NOTE: When the built-in inference code is run it must import the `model_fn()` method from the `train.py` file. This is why the training code is wrapped in a main guard (ie, `if __name__ == '__main__':`)

Since we don't need to change anything in the code that was uploaded during training, we can simply deploy the current model as-is.

NOTE: When deploying a model you are asking SageMaker to launch an compute instance that will wait for data to be sent to it. As a result, this compute instance will continue to run until *you* shut it down. This is important to know since the cost of a deployed endpoint depends on how long it has been running for.

In other words **If you are no longer using a deployed endpoint, shut it down!**

TODO: Deploy the trained model.

```
In [36]: # TODO: Deploy the trained model
         predictor = estimator.deploy(initial_instance_count=1, instance_type='ml.p2.xl
         arge')
```

```
INFO:sagemaker:Creating model with name: sagemaker-pytorch-2019-03-24-13-55-3
3-537
```

```
WARNING:sagemaker:Using already existing model: sagemaker-pytorch-2019-03-24-
13-55-33-537
```

```
INFO:sagemaker:Creating endpoint with name sagemaker-pytorch-2019-03-24-13-55
-33-537
```

```
-----
-----!
```

Step 7 - Use the model for testing

Once deployed, we can read in the test data and send it off to our deployed model to get some results. Once we collect all of the results we can determine how accurate our model is.

```
In [37]: test_X = pd.concat([pd.DataFrame(test_X_len), pd.DataFrame(test_X)], axis=1)
```

```
In [38]: # We split the data into chunks and send each chunk separately, accumulating the results.
```

```
def predict(data, rows=512):  
    split_array = np.array_split(data, int(data.shape[0] / float(rows) + 1))  
    predictions = np.array([])  
    for array in split_array:  
        predictions = np.append(predictions, predictor.predict(array))  
  
    return predictions
```

```
In [39]: predictions = predict(test_X.values)  
predictions = [round(num) for num in predictions]
```

```
In [40]: from sklearn.metrics import accuracy_score  
accuracy_score(test_y, predictions)
```

```
Out[40]: 0.8516
```

Question: How does this model compare to the XGBoost model you created earlier? Why might these two models perform differently on this dataset? Which do *you* think is better for sentiment analysis?

Answer:

I have two points to say here:

- The XGBoost model created before achieved similar accuracy of around 0.85 as well. Therefore, both models seem to be suitable for sentiment analysis.
- However, the XGBoost model uses Bag of Words (BoW) to encode the review vector (the input to the model). In contrast, the LSTM model uses an embedding vector for each word and creates a hidden state for the review by processing the sequence of word vectors. Since BoW vectors lose the order of words, and in the same time the LSTM can exploit the information from the order of words (from the hidden states), I believe the LSTM networks have a much higher potential to improve sentiment analysis results.

(TODO) More testing

We now have a trained model which has been deployed and which we can send processed reviews to and which returns the predicted sentiment. However, ultimately we would like to be able to send our model an unprocessed review. That is, we would like to send the review itself as a string. For example, suppose we wish to send the following review to our model.

```
In [41]: test_review = 'The simplest pleasures in life are the best, and this film is one of them. Combining a rather basic storyline of love and adventure this movie transcends the usual weekend fair with wit and unmitigated charm.'
```

The question we now need to answer is, how do we send this review to our model?

Recall in the first section of this notebook we did a bunch of data processing to the IMDb dataset. In particular, we did two specific things to the provided reviews.

- Removed any html tags and stemmed the input
- Encoded the review as a sequence of integers using `word_dict`

In order process the review we will need to repeat these two steps.

TODO: Using the `review_to_words` and `convert_and_pad` methods from section one, convert `test_review` into a numpy array `test_data` suitable to send to our model. Remember that our model expects input of the form `review_length, review[500]` .

```
In [42]: # TODO: Convert test_review into a form usable by the model and save the results in test_data

test_data = review_to_words(test_review)
test_data = [np.array(convert_and_pad(word_dict, test_data)[0])]
```

Now that we have processed the review, we can send the resulting array to our model to predict the sentiment of the review.

```
In [43]: predictor.predict(test_data)
```

```
Out[43]: array(0.76182634, dtype=float32)
```

Since the return value of our model is close to 1 , we can be certain that the review we submitted is positive.

Delete the endpoint

Of course, just like in the XGBoost notebook, once we've deployed an endpoint it continues to run until we tell it to shut down. Since we are done using our endpoint for now, we can delete it.

```
In [44]: estimator.delete_endpoint()
```

```
INFO:sagemaker:Deleting endpoint with name: sagemaker-pytorch-2019-03-24-13-55-33-537
```

Step 6 (again) - Deploy the model for the web app

Now that we know that our model is working, it's time to create some custom inference code so that we can send the model a review which has not been processed and have it determine the sentiment of the review.

As we saw above, by default the estimator which we created, when deployed, will use the entry script and directory which we provided when creating the model. However, since we now wish to accept a string as input and our model expects a processed review, we need to write some custom inference code.

We will store the code that we write in the `serve` directory. Provided in this directory is the `model.py` file that we used to construct our model, a `utils.py` file which contains the `review_to_words` and `convert_and_pad` pre-processing functions which we used during the initial data processing, and `predict.py`, the file which will contain our custom inference code. Note also that `requirements.txt` is present which will tell SageMaker what Python libraries are required by our custom inference code.

When deploying a PyTorch model in SageMaker, you are expected to provide four functions which the SageMaker inference container will use.

- `model_fn` : This function is the same function that we used in the training script and it tells SageMaker how to load our model.
- `input_fn` : This function receives the raw serialized input that has been sent to the model's endpoint and its job is to de-serialize and make the input available for the inference code.
- `output_fn` : This function takes the output of the inference code and its job is to serialize this output and return it to the caller of the model's endpoint.
- `predict_fn` : The heart of the inference script, this is where the actual prediction is done and is the function which you will need to complete.

For the simple website that we are constructing during this project, the `input_fn` and `output_fn` methods are relatively straightforward. We only require being able to accept a string as input and we expect to return a single value as output. You might imagine though that in a more complex application the input or output may be image data or some other binary data which would require some effort to serialize.

(TODO) Writing inference code

Before writing our custom inference code, we will begin by taking a look at the code which has been provided.

In [62]: !pygmentize serve/predict.py

```

import argparse
import json
import os
import pickle
import sys
import sagemaker_containers
import pandas as pd
import numpy as np
import torch
import torch.nn as nn
import torch.optim as optim
import torch.utils.data

from model import LSTMClassifier

from utils import review_to_words, convert_and_pad

def model_fn(model_dir):
    """Load the PyTorch model from the `model_dir` directory."""
    print("Loading model.")

    # First, load the parameters used to create the model.
    model_info = {}
    model_info_path = os.path.join(model_dir, 'model_info.pth')
    with open(model_info_path, 'rb') as f:
        model_info = torch.load(f)

    print("model_info: {}".format(model_info))

    # Determine the device and construct the model.
    device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
    model = LSTMClassifier(model_info['embedding_dim'], model_info['hidden_dim'], model_info['vocab_size'])

    # Load the store model parameters.
    model_path = os.path.join(model_dir, 'model.pth')
    with open(model_path, 'rb') as f:
        model.load_state_dict(torch.load(f))

    # Load the saved word_dict.
    word_dict_path = os.path.join(model_dir, 'word_dict.pkl')
    with open(word_dict_path, 'rb') as f:
        model.word_dict = pickle.load(f)

    model.to(device).eval()

    print("Done loading model.")
    return model

def input_fn(serialized_input_data, content_type):
    print('Deserializing the input data.')
    if content_type == 'text/plain':
        data = serialized_input_data.decode('utf-8')
        return data
    raise Exception('Requested unsupported ContentType in content_type: ' + content_type)

```

```

def output_fn(prediction_output, accept):
    print('Serializing the generated output.')
    return str(prediction_output)

def predict_fn(input_data, model):
    print('Inferring sentiment of input data.')

    device = torch.device("cuda" if torch.cuda.is_available() else "cpu")

    if model.word_dict is None:
        raise Exception('Model has not been loaded properly, no word_dict.')

    # TODO: Process input_data so that it is ready to be sent to our model.
    #       You should produce two variables:
    #       data_X   - A sequence of length 500 which represents the converted review
    #       data_len - The length of the review

    review_words = review_to_words(input_data)
    data_X, data_len = convert_and_pad(model.word_dict, review_words)

    # Using data_X and data_len we construct an appropriate input tensor. Remember
    # that our model expects input data of the form 'len, review[500]'.
    data_pack = np.hstack((data_len, data_X))
    data_pack = data_pack.reshape(1, -1)

    data = torch.from_numpy(data_pack)
    data = data.to(device)

    # Make sure to put the model into evaluation mode
    model.eval()

    # TODO: Compute the result of applying the model to the input data. The variable `result` should
    #       be a numpy array which contains a single integer which is either 1 or 0

    with torch.no_grad():
        review_prediction = model(data).to(device)
        prediction_result = np.round(review_prediction.numpy()).astype(np.int)

    return prediction_result

```

As mentioned earlier, the `model_fn` method is the same as the one provided in the training code and the `input_fn` and `output_fn` methods are very simple and your task will be to complete the `predict_fn` method. Make sure that you save the completed file as `predict.py` in the `serve` directory.

TODO: Complete the `predict_fn()` method in the `serve/predict.py` file.

Deploying the model

Now that the custom inference code has been written, we will create and deploy our model. To begin with, we need to construct a new `PyTorchModel` object which points to the model artifacts created during training and also points to the inference code that we wish to use. Then we can call the `deploy` method to launch the deployment container.

NOTE: The default behaviour for a deployed PyTorch model is to assume that any input passed to the predictor is a `numpy` array. In our case we want to send a string so we need to construct a simple wrapper around the `RealTimePredictor` class to accomodate simple strings. In a more complicated situation you may want to provide a serialization object, for example if you wanted to sent image data.

```
In [65]: from sagemaker.predictor import RealTimePredictor
         from sagemaker.pytorch import PyTorchModel

         class StringPredictor(RealTimePredictor):
             def __init__(self, endpoint_name, sagemaker_session):
                 super(StringPredictor, self).__init__(endpoint_name, sagemaker_session,
                 content_type='text/plain')

         model = PyTorchModel(model_data=estimator.model_data,
                             role = role,
                             framework_version='0.4.0',
                             entry_point='predict.py',
                             source_dir='serve',
                             predictor_cls=StringPredictor)
         predictor = model.deploy(initial_instance_count=1, instance_type='ml.m4.xlarge')
```

```
INFO:sagemaker:Created S3 bucket: sagemaker-us-east-1-538652065034
INFO:sagemaker:Creating model with name: sagemaker-pytorch-2019-03-25-16-36-38-795
INFO:sagemaker:Creating endpoint with name sagemaker-pytorch-2019-03-25-16-36-38-795
```

----- !

Testing the model

Now that we have deployed our model with the custom inference code, we should test to see if everything is working. Here we test our model by loading the first 250 positive and negative reviews and send them to the endpoint, then collect the results. The reason for only sending some of the data is that the amount of time it takes for our model to process the input and then perform inference is quite long and so testing the entire data set would be prohibitive.

```

In [66]: import glob

def test_reviews(data_dir='../data/aclImdb', stop=250):

    results = []
    ground = []

    # We make sure to test both positive and negative reviews
    for sentiment in ['pos', 'neg']:

        path = os.path.join(data_dir, 'test', sentiment, '.*.txt')
        files = glob.glob(path)

        files_read = 0

        print('Starting ', sentiment, ' files')

        # Iterate through the files and send them to the predictor
        for f in files:
            with open(f) as review:
                # First, we store the ground truth (was the review positive or
                negative)
                if sentiment == 'pos':
                    ground.append(1)
                else:
                    ground.append(0)
                # Read in the review and convert to 'utf-8' for transmission v
                ia HTTP
                review_input = review.read().encode('utf-8')
                # Send the review to the predictor and store the results
                results.append(int(predictor.predict(review_input)))

            # Sending reviews to our endpoint one at a time takes a while so w
            e
            # only send a small number of reviews
            files_read += 1
            if files_read == stop:
                break

    return ground, results

```

```

In [67]: ground, results = test_reviews()

```

```

Starting pos files
Starting neg files

```

```

In [68]: from sklearn.metrics import accuracy_score
accuracy_score(ground, results)

```

```

Out[68]: 0.852

```

As an additional test, we can try sending the `test_review` that we looked at earlier.

```
In [69]: predictor.predict(test_review)
```


```
Out[69]: b'1'
```

Now that we know our endpoint is working as expected, we can set up the web page that will interact with it. If you don't have time to finish the project now, make sure to skip down to the end of this notebook and shut down your endpoint. You can deploy it again when you come back.

Step 7 (again): Use the model for the web app

TODO: This entire section and the next contain tasks for you to complete, mostly using the AWS console.

So far we have been accessing our model endpoint by constructing a predictor object which uses the endpoint and then just using the predictor object to perform inference. What if we wanted to create a web app which accessed our model? The way things are set up currently makes that not possible since in order to access a SageMaker endpoint the app would first have to authenticate with AWS using an IAM role which included access to SageMaker endpoints. However, there is an easier way! We just need to use some additional AWS services.



The diagram above gives an overview of how the various services will work together. On the far right is the model which we trained above and which is deployed using SageMaker. On the far left is our web app that collects a user's movie review, sends it off and expects a positive or negative sentiment in return.

In the middle is where some of the magic happens. We will construct a Lambda function, which you can think of as a straightforward Python function that can be executed whenever a specified event occurs. We will give this function permission to send and receive data from a SageMaker endpoint.

Lastly, the method we will use to execute the Lambda function is a new endpoint that we will create using API Gateway. This endpoint will be a url that listens for data to be sent to it. Once it gets some data it will pass that data on to the Lambda function and then return whatever the Lambda function returns. Essentially it will act as an interface that lets our web app communicate with the Lambda function.

Setting up a Lambda function

The first thing we are going to do is set up a Lambda function. This Lambda function will be executed whenever our public API has data sent to it. When it is executed it will receive the data, perform any sort of processing that is required, send the data (the review) to the SageMaker endpoint we've created and then return the result.

Part A: Create an IAM Role for the Lambda function

Since we want the Lambda function to call a SageMaker endpoint, we need to make sure that it has permission to do so. To do this, we will construct a role that we can later give the Lambda function.

Using the AWS Console, navigate to the **IAM** page and click on **Roles**. Then, click on **Create role**. Make sure that the **AWS service** is the type of trusted entity selected and choose **Lambda** as the service that will use this role, then click **Next: Permissions**.

In the search box type `sagemaker` and select the check box next to the **AmazonSageMakerFullAccess** policy. Then, click on **Next: Review**.

Lastly, give this role a name. Make sure you use a name that you will remember later on, for example `LambdaSageMakerRole` . Then, click on **Create role**.

Part B: Create a Lambda function

Now it is time to actually create the Lambda function.

Using the AWS Console, navigate to the AWS Lambda page and click on **Create a function**. When you get to the next page, make sure that **Author from scratch** is selected. Now, name your Lambda function, using a name that you will remember later on, for example `sentiment_analysis_func` . Make sure that the **Python 3.6** runtime is selected and then choose the role that you created in the previous part. Then, click on **Create Function**.

On the next page you will see some information about the Lambda function you've just created. If you scroll down you should see an editor in which you can write the code that will be executed when your Lambda function is triggered. In our example, we will use the code below.

```
# We need to use the Low-Level Library to interact with SageMaker since the SageMaker API
# is not available natively through Lambda.
import boto3

def lambda_handler(event, context):

    # The SageMaker runtime is what allows us to invoke the endpoint that we've created.
    runtime = boto3.Session().client('sagemaker-runtime')

    # Now we use the SageMaker runtime to invoke our endpoint, sending the review we were given
    response = runtime.invoke_endpoint(EndpointName = '**ENDPOINT NAME HERE**',
    # The name of the endpoint we created
                                     ContentType = 'text/plain',
    # The data format that is expected
                                     Body = event['body'])
    # The actual review

    # The response is an HTTP response whose body contains the result of our inference
    result = response['Body'].read().decode('utf-8')

    return {
        'statusCode' : 200,
        'headers' : { 'Content-Type' : 'text/plain', 'Access-Control-Allow-Origin'
: '*' },
        'body' : result
    }
```

Once you have copy and pasted the code above into the Lambda code editor, replace the `**ENDPOINT NAME HERE**` portion with the name of the endpoint that we deployed earlier. You can determine the name of the endpoint using the code cell below.

```
In [70]: predictor.endpoint
```

```
Out[70]: 'sagemaker-pytorch-2019-03-25-16-36-38-795'
```

Once you have added the endpoint name to the Lambda function, click on **Save**. Your Lambda function is now up and running. Next we need to create a way for our web app to execute the Lambda function.

Setting up API Gateway

Now that our Lambda function is set up, it is time to create a new API using API Gateway that will trigger the Lambda function we have just created.

Using AWS Console, navigate to **Amazon API Gateway** and then click on **Get started**.

On the next page, make sure that **New API** is selected and give the new api a name, for example, `sentiment_analysis_api`. Then, click on **Create API**.

Now we have created an API, however it doesn't currently do anything. What we want it to do is to trigger the Lambda function that we created earlier.

Select the **Actions** dropdown menu and click **Create Method**. A new blank method will be created, select its dropdown menu and select **POST**, then click on the check mark beside it.

For the integration point, make sure that **Lambda Function** is selected and click on the **Use Lambda Proxy integration**. This option makes sure that the data that is sent to the API is then sent directly to the Lambda function with no processing. It also means that the return value must be a proper response object as it will also not be processed by API Gateway.

Type the name of the Lambda function you created earlier into the **Lambda Function** text entry box and then click on **Save**. Click on **OK** in the pop-up box that then appears, giving permission to API Gateway to invoke the Lambda function you created.

The last step in creating the API Gateway is to select the **Actions** dropdown and click on **Deploy API**. You will need to create a new Deployment stage and name it anything you like, for example `prod`.

You have now successfully set up a public API to access your SageMaker model. Make sure to copy or write down the URL provided to invoke your newly created public API as this will be needed in the next step. This URL can be found at the top of the page, highlighted in blue next to the text **Invoke URL**.

<https://z7fymrcze6.execute-api.us-east-1.amazonaws.com/prod> (<https://z7fymrcze6.execute-api.us-east-1.amazonaws.com/prod>)

Step 4: Deploying our web app

Now that we have a publicly available API, we can start using it in a web app. For our purposes, we have provided a simple static html file which can make use of the public api you created earlier.

In the `website` folder there should be a file called `index.html`. Download the file to your computer and open that file up in a text editor of your choice. There should be a line which contains ****REPLACE WITH PUBLIC API URL****. Replace this string with the url that you wrote down in the last step and then save the file.

Now, if you open `index.html` on your local computer, your browser will behave as a local web server and you can use the provided site to interact with your SageMaker model.

If you'd like to go further, you can host this html file anywhere you'd like, for example using github or hosting a static site on Amazon's S3. Once you have done this you can share the link with anyone you'd like and have them play with it too!

Important Note In order for the web app to communicate with the SageMaker endpoint, the endpoint has to actually be deployed and running. This means that you are paying for it. Make sure that the endpoint is running when you want to use the web app but that you shut it down when you don't need it, otherwise you will end up with a surprisingly large AWS bill.

TODO: Make sure that you include the edited `index.html` file in your project submission.

Now that your web app is working, trying playing around with it and see how well it works.

Question: Give an example of a review that you entered into your web app. What was the predicted sentiment of your example review?

Answer:

- review: "I like this movie very much, even though it scared me to death"
- predicted sentiment: "Your review was POSITIVE!"

-
- review: "I don't like this movie at all, it scared me to death"
 - predicted sentiment: "Your review was POSITIVE!"

-
- review: "This is a horrible movie, it scared me to death"
 - predicted sentiment: "Your review was NEGATIVE!"

-
- review: "I went to see this film in the theater dragging my feet, however I am currently not regretting this move."
 - predicted sentiment: "Your review was POSITIVE!"

Delete the endpoint

Remember to always shut down your endpoint if you are no longer using it. You are charged for the length of time that the endpoint is running so if you forget and leave it on you could end up with an unexpectedly large bill.

```
In [76]: try:
          predictor.delete_endpoint()
        except:
          print("No new endpoints to delete !")
```

```
INFO:sagemaker:Deleting endpoint configuration with name: sagemaker-pytorch-2
019-03-25-16-36-38-795
```

```
No new endpoints to delete !
```

```
In [ ]:
```