Rakuten Product Classification — Visualizations 3+

This notebook contains the **visualizations from the newer audit notebook starting with Figure 3**, but adapted so it can run inside the existing `liora-capstone` GitHub project.

The data is loaded at the beginning using the project's existing helper:

```
df = load_merged_data()
```

Figures 1 and 2 from the newer notebook are intentionally omitted.

1. Imports

```
Environment loaded successfully.
```

2. Load Data

```
Dataset shape: (84916, 5)
```

	designation	description	productid	imageid	prdtypecode
0	Olivia: Personalisiertes Notizbuch / 150 Seiten / Punktraster / Ca Din A5 / Rosen-Design	NaN	3804725264	1263597046	10
1	Journal Des Arts (Le) N° 133 Du 28/09/2001 - L'art Et Son Marche Salon D'art Asiatique A Paris - Jacques Barrere - F...	NaN	436067568	1008141237	2280
2	Grand Stylet Ergonomique Bleu Gamepad Nintendo Wii U - Speedlink Pilot Style	PILOT STYLE Touch Pen de marque Speedlink est 1 stylet ergonomique pour GamePad Nintendo Wii U. Pour un confort ...	201115110	938777978	50
3	Peluche Donald - Europe - Disneyland 2000 (Marionnette À Doigt)	NaN	50418756	457047496	1280
4	La Guerre Des Tuques	Luc a des idées de grandeur. Il veut organiser un jeu de guerre de boules de neige et s'arranger pour en &eci...	278535884	1077757786	2705


3. Audit Feature Construction

The following analytical features are required by Figures 3 onward.
The original dataframe `df` remains unchanged.

	designation	has_description	designation_chars	description_chars	total_text_chars
0	Olivia: Personalisiertes Notizbuch / 150 Seiten / Punktraster / Ca Din A5 / Rosen-Design	False	88	0	88
1	Journal Des Arts (Le) N° 133 Du 28/09/2001 - L'art Et Son Marche Salon D'art Asiatique A Paris - Jacques Barrere - F...	False	206	0	206
2	Grand Stylet Ergonomique Bleu Gamepad Nintendo Wii U - Speedlink Pilot Style	True	76	760	836
3	Peluche Donald - Europe - Disneyland 2000 (Marionnette À Doigt)	False	63	0	63
4	La Guerre Des Tuques	True	20	213	233

4. Figure 3 — Description Availability by Class

If missing descriptions are associated with the target, description availability itself may contain category-related information.




Finding 3 — missing descriptions are category-dependent

Observation. Class-level description availability ranges from 2.6% to 100.0%.

Quantitative validation. χ^2=43,757.8, p=0, Cramér's V=0.718.

Business implication. Description presence may improve classification, but it can also reflect seller behaviour rather than product semantics.

5. Figure 4 — Designation Length by Class




Finding 4 — title length contains target-related structure

Observation. Median designation length by class ranges from 31 to 125 characters.

Quantitative validation. Kruskal–Wallis H=19,025.3, p=0; epsilon-squared=0.224.


Business implication. Text models should consider both word and character information. For neural models, sequence length should be chosen from the observed distribution.

6. Figure 5 — Relationship Between Designation and Description Length



"Descriptions are much longer than designations, while their lengths are only moderately correlated. Therefore, we should test whether combining both text fields improves classification."

8. Figure 7 — Duplicate Designations and Conflicting Labels



Finding 7 — duplicates create a validation-leakage risk

Observation. 4,172 training rows (4.9%) belong to a repeated normalized designation. 497 rows belong to duplicate-title groups containing more than one target class.

Quantitative validation. There are 1,463 repeated-title groups and 160 conflicting-label groups.

Business implication. Compare a standard stratified split with a grouped split based on normalized designation. Review conflicting groups before modeling.

4.172 Zeilen = 4,9 % des gesamten Trainingsdatensatzes haben einen normalisierten Titel, der mindestens zweimal vorkommt. Von diesen Duplikaten gehören 497 Zeilen zu problematischen Gruppen, bei denen derselbe Titel unterschiedliche Klassenlabels besitzt.

Titel Klasse

"Samsung Galaxy S20" 10 "Samsung Galaxy S20" 10 ← normales Duplikat

"Harry Potter DVD" 40 "Harry Potter DVD" 50 ← conflicting duplicate

A **duplicate group** contains all rows that have the same normalized designation.

Example:

Row	Normalized designation	Class
1	iphone 12 black	10
2	iphone 12 black	10
3	iphone 12 black	10
4	harry potter dvd	40
5	harry potter dvd	50
6	sony headphones	30
7	sony headphones	30

This gives:

- **7 duplicate rows**
- **3 duplicate groups**
  - `iphone 12 black`
  - `harry potter dvd`
  - `sony headphones`

Only one group is conflicting:

- `harry potter dvd` → appears with class 40 and class 50

So:

- Duplicate rows = 7
- Duplicate groups = 3
- Conflicting groups = 1

9. Text-Quality Flags

	train
contains_html	18.42%
contains_url	0.24%
contains_mojibake	1.08%

	flag	train_rows
0	contains_html	15645
1	contains_url	203
2	contains_mojibake	918

10. Figure 8 — Image Duplicates and Conflicting Labels

This section audits **all training and test images referenced by the project CSV files**, rather than a random sample.

- **File duplicates:** SHA-256 of the complete file bytes; these files are byte-for-byte identical.
- **Pixel duplicates:** SHA-256 of the image dimensions and all decoded RGB pixels after applying EXIF orientation. This also detects identical decoded images stored with different metadata or encodings.
- **Label conflicts:** a repeated pixel-image group with more than one `prdtypecode` among its **training** rows. Test labels are unavailable and are not inferred.
- **Train–test overlap:** the same pixel-image hash occurs in both splits.

No resizing or perceptual hashing is used. Visually similar images with changed pixels, crops or JPEG compression may therefore remain undetected. Missing or unreadable images are reported separately and excluded from pixel-duplicate rates.

Hashes are cached under `data/processed/`; a file is rescanned when its size or modification time changes. The raw images and the original dataframe `df` are not modified.


```
Images reused from cache: 0; to scan: 98,728
Hashed 10,000/98,728 images
Hashed 20,000/98,728 images
Hashed 30,000/98,728 images
Hashed 40,000/98,728 images
Hashed 50,000/98,728 images
Hashed 60,000/98,728 images
Hashed 70,000/98,728 images
Hashed 80,000/98,728 images
Hashed 90,000/98,728 images
Hashed 98,728/98,728 images
Readable images: 98,728/98,728
```

split	train	test
catalog_rows	84916.000000	13812.000000
readable_rows	84916.000000	13812.000000
failed_rows	0.000000	0.000000
file_duplicate_groups	3264.000000	180.000000
file_duplicate_rows	8956.000000	410.000000
pixel_duplicate_groups	3264.000000	180.000000
pixel_duplicate_rows	8956.000000	410.000000
redundant_pixel_rows	5692.000000	230.000000
duplicate_rate	0.105469	0.029684
rows_in_both_splits	2937.000000	1444.000000

```
Training label conflicts: 479 groups, 1,074 rows
Shared train–test pixel–image groups: 1,265
```

	hash_prefix	rows	splits	training_classes
0	b3590c6f8cd0	53	2	1
1	7743c1bbd643	28	2	1
2	a046fed161d0	28	2	1
3	a3e6b6a6ebb6	28	2	1
4	106bf57e5a83	25	2	1
5	65b2e38ff376	24	2	1
6	0f15861ee9ca	22	2	1
7	a5f5256e3209	22	2	1
8	c24f01c7e4f7	21	2	1
9	355bfe4452bb	20	2	1

Figure 8: Exact Image Duplicates and Train–Test Overlap



How to read the duplicate counts

For a hash group containing three catalog rows, **duplicate rows = 3**, **duplicate groups = 1**, and **redundant rows = 2**. Duplicate rates count **all members** of a repeated group and use readable rows in the relevant split as their denominator.

A group shared by train and test may contain only one training row and one test row: that is **overlap**, but not a within-training or within-test duplicate. The summary reports these measures separately.

An identical image assigned to different training classes is a **label-conflict candidate**, not automatically a labeling error. Generic cover images, placeholders or shared packaging can legitimately represent different products. The example gallery is intended for review.

Examples of identical decoded images

test | class unavailable
product 1655485600 | image 1096519773

train | class 50
product 1712289008 | image 1100102350

train | class 1140
product 1655376360 | image 1096515918

Hash 437bce80a178 | 6 catalog rows

test | class unavailable
product 4167091102 | image 1306840984



train | class 2522
product 4167088572 | image 1306821275




test | class unavailable
product 4167091182 | image 1306841436




Hash b3590c6f8cd0 | 53 catalog rows


test | class unavailable
product 85756666 | image 854179052



train | class 1160
product 83464929 | image 851445095



test | class unavailable
product 85757275 | image 854179992



Hash 7743c1bbd643 | 28 catalog rows

Finding 8 — repeated images need a separate leakage and label audit

Observation. 8,956 of 84,916 readable training rows (10.5%) belong to a repeated decoded-image group. These groups contain 5,692 additional rows beyond one representative per group.

Quantitative validation. 3,264 training pixel-duplicate groups; 479 groups with conflicting training labels (1,074 rows); 1,265 image groups shared by train and test; 0 unreadable or missing images across the audited catalog. All counts use the full referenced image catalog, not a sample.

Business implication. Keep identical-image groups in the same validation fold. If title and image duplicates are both used for grouping, connect overlapping groups so neither type can cross folds. Review conflicting labels and generic placeholder images before deciding whether to remove or downweight rows. Treat official train–test overlap as an audit finding; it does not by itself prove incorrect labels or justify modifying the official test set.

11. Preprocessing Decisions Supported by Figures 3+

- Keep `has_description` as an explicit feature if validation confirms that it helps.
- Compare designation-only, description-only and combined-text models.
- Use word and character representations for text.
- Keep repeated normalized designations and identical decoded images within one validation fold; connect overlapping title/image groups when using both criteria.
- Review duplicate-image groups with conflicting training labels and generic placeholder images before removing or downweighting rows.
- Report train–test image overlap separately from duplicates within each split; leave the official test data unchanged.
- Keep image paths and loading centralized through `src.data_utils`.
- Figure 8 audits the complete training image catalog and includes test images when the project's test CSV is available. Its hash cache is stored under `data/processed/`.