



MORGAN & CLAYPOOL PUBLISHERS

CHAPTER 9


MODEL-TO-TEXT TRANSFORMATIONS

Teaching material for the book

Model-Driven Software Engineering in Practice

by Marco Brambilla, Jordi Cabot, Manuel Wimmer.

Morgan & Claypool, USA, 2012.



Copyright © 2012 Brambilla, Cabot, Wimmer.

Content

- Introduction
- Programming Languages based Code Generation
- M2T Transformation based Code Generation
- Mastering Code Generation



INTRODUCTION



Introduction

Terminology

- Code generation
 - *Wikipedia*:
„**Code generation** is the process by which a compiler's code generator converts a syntactically-correct program into a series of **instructions** that can be **executed by a machine**.“
 - *Code Generation in Action* (Herrington 2003):
„**Code generation** is the technique of using or writing programs that write **source code**.“
- Code generation (<http://en.wikipedia.org>)
 - **Compiler Engineering**: component of the synthesis phase
 - **Software Engineering**: program to generate source code
- **Résumé**: Term *Code Generation* is **overloaded!**



Introduction


Code Generation - Basic Questions

- ***How much is generated?***
 - *Which parts can be automatically generated from models?*
 - *Full or partial code generation?*
- ***What is generated?***
 - *Which kind of source code to generate?*
 - *The less code to generate, the better!*
- ***How to generate?***
 - *Which languages and tools to use for developing code generators?*
 - *GPLs vs. DSLs*



Introduction

Code Generation in MDA (just an example)



Introduction

What kind of code is generated?

- **Model-to-Text**, whereas **text** may be distinguished in
 - Program code
 - Documentation
 - Test cases
 - Model serialization (XMI)
- Direct translation to machine code possible, but inconvenient, error-prone and hard to optimize
 - Reuse existing code generators
 - Using existing functionality (frameworks, APIs, components)
 - **Motto**: The less code to generate, the better!



Introduction


Example: Platform for Web application development

- Example: developing a code generator for Web applications
- *What **options** exist for the to be generated code?*
 - **Dimensions** of Web applications: *Content, Hypertext, Presentation*
 - **Programming languages**: *Java, C#, Ruby, PHP, ...*
 - **Architectures**: *2-layer, 3-layer, MVC, ActiveRecord, ...*
 - **Frameworks**: *JSF, Spring, Struts, Hibernate, Ruby on Rails, ASP, ...*
 - **Products**: *MySQL, Tomcat, WebLogic, ...*
- *Which **combinations** are appropriate?*
 - **Experience** gained in earlier projects
 - What has proven useful?
 - **Reference architectures**



Introduction

What kind of code is generated?




Picture based on Bernhard Rumpe: *Agile Modellierung mit UML*. Springer, 2012.



Introduction

Overview of generation techniques



Based on Markus Völter. A catalog of patterns for program generation. In *Proceedings of the 8th European Conference on Pattern Languages of Programs (EuroPLoP'03)*, pages 285–320, 2003.

Introduction

Why code generation?


- Code generation enables
 - Separation of **application modeling** and **technical code**
 - Increasing **maintainability**, **extensibility**, **portability** to new hardware, operating systems, and platforms
 - **Rapid prototyping**
 - **Early and fast feedback** due to demonstrations and test runs
- Code generation enables to **combine** redundant code fragments **in one source**
 - Example: DDL, Hibernate, and Java Beans
→ may be specified in one UML Class Diagram



Introduction

Why code generation? – in contradiction to MDE? (1/2)

- Often **no “real” model simulation** possible
 - UML environments mostly do not provide simulation features
 - However, they provide **transparent transformation** to C, C#, Java, ...
 - *UML Virtual Machines*
 - **Interpreter approach** – spare code generation for certain platforms
 - Gets a new twist with fUML!
- **Semantics** of modeling languages, especially DSMLs, often defined by code generation



Introduction

Why code generation? – in contradiction to MDE? (2/2)


- Runtime environments are designed for programming languages
 - Established frameworks available (*Struts, Spring, Hibernate, ...*)
 - Systems depend on existing software (*Web Services, DB*)
 - Extensions for code level often required (*Logging*)
- **Disadvantage:** using models and code in parallel
 - No single source of information – **OUCH!**
 - Having the same information in **two** places may lead to inconsistencies, e.g., consider maintainability of systems



Introduction

Example: MiniUML_2_MiniJava

MiniUML Metamodel



MiniJava Grammar



ClassDec := Modifier **"class"** Identifier [**"extends"** Identifier] **ClassBody**;

AttributeDec := Modifier Type Identifier**";"**;

MethodDec := Modifier ReturnType Identifier **"("** ParamList **"")** **"{"** MethodBody **"}"**;

Identifier := **"{a-z" | "A-Z" | "0-9"**;

MiniUML Model



MiniJava Code

```
class Student extends Person{
    private String regNo;
    public void setRegNo(...) {...}
    public String getRegNo() {...}
}
```

PROGRAMMING LANGUAGES BASED CODE GENERATION



Programming languages

Introduction – Code generation with Java based on EMF


- Code generation may be realized using a traditional general purpose programming language, e.g., Java, C#, ...
- Models are **de-serialized** to an in-memory *object graph*
 - Pre-defined XML de-serializer provided by meta-modeling frameworks
 - Out-of-the-box support in EMF
- **Model API** eases processing of models
 - Generated automatically from metamodels
 - In EMF: .ecore -> .genmodel -> Java code
 - If metamodel not available, you may use **reflection**



Programming languages

Model APIs for processing models

- **Example:** Ecore-based metamodel and automatically generated Java code (shown as UML Class Diagram)



Programming languages

Code generation with Java: phases of code generation

1. ***Load models***

- Load XML file into memory

2. ***Process models and produce code***

- Process models by traversing the model structure
- Use model information to produce code
- Save code into String variable

3. ***Write code***

- Persist String variable to a file using streams





Programming languages

Code generation with Java: Process and Architecture

Process

Architecture



Programming languages

Running Example solved in Java

```
ResourceSet resourceSet = new ResourceSetImpl();  
Resource resource = resourceSet.getResource(URI.create("model.miniUML"));  
TreeIterator treeIter = resource.getAllContents();
```

(1) Load

Get all model elements

```
while (treeIter.hasNext()) {  
    Object object = treeIter.next();  
    if (!object instanceof Class) continue;
```

```
    Class cl = (Class) object;  
    String code = "class „ + cl.getName() + "{";  
    // generate Constructor: code += ...  
    // generate Attributes: code += ...  
    // generate Methods: code += ...  
    code += "}";
```

Query values via model API

(2) Produce

```
try {  
    FileOutputStream fos = new FileOutputStream(cl.getName() + ".java");  
    fos.write(code.getBytes());  
    fos.close();  
} catch (Exception e) {...}  
}
```

Create a file for each class

(3) Write



Programming languages

Summary

- **Advantages**

- No new languages have to be learned
- No additional tool dependencies

- **Disadvantages**

- Intermingled static/dynamic code
- Non-graspable output structure
- Lack of declarative query language
- Lack of reusable base functionality



M2T TRANSFORMATION BASED CODE GENERATION



M2T Transformation Languages...

...are Template based

- **Templates** are a well-established technique in software engineering
 - Application domains: Text processing, Web engineering, ...
 - Example:

E-Mail Text

Dear **Homer Simpson**,
Congratulations! You have won ...

Template Text

Dear **«firstName» «lastName»**,
Congratulations! You have won ...


- Components of a template-based approach
 - **Templates**
 - **Text fragments** and **embedded meta-markers**
 - **Meta-markers** query an additional data source
 - Have to be **interpreted** and **evaluated** in contrast to text fragments
 - Declarative model query: query languages (OCL, XPath, SQL)
 - Imperative model query: programming languages (Java, C#)
 - **Template engine**
 - Replaces meta-markers with data at runtime and produces output files



M2T Transformation Languages

Core Architecture

- Template-based approach at a glance



M2T Transformation Languages

Benefits

- **Separated** static/dynamic code
 - Templates separate **static** code, i.e., normal text, from **dynamic** code that is described by meta-markers
- **Explicit** output structure
 - **Primary structure** of the template is the **output structure**
 - Computation logic is embedded in this structure
- **Declarative** query language
 - **OCL** is employed to query the input models
- **Reusable** base functionality
 - Support for reading in models, serialize text to files, ...



M2T Transformation Languages

Approaches

- A bunch of template languages for M2T transformation available
 - JET, JET2
 - **Xpand, Xtend**
 - **MOFScript**
 - **Acceleo**
 - XSLT
 - ...



- **Acceleo** is a mature **implementation** of the **OMG M2T transformation standard**
 - Acceleo website: <http://www.eclipse.org/acceleo/>
 - M2T Transformation standard: <http://www.omg.org/spec/MOFM2T>
- **Template-based** language
 - Several meta-markers for useful for code generation available
- Powerful **API** supporting
 - OCL
 - String manipulation functions
 - ...
- Powerful **tooling supporting**
 - Editor, debugger, profiler, traceability between model and code, ...



- **Module** concept is provided
 - Imports the metamodels for the input models
 - Act as container for templates
- A **template** is always **defined** for a particular **meta-class**
 - Plus an optional **pre-condition** to filter instances
 - Templates may **call** each other
 - Templates may **extended** each other
 - Templates contain text and provided meta-markers



- Several meta-markers (called *tags*) are supported
- **File** Tag: To open and close files in which code is generated
- **For/If** Tag: Control constructs for defining loops and conditions
- **Query** Tag: Reusable helper functions
- **Expression** Tag: Compute values that are embedded in the output
- **Protected** Tag: Define areas that are not overridden by future generation runs



Acceleo

Example

[**module** generateJavaClass('http://smvcm1/1.0')]

[**query** public getter(att : Attribute) : String = 'get'+att.name.toUpperFirst() /]

[**query** public returnStatement(type: String) : String = if type = 'Boolean'
then 'return true;' else '...' endif /]

[**template** public javaClass(aClass : Class)]

[**file** (aClass.name.toUpperFirst()+' .java', false, 'UTF-8')]
package entities;

import java.io.Serializable;

public class [aClass.name/] implements Serializable {

[**for** (att : Attribute | aClass.atts) separator ('\n')
[javaAttribute(att)/]
[/**for**]

[**for** (op : Operation | aClass.ops) separator ('\n')
[javaMethod(op)/]
[/**for**]

}
[/**file**]
[/**template**]
...

Import metamodel
(root package)

Query

Open output file

Static Text

Template
Call

Loop

Close output file

Template definition

Meta class

Expression

[**template** public javaAttribute(att : Attribute)
private [att.type/] [att.name/];

public [att.type/] [att.getter()/]() {
return [att.name/];
}

...
[/**template**]

[**template** public javaMethod(op : Operation)
public [op.type/] [op.name/]() {
// [**protected** (op.name)]
// Fill in the operation implementation here!
[returnStatement(op.type)/]
// [**protected**]
}
[/**template**]

Protected
Area



- **Protected areas are not overridden** by the **next generator run**
- They are **marked by comments**
- Their content is **merged** with the newly produced code
 - If the right place cannot be found, warning is given!

- **Example**

```
public boolean checkAvailability(){  
    // Start of user code checkAvailability  
    // Fill in the operation implementation here!  
    return true;  
    // End of user code  
}
```



MASTERING CODE GENERATION

www.mdse-book.com



Abstracting Templates

- To ensure that generated code is **accepted** by developers (cf. *Turing test for code-generation*), familiar code should be generated
 - Especially when only a **partial** code generation is possible!
- **Abstract** code generation templates **from reference code** to have known structure and coding guidelines considered
- **Acceleo** supports dedicated **refactorings** to **transform code into templates**
 - E.g., substitute String with Expression Tag



Generating step-by-step

- **Divide code generation process into several steps**
 - Same applies as for M2M transformations!
- **Transformation chains** may use a **mixture** of M2M and M2T transformations
 - To keep the gap between the models and the code short
- If code generators **exists**, try to produce their required input format with simpler M2M or M2T transformations
 - E.g., code generator for flat state machines, transform composite state machines to flat ones and run existing code generator



Separating transformation logic from text

- **Separate** complex transformation **logic** from **text** fragments
- Use ***queries*** or ***libraries*** that are imported to the M2T transformation
- By this, templates get more **readable** and maintainable
- Queries may be **reused**



Mastering code layout

- **Code layout** is determined by the **template layout**
- Challenging to produce code layout when several control structures such as loops and conditionals are used in the template
 - Special escape characters for line breaks used for enhancing the readability of the template are provided
- Alternative
 - Use **code beautifiers** in a post-processing step
 - Supported by Xpand for Java/XML out-of-the-box




Model/code synchronization issues

- **Protected areas** help saving manually added code in succeeding generator runs
- Code contained in protected areas is **not always automatically** integrated in the newly generated code
 - Assume a method is renamed on model level
 - Where to place the code of the method implementation?
 - Which identifier to use for identifying a protected area?
 - Natural or artificial identifiers?
- Model refactorings may be replayed on the code level before the next generator run is started
 - Code in protected areas may also reflect the refactorings!



Code Generation = M2M + TCS?

- Code Generation achievable through applying a ***M2M transformations*** to a ***programming language metamodel***
- If a **TCS** is available for the programming language metamodel, the resulting ***model*** may be directly ***serialized*** into text
- **Only recommended** when
 - programming language metamodel + TCS are already **available**
 - **full** code generation is possible





MORGAN & CLAYPOOL PUBLISHERS

MODEL-DRIVEN SOFTWARE ENGINEERING IN PRACTICE

Marco Brambilla,
Jordi Cabot,
Manuel Wimmer.
Morgan & Claypool, USA, 2012.

www.mdse-book.com

www.morganclaypool.com

