

// topic 33: PCA

agenda:

1. unsupervised learning & what is PCA?
2. why PCA?
3. concept: how does PCA work?
4. evaluating PCA

unsupervised learning & PCA

- supervised learning is done to **predict** on **labelled data**
- unsupervised learning - there are no “labels”
 - i.e. clustering, PCA, LDA

dimensionality reduction

- PCA is a form of dimensionality reduction
- unsupervised because we only tell it **how many dimensions** to reduce to
- PCA reduces the dimensionality of the feature set into **n principal components** while maintaining its **variance**
- principal components are **linear combinations** of original features


why and when do we use PCA?

- the **curse of dimensionality**
 - as we have more features (columns), data points become more sparse
 - the distance between points gets greater, making it more difficult to implement some ML models
 - complexity: time and space complexity
- when to use PCA:
 - when you have a lot of continuous (not categorical) features!
 - best for clustering, or computationally-heavy ML algos like SVM

how does PCA work?

- linear algebra!
 - mathematically, **Principal Components** are found through doing **Eigendecomposition** of the **Covariance Matrix**
1. Recenter your data such that the means of each feature are 0
 2. Get the covariance matrix (in Pandas: `df.corr()`)
 3. Get the **eigenvectors** of the covariance matrix
 4. Sort the eigenvectors
 5. Multiply the eigenvectors by the recentered data (for 2 PCs, multiply by the first two eigenvectors)

Dimensionality Reduction for Visualization



Dimensionality Reduction Methods

1. PCA (for dense data):
<https://scikit-learn.org/stable/modules/generated/sklearn.decomposition.PCA.html>
2. Truncated SVD (for sparse data):
<https://scikit-learn.org/stable/modules/generated/sklearn.decomposition.TruncatedSVD.html>
3. TSNE (optimized for visualization -- separability):
<https://scikit-learn.org/stable/modules/generated/sklearn.manifold.TSNE.html>

evaluating PCA

- how many Principal Components is best for your dataset?

