Quick guide — UPS-B online UPS (UPS-B-02)

The UPS-B 10 kVA is a single-phase double-conversion UPS. This guide summarises the indicators and the main values.

Tableau 1.1 *— Main specifications*

Item	Value
Rated power	10 kVA / 9 kW
Input / output	230 V single-phase, 50 Hz
Batteries	20 blocks 12 V 7 Ah (240 V DC bus)
Runtime	8 min at full load
Heatsink temperature alarm	65 °C
Serial number	UB010-2024-0158

Document synthétique fictif — projet pédagogique MaintiDoc (EMSI 2026) — aucune valeur technique réelle

Indicators

Tableau 2.1 *— Indicators and alarms*

Code	Indicator	Meaning
UB-401	ON BATT (orange)	Running on battery
UB-402	LOW BATT (red)	Remaining runtime below 2 min
UB-403	OVLD (red)	Overload above 100 %
UB-404	TEMP (orange)	Heatsink above 65 °C
UB-405	BATT REPL (orange)	Battery replacement required
UB-406	RECT (red)	Rectifier fault

Documentation support only. See the French manual manuel_ups_b for safety instructions.

Document synthétique fictif — projet pédagogique MaintiDoc (EMSI 2026) — aucune valeur technique réelle