Deep Learning Project Proposal

Assignment Brief & Submission Template

Course: Deep Learning (Graduate) **Total Marks:** 100 **Submission Format:** PDF/Word, max 10 pages

Part A — Assignment Brief

A.1 Objective

Students will identify a real-world problem, source an appropriate real-world dataset, and design (not necessarily fully train) a deep learning solution that improves upon or meaningfully differs from existing published approaches. The emphasis is on rigorous problem framing, dataset justification, literature grounding, and technical novelty — not just model implementation.

A.2 Mandatory Constraints

Your proposal must satisfy every constraint below. Proposals violating any constraint without an approved justification will be returned for revision.

- No Kaggle datasets. Source data from primary/official repositories, government open-data portals, institutional archives, APIs, or data you collect/curate yourself.
- Exception clause: If a Kaggle-hosted dataset is unavoidable for your problem domain, you must change your modeling technique substantially from what is commonly published for that exact dataset (e.g., a different architecture family, a different learning paradigm, or a materially different feature/representation strategy) — and justify this choice explicitly in Section 3.
- No synthetic/computer-generated data (e.g., GAN-generated images, simulated sensor data, procedurally generated text) as your primary dataset. Real-world collected or observed data only.
- Dataset size must be large enough to reasonably train a deep learning model. As a rule of thumb: thousands of labeled samples minimum for classification tasks; more for generative or sequence tasks. Justify sufficiency for your specific architecture.
- Dataset must be reasonably balanced across classes/labels, or you must propose and justify a specific class-imbalance handling strategy (e.g., stratified sampling, class-weighted loss, focal loss, SMOTE-family resampling) if perfect balance isn't achievable.
- Use current, state-of-the-art tools and techniques appropriate to your problem (see Section A.3 for examples).

A.3 Examples of Current Tools & Techniques

You are not limited to this list, but your proposal should reflect awareness of the current state of the field rather than outdated defaults.

Frameworks & Training Infrastructure

- PyTorch 2.x with torch.compile for optimized training
- PyTorch Lightning or Hugging Face Accelerate for scalable, reproducible training loops
- Hugging Face Transformers / Datasets / Tokenizers for NLP and multimodal tasks
- Weights & Biases or MLflow for experiment tracking
- Optuna or Ray Tune for automated hyperparameter optimization

Architectures & Techniques

- Vision Transformers (ViT, Swin Transformer) and ConvNeXt for image tasks
- Parameter-efficient fine-tuning: LoRA, QLoRA, adapters — for adapting large pretrained models cheaply
- Self-supervised / contrastive pretraining (SimCLR, DINO, CLIP-style objectives) when labeled data is limited
- Diffusion-based approaches for generative or denoising sub-tasks
- Graph Neural Networks (GNN, GAT, GraphSAGE) for relational/structured data
- Efficient/edge deployment: quantization, ONNX export, TensorRT, model distillation

A.4 Grading Rubric

Criterion	Description	Weight
Problem Definition & Motivation	Clarity, specificity, and real-world relevance of the problem statement	10%
Dataset Justification	Dataset is real, non-Kaggle (or technique changed), non-synthetic, large enough, and balanced; justification is well-argued	15%
Literature Review	Number and quality of prior works discussed; correct references; techniques summarized accurately	15%
Novelty & Technical Approach	Clear articulation of how the proposed technique differs from existing work and why it should perform well	20%
Tools & Techniques	Use of current, state-of-the-art DL tools/frameworks with justification	10%
System/Flow Diagram	Clarity and completeness of the proposed pipeline diagram	10%
Benefits & Stakeholders	Thoughtful identification of project benefits and relevant stakeholders	10%
Overall Presentation & Formatting	Adherence to template, clarity of writing, correct citation format	10%

A.5 Submission Instructions

- Complete Part B (the template) in full — do not delete section headers.
- Maximum length: 10 pages, excluding references and diagrams.
- Use APA or IEEE citation style consistently throughout Section 3.
- Submit as a single PDF or Word file named: LastName_FirstName_DLProposal.pdf
- Diagrams may be hand-drawn (scanned/photographed) or created digitally (draw.io, Lucidchart, PowerPoint, etc.), but must be legible and properly labeled.

Part B — Project Proposal Template

Instructions: Replace each placeholder line below with your own content. Keep section numbers and headings exactly as shown.

Cover Information

Project Title: Cost-Bounded Natural-Language Forensic Search over Surveillance Video via Distilled Vision-Language Re-Ranking

---

Student Name(s) & ID(s): Wajahat Ahmed --- CS-141/2026

Course & Section: CS-5138 Deep Learning

Date: 19 September 2026

---

1. Problem Definition

A modern surveillance installation can produce thousands of automated alerts per day. When an incident is reported after the fact, investigators must locate relevant footage among large video archives. Current practice relies heavily on manual scrubbing or filtering by camera and timestamp because no efficient index exists for what actually occurs in the footage. This makes video forensics time-consuming and difficult to scale.

This project frames the problem as cross-modal text-to-video moment retrieval. The input is a free-form natural-language query and a corpus of surveillance clips. The output is a ranked list of temporally bounded video segments, each with a start and end time, ordered by relevance to the query. Performance will be evaluated using Recall@K and Mean Reciprocal Rank (MRR).

The distinguishing constraint is computational cost. Applying a vision-language model (VLM) to every query–clip pair can provide strong relevance judgments but becomes expensive as the archive grows. The research question is therefore: How much of the retrieval accuracy of an exhaustive VLM-based system can be retained while reducing VLM invocations by one to two orders of magnitude?

The project will develop a research prototype with an end-to-end demonstration, consisting of an offline training/indexing pipeline and an online retrieval path that returns relevant segments with their frames, camera information, and timestamps.

---

2. Dataset Description & Constraint Compliance

2.1 Data Source

The dataset is MEVA (Multiview Extended Video with Activities), collected and annotated by Kitware, Inc. at the Muscatatuck Urban Training Center for the IARPA DIVA programme [9]. Video is distributed through the AWS Registry of Open Data and annotations through the project's public repository. The dataset is released under a CC BY 4.0 licence.

Kaggle compliance. MEVA is not hosted on Kaggle. It originates from an institutional research archive and is distributed via the AWS Public Dataset Program, a primary source category the assignment brief names as acceptable.

Curated extension. MEVA provides activity annotations but no natural-language query set. A retrieval query set will therefore be curated as part of this project by composing queries from the existing human-made activity annotations and hand-verifying a held-out evaluation subset. This constitutes data curated by the author, which the brief also permits explicitly.

2.2 Data Characteristics

Property	Value
Total video	~328 hours, 4,259 clips, 516 GB
Annotated portion	~184 hours with human annotations
Activity classes	37 activity types
Annotation type	Bounding boxes of actors and props, with activity labels and temporal extents
Cameras	Multiple synchronised fixed viewpoints, indoor and outdoor
Collection method	Filmed on real cameras at a physical urban training facility, under IRB oversight and approval
Modality	RGB video

2.3 Size & Balance Justification

Sufficiency 184 annotated hours across 37 activity types yields tens of thousands of temporally localised activity instances — far above the "thousands of labelled samples" threshold. For the retrieval task, each annotated activity segment provides a visually grounded training instance, while multiple verified natural-language queries can be associated with the same segment to improve linguistic variation. These paraphrases are treated as additional textual views of the same visual instance rather than independent video samples. The corpus is also large enough that retrieval is genuinely difficult: a 4,259-clip search space makes Recall@1 a meaningful measurement rather than a near-trivial one, which a small corpus would not.

Balance. MEVA's 37 activity classes are naturally long-tailed, with common activities such as "person walks" vastly outnumber rare ones such as "person opens facility door". Three strategies will be applied and reported:

- Class-balanced sampling of query–clip training pairs, capping the contribution of head classes.
- Macro-averaged Recall@K reported alongside micro-averaged, so head classes cannot mask tail-class failure.
- A stratified evaluation query set constructed with approximately equal query counts per activity class, decoupling evaluation balance from corpus balance.

For the contrastive training objective, in-batch negatives are used, so class imbalance affects sampling rather than the loss formulation directly.

---

3. Literature Review — Existing Work on This Problem

Seven prior works are summarised below, spanning the three lines of research this project draws on: contrastive vision-language pretraining, which makes cross-modal retrieval possible at scale; cross-encoder re-ranking and surveillance-specific retrieval systems, which achieve higher precision at a cost none of them quantify; and knowledge distillation, which provides the mechanism this project uses to remove that cost. Full citations appear in the References section.

Reference (Author, Year)	Technique Used	Key Result / Limitation
Radford et al., 2021 [1]	CLIP: contrastive image-text pretraining on ~400M web pairs; dual encoder producing a shared embedding space	Enables zero-shot cross-modal retrieval, and independent encoders allow embeddings to be precomputed for sub-linear search. Limitation: trained on web photographs, so accuracy degrades on fixed elevated surveillance viewpoints with small, distant subjects and compression artefacts.
Li et al., 2023 [2]	BLIP-2: Q-Former bridging a frozen image encoder and frozen LLM; image-text matching head used as a cross-encoder re-ranker	Substantially higher precision than dual encoders through joint query-candidate encoding. Limitation: cost grows linearly with the number of pairs scored, so exhaustive application across an archive is infeasible.
Tran et al., 2025 [3]	Unified multi-granularity framework (CLIP + BEiT-3), keyframe deduplication via TransNetV2, temporal re-ranking over neighbouring frames	Improves retrieval robustness on hour-long video. Limitation: evaluation reports accuracy metrics only; inference cost and model invocation counts are not characterised.
SurveiLens, 2026 [4]	Natural-language moment retrieval for CCTV: frame sampling, captioning, semantic similarity, temporal localisation	Demonstrates investigator-facing retrieval on real surveillance footage. Limitation: captioning every sampled frame is itself the dominant expense, and no cost model is presented.
ForeSea, 2026 [5]	Forensic search over surveillance video with multi-modal queries combining text and image exemplars	Handles heterogeneous query types in a forensic workflow. Limitation: reports retrieval quality without characterising the accuracy/compute trade-off.
Wu et al., 2024 [6]	VadCLIP: adapts CLIP for weakly supervised video anomaly detection via dual-branch prompt learning	Confirms that vision-language transfer to the surveillance domain is viable. Limitation: addresses closed-set anomaly detection rather than open-vocabulary retrieval from arbitrary free text supplied at inference time.
Hinton et al., 2015 [7]; Hofstaetter et al., 2020 [8]	Knowledge distillation; cross-architecture distillation of an expensive cross-encoder into a cheaper ranking model using a margin-based objective	Established that a teacher's ranking behaviour can be transferred to a student at a fraction of inference cost, recovering much of its effectiveness. Limitation: demonstrated for text retrieval; not applied to vision-language re-ranking over surveillance video.

References (full citations, IEEE/APA format):

[1] A. Radford et al., "Learning Transferable Visual Models From Natural Language Supervision," in Proc. 38th Int. Conf. Machine Learning (ICML), 2021, pp. 8748–8763.

[2] J. Li, D. Li, S. Savarese, and S. Hoi, "BLIP-2: Bootstrapping Language-Image Pre-training with Frozen Image Encoders and Large Language Models," in Proc. 40th Int. Conf. Machine Learning (ICML), 2023.

[3] T. Tran et al., "Towards Efficient and Robust Moment Retrieval System: A Unified Framework for Multi-Granularity Models and Temporal Reranking," in Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition Workshops (CVPRW), 2025.

[4] "SurveiLens: Natural Language-Based Moment Retrieval for Surveillance Video Analysis," in Proc. IEEE Conf., 2026. [Online]. Available: https://ieeexplore.ieee.org/document/11400480/

[5] "ForeSea: AI Forensic Search with Multi-modal Queries for Video Surveillance," arXiv:2603.22872, 2026.

[6] P. Wu et al., "VadCLIP: Adapting Vision-Language Models for Weakly Supervised Video Anomaly Detection," in Proc. AAAI Conf. Artificial Intelligence, 2024.

[7] G. Hinton, O. Vinyals, and J. Dean, "Distilling the Knowledge in a Neural Network," arXiv:1503.02531, 2015.

[8] S. Hofstätter, S. Althammer, M. Schröder, M. Sertkan, and A. Hanbury, "Improving Efficient Neural Ranking Models with Cross-Architecture Knowledge Distillation," arXiv:2010.02666, 2020.

[9] K. Corona, K. Osterdahl, R. Collins, and A. Hoogs, "MEVA: A Large-Scale Multiview, Multimodal Video Dataset for Activity Detection," in Proc. IEEE/CVF Winter Conf. Applications of Computer Vision (WACV), 2021, pp. 1060–1068.

[10] J. Lei, T. L. Berg, and M. Bansal, "QVHighlights: Detecting Moments and Highlights in Videos via Natural Language Queries," in Proc. Advances in Neural Information Processing Systems (NeurIPS), 2021.

---

4. Proposed Technique & Novelty

4.1 How Your Approach Differs

The proposed system is a three-stage cascade in which the expensive component is progressively eliminated rather than merely reduced. Against CLIP [1], the difference is that the retrieval encoder is not used off the shelf: it is domain-adapted to fixed-camera surveillance imagery through contrastive fine-tuning with low-rank adaptation, treating the web-to-surveillance distribution shift as an explicit and separately measured problem rather than an accepted cost. Against BLIP-2 [2], the difference is where the cross-encoder runs. Instead of invoking it at query time, this project uses a vision-language model solely as a teacher during training; at inference the teacher is replaced by a distilled student, so the expensive computation is paid once offline rather than repeatedly per query.

Against the surveillance retrieval systems [3], [4], [5], the difference is what is measured. Those works optimise and report accuracy; this project treats model invocations, tokens, latency and monetary cost as first-class reported quantities, and presents the outcome as a recall-versus-cost frontier across several operating points rather than a single configuration. Against VadCLIP [6], the difference is task formulation: retrieval here is open-vocabulary, responding to arbitrary text supplied at inference time, rather than scoring against a fixed anomaly taxonomy. Against Hofstätter et al. [8], the difference is modality and domain — cross-encoder to student distillation is carried from text retrieval into vision-language retrieval over surveillance video, where the teacher is multimodal and the cost problem is considerably more severe.

Stated plainly, the cascaded retrieval architecture is established prior work and is deliberately reused. The contributions claimed are three: the distillation of a vision-language re-ranker into a deployable student for this task; the domain adaptation of the retrieval encoder to surveillance imagery; and the explicit characterisation of the accuracy-versus-cost frontier, which the surveyed literature does not report.

4.2 Why This Should Produce Good Results

Three hypotheses are advanced, each framed so that it can be rejected by the experiments rather than assumed.

The first is that domain adaptation will improve first-stage recall. CLIP is trained on web photographs while surveillance footage differs systematically in viewpoint, subject scale, illumination and compression. Contrastive fine-tuning on in-domain pairs has repeatedly recovered substantial performance in comparable out-of-distribution transfers, and low-rank adaptation permits this on a modest in-domain set without disturbing the general visual semantics learned during pretraining. The hypothesis is falsifiable: if the adapted encoder does not exceed the frozen baseline on Recall@10, it is rejected.

The second is that a distilled student will retain most of the teacher's ranking quality at a small fraction of its cost. The precedent is cross-architecture distillation in text retrieval [8], and the mechanism transfers for two reasons. The teacher supplies a dense, graded relevance signal over far more pairs than human annotation could produce, and the student is required to learn a ranking function over a narrow domain rather than general multimodal reasoning. The narrowness of the domain is an advantage for the student rather than a limitation.

The third is that the accuracy-versus-cost curve will be strongly concave. Because first-stage retrieval already places most true positives within the top-K candidates, escalating only a small subset to the teacher should capture most of

the achievable gain, with sharply diminishing returns beyond that point. Should the curve prove approximately linear instead, the cascade offers no advantage over exhaustive scoring, and that negative result would itself be worth reporting.

Acknowledged limitation. MEVA activities are scripted performances by participants at a training facility rather than spontaneous incidents, so absolute retrieval figures may be optimistic relative to uncontrolled footage. Because this affects all experimental arms equally, comparisons between arms remain valid, and the limitation will be stated explicitly in the evaluation.

4.3 Tools & Techniques to Be Used

Tool / Technique	Role	Justification
PyTorch 2.x with torch.compile	Core training framework	Graph compilation gives material throughput gains on the repeated encoder passes that dominate training time.
Hugging Face Transformers / Datasets	Models and data pipeline	Canonical source for CLIP/SigLIP and open-weight vision-language checkpoints; reproducible dataset handling.
SigLIP or CLIP ViT-B/16	First-stage dual encoder	Independent encoders allow clip embeddings to be precomputed and searched sub-linearly, which is what makes archive-scale retrieval tractable.
LoRA / QLoRA (PEFT)	Parameter-efficient domain adaptation	Adapts a large pretrained encoder on a modest in-domain set without full fine-tuning, avoiding catastrophic forgetting of general visual semantics.
Open-weights VLM as teacher	Relevance labelling for distillation	Local execution removes per-call API cost, makes large-scale label generation feasible, and avoids transmitting footage to a third party.
Knowledge distillation (margin-MSE)	Training the student re-ranker	The central technique: transfers the teacher's ranking behaviour into a model small enough to deploy.
ChromaDB	Vector index with metadata filtering	Stores embeddings alongside the filter keys needed for hybrid queries constrained by camera and time range, which vector similarity alone cannot express.
SQLite	Alert metadata store	Holds camera, timestamps, detector provenance and frame paths. Kept separate from the vector index because the index is rebuildable and the metadata is not.
Quantisation and ONNX export	Student deployment	Demonstrates the efficiency claim end to end and matches the edge-deployment techniques named in the brief.
Weights & Biases	Experiment tracking	Multi-arm ablation with cost metrics requires systematic run comparison.
Optuna	Hyperparameter optimisation	Tunes the escalation threshold and distillation temperature, which directly control the cost–accuracy trade-off.

---

5. System / Flow Diagram




Figure 1. System architecture. Lane A is the offline path: the corpus is sampled and embedded by the domain-adapted encoder to build the index, while activity annotations yield query–clip pairs that the vision-language teacher scores in order to train the student re-ranker by distillation. Lane B is alert ingestion: when the detector raises an alert, a variable number of frames are sampled and embedded with the same encoder weights used to build the index, with vectors written to the vector store and metadata to the relational store. Lane C is the query path: the query is encoded, filtered vector search returns candidates, the student re-ranks all of them cheaply, and only a small subset is escalated to the vision-language model. Components trained in this project are shaded.

6. Expected Benefits

Technical contribution: A characterisation of the accuracy-versus-cost frontier for VLM-assisted video retrieval — an axis the surveyed literature reports almost exclusively in terms of accuracy. The distilled re-ranker is a reusable artefact independent of the surveillance domain.

Operational impact: Reduces post-incident footage review from hours of manual scrubbing to a natural-language query, without requiring the operator to know camera identifiers or timestamps in advance.

Efficiency and accessibility: By removing the per-query dependence on a large VLM, the system becomes deployable on modest on-premise hardware. This matters disproportionately for low-resource deployments — municipal authorities, campuses, small businesses — where per-query API costs would otherwise be prohibitive.

Privacy: Local inference means footage never leaves the operator's infrastructure, which is materially better than architectures that stream frames to a third-party API.

Reusable evaluation asset: The curated natural-language query set over MEVA does not currently exist and will be released alongside the project.

7. Stakeholders

Stakeholder	Interest / Impact
Security operators and investigators	Primary users. Direct reduction in time-to-evidence; can query in plain language rather than by camera and timestamp.
Facility and transport operators	Faster incident response and lower review labour cost; feasible on-premise deployment without recurring API spend.
Law enforcement / legal process	Faster evidence location. Requires that retrieval be treated as an investigative aid whose outputs are human-verified, never as automated determination of fact.
Members of the public under surveillance	Affected party. Semantic search over footage increases the power of an existing archive, which is a genuine privacy consideration; local-only inference and access logging are partial mitigations, and the system performs retrieval, not identification.
Computer vision researchers	Gain a cost-aware evaluation protocol and a natural-language query benchmark over a CC BY 4.0 corpus.
Data protection regulators	Interest in scope limitation and auditability; the design deliberately excludes biometric identification and retrieves events, not persons.

8. Timeline

Phase	Activity	Duration
1	Data collection and preprocessing: corpus and annotation acquisition, alignment of annotations to video, derivation of query–clip pairs from human activity labels, and verification of the held-out evaluation split	Week 1
2	Baseline: frozen dual encoder + vector index; Recall@K measured end-to-end. Establishes a complete working system and the lower bound of the cost curve.	Week 2–3
3	Domain adaptation (LoRA contrastive fine-tuning); VLM teacher labelling; distillation of the student re-ranker	Week 4–5
4	Ablation across five operating points; recall-versus-cost Pareto frontier; teacher-exhaustive upper bound; error analysis including per-activity recall	Week 6
5	Alert ingestion pipeline and query interface end-to-end; report and presentation	Week 7–8