

# Introduction to Fuzzy Cognitive Maps

Miklós F. Hatwagner

**Abstract** Each chapter should be preceded by an abstract (no more than 200 words) that summarizes the content. The abstract will appear *online* at [www.SpringerLink.com](http://www.SpringerLink.com) and be available with unrestricted access. This allows unregistered users to read the abstract as a teaser for the complete chapter.

Please use the 'starred' version of the `abstract` command for typesetting the text of the online abstracts (cf. source file of this chapter template `abstract`) and include them with the source files of your manuscript. Use the plain `abstract` command if the abstract is also to appear in the printed version of the book.


## 1 The birth of Fuzzy Cognitive Maps

Cognitive Maps (CM) are used in political analysis and decision making in international relations, foreign policy for a long time. The method was suggested by Robert Axelrod in his book [1] in the late '70s. According to Bart Kosko's description in [13], these maps are signed digraphs. Graphs, as algebraic structures have two components: nodes and edges (arcs). In CM, nodes represent variable *concepts* (eg. social instability) and the causal connections among these concepts are characterized by edges. The edges have a direction and a sign. If concept *A* causally increases concept *B*, it is represented by an edge from *A* to *B* with positive sign. On the other hand, if *A* reduces the value of *B*, the edge has a negative sign. Kosko illustrated CM with an example based on Henry Kissinger's essay "Starting Out in the Direction of Middle East Peace" published in *Los Angeles Times* in 1982 (see Fig. 1). Besides the graph, he also composed the adjacency (connection, weight) matrix (Fig. 2) of the model. Only three different values can be found in this matrix, representing the causal relationship among concepts. If  $w_{ij} = w(C_i, C_j)$  is 1, concept  $C_1$  causally increases the value of  $C_2$  (positive edges). On the contrary, if  $C_1$  causally decreases

---

Miklós F. Hatwagner  
Széchenyi István University, Győr, Hungary e-mail: [miklos.hatwagner@sze.hu](mailto:miklos.hatwagner@sze.hu)

the value of  $C_2$ , it is represented by  $-1$  (negative edges), and the value 0 indicates the lack of causal connection.



**Fig. 1** The Cognitive Map drawn by Kosko based on Kissinger's essay.

$$\begin{matrix}
 & C_1 & C_2 & C_3 & C_4 & C_5 & C_6 \\
 \begin{matrix} C_1 \\ C_2 \\ C_3 \\ C_4 \\ C_5 \\ C_6 \end{matrix} & \begin{pmatrix} 0 & -1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & -1 \\ 0 & 0 & 0 & -1 & 0 & -1 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}
 \end{matrix}$$

**Fig. 2** The adjacency matrix of the CM based on Kissinger's essay.

It became quickly evident that the structure of a Cognitive Map imply too much limitations. The degree of causality, the levels of the causal effects (sometimes—often, little—much, etc.) cannot be expressed with the existing tool, and needs further development. Kosko introduced the Fuzzy Cognitive Map (FCM) [13], where the edges may have several causality values. This way the original CM turned into a bipolar fuzzy graph [22]. Kosko also developed a fuzzy causal algebra for propagating causality in it, making the static analysis of the model possible. The concepts may

affect other concepts indirectly because of the cyclic and non-feedforward structure of FCM.

## 2 Simulations

The visual representation and formal description of models may help experts to review the structure of the studied system, but the real benefit of FCMs is the possibility of running simulations. This can be done by dynamic analysis [14]. Using a simple inference technique, the next state of concepts (also called the *activation values* of concepts, based on the similarity of FCMs and artificial neural networks) can be calculated using their current state and the weight of connections among them [4, 19]. This way what-if analysis can be performed which is very useful for decision makers.

### 2.1 Inference rules

Kosko defined the first, and still widely applied inference rule (Eq. 1). In this case concepts are not allowed to directly influence themselves. With other words, a concept does not have “memory”, technically speaking the edges must connect different concepts (i.e. self-loops are forbidden), but indirect feedbacks are still possible. Accordingly, the main diagonal of the connection matrix contains only zeros. These models are called FCMs of Type I [18].

$$A_i^{t+1} = f \left( \sum_{\substack{j=1 \\ j \neq i}}^n w_{ji} A_j^t \right) \quad (1)$$

Here,  $A_i^{t+1}$  is the activation value of concept  $i$  at time step  $t + 1$ ,  $n$  is the number of concepts and  $f(\cdot)$  is the *threshold* (transformation, squeezing) function. Without this function, the activation values of concepts may exceed or fall below their allowed extreme values.

FCMs of Type III allow concepts to take into account their current states during the calculation of the next state, and apply the inference rule defined by Eq. 2. In this case, the main diagonal of the connection matrix may contain nonzero values, which are often ones in practice.

$$A_i^{t+1} = f \left( w_{ii} A_i^t + \sum_{\substack{j=1 \\ j \neq i}}^n w_{ji} A_j^t \right) \quad (2)$$

FCMs of Type II also have a one step memory, but the weight of self-loops ( $k_1$ ) are the same for all concepts. Moreover, the influence coming from other concepts can be limited as well ( $k_2$ , see Eqs. 3, 4).

$$A_i^{t+1} = f \left( k_1 A_i^t + k_2 \sum_{\substack{j=1 \\ j \neq i}}^n w_{ji} A_j^t \right) \quad (3)$$

$$0 < k_1, k_2 \leq 1 \quad (4)$$

Papageorgiu suggested the re-scale inference rule (Eq. 5) in [17], because problems emerged in cases where the initial values of concepts were 0 or 0.5, assuming that the initial states are known at all. This modified inference rule yielded more reliable and natural results than other FCM versions.

$$A_i^{t+1} = f \left( (2A_i^t - 1) + \sum_{\substack{j=1 \\ j \neq i}}^n w_{ji} \cdot (2A_j^t - 1) \right) \quad (5)$$

## 2.2 Threshold functions

In general, the activation values are in the  $A_i \in [0, 1]$  interval. Several threshold functions were published during the years, but the most widely applied one is the *sigmoid* or *logistics* function (Eq. 6):


$$f_{\text{sigmoid}}(x) = \frac{1}{1 + e^{-\lambda x}} \quad (6)$$

where the  $\lambda > 0$  specifies the steepness of the function. It's typical value is 5. With greater values it approximates a binary function, with lower values a linear function (see Fig. 3).

### Choosing an appropriate $\lambda$ value

Is there an “appropriate” value of this parameter? According to Bueno and Salmeron [3], the appropriate value should be found during an experimentation phase. As it was pointed out in [8, 12], the convergence speed and the final, stable values of concepts are heavily affected by the value of parameter  $\lambda$  (see Fig. 4). Despite of the different results, different  $\lambda$  values does not change the result of a simulation qualitatively, because the sigmoid function is strictly monotonically increasing. In practice, it is still worth to find an “optimal” value for  $\lambda$ , because sometimes the otherwise hardly different concept states may become distinguishable, and the order of concepts can be defined, if it is required. A possible method for “lambda optimization” is to

maximize the standard deviation of final concept values (Fig. 5) even by a quick local search algorithm, eg. the Golden Section Search.




**Fig. 3** Steepness of the sigmoid function with various  $\lambda$  parameters.

Even if the value of  $\lambda$  can be considered “optimal”, a scalar value is unable to unleash the full modeling potential of an FCM. In an extreme case, every concept may have its own, specific  $\lambda$  value, in order to get more realistic predictions. This way, the inference rule defined by Eq. 1 can be re-written to Eq. 7, where  $f_i$  represents the threshold function of concept  $C_i$  that uses  $\lambda_i$ . This approach increases the number of model parameters, however. The benefits of using FCMs were their simple structure, which can be understood easily by stakeholders, experts of different fields, and the values (initial states of concepts, connection weights) can be matched to real values or effects in a straightforward way. The values of  $\lambda$  do not have trivial connection with any real world objects, however, and their values can be set with trial and error technique or computationally. It also increases the required computational power of applications because it increases the number of model parameters. A good balance can be found if some concepts have their own parameters, the others share a common value.


$$A_i^{t+1} = f_i \left( \sum_{j=1}^n w_{ji} A_j^t \right) \quad (7)$$

Concepts may be classified in three groups: if a concept influences the state of other concepts, but not affected by other concepts, it can be called an *input* concept. Depending on the applied inference method, these concepts keep their initial values or



**Fig. 4** The final concept values of a Stakeholder Relationship Management System as function of parameter  $\lambda$ .  $\lambda = 0.664$  maximized the standard deviation of concept values (marked with the thick vertical line).

their values can be sustained artificially (like “sustained inputs” in [4]), therefore they do not need threshold function and parameter  $\lambda$  neither. Another group of concepts



**Fig. 5** Standard deviation of final concept values of a Stakeholder Relationship Management System calculated with different  $\lambda$  values.

is affected by other concepts but its elements do not influence the state of other concepts. In many applications, only these concepts are used for decision making, and they are called *output* concepts. The remaining concepts are both affected by and they also affect other concepts, and are called *intermediate* concepts [2].

If all output concepts have specific  $\lambda$  values, and intermediate concepts have a common  $\lambda$ , the complexity of the model remains moderate but its forecasting ability can be increased as it happened in [11]. If historical time series data are available,  $\lambda$ s can be optimized with eg. the Big Bang – Big Crunch algorithm [20].


The *sign* function (Eq. 8) is also a popular threshold function, but because of the two available values, a concept can only be activated (1) or deactivated (0).

$$f_{\text{sign}}(x) = \begin{cases} 1, & x > 0, \\ 0, & x \leq 0 \end{cases} \quad (8)$$

In some cases the system to be modeled requires the activation values to be in  $A_i \in [-1, +1]$ , and different threshold functions have to be applied. If continuous states are allowed, the *hyperbolic tangent* function (Eq. 9) is a possible choice:

$$f_{\text{ht}}(x) = \tanh(\lambda x) = \frac{e^{\lambda x} - e^{-\lambda x}}{e^{\lambda x} + e^{-\lambda x}} \quad (9)$$

The  $\lambda$  parameter can be used here as well, and has similar effect on the steepness of the function than on sigmoid function's (Fig. 6).



**Fig. 6** Steepness of the hyperbolic tangent function with various  $\lambda$  parameters.

If only discrete states have to be used, the *trivalent* function (Eq. 10) can be the solution. The value 1 expresses the increasing, the value  $-1$  expresses the decreasing and 0 means the stable state of a concept. A slightly modified version of this function can be found in [21] (Eq. 11).

$$f_{\text{trivalent1}}(x) = \begin{cases} 1, & x > 0, \\ 0, & x = 0, \\ -1, & x < 0. \end{cases} \quad (10)$$

$$f_{\text{trivalent2}}(x) = \begin{cases} 1, & x \geq 0.5, \\ 0, & -0.5 < x < 0.5, \\ -1, & x \leq -0.5. \end{cases} \quad (11)$$

### 2.3 Simulation outcomes

During simulations, the states of concepts continuously evolve, until one of the three possible outcomes happens [19]:

1. In most cases, the activation values converge very quickly to a stable state (equilibrium point, see Eq. 12). These states are also called *fixed points* (FPs). Depending on the connection matrix, initial state, inference rule, threshold function and its  $\lambda$  parameter (if applied), a model may have multiple FPs.

$$\exists t_{\text{FP}} \in \mathbb{N} : A_i^{t+1} = A_i^t, \forall t \geq t_{\text{FP}}, i = 1, \dots, m \quad (12)$$

2. Sometimes the system enters a *limit cycle* (LC). In these cases after several time steps, a  $T$  steps long sequence of state vectors starts to repeat (see Eq. 13).

$$\exists t_{\text{LC}}, T \in \mathbb{N} : A_i^{t+T} = A_i^t, \forall t \geq t_{\text{LC}}, i = 1, \dots, m \quad (13)$$

3. The system never stabilizes, behaves chaotically.

It's easy to prove that bivalent and trivalent systems cannot behave chaotically. The process of simulations are deterministic, and the number of different state vectors is  $2^N$  or  $3^N$ , respectively, where  $N$  is the number of concepts. According to this, if the system is unstable, its states are going to repeat after  $2^N$  or  $3^N$  time steps, or earlier. FPs and LCs are related to the hidden patterns described in Kosko's work [14].

In contrast, continuous state FCMs may enter practically infinite different states, thus chaotic behavior is possible. It happens especially often in case of Type III FCMs, which enter LCs frequently as well [15]. Martchenko et al. also defined the condition of stability, too, which depends on the connection matrix.

Harmati et al. went further [5] and determined the conditions of convergence and the number of FPs. According to their results, if the FCM uses sigmoid threshold function and the inequality



$$\|W\|_F < \frac{4}{\lambda} \quad (14)$$

holds, then the FCM has exactly one FP, without any LCs or chaotic patterns. Here  $W$  is the connection matrix,  $\|\cdot\|_F$  is the Frobenius-norm of the matrix defined by Eq. 15, and  $\lambda$  is the steepness of the threshold function.

$$\|W\|_F = \left( \sum_i \sum_j w_{ij}^2 \right)^{1/2} \quad (15)$$

Similarly, if the hyperbolic tangent function is applied and Eq. 16 holds, the FCM has one and only one FP. These theorems are valid even if the connection matrix contains direct feedbacks.

$$\|W\|_F < \frac{1}{\lambda} \quad (16)$$

Moreover, if the sigmoid or hyperbolic tangent threshold functions are used, and  $W$  contains only non-negative elements then the FCM has FP, regardless of the value of  $\lambda$ . Similar contexts were also explored in case of some extended versions of FCM, the Grey FCMs [6] and Fuzzy Set Valued Sigmoid FCMs [7].


These are remarkable achievements because some of the behavioral properties of an FCM can be revealed without executing an exhaustive set of simulations, which is computationally very intensive. Unfortunately it is often unavoidable. If the model is made by experts, it may contain many subjective elements, eg. it is really hard to define the exact weight of a relationship. Even a small difference in the weights may lead to different behaviour, however. It is worth investigate the effect of small model modifications on behavioural properties, but it means a huge job which must be automated like in [10, 9]. The search space is huge for an exhaustive search hence Bacterial Evolutionary Algorithm [16] was applied to generate and analyse the behavioral difference caused by slightly modified model versions and  $\lambda$  values. If modified models with significantly different dynamic behaviour are found, experts are suggested to consider some changes on the model.

## 2.4 An example simulation

## 2.5 Subsection Heading

Instead of simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Further on please use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

Please do not use quotation marks when quoting texts! Simply use the `quotation` environment – it will automatically be rendered in line with the preferred layout.



**Fig. 7** Graphical representation of the example FCM.

### 2.5.1 Subsubsection Heading


Instead of simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Further on please use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.5, see also Fig. 7<sup>1</sup>

Please note that the first line of text that follows a heading is not indented, whereas the first lines of all subsequent paragraphs are.

#### Paragraph Heading

Instead of simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Further on please use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

**Fig. 8** If the width of the figure is less than 7.8 cm use the `sidecaption` command to flush the caption on the left side of the page. If the figure is positioned at the top of the page, align the sidecaption with the top of the figure – to achieve this you simply need to use the optional argument `[t]` with the `sidecaption` command



<sup>1</sup> If you copy text passages, figures, or tables from other works, you must obtain *permission* from the copyright holder (usually the original publisher). Please enclose the signed permission with the manuscript. The sources must be acknowledged either in the captions, as footnotes or in a separate section of the book.

Please note that the first line of text that follows a heading is not indented, whereas the first lines of all subsequent paragraphs are.

For typesetting numbered lists we recommend to use the `enumerate` environment – it will automatically rendered in line with the preferred layout.

1. Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.
  - a. Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.
  - b. Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.
2. Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.

### *Subparagraph Heading*

In order to avoid simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2, see also Fig. 8.

For unnumbered list we recommend to use the `itemize` environment – it will automatically be rendered in line with the preferred layout.

- Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development, cf. Table 1.
  - Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.
  - Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.
- Livelihood and survival mobility are oftentimes coutcomes of uneven socioeconomic development.


**Run-in Heading Boldface Version** Use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

***Run-in Heading Boldface and Italic Version*** Use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

### **Run-in Heading Displayed Version**

Use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

**Fig. 9** If the width of the figure is less than 7.8 cm use the `sidecaption` command to flush the caption on the left side of the page. If the figure is positioned at the top of the page, align the sidecaption with the top of the figure – to achieve this you simply need to use the optional argument `[t]` with the `sidecaption` command



**Table 1** Please write your table caption here

Classes	Subclass	Length	Action Mechanism
Translation	mRNA <sup>a</sup>	22 (19–25)	Translation repression, mRNA cleavage
Translation	mRNA cleavage	21	mRNA cleavage
Translation	mRNA	21–22	mRNA cleavage
Translation	mRNA	24–26	Histone and DNA Modification

<sup>a</sup> Table foot note (with superscript)

### 3 Section Heading

Instead of simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Further on please use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

Please note that the first line of text that follows a heading is not indented, whereas the first lines of all subsequent paragraphs are.

If you want to list definitions or the like we recommend to use the `description` environment – it will automatically rendered in line with the preferred layout.

- Type 1 That addresses central themes pertaining to migration, health, and disease. In Sect. 1, Wilson discusses the role of human migration in infectious disease distributions and patterns.
- Type 2 That addresses central themes pertaining to migration, health, and disease. In Sect. 2.5, Wilson discusses the role of human migration in infectious disease distributions and patterns.

### 3.1 Subsection Heading

In order to avoid simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

Please note that the first line of text that follows a heading is not indented, whereas the first lines of all subsequent paragraphs are.

If you want to emphasize complete paragraphs of texts we recommend to use the newly defined class option `graybox` and the newly defined environment `svgraybox`. This will produce a 15 percent screened box 'behind' your text.

If you want to emphasize complete paragraphs of texts we recommend to use the newly defined class option and environment `svgraybox`. This will produce a 15 percent screened box 'behind' your text.

#### 3.1.1 Subsubsection Heading

Instead of simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Further on please use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

Please note that the first line of text that follows a heading is not indented, whereas the first lines of all subsequent paragraphs are.

**Theorem 1** *Theorem text goes here.*

**Definition 1** Definition text goes here.

**Proof** Proof text goes here. □

#### Paragraph Heading

Instead of simply listing headings of different levels we recommend to let every heading be followed by at least a short passage of text. Further on please use the  $\LaTeX$  automatism for all your cross-references and citations as has already been described in Sect. 2.

Note that the first line of text that follows a heading is not indented, whereas the first lines of all subsequent paragraphs are.

**Theorem 2** *Theorem text goes here.*

**Definition 2** Definition text goes here.

***Proof*** Proof text goes here.

□

### Trailer Head

If you want to emphasize complete paragraphs of texts in an `Trailer Head` we recommend to use

```
\begin{trailer}{Trailer Head}
...
\end{trailer}
```

---

### ? Questions

If you want to emphasize complete paragraphs of texts in an `Questions` we recommend to use

```
\begin{question}{Questions}
...
\end{question}
```

---

**> Important**

If you want to emphasize complete paragraphs of texts in an **Important** we recommend to use

```
\begin{important}{Important}
...
\end{important}
```

---

**! Attention**

If you want to emphasize complete paragraphs of texts in an **Attention** we recommend to use

```
\begin{warning}{Attention}
...
\end{warning}
```

---

**Program Code**

If you want to emphasize complete paragraphs of texts in an **Program Code** we recommend to use

```
\begin{programcode}{Program Code}
\begin{verbatim}...\end{verbatim}
\end{programcode}
```

---

**Tips**

If you want to emphasize complete paragraphs of texts in an **Tips** we recommend to use

```
\begin{tips}{Tips}
...
\end{tips}
```

---

### Overview

If you want to emphasize complete paragraphs of texts in an **Overview** we recommend to use

```
\begin{overview}{Overview}
...
\end{overview}
```

---

### Background Information

If you want to emphasize complete paragraphs of texts in an **Background Information** we recommend to use

```
\begin{backgroundinformation}{Background Information}
...
\end{backgroundinformation}
```

---

### Legal Text

If you want to emphasize complete paragraphs of texts in an **Legal Text** we recommend to use

```
\begin{legalttext}{Legal Text}
...
\end{legalttext}
```

---

**Acknowledgements** If you want to include acknowledgments of assistance and the like at the end of an individual chapter please use the `acknowledgement` environment – it will automatically be rendered in line with the preferred layout.

## Appendix

When placed at the end of a chapter or contribution (as opposed to at the end of the book), the numbering of tables, figures, and equations in the appendix section continues on from that in the main text. Hence please *do not* use the `appendix` command when writing an appendix at the end of your chapter or contribution. If there is only one the appendix is designated “Appendix”, or “Appendix 1”, or “Appendix 2”, etc. if there is more than one.

$$a \times b = c \tag{17}$$



## References

1. Robert Axelrod. *Structure of decision: The cognitive maps of political elites*. Princeton university press, Princeton, NJ, 1976.
2. Yiannis Boutalis, Manolis A Christodoulou, Dimitrios Theodoridis, and Theodore Kottas. System identification and adaptive control. *Theory and Applications of the Neurofuzzy and Fuzzy Cognitive Network Models*, 2014.
3. Salvador Bueno and Jose L. Salmeron. Benchmarking main activation functions in fuzzy cognitive maps. *Expert Syst. Appl.*, 36(3):5221–5229, April 2009.
4. Julie A Dickerson and Bart Kosko. Virtual worlds as fuzzy cognitive maps. *Presence: Teleoperators & Virtual Environments*, 3(2):173–189, 1994.
5. István Á Harmati, Miklós F Hatwágner, and László T Kóczy. On the existence and uniqueness of fixed points of fuzzy cognitive maps. In *International Conference on Information Processing and Management of Uncertainty in Knowledge-Based Systems*, pages 490–500. Springer, 2018.
6. István Á Harmati and László T Kóczy. On the convergence of fuzzy grey cognitive maps. In *Conference on Information Technology, Systems Research and Computational Physics*, pages 74–84. Springer, 2018.
7. István Á Harmati and László T Kóczy. On the existence and uniqueness of fixed points of fuzzy set valued sigmoid fuzzy cognitive maps. In *2018 IEEE International Conference on Fuzzy Systems (FUZZ-IEEE)*, pages 1–7. IEEE, 2018.
8. M. F. Hatwagner and L. T. Koczy. Parameterization and concept optimization of fcm models. In *2015 IEEE International Conference on Fuzzy Systems (FUZZ-IEEE)*, pages 1–8, Istanbul, aug 2015. IEEE.
9. Miklós F Hatwagner, Gyula Vastag, Vesa A Niskanen, and László T Kóczy. Improved behavioral analysis of fuzzy cognitive map models. In *International Conference on Artificial Intelligence and Soft Computing*, pages 630–641. Springer, 2018.
10. Miklós F Hatwágner, Gyula Vastag, Vesa A Niskanen, and László T Kóczy. Banking applications of fcm models. In *Trends in Mathematics and Computational Intelligence*, pages 61–72. Springer, 2019.
11. Miklós Ferenc Hatwágner, Engin Yesil, M Furkan Dodurka, Elpiniki Papageorgiou, Leon Urbas, and László T Kóczy. Two-stage learning based fuzzy cognitive maps reduction approach. *IEEE Transactions on Fuzzy Systems*, 26(5):2938–2952, 2018.
12. M. F. Hatwágner, A. Torma, and L. T. Kóczy. Parameter dependence of fuzzy cognitive maps' behaviour. In *2015 10th Asian Control Conference (ASCC)*, pages 1–6, May 2015.
13. B. Kosko. Fuzzy cognitive maps. *Int. J. Man-Machine Studies*, 24:65–75, 1986.
14. Bart Kosko. Hidden patterns in combined and adaptive knowledge networks. *International Journal of Approximate Reasoning*, 2(4):377–393, 1988.
15. AS Martchenko, Ivan L Ermolov, Peter P Groumpos, Jury V Poduraev, and Chrysostomos D Stylios. Investigating stability analysis issues for fuzzy cognitive maps. In *11th Mediterranean Conference on Control and Automation-MED'03*, 2003.
16. Norberto Eiji Nawa and Takeshi Furuhashi. Bacterial evolutionary algorithm for fuzzy system design. In *SMC'98 Conference Proceedings. 1998 IEEE International Conference on Systems, Man, and Cybernetics (Cat. No. 98CH36218)*, volume 3, pages 2424–2429. IEEE, 1998.
17. E. I. Papageorgiou. A new methodology for decisions in medical informatics using fuzzy cognitive maps based on fuzzy rule-extraction techniques. *Applied Soft Computing*, 11:500–513, 2011.
18. Chrysostomos D Stylios, Peter P Groumpos, et al. Mathematical formulation of fuzzy cognitive maps. In *Proceedings of the 7th Mediterranean Conference on Control and Automation*, pages 2251–2261, 1999.
19. Athanasios K Tsadiras. Comparing the inference capabilities of binary, trivalent and sigmoid fuzzy cognitive maps. *Information Sciences*, 178(20):3880–3894, 2008.
20. Engin Yesil and Leon Urbas. Big bang-big crunch learning method for fuzzy cognitive maps. *World Academy of Science, Engineering & Technology*, 71:816–825, 2010.

21. Engin Yesil, Leon Urbas, and Anday Demirsoy. Fcm-gui: A graphical user interface for big bang-big crunch learning of fcm. In *Fuzzy Cognitive Maps for Applied Sciences and Engineering*, pages 177–198. Springer, 2014.
22. W-R Zhang. Bipolar fuzzy sets. In *Fuzzy Systems Proceedings, 1998. IEEE World Congress on Computational Intelligence., The 1998 IEEE International Conference on*, volume 1, pages 835–840. IEEE, 1998.