

THOR 6030 | 6S3P FPV Drone Battery Pack



Product Overview

Application: High-performance FPV drones, UAS, Robotics
Cell Configuration: 6S3P (6 series, 3 parallel)
Chemistry: Lithium Ion
Cell Type: 21700

Electrical Specifications

	Molicel			Amprius		Samsung	
	P42A	P45B	P50B	SA112	SA117	40T	50S
Capacity (Ah)	12.6	13.5	15	19.5	20.4	12	15
Energy (Wh)	272.2	291.6	324	421.2	440.6	259.2	324
Storage Voltage (V)	21.6	-	-	-	-	-	-
Charge Voltage (V)	25.2	-	-	-	-	-	-
Cutoff Voltage (V)	15	-	-	-	-	-	-
Continuous Discharge (A)	135	135	180	39	39	105	75
Discharge Power (W)	2916	2916	3888	842	842	2268	1620
Regular Charge Rate (A)	15	-	-	-	-	-	-
Max Charge Rate (A)	15	-	-	-	-	-	-
Recommended Charge Rate	0.5C to 1C	-	-	-	-	-	-
Gravimetric Energy (Wh/kg)	205	220	238	309	324	204	238
Volumetric Energy (Wh/cm^3)	0.34	0.37	0.41	0.53	0.55	0.32	0.41

Mechanical Specifications

Pack Weight (g) ±10 g	1325	1325	1361	1361	1361	1271	1361
-----------------------	------	------	------	------	------	------	------

- Pack Dimensions (mm): ~163 x 70 x 70 mm
- Connector Type: XT60H-F (2 pin)
- Balancing Lead: JST-XHP-7 (7 pin)
- Housing: Heat shrink + foam padding

Environmental and Safety Ratings

- Operating Temp (discharge): -40 to +60°C
- Operating Temp (charge): -20 to +60°C
- Storage Temp: <35, <23 long term°C
- Cycle Life: >500 cycles @ <80% DoD under normal operating conditions
- Certifications (Cells): UN38.3, IEC 62133, UL1642
- Certifications (Pack): N/A
- BMS / Protection: None

Ordering Info

	P42A	P45B	P50B	SA112	SA117	40T	50S
PN-Suffix	-42A	-45B	-50B	-112	-117	-40T	-50S

- Cell lead time, availability and pricing may vary, please email us for the latest information.



Safety & Handling

- Storage Voltage: 21 V pack voltage (3.5 V cell)
- Avoid over-discharge below 3.0 V/cell
- Do not puncture, crush, drop, overheat, or short-circuit
- Use proper cell balance when charging
- Monitor pack temperature during use
- Fuse or protect high current paths
- Intended for use only within electrical and environmental specifications

Warranty & Disclaimers

- Warranty: 2 months from date of delivery
- Limitations: Excludes crash, water, overcurrent damage, and use outside specifications
- Disclaimer: Performance depends on usage and conditions

WAKE ENERGY Inc.
THOR-6030-XXX
REV. A SHEET 1 of 2

