

What's new in the AMD Opteron™ 6100 Series Processor (Codenamed "Magny-Cours")?

Platform		Processor	Socket	Chipset
Opteron 6000		Opteron 6100	G34	56x0/5100
	(codenamed "Maranello")	(codenamed "Magny-Cours")		


- 8- or 12-Core AMD Opteron™ Processors on the AMD Opteron 6000 Series platform (Socket G34, codenamed "Maranello" with the AMD SR56x0 / SP5100 Chipset)
- New Power Management Features
 - Cool Speed
 Cool Speed protects processor integrity by reducing power states when a temperature limit is reached
 - C1E
 Promotes significant power savings. C1E detects when processor cores are idle: HyperTransport links are powered down, and the cores go into a deeper sleep state.
 - Enhanced APML with Precision Thermal Monitor
 APML is the interface for monitoring and controlling system resources, and Precision Thermal Monitor closely monitors power/cooling, and proactively alerts the Base Management Controller (BMC).
- Memory: Quad Channel U/RDDR3 at 800MHz, 1066MHz, and 1333MHz
- HyperTransport: 4x HT3 (HT 3.0), with up to 25.6 GB/s at 6.4 GT/s per link
- Cache: 12MB L3 cache per socket

The server platform you can count on as real-world workloads become increasingly complex and demanding





Series Transitions: AMD Opteron Server Roadmap





Product Specifications


Process		ACP ¹	Model	Clock Frequency / NB Frequency (GHz)	Cores	L2 Cache	L3 Cache	Max Memory Speed	System Bus Speed
45nm		105W	6176 SE	2.3 / 1.8	12	12 x 512KB	12MB	1333MHz	6.4GT/s
		80W	6174 6172 6168 6136	2.2 / 1.8 2.1 / 1.8 1.9 / 1.8 2.4 / 1.8	12	12 x 512KB	12MB	1333MHz	6.4GT/s
45	WER		6134 6128 6164 HE	2.3 / 1.8 2.0 / 1.8 1.7 / 1.8	12	8 x 512KB			
	LOW POWER	65W	6128 HE 6124 HE	2.0 / 1.8 1.8 / 1.8	8 8	8 x 512KB 8 x 512KB	12MB	1333MHz	6.4GT/s

ACP stands for Average CPU Power.






Processor Block Diagram for 2P Mainboards





Processor Block Diagram for 4P Mainboards








AMD Opteron[™] 6100 Series Processor

Memory Population Guidelines: 2 DIMMs per channel



Mainboards with 2 DIMMs per Channel¹


	DIMM Bank A	DIMM Bank B	Max MHz, 1.5V DIMMs	Max MHz, 1.35V DIMMs	Max GB/Channel
UDIMM	1R or 2R	Empty, 1R or 2R	1333	1066	8GB
	1R or 2R	Empty, 1R or 2R	1333	1066	16GB
RDIMM	4R	Empty	1333	1066	16GB
	4R	1R, 2R, or 4R	1066	800	32GB

¹ AMD supports single, dual, and quad rank (1R, 2R, and 4R). There is no distinction between memory population scenarios for 2P and 4P servers.





Memory Population Guidelines: 3 DIMMs per channel



Mainboards with 3 DIMMs per Channel¹


	DIMM Bank A	DIMM Bank B	DIMM Bank C	Max MHz, 1.5V DIMMs	Max MHz, 1.35V DIMMs	Max GB/Channel
UDIMM	1R or 2R	Empty	Empty, 1R or 2R	1333	1066	8GB
	1R	1R	1R	1333	1066	12GB
	1R or 2R	Empty	Empty, 1R or 2R	1333	1066	16GB
DDIMM	2R	1R or 2R	1R or 2R	1066	800	24GB
RDIMM	Empty	4R	Empty	1066	1066	16GB
	1R or 2R	4R	Empty	800	800	24GB
	1R or 2R	4R	1R or 2R	800	667	32GB

¹ AMD supports single, dual, and quad rank (1R, 2R, and 4R). There is no distinction between memory population scenarios for 2P and 4P servers.






HT3 Connections for 2P Mainboards





HT3 Connections for 4P Mainboards







AMD Opteron[™] 6100 Series Processor

Rackmount Servers with the AMD Opteron 6100 Series

- Rackform nServ A161
- Rackform nServ A331
- Rackform nServ A335
- Rackform nServ A350
- Rackform nServ A4410
- Rackform nServ A4410–IB





Contact Silicon Mechanics

For answers regarding processor selection or other questions, contact one of the Experts at Silicon Mechanics:

Email: <u>sales@siliconmechanics.com</u>

Toll Free: 866.352.1173

www.siliconmechanics.com