

Error Handling and Debugging (8)

HTML issues, PHP problems, SQL errors, or MySQL mistakes.

PHP errors fall into three general areas:

- 1) **Syntactical**: Syntactical errors are the most common and the easiest to fix.
- 2) **Run-time**: include those things that do not stop a PHP script from executing but do stop the script from doing everything it was supposed to do
- 3) **Logical**: is the worst because PHP will not necessarily report it to you.

Displaying php errors: PHP provides remarkably useful and descriptive error messages when things use

By use the => ini_set () function

Adjusting Error Reporting in PHP:

- 1) Notices, which do not stop the execution of a script and may not necessarily be a problem.
- 2) Warnings, which indicate a problem but do not stop a script's execution.
- 3) Errors, which stop a script from continuing.

Using PHP with MySQL (9)

Connecting to MySQL :

- 1) mysqli_connect (hostname, → username, password, db_name);
- 2) \$var = select or insert or update or delete
- 3) mysqli_query(dbc, var);
- 4) mysqli_close();

executing Simple Queries: mysqli_query(dbc, query);

The queries can be as basic as inserts, updates, and deletions.

ensuring Secure SQL: Database security with respect to PHP comes down to three broad issues:

1. Protecting the MySQL access information
2. Not revealing too much about the database
3. Being cautious when running queries, particularly those involving usersubmitted data.

Counting Returned Records: mysqli_num_rows(). This function returns the number of rows

by a SELECT query. It takes one argument.

Web Application Development (11)

You'll need to edit this file if any of these conditions apply:

- 1) file uploads is disabled.
- 2) PHP has no temporary directory to use.
- 3) You will be uploading.

MAX_FILE_SIZE hidden input is a form restriction on how large the chosen file can be, in bytes, and must come before the file input.

the uploaded file can be accessed using the **\$_FILES superglobal**. The variable will be an array of values, listed **move_uploaded_file()** function can transfer it from the temporary directory to its permanent location.

date_default_timezone_set(). This function is used to establish the default time zone.

checkdate() function takes a month, a day, and a year and returns those any time.

Cookies and Sessions (12)

. The two best PHP tools for this purpose are cookies and sessions.

cookies store data in the user's Web browser and sessions store data on the server itself.

The store data 4 KB

Create => setcookie ('name', 'waleed' , time()+ 120);

header ('Location: cp/waleed/index.php');

Delete => unset(\$_COOKIE);

setcookie ('name', 'waleed' , time()-120);

header ('Location: cp/waleed/index.php');

Sessions are generally more secure than cookies and can store much more information.

Create => session_start();

\$_SESSION['USER'] = 'WALEED';

header ('Location: cp/waleed/index.php');

Delete => session_start();

session_destroy();

Sessions have the following advantages over cookies:

- 1) . They are generally more secure.
- 2) They allow for more data to be stored.
- 3) They can be used without cookies.

cookies have the following advantages over sessions:

- 1) They are easier to program.
- 2) They require less of the server.
- 3) They can be made to last far longer

Security Methods (13)

attacks are referred to as cross-site scripting (XSS).

PHP includes a handful of functions for handling HTML and other code found within strings. These include:

- 1) **htmlspecialchars()**, which turns &, ' , " , into an HTML entity format (&, " , etc.);
- 2) **htmlentities()**, which turns all applicable characters into their HTML entity format.
- 3) **strip_tags()**, which removes all HTML and PHP tags.

- **nl2br()** function => remove the
 HTML

An OOP Primer (14)

Working with MySQL:

There are three defined classes that you will use herein:

- 1) **MySQLi**, the primary class, provides a database connection, a querying method, and more.
- 2) **MySQLi_Result**, is used to handle the results of SELECT queries (among others).
- 3) **MySQLi_STMT** is for performing prepared statements