1. Register

URL: http://mllazaccount.runasp.net/api/Identity/Accounts

Method: POST

Endpoint: /accounts Description:

create new account

Body (JSON):

```
{
  "fullName": "name",
  "email": "email@gmail.com",
  "phoneNumber": "phone",
  "password": "password",
  "confirmPassword": "confirm password"
}
```

Response:

```
{
“success message”: “rigster successfully”
}
```

---

2. Login

URL: http://mllazaccount.runasp.net/api/Identity/Accounts/Login

Method: POST

Endpoint: /Accounts/Login

Description: login by email and password

Body (JSON):


```
{
  "email": "",
  "password": "",
}
```


Response:


```
{
    "success": "Login Successfully",
    "name": "name  ",
    "id": "id",
    "userEmail": "email.gmail.com",
    "userPhone": "phone",
    "role": "role",
    "token": "token"
}
```


---

3. ForgetPassword

URL: http://mllazaccount.runasp.net/api/Identity/Accounts/ForgetPassword

Method: GET

Endpoint: /Accounts/ForgetPassword

Description:

order to reset password by email

Body (JSON):

```
{
  "email": "email",
}
```

Response:

```
{
    "success": "email valid",
    "userId": "id  ",
}
```

---

4. Reset Password

URL: http://mllazaccount.runasp.net/api/Identity/Accounts/ResetPassword

Method: POST

Endpoint: /Accounts/ResetPassword

Description: reset password by user id and password confirmpassword

Body (JSON):

```
{
  "userId": "id",
  "password": "",
  "confirmPassword": ""
```

}

Response:

{

“Success”: “successfully reset password”

}

---

5. Gust Login

URL: http://mllazaccount.runasp.net/api/Identity/Accounts/GustLogin

Method: POST

Endpoint: /Accounts/GustLogin

Description: login as a gust

Body: No body

Response:

{

"success": "Login Successfully as Gust",

"name": "name",

"id": "id",

"role": "role",

“token”: “token”

}

---

6. Make Report
URL: http://mllazaccount.runasp.net/api/User/Reports/Report
Method: Post

EndPoint: /Reports/Report

Description: user make report from this method

Body (from-data) :

{

Title : " text "

Description : " text "

Image : " file "

Location : " text "

}

Response :

{

Message : submet report successfully

}

---

7. GetReport

URL: http://mllazaccount.runasp.net/api/User/Reports/GetReport

Method : Get

Endpoint: /Reports/GetReport

Description : Get All report for the current user

NO Body

Response:

{

All report for the current user

}

---

8. StatusUpdate

URL : http://mllazaccount.runasp.net/api/User/Reports/StatusUpdate

Endpoint : /Reports/StatusUpdate

Method : Put

Description : this method change status dependent number of parameter and signature , Case 1 if you send just id status changed to (جار التحقق من البلاغ) , Case 2 if you send the id and message (رسالة شكر مثلا) and true status changed to (البلاغ اتحل) , Case 3 if you send id and message (اسباب رفض البلاغ) and false status changed to (البلاغ اترفض).

Body (from json) :
{
  "Id": "2",
"Message": "البلاغ اترف ض",
  "IsApproved": false
}

Response:
{
   "message": "Report status updated successfully"
}

---

9. ChangeRole

URL: http://mllazaccount.runasp.net/api/User/Reports/ChangeRole

Endpoint : /Reports/ChangeRole

Method : Put

Description : this method take for user id and role you want to change to the user and change it

Body (from json)

```
{
   "UserId": "2d7e2021-fb31-4ecc-b510-4efe363d9536",
   "Role": "admin"
}
```


Response:

```
{
   "message": "role changed success"
}
```


---

10. GetAllUser

URL: http://mllazaccount.runasp.net/api/User/Reports/GetAllUser

Endpoint : /Reports/ GetAllUser

Method: Get

Description : get all user in the app

No body

Response :
{
Return all users
}

---

11. GetAllReport

URL : http://mllazaccount.runasp.net/api/User/Reports/GetAllReport

EndPoint : /Reports/ GetAllReport

Method : Get

Description: get all reports in the app

No body

Response : {

Return all reports
}