Gentrification

Daniel Fuller

2026-09-11

Gentrification

Read in the CANUE developed gentrification data converted to the postal code level

```
gentri_pc <- read_csv("/Users/dlf545/Library/CloudStorage/OneDrive-UniversityofSaskatchewan/CSDUL data/C
```

```
## Rows: 863541 Columns: 15
## -- Column specification --------------------------------------------------------
## Delimiter: ","
## chr  (4): postalcode16, province, gen16_04, gen16_09
## dbl (11): gen16_01, gen16_02, gen16_03, gen16_05, gen16_06, gen16_07, gen16_...
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
glimpse(gentri_pc)
```


```
## Rows: 863,541
## Columns: 15
## $ postalcode16 <chr> "A0A0A1", "A0A0A2", "A0A0A3", "A0A0A4", "A0A0A5", "A0A0A6~
## $ province     <chr> "NL", "NL", "NL", "NL", "NL", "NL", "NL", "NL", "NL", "NL~
## $ gen16_01     <dbl> -9999.00, -9999.00, -9999.00, -9999.00, -9999.00, -9999.0~
## $ gen16_02     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_03     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_04     <chr> "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "~
## $ gen16_05     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_06     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_07     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_08     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_09     <chr> "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "~
## $ gen16_10     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_11     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_12     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_13     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
```

```
summary(gentri_pc$gen16_13)
```

```
##    Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##   -9999       0       0   -2476       0       1
```

```
ggplot(data = gentri_pc, aes(gen16_13)) +
        geom_histogram() +
        theme_minimal()
```

```
## `stat_bin()` using `bins = 30`. Pick better value `binwidth`.
```



Joining Sprawl PC to PCCF+

Read in the PCCF+ data

```
pccf_plus <- read_csv("/Users/dlf545/Library/CloudStorage/OneDrive-UniversityofSaskatchewan/CSDUL data/
```

```
## Rows: 863541 Columns: 83
## -- Column specification --------------------------------------------------------
## Delimiter: ","
## chr (31): CODER, VERSION, PCODE, DB, DB_ir2021, CSDname, CSDtype, CMA, CMAty...
## dbl (51): PR, DAuid, CSDuid, Tracted, SACcode, SACtype, CCSuid, FEDuid, DPLu...
## lgl  (1): ID
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
glimpse(pccf_plus)
```

```
## Rows: 863,541
## Columns: 83
## $ CODER         <chr> "R", "R", "R", "R", "R", "R", "R", "R", "R", "R", "R", "~
## $ VERSION       <chr> "8B", "8B", "8B", "8B", "8B", "8B", "8B", "8B", "8B", "8~
## $ ID            <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ PCODE         <chr> "A0A0A1", "A0A0A2", "A0A0A3", "A0A0A4", "A0A0A5", "A0A0A~
## $ PR            <dbl> 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, ~
## $ DAuid         <dbl> 10010562, 10010520, 10010690, 10010549, 10010520, 100106~
## $ DB            <chr> "011", "007", "037", "005", "007", "037", "010", "036", ~
## $ DB_ir2021     <chr> "F", "F", "F", "F", "F", "F", "F", "F", "F", "F", "F", "~
```

```
## $ CSDuid        <dbl> 1001464, 1001374, 1001452, 1001434, 1001374, 1001452, 10~
## $ CSDname       <chr> "Avondale", "Division No.  1, Subd. I", "Division No.  1~
## $ CSDtype       <chr> "T", "SNO", "SNO", "T", "SNO", "SNO", "SNO", "SNO", "SNO~
## $ CMA           <chr> "000", "000", "000", "000", "000", "000", "000", "000", ~
## $ CMAtype       <chr> "G", "I", "G", "H", "I", "G", "I", "G", "G", "J", "G", "~
## $ CMAname       <chr> "Strong metropolitan influenced zone (N.L.) / Zone d'inf~
## $ CTname        <chr> "0000.00", "0000.00", "0000.00", "0000.00", "0000.00", "~
## $ Tracted       <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,~
## $ SACcode       <dbl> 996, 998, 996, 997, 998, 996, 998, 996, 996, 999, 996, 9~
## $ SACtype       <dbl> 4, 6, 4, 5, 6, 4, 6, 4, 4, 7, 4, 7, 4, 5, 6, 6, 6, 4, 6,~
## $ CCSuid        <dbl> 1001472, 1001357, 1001472, 1001472, 1001357, 1001472, 10~
## $ FEDuid        <dbl> 10001, 10001, 10001, 10001, 10001, 10001, 10001, 10001, ~
## $ FEDname       <chr> "Avalon", "Avalon", "Avalon", "Avalon", "Avalon", "Avalo~
## $ DPLuid        <dbl> 10, 100385, 10, 10, 100385, 10, 100385, 100252, 10, 10, ~
## $ DPLtype       <chr> NA, "DPL", NA, NA, "DPL", NA, "DPL", "DPL", NA, NA, NA, ~
## $ DPLname       <chr> NA, "Bristols Hope", NA, NA, "Bristols Hope", NA, "Brist~
## $ ERuid         <dbl> 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 1010, 10~
## $ ERname        <chr> "Avalon Peninsula", "Avalon Peninsula", "Avalon Peninsul~
## $ CARuid        <dbl> 1001, 1001, 1001, 1001, 1001, 1001, 1001, 1001, 1001, 10~
## $ CARname       <chr> "Census Agricultural Region 1", "Census Agricultural Reg~
## $ PopCtrRAPuid  <dbl> 109910, 100136, 109910, 109910, 100136, 109910, 100136, ~
## $ PopCtrRAname  <chr> "Newfoundland and Labrador Rural Area / R\xe9gion rurale~
## $ PopCtrRAtype  <dbl> 5, 4, 5, 5, 4, 5, 4, 5, 5, 5, 5, 5, 5, 5, 4, 5, 5, 5, 4,~
## $ PopCtrRAclass <dbl> 1, 2, 1, 1, 2, 1, 2, 1, 1, 1, 1, 1, 1, 1, 2, 1, 1, 1, 2,~
## $ CSize         <dbl> 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5,~
## $ CSizeMIZ      <dbl> 5, 7, 5, 6, 7, 5, 7, 5, 5, 7, 5, 7, 5, 6, 7, 7, 7, 5, 7,~
## $ HRuid         <dbl> 1021, 1021, 1021, 1021, 1021, 1021, 1021, 1021, 1021, 10~
## $ HRename       <chr> "Eastern Rural Zone", "Eastern Rural Zone", "Eastern Rur~
## $ HRfname       <chr> "Eastern Rural Zone", "Eastern Rural Zone", "Eastern Rur~
## $ AHRuid        <dbl> 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10, ~
## $ AHRename      <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ AHRfname      <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ SLI           <dbl> 1, 9, 9, 1, 9, 9, 9, 9, 9, 1, 1, 1, 1, 1, 9, 9, 9, 9, 9,~
## $ Rep_Pt_type   <dbl> 3, 9, 9, 3, 9, 9, 3, 9, 9, 3, 3, 3, 3, 3, 9, 9, 9, 9, 9,~
## $ RPF           <dbl> 3, 6, 6, 3, 6, 6, 5, 6, 6, 3, 3, 3, 3, 3, 6, 6, 6, 6, 6,~
## $ PCtype        <dbl> 3, 9, 9, 3, 9, 9, 9, 9, 9, 3, 3, 3, 3, 3, 9, 9, 9, 9, 9,~
## $ DMT           <chr> "W", "9", "9", "W", "9", "9", "W", "9", "9", "W", "W", "~
## $ H_DMT         <chr> "W", NA, NA, "W", NA, NA, "W", NA, NA, "W", "W", "W", "W~
## $ DMTDIFF       <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ PO            <dbl> 1, 2, 2, 1, 2, 2, 2, 2, 2, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2,~
## $ QI            <chr> "NNN", "999", "999", "NNN", "999", "999", "999", "999", ~
## $ Source        <dbl> 1, 9, 9, 1, 9, 9, 9, 9, 9, 1, 1, 1, 6, 1, 9, 9, 9, 9, 9,~
## $ Lat           <dbl> 47.39675, 47.71381, 47.35304, 47.52908, 47.71381, 47.353~
## $ Long          <dbl> -53.22259, -53.21024, -53.29517, -53.27264, -53.21024, -~
## $ Link_Source   <chr> "F", "5", "5", "F", "5", "5", "C", "5", "5", "F", "F", "~
## $ Link          <dbl> 9, 0, 0, 9, 0, 0, 7, 0, 0, 9, 9, 6, 9, 9, 0, 0, 0, 0, 0,~
## $ nCD           <dbl> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,~
## $ nCSD          <dbl> 1, 2, 2, 1, 2, 2, 1, 2, 2, 1, 1, 2, 1, 1, 2, 2, 2, 2, 2,~
## $ PREC          <chr> "5", "4", "4", "5", "4", "4", "5", "4", "4", "5", "5", "~
## $ Comm_Name     <chr> "AVONDALE", NA, NA, "SOUTH RIVER", NA, NA, NA, NA, NA, "~
## $ AirLift       <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ InstFlag      <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ Resflag       <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ InuitLands    <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,~
```

```
## $ BTIPPE        <dbl> 44735, 58153, 55655, 55928, 58153, 55655, 58153, 55655, ~
## $ ATIPPE        <dbl> 39951, 49097, 49980, 49108, 49097, 49980, 49097, 49980, ~
## $ QABTIPPE      <dbl> 2, 4, 4, 4, 4, 4, 4, 4, 4, 999, 3, 4, 4, 2, 4, 4, 4, 4, ~
## $ QNBTIPPE      <dbl> 1, 2, 2, 2, 2, 2, 2, 2, 2, 999, 2, 2, 2, 1, 2, 2, 2, 2, ~
## $ DABTIPPE      <dbl> 4, 8, 8, 8, 8, 8, 8, 8, 8, 999, 6, 7, 7, 3, 8, 8, 8, 8, ~
## $ DNBTIPPE      <dbl> 2, 4, 4, 4, 4, 4, 4, 4, 4, 999, 3, 3, 3, 2, 4, 4, 4, 4, ~
## $ QAATIPPE      <dbl> 2, 4, 5, 4, 4, 5, 4, 5, 5, 999, 3, 4, 4, 1, 4, 4, 4, 5, ~
## $ QNATIPPE      <dbl> 1, 2, 2, 2, 2, 2, 2, 2, 2, 999, 1, 2, 2, 1, 2, 2, 2, 2, ~
## $ DAATIPPE      <dbl> 4, 8, 9, 8, 8, 9, 8, 9, 9, 999, 6, 7, 8, 2, 8, 8, 8, 9, ~
## $ DNATIPPE      <dbl> 2, 4, 4, 4, 4, 4, 4, 4, 4, 999, 2, 3, 4, 1, 4, 4, 4, 4, ~
## $ IMPFLG        <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,~
## $ DA11uid       <dbl> 10010562, 10010520, 10010690, 10010549, 10010520, 100106~
## $ DB11uid       <dbl> 1001056204, 1001052007, 1001069014, 1001054905, 10010520~
## $ DA06uid       <dbl> 10010562, 10010520, 10010690, 10010549, 10010520, 100106~
## $ DA01uid       <dbl> 10010112, 10010372, 10010117, 10010088, 10010372, 100101~
## $ EA96uid       <dbl> 10006006, 10001056, 10007086, 10001005, 10001056, 100070~
## $ EA91uid       <dbl> 10006006, 10001056, 10007086, 10001005, 10001056, 100070~
## $ EA86uid       <dbl> 10006018, 10001062, 10006004, 10001009, 10001062, 100060~
## $ EA81uid       <dbl> 10006018, 10001062, 10006003, 10001009, 10001062, 100060~
## $ DA16uid       <dbl> 10010562, 10010520, 10010690, 10010549, 10010520, 100106~
## $ DB16uid       <dbl> 10010562004, 10010520007, 10010690014, 10010549005, 1001~
```

```
pccf_plus <- pccf_plus |> select(PCODE, CTname, DAuid, CSDuid, CMA, Tracted, DA16uid, DB16uid, Lat, Lon
```

```
gentri_join <- full_join(gentri_pc, pccf_plus, c("postalcode16" = "PCODE"))

gentri_join <- gentri_join %>% replace_with_na(replace = list(gen16_13 = -9999.0000))
gentri_join <- gentri_join %>% replace_with_na(replace = list(gen16_13 = -9))


summary(gentri_join$gen16_13)
```

```
##    Min. 1st Qu.  Median    Mean 3rd Qu.    Max.     NAs
## 0.00000 0.00000 0.00000 0.01925 0.00000 1.00000  213805
```

```
ggplot(data = gentri_join) +
        geom_histogram(aes(gen16_13), alpha = 0.5, fill = "red") +
        theme_minimal()
```

```
## `stat_bin()` using `bins = 30`. Pick better value `binwidth`.
```

```
## Warning: Removed 213805 rows containing non-finite outside the scale range
## (`stat_bin()`).
```



We remove air values of -9999.0000 and -9 because those are missing.

Group by DA for joined data

Do a group by 2016 DA to be able to join the CANUE sprawl data to the original sprawl data as a check.

```
glimpse(gentri_join)
```

```
## Rows: 863,541
## Columns: 24
## $ postalcode16 <chr> "A0A0A1", "A0A0A2", "A0A0A3", "A0A0A4", "A0A0A5", "A0A0A6~
## $ province     <chr> "NL", "NL", "NL", "NL", "NL", "NL", "NL", "NL", "NL", "NL~
## $ gen16_01     <dbl> -9999.00, -9999.00, -9999.00, -9999.00, -9999.00, -9999.0~
## $ gen16_02     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_03     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_04     <chr> "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "~
## $ gen16_05     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_06     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_07     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_08     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_09     <chr> "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "NULL", "~
## $ gen16_10     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_11     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_12     <dbl> -9999, -9999, -9999, -9999, -9999, -9999, -9999, -9999, -~
## $ gen16_13     <dbl> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, 0~
## $ CTname       <chr> "0000.00", "0000.00", "0000.00", "0000.00", "0000.00", "0~
## $ DAuid        <dbl> 10010562, 10010520, 10010690, 10010549, 10010520, 1001069~
## $ CSDuid       <dbl> 1001464, 1001374, 1001452, 1001434, 1001374, 1001452, 100~
```

```
## $ CMA          <chr> "000", "000", "000", "000", "000", "000", "000", "000", "~
## $ Tracted      <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ~
## $ DA16uid      <dbl> 10010562, 10010520, 10010690, 10010549, 10010520, 1001069~
## $ DB16uid      <dbl> 10010562004, 10010520007, 10010690014, 10010549005, 10010~
## $ Lat          <dbl> 47.39675, 47.71381, 47.35304, 47.52908, 47.71381, 47.3530~
## $ Long         <dbl> -53.22259, -53.21024, -53.29517, -53.27264, -53.21024, -5~
```

```
gentri_join_da <- gentri_join |>
                    group_by(DA16uid) |>
                      summarize(
                        gen16_13 = first(gen16_13),
                        postalcode16 = first(postalcode16),
                        DB16uid = first(DB16uid),
                        CTname = first(CTname),
                        CMA = first(CMA),
                        Tracted = first(Tracted),
                        Lat = median(Lat, na.rm = TRUE),
                        Long = median(Long, na.rm = TRUE),
                       )

table(gentri_join_da$gen16_13)
```

```
##
##     0     1
## 35831   777
```

Join OG Sprawl data with CANUE PC Sprawl data

Here the CT name variable is sort of a mess, not clear why they don't have a proper CT variable. So I went here https://www12.statcan.gc.ca/census-recensement/alternative_alternatif.cfm?l=eng&dispext=zip&teng=2016_92-151_XBB_csv.zip&loc=http://www12.statcan.gc.ca/census-recensement/2016/geo/ref/gaf/files-fichiers/2016_92-151_XBB_csv.zip&k=%20%20%20%2023271 to get the proper conversion file from DAIUD to CT.

Select the variables we want from the 2016 census geography conversion file.

```
conv_file <- read_csv("/Users/dlf545/Library/CloudStorage/OneDrive-UniversityofSaskatchewan/CSDUL data/
```

```
## Rows: 489905 Columns: 48
## -- Column specification --------------------------------------------------------
## Delimiter: ","
## chr (24): PRname/PRnom, PRename/PRanom, PRfname/PRfnom, PReabbr/PRaabbrev, P...
## dbl (23): DBuid/IDidu, DBpop2016/IDpop2016, DBtdwell2016/IDtlog2016, DBurdwe...
## lgl  (1): DBir2016/IDri2016
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
glimpse(conv_file)
```

```
## Rows: 489,905
## Columns: 48
## $ `DBuid/IDidu`                 <dbl> 10020117004, 10020117003, 10020117008, ~
## $ `DBpop2016/IDpop2016`         <dbl> 36, 35, 46, 30, 26, 78, 93, 0, 100, 0, ~
## $ `DBtdwell2016/IDtlog2016`     <dbl> 13, 21, 28, 28, 44, 35, 39, 0, 46, 0, 1~
## $ `DBurdwell2016/IDrh2016`      <dbl> 10, 16, 21, 15, 17, 33, 37, 0, 41, 0, 1~
## $ `DBarea2016/IDsup2016`        <dbl> 0.6124, 3.8578, 0.3800, 7.7079, 3.9179,~
```

```
## $ `DBir2016/IDri2016`            <lgl> FALSE, FALSE, FALSE, FALSE, FALSE, FALS~
## $ `DAuid/ADidu`                  <dbl> 10020117, 10020117, 10020117, 10010746,~
## $ `DArplamx/ADlamx`              <dbl> 8852175, 8852175, 8852175, 8927992, 892~
## $ `DArplamy/ADlamy`              <dbl> 1980863, 1980863, 1980863, 2040576, 204~
## $ `DArplat/Adlat`                <dbl> 46.93298, 46.93298, 46.93298, 47.00466,~
## $ `DArplong/ADlong`              <dbl> -55.36201, -55.36201, -55.36201, -54.10~
## $ `PRuid/PRidu`                  <dbl> 10, 10, 10, 10, 10, 10, 10, 10, 10, 10,~
## $ `PRname/PRnom`                 <chr> "Newfoundland and Labrador / Terre-Neuv~
## $ `PRename/PRanom`               <chr> "Newfoundland and Labrador", "Newfoundl~
## $ `PRfname/PRfnom`               <chr> "Terre-Neuve-et-Labrador", "Terre-Neuve~
## $ `PReabbr/PRaabbrev`            <chr> "N.L.", "N.L.", "N.L.", "N.L.", "N.L.",~
## $ `PRfabbr/PRfabbrev`            <chr> "T.-N.-L.", "T.-N.-L.", "T.-N.-L.", "T.~
## $ `FEDuid/CEFidu`                <dbl> 10002, 10002, 10002, 10001, 10001, 1000~
## $ `FEDname/CEFnom`               <chr> "Bonavista--Burin--Trinity", "Bonavista~
## $ `ERuid/REidu`                  <dbl> 1020, 1020, 1020, 1010, 1010, 1020, 102~
## $ `ERname/REnom`                 <chr> "South Coast--Burin Peninsula / C\xf4te~
## $ `CDuid/DRidu`                  <dbl> 1002, 1002, 1002, 1001, 1001, 1002, 100~
## $ `CDname/DRnom`                 <chr> "Division No.  2", "Division No.  2", "~
## $ `CDtype/DRgenre`               <chr> "CDR", "CDR", "CDR", "CDR", "CDR", "CDR~
## $ `ADAuid/ADAidu`                <dbl> 10020001, 10020001, 10020001, 10010035,~
## $ ADAcode                        <chr> "0001", "0001", "0001", "0035", "0035",~
## $ `CSDuid/SDRidu`                <dbl> 1002006, 1002006, 1002006, 1001214, 100~
## $ `CSDname/SDRnom`               <chr> "Division No.  2, Subd. F", "Division N~
## $ `CSDtype/SDRgenre`             <chr> "SNO", "SNO", "SNO", "SNO", "SNO", "SNO~
## $ `SACtype/CSSgenre`             <dbl> 7, 7, 7, 7, 7, 5, 5, 7, 7, 7, 7, 7, 5, ~
## $ `SACcode/CSScode`              <chr> "999", "999", "999", "999", "999", "997~
## $ `CCSuid/SRUidu`                <dbl> 1002001, 1002001, 1002001, 1001214, 100~
## $ `CCSname/SRUnom`               <chr> "Division No.  2, Subd. E", "Division N~
## $ `DPLuid/LDidu`                 <dbl> 100100, 100100, 100100, 100101, 100101,~
## $ `DPLname/LDnom`                <chr> "Little St. Lawrence", "Little St. Lawr~
## $ `DPLtype/LDgenre`              <chr> "DPL", "DPL", "DPL", "DPL", "DPL", "DPL~
## $ `CMAPuid/RMRPidu`              <dbl> 10999, 10999, 10999, 10999, 10999, 1099~
## $ `CMAuid/RMRidu`                <chr> "999", "999", "999", "999", "999", "997~
## $ `CMAname/RMRnom`               <chr> "No metropolitan influenced zone (N.L.)~
## $ `CMAtype/RMRgenre`             <chr> "J", "J", "J", "J", "J", "H", "H", "J",~
## $ `CTuid/SRidu`                  <chr> "9910.00", "9910.00", "9910.00", "9910.~
## $ `CTcode/SRcode`                <chr> "9910", "9910", "9910", "9910", "9910",~
## $ `CTname/SRnom`                 <chr> "9910.00", "9910.00", "9910.00", "9910.~
## $ `POPCTRRAPuid/CTRPOPRRPidu`    <dbl> 109910, 109910, 109910, 109910, 109910,~
## $ `POPCTRRAuid/CTRPOPRRidu`      <chr> "9910", "9910", "9910", "9910", "9910",~
## $ `POPCTRRAname/CTRPOPRRnom`     <chr> "Newfoundland and Labrador Rural Area /~
## $ `POPCTRRAtype/CTRPOPRRgenre`   <dbl> 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, ~
## $ `POPCTRRAclass/CTRPOPRRclasse` <dbl> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
```

```
conv_file <- conv_file |> select('DAuid/ADidu', 'CTuid/SRidu', 'CMAuid/RMRidu', 'CTcode/SRcode', 'CTname
```

```
gentri_da_conv <- left_join(gentri_join_da, conv_file, c("DA16uid" = "DAuid/ADidu"))

gentri_da_conv$`CTuid/SRidu` <- as.numeric(gentri_da_conv$`CTuid/SRidu`)
```

Select and write a new clean file

```
gentri_data_CSDUL <- gentri_da_conv
```

	n=48795
gentrified	
0	35831 (98)
1	777 (2)
Missing	12187

```
selection <- c(
  da16uid = "DA16uid",
  postalcode16 = "postalcode16",
  cmauid = "CMAuid/RMRidu",
  ctcode = "CTcode/SRcode",
  ctname = "CTname/SRnom",
  gentrified = "gen16_13"
)

gentri_data_CSDUL <- gentri_data_CSDUL |> select(all_of(selection))

gentri_data_CSDUL <- distinct(gentri_data_CSDUL)


gentri_data_CSDUL$gentrified <- as.factor(gentri_data_CSDUL$gentrified)

write_csv(gentri_data_CSDUL, "/Users/dlf545/Library/CloudStorage/OneDrive-UniversityofSaskatchewan/CSDU
```

Descriptive Statistics

```
rm_covsum(data=gentri_data_CSDUL,
covs=c('gentrified'),all.stats = TRUE)
```

```
ggplot(gentri_data_CSDUL) +
      geom_bar(aes(gentrified))
```



Mapping


```
ct_map <- get_census(dataset='CA16', regions=list(C = "01"),
                          vectors=c("v_CA21_1", "v_CA21_2"),
                          level='CT', use_cache = TRUE, geo_format = 'sf', quiet = TRUE)

ct_map$GeoUID <- as.numeric(ct_map$GeoUID)

gentri_data_CSDUL$ctname <- as.numeric(gentri_data_CSDUL$ctname)

map <- full_join(ct_map, gentri_data_CSDUL, c("GeoUID" = "ctname"))

ggplot() +
  geom_sf(data = map, aes(fill = gentrified)) +
  theme_minimal()
```



Map for Saskatoon only

```
saskatoon_map <- map |> filter(`Region Name` == "Saskatoon")

ggplot() +
  geom_sf(data = saskatoon_map, aes(fill = gentrified)) +
  theme_minimal()
```

