



Universidade de Brasília

Tomate Cerveja

Wallace Wu, Pedro Gallo, Henrique Ramos

2024-02-07

- 1 Contest
- 2 Mathematics
- 3 Data structures
- 4 Numerical
- 5 Number theory
- 6 Combinatorial
- 7 Graph
- 8 Geometry
- 9 Strings
- 10 Miscellaneous

Contest (1)

template.cpp33 lines

```
#include <bits/stdc++.h>
using namespace std;
#define sws cin.tie(0)->sync_with_stdio(0)

#define endl '\n'
#define ll long long
#define ld long double
#define pb push_back
#define ff first
#define ss second
#define pll pair<ll, ll>
#define vll vector<ll>

#define teto(a, b) ((a+b-1)/(b))
#define LSB(i) ((i) & -(i))
#define MSB(i) (32 - __builtin_clz(i)) //64 - clzll
#define BITS(i) __builtin_popcountll(i) //count set bits

mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());

#define debug(a...) cerr<<#a<<" ";for(auto b:a)cerr<<b<<" ";
cerr<<endl;
template<typename... A> void dbg(A const&... a){(cerr<<"{"<<a
<<" "}, ...);cerr<<endl;}

const int MAX = 3e5+10;
const int INF = INT32_MAX;
const long long MOD = 1e9+7;
const long long LLINF = INT64_MAX;
const long double EPS = 1e-7;
const long double PI = acos(-1);

int32_t main(){ sws;

}
```

.bashrc1 lines

```
alias comp='g++ -std=c++17 -g3 -ggdb3 -O3 -Wall -Wextra -
fsanitize=address,undefined -Wshadow -Wconversion -
D_GLIBCXX_ASSERTIONS -o test'
```

hash.sh3 lines

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed. CTRL+D to send EOF
cpp -dD -P -fpreprocessed | tr -d '[:space:]' | md5sum | cut -c
-6
```

troubleshoot.txt52 lines

```
Pre-submit:
Write a few simple test cases if sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Make sure to submit the right file.

Wrong answer:
Print your solution! Print debug output, as well.
Are you clearing all data structures between test cases?
Can your algorithm handle the whole range of input?
Read the full problem statement again.
Do you handle all corner cases correctly?
Have you understood the problem correctly?
Any uninitialized variables?
Any overflows?
Confusing N and M, i and j, etc.?
Are you sure your algorithm works?
What special cases have you not thought of?
Are you sure the STL functions you use work as you think?
Add some assertions, maybe resubmit.
Create some testcases to run your algorithm on.
Go through the algorithm for a simple case.
Go through this list again.
Explain your algorithm to a teammate.
Ask the teammate to look at your code.
Go for a small walk, e.g. to the toilet.
Is your output format correct? (including whitespace)
Rewrite your solution from the start or let a teammate do it.

Runtime error:
Have you tested all corner cases locally?
Any uninitialized variables?
Are you reading or writing outside the range of any vector?
Any assertions that might fail?
Any possible division by 0? (mod 0 for example)
Any possible infinite recursion?
Invalidated pointers or iterators?
Are you using too much memory?
Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:
Do you have any possible infinite loops?
What is the complexity of your algorithm?
Are you copying a lot of unnecessary data? (References)
How big is the input and output? (consider scanf)
Avoid vector, map. (use arrays/unordered_map)
What do your teammates think about your algorithm?

Memory limit exceeded:
What is the max amount of memory your algorithm should need?
Are you clearing all data structures between test cases?
```

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{matrix} ax + by = e \\ cx + dy = f \end{matrix} \Rightarrow \begin{matrix} x = \frac{ed - bf}{ad - bc} \\ y = \frac{af - ec}{ad - bc} \end{matrix}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

2.2 Recurrences

If $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$, and r_1, \dots, r_k are distinct roots of $x^k - c_1x^{k-1} - \dots - c_k$, there are d_1, \dots, d_k s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g.

$$a_n = (d_1n + d_2)r^n.$$

2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$

$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$

$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x + b \cos x = r \sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \operatorname{atan2}(b, a)$.

2.4 Geometry

2.4.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

$m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

2.4.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$

2.4.3 Spherical coordinates

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$.



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \operatorname{atan2}(y, x) \end{aligned}$$

2.5 Derivatives/Integrals

$$\begin{aligned} \frac{d}{dx} \arcsin x &= \frac{1}{\sqrt{1 - x^2}} & \frac{d}{dx} \arccos x &= -\frac{1}{\sqrt{1 - x^2}} \\ \frac{d}{dx} \tan x &= 1 + \tan^2 x & \frac{d}{dx} \arctan x &= \frac{1}{1 + x^2} \\ \int \tan ax &= -\frac{\ln |\cos ax|}{a} & \int x \sin ax &= \frac{\sin ax - ax \cos ax}{a^2} \\ \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \operatorname{erf}(x) & \int x e^{ax} dx &= \frac{e^{ax}}{a^2} (ax - 1) \end{aligned}$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$\begin{aligned} 1 + 2 + 3 + \dots + n &= \frac{n(n + 1)}{2} \\ 1^2 + 2^2 + 3^2 + \dots + n^2 &= \frac{n(2n + 1)(n + 1)}{6} \\ 1^3 + 2^3 + 3^3 + \dots + n^3 &= \frac{n^2(n + 1)^2}{4} \\ 1^4 + 2^4 + 3^4 + \dots + n^4 &= \frac{n(n + 1)(2n + 1)(3n^2 + 3n - 1)}{30} \end{aligned}$$

2.7 Series

$$\begin{aligned} e^x &= 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty) \\ \ln(1 + x) &= x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1) \\ \sqrt{1 + x} &= 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1) \\ \sin x &= x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty) \\ \cos x &= 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty) \end{aligned}$$

2.8 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2 V(X) + b^2 V(Y).$$

2.8.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\operatorname{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1 - p)^{n - k}$$

$$\mu = np, \sigma^2 = np(1 - p)$$

$\operatorname{Bin}(n, p)$ is approximately $\operatorname{Po}(np)$ for small p .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\operatorname{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1 - p)^{k - 1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1 - p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\operatorname{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

2.8.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $U(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$
$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$
$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

2.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let X_1, X_2, \dots be a sequence of random variables generated by the Markov process. Then there is a transition matrix $\mathbf{P} = (p_{ij})$, with $p_{ij} = \Pr(X_n = i | X_{n-1} = j)$, and $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$ is the probability distribution for X_n (i.e., $p_i^{(n)} = \Pr(X_n = i)$), where $\mathbf{p}^{(0)}$ is the initial distribution.

π is a stationary distribution if $\pi = \pi \mathbf{P}$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state i . π_j / π_i is the expected number of visits in state j between two visits in state i .

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, π_i is proportional to node i 's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1). $\lim_{k \rightarrow \infty} \mathbf{P}^k = \mathbf{1}\pi$.

A Markov chain is an A-chain if the states can be partitioned into two sets \mathbf{A} and \mathbf{G} , such that all states in \mathbf{A} are absorbing ($p_{ii} = 1$), and all states in \mathbf{G} leads to an absorbing state in \mathbf{A} . The probability for absorption in state $i \in \mathbf{A}$, when the initial state is j , is $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$. The expected time until absorption, when the initial state is i , is $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$.

Data structures (3)

3.1 Disjoint Set Union

There are two optional improvements: -Tree Balancing -Path Compression

If one improvement is used, the time complexity will become $O(\log N)$

If both are used, $O(\alpha) \approx O(5)$

```
dsu.cpp
Description: Disjoint Set Union with path compression and tree balancing
Time: O(α)
0479c4, 22 lines

struct DSU{
    vll group, card;
    DSU (ll n){
        n += 1; // 0-idx -> 1-idx
        group = vll(n);
        iota(group.begin(), group.end(), 0);
        card = vll(n, 1);
    }
    ll find(ll i){
        return (i == group[i]) ? i : (group[i] = find(group[i]))
    };
    // returns false if a and b are already in the same component
    bool join(ll a ,ll b){
        a = find(a);
        b = find(b);
        if (a == b) return false;
        if (card[a] < card[b]) swap(a, b);
        card[a] += card[b];
        group[b] = a;
        return true;
    }
};
```

Numerical (4)

Number theory (5)

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL.MAX		

Graph (7)

7.1 Fundamentals

7.2 Network flow

In optimization theory, maximum flow problems involve finding a feasible flow through a flow network that obtains the maximum possible flow rate.

```
dinic.cpp
Description: Run several bfs to compute the residual graph until a max flow configuration is discovered
Time: General Case, O(V^2E); Unit Capacity, O((V+E)√E); Bipartite and unit capacity, O((V+E)√V)
dealb7, 86 lines

// remember to duplicate vertices for the bipartite graph
// N = number of nodes, including sink and source
const ll N = 700;

struct Dinic {
    struct Edge {
        ll from, to, flow, cap;
    };
    vector<Edge> edges;

    vector<ll> g[N];
    ll ne = 0, lvl[N], vis[N], pass;
    ll qu[N], px[N], qt;

    ll run(ll s, ll sink, ll minE) {
        if (s == sink) return minE;
        ll ans = 0;
        for (; px[s] < (int)g[s].size(); px[s]++){
            ll e = g[s][ px[s] ];
            auto &v = edges[e], &rev = edges[e^1];
            if( lvl[v.to] != lvl[s]+1 || v.flow >= v.cap) continue;
            ll tmp = run(v.to, sink, min(minE, v.cap - v.flow));
            v.flow += tmp, rev.flow -= tmp;
            ans += tmp, minE -= tmp;
            if (minE == 0) break;
        }
        return ans;
    }
};
```

```

bool bfs(ll source, ll sink) {
    qt = 0;
    qu[qt++] = source;
    lvl[source] = 1;
    vis[source] = ++pass;
    for(ll i=0; i<qt; i++) {
        ll u = qu[i];
        px[u] = 0;
        if (u == sink) return 1;
        for(auto& ed : g[u]) {
            auto v = edges[ed];
            if (v.flow >= v.cap || vis[v.to] == pass)
                continue;
            vis[v.to] = pass;
            lvl[v.to] = lvl[u]+1;
            qu[qt++] = v.to;
        }
    }
    return false;
}

ll flow(ll source, ll sink) { // max_flow
    reset_flow();
    ll ans = 0;
    while(bfs(source, sink))
        ans += run(source, sink, LLINF);
    return ans;
}

void addEdge(ll u, ll v, ll c, ll rc = 0) { // c = capacity
    , rc = retro-capacity;
    Edge e = {u, v, 0, c};
    edges.pb(e);
    g[u].pb(ne++);
    e = {v, u, 0, rc};
    edges.pb(e);
    g[v].pb(ne++);
}

void reset_flow() {
    for (ll i=0; i<n; i++) edges[i].flow = 0;
    memset(lvl, 0, sizeof(lvl));
    memset(vis, 0, sizeof(vis));
    memset(qu, 0, sizeof(qu));
    memset(px, 0, sizeof(px));
    qt = 0; pass = 0;
}

// cut set cost = minimum cost = max flow
// cut set is the set of edges that, if removed,
// will disrupt flow from source to sink and make it 0.
vector<pll> cut() {
    vector<pll> cuts;
    for (auto [from, to, flow, cap]: edges)
        if (flow == cap and vis[from] == pass and vis[to] <
            pass and cap > 0)
            cuts.pb({from, to});
    return cuts;
}
};

```

7.2.1 Minimum Cut

In computer science and optimization theory, the max-flow min-cut theorem states that in a flow network, the maximum amount of flow passing from the source to the sink is equal to the total weight of the edges in a minimum cut, i.e., the smallest total weight of the edges which if removed would disconnect the source from the sink.

Let's define an s-t cut $C = (S\text{-component}, T\text{-component})$ as a partition of $V \in G$ such that source $s \in S\text{-component}$ and sink $t \in T\text{-component}$. Let's also define a cut-set of C to be the set $(u, v) \in E \mid u \in S\text{-component}, v \in T\text{-component}$ such that if all edges in the cut-set of C are removed, the Max Flow from s to t is 0 (i.e., s and t are disconnected). The cost of an s-t cut C is defined by the sum of the capacities of the edges in the cut-set of C .

The by-product of computing Max Flow is Min Cut! After Max Flow algorithm stops, we run graph traversal (DFS/BFS) from source s again. All reachable vertices from source s using positive weighted edges in the residual graph belong to the S-component. All other unreachable vertices belong to the T-component. All edges connecting the S-component to the T-component belong to the cut-set of C . The Min Cut value is equal to the Max Flow value. This is the minimum over all possible s-t cuts values.

7.2.2 Matching with Flow

By modeling a bipartite graph, with some Vertices (that will choose a match) to be on the L graph and some Vertices (that will be chosen) on the R. Set the correct capacities for these edges and also for the edges that connects the sink and source. After this modeling and running the dinic max flow algorithm, one will generate a possible matching (if it is possible).

A special case of matching is the perfect matching, which includes all vertices from the bipartite graph L and R.

A maximum matching has the maximum cardinality. A perfect matching is a maximum matching. But the opposite is not necessarily true.

It's possible to access `dinic.edges`, which is a vector that contains all edges and also its respective attributes, like the *flow* passing through each edge. Remember to consider that negative flow exist for reverse edges.

7.3 Matching

7.4 Coloring

7.5 Undirected Graph

Bridges and Articulation Points are concepts for undirected graphs!

7.5.1 Bridges (Cut Edges)

Also called **isthmus** or **cut arc**.

A back-edge is never a bridge!

A **lowlink** for a vertex U is the closest vertex to the root reachable using only span edges and a *single* back-edge, starting in the subtree of U .

After constructing a DFS Tree, an edge (u, v) is a bridge \iff there is no back-edge from v (or a descendent of v) to u (or an ancestor of u)

To do this efficiently, it's used $tin[i]$ (entry time of node i) and $low[i]$ (minimum entry time considering all nodes that can be reached from node i).

In another words, a edge (u, v) is a bridge \iff the $low[v] \geq tin[u]$.

bridges.cpp

Description: Using the concepts of entry time (tin) and lowlink (low), an edge is a bridge if, and only if, $low[v] > tin[u]$
Time: $\mathcal{O}(V + E)$

87e0d3, 25 lines

```

vector<vll> g(MAX);
ll timer = 1;
ll tin[MAX], low[MAX];
vector<pll> bridges;

void dfs(ll u, ll p = -1) {
    tin[u] = low[u] = timer++;
    for(auto v : g[u]) if (v != p) {
        if (tin[v]) // v was visited ({u,v} is a back-edge)
            // considering a single back-edge:
            low[u] = min(low[u], tin[v]);
        else { // v wasn't visited ({u, v} is a span-edge)
            dfs(v, u);
            // after low[v] was computed by dfs(v, u):
            low[u] = min(low[u], low[v]);
            if (low[v] > tin[u])
                bridges.pb({u, v});
        }
    }
}

void findBridges(ll n) {
    for(ll i=1; i<=n; i++) if (!tin[i])
        dfs(i);
}

```

7.5.2 Bridge Tree

After merging *vertices* of a **2-edge connected component** into single vertices, and leaving only bridges, one can generate a Bridge Tree.

Every **2-edge connected component** has following properties:

- For each pair of vertices A, B inside the same component, there are at least 2 distinct paths from A to B (which may repeat vertices).

bridgeTree.cpp

Description: After finding bridges, set an component id for each vertice, then merge vertices that are in the same 2-edge connected component
Time: $\mathcal{O}(V + E)$

6d00bd, 47 lines

```
// g: u -> {v, edge id}
vector<vector<pll>> g(MAX);
vector<vll> gc(MAX);
ll timer = 1;
ll tin[MAX], low[MAX], comp[MAX];
bool isBridge[MAX];

void dfs(ll u, ll p = -1) {
    tin[u] = low[u] = timer++;
    for(auto [v, id] : g[u]) if (v != p) {
        if (tin[v])
            low[u] = min(low[u], tin[v]);
        else {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] > tin[u])
                isBridge[id] = 1;
        }
    }
}

void dfs2(ll u, ll c, ll p = -1) {
    comp[u] = c;
    for(auto [v, id] : g[u]) if (v != p) {
        if (isBridge[id]) continue;
        if (!comp[v]) dfs2(v, c, u);
    }
}

void bridgeTree(ll n) {
    // find bridges
    for(ll i=1; i<=n; i++) if (!tin[i])
        dfs(i);

    // find components
    for(ll i=1; i<=n; i++) if (!comp[i])
        dfs2(i, i);

    // condensate into a TREE (or TREES if disconnected)
    for(ll u=1; u<=n; u++) {
        for(auto [v, id] : g[u]) {
            if (comp[u] != comp[v]) {
                gc[comp[u]].pb(comp[v]);
            }
        }
    }
}
```

7.5.3 Articulation Points

One Vertice in a graph is considered a Articulation Points or Cut Vertice if its removal in the graph will generate more disconnected components

articulation.cpp

Description: if $low[v] \geq tin[u]$, u is an articulation points The root is a corner case

Time: $\mathcal{O}(V + E)$

8707a0, 29 lines

```
vector<vll> g(MAX);
ll timer = 1;
ll low[MAX], tin[MAX], isAP[MAX];
// when vertex i is removed from graph
// isAP[i] is the quantity of new disjoint components created
```

```
// isAP[i] >= 1 {i is a Articulation Point}
void dfs(ll u, ll p = -1) {
    low[u] = tin[u] = timer++;

    for(auto v : g[u]) if (v != p) {
        if (tin[v]) // visited
            low[u] = min(low[u], tin[v]);
        else { // not visited
            dfs(v, u);
            low[u] = min(low[u], low[v]);

            if (low[v] >= tin[u])
                isAP[u]++;
        }
    }

    // corner case: root
    if (p == -1 and isAP[u]) isAP[u]--;
}

void findAP(ll n) {
    for(ll i=1; i<=n; i++) if (!tin[i])
        dfs(i);
}
```

7.5.4 Block Cut Tree

After merging *edges* of a **2-vertex connected component** into single vertices, one can obtain a block cut tree.

2-vertex connected components are also called as biconnected component

Every bridge by itself is a biconnected component

Each edge in the block-cut tree connects exactly an Articulation Point and a biconnected component (bipartite graph)

Each biconnected component has the following properties:

- For each pair of edges, there is a cycle that contains both edges
- For each pair of vertices A, B inside the same connected component, there are at least 2 distinct paths from A to B (which do not repeat vertices).

blockCutTree.cpp

Description: After Merging 2-Vertex Connected Components, one can generate a block cut tree

Time: $\mathcal{O}(V + E)$

f752d5, 100 lines

```
// Block-Cut Tree (bruno monteiro)
//
// Cria a block-cut tree, uma arvore com os blocos
// e os pontos de articulacao
// Blocos sao as componentes 2-vertice-conexas maximais
// Uma 2-coloracao da arvore eh tal que uma cor sao
// os componentes, e a outra cor sao os pontos de articulacao
//
// Funciona para grafo nao conexo
//
// isAP[i] responde o numero de novas componentes conexas
// criadas apos a remocao de i do grafo g
// Se isAP[i] >= 1, i eh ponto de articulacao
//
// Para todo i < blocks.size()
```

```
// blocks[i] eh uma componente 2-vertice-conexa maximal
// blockEdges[i] sao as arestas do bloco i
//
// tree eh a arvore block-cut-tree
// tree[i] eh um vertice da arvore que corresponde ao bloco i
//
// comp[i] responde a qual vertice da arvore vertice i pertence
//
// Arvore tem no maximo 2n vertices
//
// O(n+m)

// 0-idx graph!!!
vector<vll> g(MAX), tree, blocks; // 2-vertex-connected-COMPONENTS
vector<vector<pll>> blockEdges;
stack<ll> st; // st for vertices,
stack<pll> st2; // st2 for edges
vector<ll> low, tin, comp, isAP;
ll timer = 1;

void dfs(ll u, ll p = -1) {
    low[u] = tin[u] = timer++;

    st.push(u);

    // add only back-edges to stack
    if (p != -1) st2.push({u, p});
    for(auto v : g[u]) if (v != p) {
        if (tin[v] != -1) // visited
            st2.push({u, v});
    }

    for(auto v : g[u]) if (v != p) {
        if (tin[v] != -1) // visited
            low[u] = min(low[u], tin[v]);
        else { // not visited
            dfs(v, u);
            low[u] = min(low[u], low[v]);

            if (low[v] >= tin[u]) {
                isAP[u] += 1;

                blocks.pb(vll(1, u));
                while(blocks.back().back() != v)
                    blocks.back().pb(st.top()), st.pop();

                blockEdges.pb(vector<pll>(1, st2.top()), st2.pop());
                while(blockEdges.back().back() != pair<ll, ll>(v, u))
                    blockEdges.back().pb(st2.top()), st2.pop();
            }
        }
    }

    // corner case: root
    if (p == -1 and isAP[u]) isAP[u]--;
}
```

```
void blockCutTree(ll n) {

    // initialize vectors and reset
    tree.clear(), blocks.clear(), blockEdges.clear();
    st = stack<ll>(), st2 = stack<pll>();
    tin.assign(n, -1);
    low.assign(n, 0), comp.assign(n, 0), isAP.assign(n, 0);
    timer = 1;
```



```
// find Articulation Points
for(ll i=0; i<n; i++) if (tin[i] == -1)
    dfs(i);

// set component id for APs
tree.assign(blocks.size(), vll());
for(ll i=0; i<n; i++) if (isAP[i])
    comp[i] = tree.size(), tree.pb(vll());

// set component id for non-APs and construct tree
for(ll u=0; u<(ll)blocks.size(); u++) {
    for(auto v : blocks[u]) {
        if (!isAP[v])
            comp[v] = u;
        else
            tree[u].pb(comp[v]), tree[comp[v]].pb(u);
    }
}
```

7.5.5 Minimum Spanning Tree

A minimum spanning tree (MST) or minimum weight spanning tree is a subset of the edges of a connected, edge-weighted undirected graph that connects all the vertices together, without any cycles and with the minimum possible total edge weight. That is, it is a spanning tree whose sum of edge weights is as small as possible.

kruskal.cpp

Description: Sort all edges in crescent order by weight, include all edges which joins two disconnected trees. In case of tie, choose whichever. Dont include edges that will join a already connected part of the tree.
Time: $\mathcal{O}(E \log E \alpha)$

```
// use DSU struct
struct DSU{};

set<array<ll, 3>> edges;

int32_t main(){ sws;
    ll n, m; cin >> n >> m;
    DSU dsu(n+1);
    for(ll i=0; i<m; i++) {
        ll u, v, w; cin >> u >> v >> w;
        edges.insert({w, u, v});
    }
    ll minCost = 0;
    for(auto [w, u, v] : edges) {
        if (dsu.find(u) != dsu.find(v)) {
            dsu.join(u, v);
            minCost += w;
        }
    }
    cout << minCost << endl;
}
```

7.6 Directed Graph

7.6.1 Topological Sort

Sort a directed graph with no cycles (DAG) in an order which each source of an edge is visited before the sink of this edge.

Cannot have cycles, because it would create a contradiction of which vertices whould come before.

It can be done with a DFS, appending in the reverse order of transversal. Also a stack can be used to reverse order

toposort.cpp

Description: Using DFS pos order transversal and inverting the order, one can obtain the topological order
Time: $\mathcal{O}(V + E)$

```
vector<vll> g(MAX, vll());
vector<bool> vis;
vll topological;

void dfs(ll u) {
    vis[u] = 1;
    for(auto v : g[u]) if (!vis[v]) dfs(v);
    topological.pb(u);
}

// 1-indexed
void topological_sort(ll n) {
    vis.assign(n+1, 0);
    topological.clear();
    for(ll i=1; i<=n; i++) if (!vis[i]) dfs(i);
    reverse(topological.begin(), topological.end());
}
```

7.6.2 Kosaraju

A Strongly Connected Component is a maximal subgraph in which every vertex is reachable from any vertex inside this same subgraph.

A important *property* is that the inverted graph or transposed graph has the same SCCs as the original graph.

kosaraju.cpp

Description: By using the fact that the inverted graph has the same SCCs, just do a DFS twice to find all SCCs. A condensated graph can be created if wished. The condensated graph is a DAG!!
Time: $\mathcal{O}(V + E)$

```
struct Kosaraju {
    ll n;
    vector<vll> g, gi, gc;
    vector<bool> vis;
    vector<ll> comp;
    stack<ll, vll> st;

    void dfs(ll u) { // g
        vis[u] = 1;
        for(auto v : g[u]) if (!vis[v]) dfs(v);
        st.push(u);
    }

    void dfs2(ll u, ll c) { // gi
        comp[u] = c;
        for(auto v : gi[u]) if (comp[v] == -1) dfs2(v, c);
    }

    Kosaraju(vector<vll> &g_)
        : g(g_), n(g_.size()-1) { // 1-idx

        gi.assign(n+1, vll());
        for(ll i=1; i<=n; i++) {
            for(auto j : g[i])
                gi[j].pb(i);
        }
    }
}
```

```
gc.assign(n+1, vll());
vis.assign(n+1, 0);
comp.assign(n+1, -1);
st = stack<ll, vll>();

for(ll i=1; i<=n; i++) if (!vis[i]) dfs(i);

while(!st.empty()) {
    auto u = st.top(); st.pop();
    if (comp[u] == -1) dfs2(u, u);
}

for(ll u=1; u<=n; u++)
    for(auto v : g[u])
        if (comp[u] != comp[v])
            gc[comp[u]].pb(comp[v]);
}
```

7.6.3 2-SAT

SAT (Boolean satisfiability problem) is NP-Complete.

2-SAT is a restriction of the SAT problem, in 2-SAT every clause has exactly two variables: $(X_1 \vee X_2) \wedge (X_2 \vee X_3)$

Every restriction or implication are represented in the graph as directed edges.

The algorithm uses kosaraju to check if any $(X$ and $\neg X)$ are in the same Strongly Connected Component (which implies that the problem is impossible).

If it doesn't, there is at least one solution, which can be generated using the topological sort of the same kosaraju (opting for the variables that appers latter in the sorted order)

2sat.cpp

Description: Kosaraju to find if there are SCCs. If there are not cycles, use toposort to choose states
Time: $\mathcal{O}(V + E)$

```
// 0-idx graph !!!!
struct TwoSat {
    ll N; // needs to be the twice of the number of variables
    // node with idx 2x => variable x
    // node with idx 2x+1 => variable !x

    vector<vll> g, gi;
    // g = graph; gi = transposed graph (all edges are inverted)

    TwoSat(ll n) { // number of variables (add +1 faor 1-idx)
        N = 2*n;
        g.assign(N, vll());
        gi.assign(N, vll());
    }

    ll idx; // component idx
    vector<ll> comp, order; // topological order (reversed)
    vector<bool> vis, chosen;
    // chosen[x] == 0 -> x was assigned
    // chosen[x] == 1 -> !x was assigned

    // dfs and dfs2 are part of kosaraju algorithm
    void dfs(ll u) {
        vis[u] = 1;
    }
}
```

```

    for (ll v : g[u]) if (!vis[v]) dfs(v);
    order.pb(u);
}

void dfs2(ll u, ll c) {
    comp[u] = c;
    for (ll v : gi[u]) if (comp[v] == -1) dfs2(v, c);
}

bool solve() {
    vis.assign(N, 0);
    order = vector<ll>();
    for (ll i = 0; i < N; i++) if (!vis[i]) dfs(i);

    comp.assign(N, -1); // comp = 0 can exist
    idx = 1;
    for (ll i=(ll)order.size()-1; i>=0; i--) {
        ll u = order[i];
        if (comp[u] == -1) dfs2(u, idx++);
    }

    chosen.assign(N/2, 0);
    for (ll i = 0; i < N; i += 2) {
        // x and !x in the same component => contradiction
        if (comp[i] == comp[i+1]) return false;
        chosen[i/2] = comp[i] < comp[i+1]; // choose latter
        node
    }
    return true;
}

// a (with flagA) implies => b (with flagB)
void add(ll a, bool fa, ll b, bool fb) {
    // {fa == 0} => a
    // {fa == 1} => !a
    a = 2*a + fa;
    b = 2*b + fb;
    g[a].pb(b);
    gi[b].pb(a);
}

// force a state for a certain variable (must be true)
void force(ll a, bool fa) {
    add(a, fa^1, a, fa);
}

// xor operation: one must exist, and only one can exist
void exclusive(ll a, bool fa, ll b, bool fb) {
    add(a, fa^0, b, fb^1);
    add(a, fa^1, b, fb^0);
    add(b, fb^0, a, fa^1);
    add(b, fb^1, a, fa^0);
}

// nand operation: no more than one can exist
void nand(ll a, bool fa, ll b, bool fb) {
    add(a, fa^0, b, fb^1);
    add(b, fb^0, a, fa^1);
}
};

```

7.7 Trees

lca.cpp

Description: Solves LCA for trees

Time: $\mathcal{O}(N \log(N))$ to build, $\mathcal{O}(\log(N))$ per query

7afcia, 54 lines

```

struct BinaryLifting {
    ll n, logN = 20; // ~1e6
    vector<vll> g;

```

```

    vector<ll> depth;
    vector<vll> up;

    BinaryLifting(vector<vll> &g_)
        : g(g_), n(g_.size() + 1) { // 1-idx
        depth.assign(n, 0);

        while((1 << logN) < n) logN++;
        up.assign(n, vll(logN, 0));
        build();
    }

    void build(ll u = 1, ll p = -1) {
        for(ll i=1; i<logN; i++) {
            up[u][i] = up[ up[u][i-1] ][i-1];
        }

        for(auto v : g[u]) if (v != p) {
            up[v][0] = u;
            depth[v] = depth[u] + 1;
            build(v, u);
        }
    }

    ll go(ll u, ll dist) { // O(log(n))
        for(ll i=logN-1; i>=0; i--) { // bigger jumps first
            if (dist & (1LL << i)) {
                u = up[u][i];
            }
        }
        return u;
    }

    ll lca(ll a, ll b) { // O(log(n))
        if (depth[a] < depth[b]) swap(a, b);
        a = go(a, depth[a] - depth[b]);
        if (a == b) return a;

        for(ll i=logN-1; i>=0; i--) {
            if (up[a][i] != up[b][i]) {
                a = up[a][i];
                b = up[b][i];
            }
        }
        return up[a][0];
    }

    ll lca(ll a, ll b, ll root) { // lca(a, b) when tree is
        rooted at 'root'
        return lca(a, b)^lca(b, root)^lca(a, root); //magic
    }
};

```

queryTree.cpp

Description: Binary Lifting for min, max weight present in a simple path

Time: $\mathcal{O}(N \log(N))$ to build; $\mathcal{O}(\log(N))$ per query

75ba37, 67 lines

```

struct BinaryLifting {
    ll n, logN = 20; // ~1e6
    vector<vpll> g;
    vector<ll> depth;
    vector<vll> up, mx, mn;

    BinaryLifting(vector<vpll> &g_)
        : g(g_), n(g_.size() + 1) { // 1-idx
        depth.assign(n, 0);

        while((1 << logN) < n) logN++;
        up.assign(n, vll(logN, 0));

```

```

        mx.assign(n, vll(logN, -INF));
        mn.assign(n, vll(logN, INF));
        build();
    }

    void build(ll u = 1, ll p = -1) {

        for(ll i=1; i<logN; i++) {
            mx[u][i] = max(mx[u][i-1], mx[ up[u][i-1] ][i-1]);
            mn[u][i] = min(mn[u][i-1], mn[ up[u][i-1] ][i-1]);
            up[u][i] = up[ up[u][i-1] ][i-1];
        }

        for(auto [v, w] : g[u]) if (v != p) {
            mx[v][0] = mn[v][0] = w;
            up[v][0] = u;
            depth[v] = depth[u] + 1;
            build(v, u);
        }
    }

    array<ll, 3> go(ll u, ll dist) { // O(log(n))
        ll mxval = -INF, mnval = INF;
        for(ll i=logN-1; i>=0; i--) { // bigger jumps first
            if (dist & (1LL << i)) {
                mxval = max(mxval, mx[u][i]);
                mnval = min(mnval, mn[u][i]);
                u = up[u][i];
            }
        }
        return {u, mxval, mnval};
    }

    array<ll, 3> query(ll u, ll v) { // O(log(n))
        if (depth[u] < depth[v]) swap(u, v);

        auto [a, mxval, mnval] = go(u, depth[u] - depth[v]);
        ll b = v;

        if (a == b) return {a, mxval, mnval};

        for(ll i=logN-1; i>=0; i--) {
            if (up[a][i] != up[b][i]) {
                mxval = max({mxval, mx[a][i], mx[b][i]});
                mnval = min({mnval, mn[a][i], mn[b][i]});
                a = up[a][i];
                b = up[b][i];
            }
        }

        mxval = max({mxval, mx[a][0], mx[b][0]});
        mnval = min({mnval, mn[a][0], mn[b][0]});
        return {up[a][0], mxval, mnval};
    }
};

```

7.8 Math

Geometry (8)

Strings (9)

9.1 Hashing

Hashing consists in generating a Polynomial for the string, therefore, assigning each distinct string to a specific numeric value. In practice, there will always be some collisions:

Probability of colision: $= \frac{n^2}{2m}$

n = Comparissons, m = mod size

when using multiple mods, they multiply: $m = m1 * m2$

hashing.cpp
Description: Create a numerical value for a string by using polynomial hashing
Time: $\mathcal{O}(n)$ to build, $\mathcal{O}(1)$ per query

```
c3a650, 43 lines
// s[0]*P^n + s[1]*P^(n-1) + ... + s[n]*P^0
// 0-idx
struct Hashing {
    ll n, mod;
    string s;
    vector<ll> p, h; // p = P^i, h = accumulated hash sum

    const ll P = 31; // can be 53

    Hashing(string &s_, ll m)
        : n(s_.size()), s(s_), mod(m), p(n), h(n) {

        for(ll i=0; i<n; i++)
            p[i] = (i ? P*p[i-1] : 1) % mod;

        for(ll i=0; i<n; i++)
            h[i] = (s[i] + P*(i ? h[i-1] : 0)) % mod;
    }

    ll query(ll l, ll r) { // [l, r] inclusive (0-idx)
        ll hash = h[r] - (l ? (p[r-l+1]*h[l-1]) % mod : 0);
        return hash < 0 ? hash + mod : hash;
    }
};

// for codeforces:
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());

int32_t main() { sws;
    vector<ll> mods = {
        1000000009,10000000021,10000000033,
        10000000087,10000000093,10000000097,
        1000000103,1000000123,1000000181,
        1000000207,1000000223,1000000241,
        1000000271,1000000289,1000000297
    };

    shuffle(mods.begin(), mods.end(), rng);

    string s; cin >> s;

    Hashing hash(s, mods[0]);
}
```

9.2 Z-Function

Suppose we are given a string s of length n . The Z-function for this string is an array of length n where the i -th element is equal to the greatest number of characters starting from the position i that coincide with the first characters of s (the prefix of s)

The first element of the Z-function, $z[0]$, is generally not well defined. This implementation assumes it as $z[0] = 0$. But it can also be interpreted as $z[0] = n$ (all characters coincide).

Can be used to solve the following simples problems:

hashing zfunction kmp manacher

- Find all occurrences of a pattern p in another string s . ($p + '$' + s$) ($z[i] == p.size()$)
- Find all borders. A border of a string is a prefix that is also a suffix of the string but not the whole string. For example, the borders of $abcbabcbab$ are ab and $abcb$. ($z[8] = 2, z[5] = 5$) ($z[i] = n-i$)
- Find all period lengths of a string. A period of a string is a prefix that can be used to generate the whole string by repeating the prefix. The last repetition may be partial. For example, the periods of $abcbca$ are **abc**, **abcbabc** and **abcbabca**.

It works because $(z[i] + i \neq n)$ is the condition when the common characters of $z[i]$ in addition to the elements already passed, exceeds or is equal to the end of the string. For example:

$abaabababab\ z[8] = 2$

abaababab is the period; the remaining ($z[i]$ characters) are a prefix of the period; and when all these characters are combined, it can form the string (which has n characters).

zfunction.cpp
Description: For each substring starting at position i , compute the maximum match with the original prefix. $z[0] = 0$
Time: $\mathcal{O}(n)$

```
14b37c, 12 lines
vector<ll> z_function(string &s) { // O(n)
    ll n = (ll) s.length();
    vector<ll> z(n);
    for (ll i=1, l=0, r=0; i<n; i++) {
        if (i <= r) z[i] = min(r - i + 1, z[i - l]);

        while (i + z[i] < n and s[z[i]] == s[i + z[i]]) z[i]++;

        if (r < i + z[i] - 1) l = i, r = i + z[i] - 1;
    }
    return z;
}
```

9.3 KMP

KMP stands for Knuth-Morris-Pratt and computes the prefix function.

You are given a string s of length n . The prefix function for this string is defined as an array π of length n , where $\pi[i]$ is the length of the longest proper prefix of the substring $s[0 \dots i]$ which is also a suffix of this substring. A proper prefix of a string is a prefix that is not equal to the string itself. By definition, $\pi[0] = 0$.

For example, prefix function of string $"abcabcd"$ is $[0, 0, 0, 1, 2, 3, 0]$, and prefix function of string $"aabaaab"$ is $[0, 1, 0, 1, 2, 2, 3]$.

kmp.cpp
Description: Computes the prefix function
Time: $\mathcal{O}(n)$

```
48408b, 13 lines
vector<ll> kmp(string &s) { // O(n)
    ll n = (ll) s.length();
    vector<ll> pi(n);
    for (ll i = 1; i < n; i++) {
        ll j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}
```

9.4 Manacher

Manacher's Algorithm is used to find all palindromes in a string.

For each substring, centered at i , find the longest palindrome that can be formed.

Works best for odd size string, so we convert all string to odd ones by adding and extra characters between the original ones

Therefore, the value stored in the vector cnt is actually $palindrome-len + 1$.

manacher.cpp
Description: Covert String to odd length to use manacher, which computes all the maximum lengths of all palindromes in the given string
Time: $\mathcal{O}(2n)$

```
0c2a2b, 46 lines
struct Manacher {
    string s, t;
    vector<ll> cnt;

    // t is the transformed string of s, with odd size
    Manacher(string &s_) : s(s_) {
        t = "#";
        for(auto c : s) {
            t += c, t += "#";
        }
        count();
    }

    // perform manacher on the odd string
    // cnt will give all the palindromes centered in i
    // for the odd string t
    void count() {
        ll n = t.size();
        string aux = "$" + t + "^";
        vector<ll> p(n + 2);
        ll l = 1, r = 1;
        for(ll i = 1; i <= n; i++) {
            p[i] = max(0LL, min(r - i, p[l + (r - i)]));
            while(aux[i - p[i]] == aux[i + p[i]]) {
                p[i]++;
            }
            if(i + p[i] > r) {
                l = i - p[i], r = i + p[i];
            }
        }
    }
}
```

```
        cnt = vector<ll>(p.begin() + 1, p.end() - 1);
    }

    // compute a longest palindrome present in s
    string getLongest() {
        ll len = 0, pos = 0;
        for(ll i=0; i<(ll)t.size(); i++) {
            ll sz = cnt[i]-1;
            if (sz > len) {
                len = sz;
                pos = i;
            }
        }
        return s.substr(pos/2 - len/2, len);
    }
};
```

9.5 Booth

An efficient algorithm which uses a modified version of KMP to compute the least amount of rotation needed to reach the **lexicographically minimal string rotation**.

A rotation of a string can be generated by moving characters one after another from beginning to end. For example, the rotations of *acab* are *acab*, *caba*, *abac*, and *baca*.

booth.cpp

Description: Use a modified version of KMP to find the lexicographically minimal string rotation

Time: $\mathcal{O}(n)$

64184b, 30 lines

```
// Booth Algorithm
ll least_rotation(string &s) { // O(n)
    ll n = s.length();
    vector<ll> f(2*n, -1);
    ll k = 0;
    for(ll j=1; j<2*n; j++) {
        ll i = f[j-k-1];
        while(i != -1 and s[j % n] != s[(k+i+1) % n] ) {
            if (s[j % n] < s[(k+i+1) % n])
                k = j - i - 1;
            i = f[i];
        }
        if (i == -1 and s[j % n] != s[(k+i+1) % n] ) {
            if (s[j % n] < s[(k+i+1) % n])
                k = j;
            f[j - k] = -1;
        }
        else
            f[j - k] = i + 1;
    }
    return k;
}

int32_t main(){ sws;
    string s; cin >> s;
    ll n = s.length();
    ll ans_idx = least_rotation(s);
    string tmp = s + s;
    cout << tmp.substr(ans_idx, n) << endl;
}
```

Miscellaneous (10)

Techniques (A)

techniques.txt	159 lines
Recursion	
Divide and conquer	
Finding interesting points in N log N	
Algorithm analysis	
Master theorem	
Amortized time complexity	
Greedy algorithm	
Scheduling	
Max contiguous subvector sum	
Invariants	
Huffman encoding	
Graph theory	
Dynamic graphs (extra book-keeping)	
Breadth first search	
Depth first search	
* Normal trees / DFS trees	
Dijkstra's algorithm	
MST: Prim's algorithm	
Bellman-Ford	
Konig's theorem and vertex cover	
Min-cost max flow	
Lovasz toggle	
Matrix tree theorem	
Maximal matching, general graphs	
Hopcroft-Karp	
Hall's marriage theorem	
Graphical sequences	
Floyd-Warshall	
Euler cycles	
Flow networks	
* Augmenting paths	
* Edmonds-Karp	
Bipartite matching	
Min. path cover	
Topological sorting	
Strongly connected components	
2-SAT	
Cut vertices, cut-edges and biconnected components	
Edge coloring	
* Trees	
Vertex coloring	
* Bipartite graphs (=> trees)	
* 3^n (special case of set cover)	
Diameter and centroid	
K'th shortest path	
Shortest cycle	
Dynamic programming	
Knapsack	
Coin change	
Longest common subsequence	
Longest increasing subsequence	
Number of paths in a dag	
Shortest path in a dag	
Dynprog over intervals	
Dynprog over subsets	
Dynprog over probabilities	
Dynprog over trees	
3^n set cover	
Divide and conquer	
Knuth optimization	
Convex hull optimizations	
RMQ (sparse table a.k.a 2^k-jumps)	
Bitonic cycle	
Log partitioning (loop over most restricted)	
Combinatorics	

Computation of binomial coefficients	
Pigeon-hole principle	
Inclusion/exclusion	
Catalan number	
Pick's theorem	
Number theory	
Integer parts	
Divisibility	
Euclidean algorithm	
Modular arithmetic	
* Modular multiplication	
* Modular inverses	
* Modular exponentiation by squaring	
Chinese remainder theorem	
Fermat's little theorem	
Euler's theorem	
Phi function	
Frobenius number	
Quadratic reciprocity	
Pollard-Rho	
Miller-Rabin	
Hensel lifting	
Vieta root jumping	
Game theory	
Combinatorial games	
Game trees	
Mini-max	
Nim	
Games on graphs	
Games on graphs with loops	
Grundy numbers	
Bipartite games without repetition	
General games without repetition	
Alpha-beta pruning	
Probability theory	
Optimization	
Binary search	
Ternary search	
Unimodality and convex functions	
Binary search on derivative	
Numerical methods	
Numeric integration	
Newton's method	
Root-finding with binary/ternary search	
Golden section search	
Matrices	
Gaussian elimination	
Exponentiation by squaring	
Sorting	
Radix sort	
Geometry	
Coordinates and vectors	
* Cross product	
* Scalar product	
Convex hull	
Polygon cut	
Closest pair	
Coordinate-compression	
Quadtrees	
KD-trees	
All segment-segment intersection	
Sweeping	
Discretization (convert to events and sweep)	
Angle sweeping	
Line sweeping	
Discrete second derivatives	
Strings	
Longest common substring	
Palindrome subsequences	

Knuth-Morris-Pratt	
Tries	
Rolling polynomial hashes	
Suffix array	
Suffix tree	
Aho-Corasick	
Manacher's algorithm	
Letter position lists	
Combinatorial search	
Meet in the middle	
Brute-force with pruning	
Best-first (A*)	
Bidirectional search	
Iterative deepening DFS / A*	
Data structures	
LCA (2^k-jumps in trees in general)	
Pull/push-technique on trees	
Heavy-light decomposition	
Centroid decomposition	
Lazy propagation	
Self-balancing trees	
Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)	
Monotone queues / monotone stacks / sliding queues	
Sliding queue using 2 stacks	
Persistent segment tree	