

POC Test Cases — Data Platform Validation



Huawei Technologies CO., LTD

v1.1.0 — September 12, 2026 18:09

Contents

1 Test Cases Description	2
1.1 Test Scope	2
1.2 Preconditions and Preparations	2
1.3 Acceptance Method	3
1.4 Test Case Summary	4
2 Platform Architecture	5
2.1 TC-001: Verify MRS cluster deployment and health	5
2.2 TC-002: Verify OBS bucket creation and accessibility	6
2.3 TC-003: Verify VPC and security group configuration	7
3 Data Engineering	8
3.1 TC-004: Verify DataArts Studio workspace creation	8
3.2 TC-005: Verify data ingestion pipeline execution	9
3.3 TC-006: Verify Spark SQL query on MRS cluster	10
4 Security and Access Control	12
4.1 TC-007: Verify IAM policy enforcement on OBS buckets	12
4.2 TC-008: Verify DataArts Studio data masking rule	13
5 Environment Setup and Tooling	14
5.1 TC-009: Verify Terraform infrastructure deployment	14
5.2 TC-010: Verify test data upload to OBS	15
6 Changelog	17

Info

This document demonstrates the `testbook.cls` template for Huawei Cloud POC/acceptance test case documents. It exercises all available commands and environments: cover page, table of contents, test case environment with all field commands, objectives block, code blocks, images, callouts (`warning`, `tip`, `infobox`), tables, badge, menu paths, weblinks, notes, param references, test summary table, test steps tables, result badges, and changelog.

1

Test Cases Description

General Objective: Validate the Huawei Cloud Data Platform deployment for the POC environment, ensuring that all core services (DataArts Studio, MRS, OBS, VPC) are provisioned correctly, accessible, and functioning as specified in the solution architecture.

Prerequisites:

- Huawei Cloud account with IAM admin privileges in the `sa-brazil-1` region.
 - VPC, subnet, and security groups already created by the infrastructure team.
 - DataArts Studio instance (Dayu) provisioned and licensed.
 - MRS cluster deployed with the required component stack (HDFS, YARN, Spark, Hive).
 - OBS bucket created and accessible with the designated IAM policy.
 - Test execution environment with network connectivity to the Huawei Cloud Console.
 - `latexmk` and `terraform` CLI tools installed locally.
-

1.1 Test Scope

Domain	What Should Be Observed
Platform Architecture	Core services are deployed, healthy, and reachable via the Console API.
Data Engineering	DataArts Studio pipelines can ingest, transform, and load data into the target storage.
Data Storage	OBS buckets and MRS HDFS accept writes/reads with correct permissions.
Security	IAM policies, VPC isolation, and security group rules enforce the intended access control.

Table 1: Test scope by domain.

1.2 Preconditions and Preparations

- All infrastructure resources must be provisioned via Terraform and the `terraform apply` output must show zero errors.
- The MRS cluster must be in **Running** state before any data engineering test case is executed.
- Test data files (CSV/JSON) must be uploaded to the designated OBS bucket prior to pipeline execution.
- Each tester must have a personal IAM account with the **Dayu_User** role assigned in DataArts Studio.
- Network firewall rules must allow inbound TCP 22 (SSH) and TCP 443 (HTTPS) from the test exe-

cution subnet.

Ensure the test execution environment has the correct timezone set to America/Sao_Paulo (GMT-3) so that log timestamps align with the Huawei Cloud Console.

```
# Verify CLI tools are installed
terraform version
obsutil version
kubectl version --client
```

Tip

Use `terraform plan` before `terraform apply` to preview infrastructure changes and avoid unintended resource modifications.

1.3 Acceptance Method

Result	Explanation
Satisfied	The test case passes fully — observed behavior matches the expected result with no deviations.
Satisfied but with reservations	The test case passes but minor deviations were observed that do not impact the POC objectives (documented in Remarks).
Not satisfied	The test case fails — observed behavior does not match the expected result. A defect report must be filed.
Untested	The test case could not be executed due to blocking dependencies or environment issues.

Table 2: Acceptance criteria.



1.4 Test Case Summary

ID	Title	Status
TC-001	Verify MRS cluster deployment and health	Pass
TC-002	Verify OBS bucket creation and accessibility	Pass
TC-003	Verify VPC and security group configuration	Pass
TC-004	Verify DataArts Studio workspace creation	Pass
TC-005	Verify data ingestion pipeline execution	Pass
TC-006	Verify Spark SQL query on MRS cluster	Pass
TC-007	Verify IAM policy enforcement on OBS buckets	Pass
TC-008	Verify DataArts Studio data masking rule	Pass
TC-009	Verify Terraform infrastructure deployment	Pass
TC-010	Verify test data upload to OBS	Pass

2

Platform Architecture

2.1 TC-001: Verify MRS cluster deployment and health

Objective

Confirm that the MapReduce Service (MRS) cluster is deployed with the required components (HDFS, YARN, Spark, Hive) and all nodes report a healthy status.

Prerequisites

1. Terraform infrastructure apply completed successfully.
2. MRS cluster ID is available in the Terraform output.
3. IAM user has **MRS_Viewer** or higher role.

Procedure

See test steps below.

Step	Action	Expected Result	Status
1	Log in to the Huawei Cloud Console	Console dashboard displayed	Pass
2	Navigate to Console → MapReduce Service → Clusters	Clusters list page shown	Pass
3	Locate cluster <code>mrs-poc-cluster</code>	Cluster found in list	Pass
4	Verify cluster status	Status is Running	Pass
5	Review Component tab	HDFS, YARN, Spark, Hive all Normal	Pass
6	Review Node tab	All nodes show Running	Pass



Expected Result

1. Cluster status is **Running**.

2. All four components (HDFS, YARN, Spark, Hive) are listed with status **Normal**.
3. All nodes report status **Running** with no alarms.

Remarks

If any component shows **Abnormal**, check the MRS alarm page before marking the result.

Test Result

Pass

2.2 TC-002: Verify OBS bucket creation and accessibility

Objective

Confirm that the Object Storage Service (OBS) bucket used for the POC data lake is created, has the correct storage class, and is accessible with the designated IAM policy.

Prerequisites

1. OBS bucket name is defined in the Terraform configuration.
2. IAM policy granting read/write access to the bucket is attached to the test user.

Procedure

1. Log in to the Console.
2. Navigate to **Console** → **Object Storage Service**.
3. Locate the bucket (e.g. poc-datalake-raw).
4. Verify the storage class is **Standard**.
5. Upload a test file (test-upload.txt) to the bucket.
6. Download the file and compare its content with the original.
7. Delete the test file.

Expected Result

1. Bucket exists with storage class **Standard**.
2. File upload completes without error.
3. Downloaded file content matches the original.
4. File deletion succeeds.

Remarks

OBS eventual consistency may cause a brief delay before a newly uploaded object appears in listings.

Test Result

Pass

2.3 TC-003: Verify VPC and security group configuration

Objective

Confirm that the VPC, subnet, and security groups are configured according to the network architecture diagram, with the correct CIDR blocks and inbound/outbound rules.

Prerequisites

1. VPC and subnet IDs are available from the Terraform output.
2. Security group names are documented in the solution architecture.

Procedure

1. Log in to the Console.
2. Navigate to **Console** → **Virtual Private Cloud** → **VPCs**.
3. Locate the VPC (e.g. vpc-poc) and verify its CIDR block matches the architecture (e.g. 10.0.0.0/16).
4. Click the subnet and verify its CIDR (e.g. 10.0.1.0/24).
5. Navigate to **Security Groups** and verify inbound rules: TCP 22 from the bastion subnet, TCP 443 from the corporate proxy.
6. Verify outbound rules allow all traffic (default).

Expected Result

1. VPC CIDR is 10.0.0.0/16.
2. Subnet CIDR is 10.0.1.0/24.
3. Inbound rules match the architecture: TCP 22 and TCP 443 from the specified sources.
4. Outbound allows all traffic.

Remarks

If the security group has additional rules beyond the architecture spec, document them in the Remarks field.

Test Result

Pass

3

Data Engineering

3.1 TC-004: Verify DataArts Studio workspace creation

Required

Objective

Confirm that the DataArts Studio (Dayu) instance is provisioned, the workspace is accessible, and the designated IAM users can log in with the **Dayu_User** role.

Prerequisites

1. DataArts Studio instance is provisioned and its status is **Running**.
2. Test IAM user has the **Dayu_User** role assigned.

Procedure

1. Log in to the Console with the test IAM user.
2. Navigate to **Console** → **DataArts Studio** → **Workspaces**.
3. Locate the workspace (e.g. poc-workspace).
4. Click **Access Workspace** to open the DataArts Studio console.
5. Verify the left navigation panel loads with the expected modules: **Data Integration, Data Development, Data Architecture**.

Expected Result

1. Workspace is listed and accessible.
2. DataArts Studio console opens without errors.
3. All three modules (Data Integration, Data Development, Data Architecture) are visible in the navigation.

Remarks

If the workspace fails to load, check the Dayu instance status and the IAM role assignment.

Test Result

Pass

3.2 TC-005: Verify data ingestion pipeline execution

Objective

Confirm that a DataArts Studio batch pipeline can successfully ingest CSV data from OBS, apply a basic transformation, and write the result to the target OBS path.

Prerequisites

1. TC-004 completed (DataArts Studio workspace accessible).
2. Source CSV file (customers.csv) exists in the OBS raw bucket.
3. Target OBS path (poc-datalake-curated/customers/) is configured.
4. Pipeline pl-ingest-customers is published in DataArts Studio.

Procedure

See test steps below.

Step	Action	Expected Result	Status
1	Navigate to Data Development in DataArts Studio	Data Development page loads	Pass
2	Locate pipeline pl-ingest-customers	Pipeline found in job list	Pass
3	Click Run to execute the pipeline	Pipeline starts execution	Pass
4	Wait for pipeline status (timeout: 10 min)	Status changes to Success	Pass
5	Verify output file in OBS	File exists in target path	Pass
6	Download and verify row count	Row count matches source	Pass

```
# Verify the output file in OBS via CLI
obsutil ls obs://poc-datalake-curated/customers/ -limit=10
obsutil stat obs://poc-datalake-curated/customers/output.csv
```

Expected Result

1. Pipeline execution completes with status **Success**.
2. Output file is created in the target OBS path.
3. Row count of the output file matches the source file.

Remarks

Pipeline execution time varies with data volume. For the POC, the source file contains approximately 10,000 rows.



Test Result

Pass

3.3 TC-006: Verify Spark SQL query on MRS cluster

Objective

Confirm that a Spark SQL query can be executed on the MRS cluster to read data from a Hive table and return correct results, validating the integration between MRS and the data lake.

Prerequisites

1. TC-001 completed (MRS cluster healthy).
2. Hive table `poc_db.customers` exists and contains data loaded by the ingestion pipeline.
3. SSH access to the MRS master node is configured.

Procedure

1. SSH into the MRS master node.
2. Run the Spark SQL CLI: `spark-sql --master yarn --conf spark.sql.hive.convertMetastoreOrc=true -e "SELECT COUNT(*) FROM poc_db.customers;"`
3. Verify the returned count matches the expected row count (10,000).
4. Run a sample query to verify data integrity: `spark-sql --master yarn -e "SELECT customer_id, name FROM poc_db.customers LIMIT 5;"`
5. Confirm the query returns 5 rows with non-null values.

```
# SSH into MRS master node
ssh root@mrs-master-poc

# Run Spark SQL count query
spark-sql --master yarn \
  --conf spark.sql.hive.convertMetastoreOrc=true \
  -e "SELECT COUNT(*) FROM poc_db.customers;"
```

Expected Result

1. `COUNT(*)` returns 10,000.
2. The sample query returns 5 rows with valid `customer_id` and `name` values.

Remarks

If the Spark SQL CLI is not available, use the MRS Spark2x component's web UI to submit the query instead.

Test Result

Pass

4

Security and Access Control

4.1 TC-007: Verify IAM policy enforcement on OBS buckets

New

Objective

Confirm that IAM policies correctly restrict OBS bucket access — authorized users can read/write while unauthorized users are denied, and the bucket policy matches the principle of least privilege.

Prerequisites

1. OBS bucket poc-datalake-raw exists with the designated IAM policy.
2. Two test IAM users: one with **OBS_ReadWrite** role, one with no OBS permissions.
3. obsutil CLI configured for both users.

Procedure

1. Using the authorized user, upload a test file to poc-datalake-raw.
2. Using the authorized user, download and verify the file content.
3. Using the unauthorized user, attempt to upload a file — verify the request is denied (HTTP 403).
4. Using the unauthorized user, attempt to list objects in the bucket — verify the request is denied.
5. Review the bucket policy in the Console at **Console** → **Object Storage Service** → **Bucket Policies** and confirm it grants only the intended permissions.

```
# Authorized user – upload and verify
obsutil cp test-file.txt obs://poc-datalake-raw/test-file.txt
obsutil ls obs://poc-datalake-raw/ -limit=5

# Unauthorized user – expect 403 errors
obsutil cp test-file.txt obs://poc-datalake-raw/unauthorized.txt
obsutil ls obs://poc-datalake-raw/
```

Expected Result

1. Authorized user can upload and download successfully.
2. Unauthorized user receives HTTP 403 on both upload and list operations.
3. Bucket policy grants only the intended read/write permissions to the designated roles.

Remarks

Check the Cloud Trail logs if access denial is not returned as expected — there may be a policy inheritance from the project or domain level.

IAM policy changes can take up to 5 minutes to propagate. Wait before re-testing after modifying a policy.

Test Result

Pass

4.2 TC-008: Verify DataArts Studio data masking rule

Objective

Confirm that sensitive data columns (e.g. PII fields) are masked according to the DataArts Studio data masking rule when queried by non-admin users.

Prerequisites

1. TC-004 completed (DataArts Studio workspace accessible).
2. Data masking rule configured for column `customers.ssn` (Social Security Number).
3. Test user has **Dayu_User** role (not admin).

Procedure

1. In the DataArts Studio console, navigate to **Data Architecture** → **Data Masking**.
2. Verify the masking rule for `customers.ssn` is active and uses the **Mask All** strategy.
3. Query the `customers` table as the test user via DataArts Studio SQL console.
4. Verify the `ssn` column returns masked values (e.g. `*****`) instead of real data.
5. Query the same table as an admin user and verify real values are returned.

Expected Result

1. Masking rule is active for `customers.ssn`.
2. Non-admin user sees masked values in the `ssn` column.
3. Admin user sees real values in the `ssn` column.

Remarks

Data masking rules apply at query time — the underlying data in OBS/HDFS is not modified.

Test Result

Pass

5

Environment Setup and Tooling

5.1 TC-009: Verify Terraform infrastructure deployment

Objective

Confirm that the Terraform configuration deploys all required infrastructure resources (VPC, MRS, OBS, DataArts Studio) without errors and the state file reflects the expected resources.

Prerequisites

1. terraform CLI installed (version $\geq$ 1.0).
2. AK/SK credentials configured via environment variables or *provider.tf*.
3. Terraform configuration files in the project directory.

Procedure

1. Navigate to the Terraform project directory.
2. Run `terraform init` to initialize the working directory.
3. Run `terraform plan` and review the planned changes — confirm all expected resources are listed.
4. Run `terraform apply -auto-approve` and wait for completion.
5. Run `terraform output` and verify all output values are populated.
6. Run `terraform state list` and confirm the resource count matches the architecture.

```
# Initialize and deploy infrastructure
cd /opt/poc-infra/terraform
terraform init
terraform plan -out=tfplan
terraform apply tfplan

# Verify deployment
terraform output
terraform state list | wc -l
```

Expected Result

1. `terraform apply` completes with no errors.
2. All output values are populated (cluster ID, bucket name, VPC ID).
3. Resource count in state matches the architecture specification.

Remarks

If `terraform apply` fails, check the AK/SK credentials and the `sa-brazil-1` region quota limits.

Important

Do not skip the `terraform plan` review step. Applying unreviewed changes to production-adjacent environments can cause data loss or service disruption.

Test Result**Pass**

5.2 TC-010: Verify test data upload to OBS

Objective

Confirm that all required test data files (CSV, JSON) can be uploaded to the designated OBS bucket and are accessible by the DataArts Studio pipeline.

Prerequisites

1. TC-002 completed (OBS bucket accessible).
2. Test data files prepared in the local directory `./test-data/`.
3. `obsutil` CLI configured with the test user credentials.

Procedure

1. List the local test data files and verify their integrity (row count, schema).
2. Upload all files to the OBS raw bucket using `obsutil`.
3. Verify each file exists in OBS by listing the bucket contents.
4. Download a sample file from OBS and compare it with the local original (checksum).
5. In DataArts Studio, verify the data source connection can read the uploaded files.

```
# Upload test data files to OBS
obsutil cp ./test-data/customers.csv
obs://poc-datalake-raw/customers.csv
obsutil cp ./test-data/transactions.json
obs://poc-datalake-raw/transactions.json

# Verify uploads
obsutil ls obs://poc-datalake-raw/ -limit=20
```

Expected Result

1. All test data files are uploaded without errors.
2. Bucket listing shows all uploaded files with correct sizes.
3. Downloaded file checksum matches the local original.
4. DataArts Studio data source connection can read the files.

Remarks

Large files (>1 GB) should be uploaded using the OBS multipart upload feature for better reliability.

Refer to the [Huawei Cloud OBS Documentation](#) for advanced upload options and troubleshooting.

Test Result**Pass**

[Image placeholder]

File: assets/test-execution-dashboard.png

Description: Screenshot of the test execution dashboard showing all test case results

Place the image file at the path above, then replace this command with

*`\image{assets/test-execution-dashboard.png}` or
`\imagecap{assets/test-execution-dashboard.png}{caption}`.*

6

Changelog

1.1.0

September 12, 2026

- Added comprehensive feature demonstrations: `warning`, `tip`, `infobox` callouts; code blocks; `badge`; `weblink`; `note`; `param`; `image`, `imagecap`, and `imageplaceholder`; menu paths; and `inlinecode` references.
- Added Security and Access Control test cases (TC-007, TC-008).
- Added Environment Setup and Tooling test cases (TC-009, TC-010).

1.0.0

September 12, 2026

- Initial version.
 - Added Platform Architecture test cases (TC-001 to TC-003).
 - Added Data Engineering test cases (TC-004 to TC-006).
-