

Building REST Services



DEVELOPMENTMENTOR

DEVELOPING PEOPLE WHO DEVELOP SOFTWARE



- Why REST?
- Exposing REST services using the ASP.NET WebAPI



- Systems built on SOA often use SOAP
 - defined standard
 - built in extensibility infrastructure
 - higher order protocols agreed
 - agreed metadata formats
 - supports arbitrary network protocols



- SOAP has issues
- Plumbing can be highly complex
 - e.g. WS-Security
- Service operations at single endpoint
 - scaling out problematic
 - sequence of multiple operations not defined
- “Runs on web” not “part of web”
 - all messages use POST
 - HTTP caching not supported
- Client needs special coding to remember place in series of message exchanges
 - nothing inherent in exchange tells client where they had got to




- Alternate way to define services
 - all operations identified by resource **URI** and **HTTP verb**
 - GET = read – must not change state of system
 - PUT = insert/update - idempotent
 - DELETE = delete - idempotent
 - POST = non-idempotent changes in state
- Many large scale systems built using REST approach
 - Amazon S3
 - Google Search API
 - Azure storage API

GET <http://www.acme.com/widgets/bypartno?partno=456>




- Resources identified by URIs
 - <http://www.google.com/search?hl=en&q=REST>
 - <http://news.bbc.co.uk/2/hi/africa/7322468.stm>
- GET is commonly cached on the client, proxy server or web server
- Link from one place to another not necessarily on the same machine
 - allows expensive operations to be dealt with by different servers/databases
 - allows simple horizontal partitioning of data

<http://www1.acme.com/customer/abbott48>



**Customer
DB A-M**

<http://www2.acme.com/customer/smith123>



**Customer
DB N-Z**



- No defined order for SOAP operations
 - InvalidOperationException
- REST response message defines the **next valid URIs** for message exchange
 - URIs may be **data dependent**

```
<product>
  <id>123</id>
  <desc>Infinite Improbability Drive</desc>
  <actions>
    <action name="techdetails"
      uri="http://www.heartofgold.com/product/123/techdetails"
      verb="GET" />
    <action name="purchase"
      uri="http://www.heartofgold.com/basket/add"
      verb="PUT" />
  </actions>
</product>
```



- URIs change during message exchange
 - next possible operations contained in response message
- Client can stop exchange and continue later
 - URI contains all contextual information
 - may not be possible in all circumstances
 - e.g. loan offer only valid for 48 hours



- REST is not bound to XML
 - URI may contain all data operation requires
 - XML and JSON common for sending complex data
- Response message can be any HTTP content type
 - XML
 - JSON
 - JPEG
 - MPEG
- Applications can define their own media type
 - Often specialized form of other formats

application/bookstore+xml



- No metadata standard
 - message “specifications” bespoke
- No standard for “actions”
 - format for next available operations bespoke
- Tool support challenging due to lack of metadata
- Wedded to HTTP
 - not formally but in practical terms
- Building a **good** REST API harder than first seems
 - very easy to end up with RPC like API rather than relying on URIs



- WebAPI ships as part of MVC4
 - Originally part of WCF
 - WCF still bootstraps non IIS hosting
- Specialized core components
 - Controller based on ApiController
 - Route registration based on HttpWebRoute



- Derive class from ApiController
- Methods map to verbs
 - Get
 - Post
 - Delete
 - Put
- Route maps to correct override

```
public class BooksController : ApiController{  
    public IEnumerable<Book> Get(){  
        //...  
    }  
    public Resource<Book> Get(string id){  
        // ...  
    }  
}
```

HTTP as the Application Protocol



- HTTP drives the message exchange
- Need to be able to tightly integrate with HTTP
 - HttpRequestMessage
 - HttpResponseMessage

```
public Resource<Book> Get(HttpRequestMessage request, string id)
{
    // use request details
}
```

```
public HttpResponseMessage Post(HttpRequestMessage request)
{
    Book book = request.Content.ReadAsAsync<Book>().Result;

    var response = new HttpResponseMessage(HttpStatusCode.Created);

    response.Headers.Location = new Uri(request.RequestUri.AbsoluteUri +
                                         "/" + book.ISBN);

    return response;
}
```



- HTTP uses status codes for error conditions
 - Can also send response data
- Raise error conditions by throwing `HttpResponseException`

```
Book book = AmazonLite.GetBookByISBN(id);  
  
if (book == null)  
{  
    var msg = new HttpResponseMessage(HttpStatusCode.NotFound);  
    throw new HttpResponseException(msg);  
}
```



- Different clients want data in different formats
 - Xml
 - Json
 - XHTML
- Clients states preferences with Accept HTTP header

```
Accept: application/xhtml+xml,application/xml
```

- WebAPI looks at Accept header and formats application supports and returns compatible format
 - Json is default
 - XML via DataContractSerializer



- Can add custom media types to standard serializers

```
GlobalConfiguration.Configuration
    .Formatters
    .XmlFormatter
    .SupportedMediaTypes
    .Add(new MediaTypeHeaderValue("application/book+xml"));
```

- Can add own custom formatters to control serialization
 - Derive from MediaTypeFormatter
 - Add to Formatters collection
 - Can take over existing format by Insert into Formatters collection before existing formatter



- Hypermedia (link) support is a central requirement of REST based systems
 - WebAPI does not do this for you
- Number of options
 - Operation generates links
 - Formatter generates links
 - Use XHTML and Razor

```
public class Resource<T>
{
    public Resource(T item) : this(item, new Dictionary<string, string>()) {
    }
    public Resource(T item, Dictionary<string, string> links ) {
        // ...
    }
    public T ResourceValue { get; private set; }
    public ILinkCollection Links { get; private set; }
}
```



- Low technology barrier
 - Use HTTP
 - No generated proxies
 - WebRequest
 - HttpClient / System.Json

```
var client = new HttpClient {  
    BaseAddress = new Uri("http://localhost.:16523/api/")  
};  
  
client.DefaultRequestHeaders  
    .Accept  
    .Add(new MediaTypeWithQualityHeaderValue("application/json"));  
  
Task<HttpResponseMessage> responseTask = client.GetAsync("books");  
  
Task<string> response = responseTask.Result.Content.ReadAsStringAsync();  
  
dynamic json = JsonValue.Parse(response.Result);  
foreach (dynamic item in json)  
{  
    Console.WriteLine((string)item.ResourceValue.Title);  
}
```



- REST is a powerful model for public APIs
 - Support all clients
- WebAPI makes building REST system straightforward