

5 GHz Channel Allocations 500 MHz



		5000 + 5 X Ch. Number				DFS Channels				DFS Channels												165 was ISM, now U-NII-3					UNII-4					
Qty	Frequency	U-NII-1				U-NII-2a				U-NII-2c (Extended)								U-NII-3					UNII-4			Qty	Qty					
	Radio Band									TDWR																						
	Center Freq	5.180	5.200	5.220	5.240	5.260	5.280	5.300	5.320	5.500	5.520	5.540	5.560	5.580	5.600	5.620	5.640	5.660	5.680	5.700	5.720	5.745	5.765	5.785	5.805	5.825	5.845	5.865	5.885			
	25	20 MHz	36	40	44	48	52	56	60	64	100	104	108	112	116	120	124	128	132	136	140	144	149	153	157	161	165	169	173	177	25	28
	12	40 MHz	38		46		54		62		102		110		118		126		134		142		151		159		167		175		12	14
6	80 MHz	42				58				106				122				138				155				171				6	7	
3	160 MHz	50								114												163								3	4	
FCC - US		1,000 mW Tx Power Indoor & Outdoor No DFS needed				250 mw w/6dBi Indoor & Outdoor DFS Required				250 mw w/6dBi Indoor & Outdoor DFS Required				120, 124, 128 US - Allowed				144 Now Allowed				1,000 mW Tx Power Indoor & Outdoor No DFS needed										
ISED - Canada		FCC - Except Outdoor License Req. >200 mW				Same as FCC				Same as FCC				TDWR Not Allowed				Same as FCC				Canada PTP allows Higher EIRP										
ACMA - Australia		200 mW EIRP Indoor				200 mW EIRP - DFS & TPC 100 mW EIRP - DFS-Only Indoor				1,000 mW - DFS & TPC 500 mW - DFS-Only - No TPC Indoor/Outdoor				TDWR Not Allowed				1,000 mW - DFS & TPC 500 mW - DFS-Only Indoor/Outdoor				4,000 mW Tx Power Indoor & Outdoor No DFS needed										
ETSI - EU		100 mW No DFS/TPC Indoor				200 mW EIRP DFS/TPC Indoor				1,000 mW EIRP DFS/TPC Indoor/Outdoor								UK No 144		4,000 mW EIRP DFS/TPC - Outdoor Fixed Wireless Access												
		200 mW EIRP DFS/TPC - Indoor												10-min TWDR Scan Time				25mW SRD		25mW - SRD - No DFS												
20 MHz		36	40	44	48	52	56	60	64	100	104	108	112	116	120	124	128	132	136	140	144	149	153	157	161	165	169	173	177			
Center Freq		5.180	5.200	5.220	5.240	5.260	5.280	5.300	5.320	5.500	5.520	5.540	5.560	5.580	5.600	5.620	5.640	5.660	5.680	5.700	5.720	5.745	5.765	5.785	5.805	5.825	5.845	5.865	5.885			
		<- Wavelength 5.8cm - 2.3"																Wavelength 5.1cm - 2.0" ->														
Free Space Path Loss 1m		45.74	45.77	45.80	45.84	45.87	45.90	45.94	45.97	46.26	46.29	46.32	46.35	46.38	46.41	46.44	46.48	46.51	46.54	46.57	46.60	46.64	46.67	46.70	46.73	46.76	46.79	46.82	46.84			