

HAM RADIO REFERENCE

General License Frequency Chart

US amateur HF privileges by band, General class

Keith Parsons — keith@wlanpros.com • June 28, 2026

General License Frequency Chart

US amateur radio privileges for the **General** class license. Frequency segments are the General-class allocations under 47 CFR §97.301; the power column follows §97.313. Operating notes flag when each band tends to open.

HF bands — General class

Band	Frequency	General-class segments	Voice	Max power	Operating notes
160 m	1.800–2.000 MHz	1800–2000 kHz (all modes)	LSB	1500 W PEP	Night owl
80 m	3.500–4.000 MHz	3525–3600 kHz (CW/data); 3800–4000 kHz (phone)	LSB	1500 W PEP	Evenings & nights
60 m	5 MHz (channelized)	4 channels + 5351.5–5366.5 kHz segment	USB	100 W ERP (channels) / 9.15 W ERP (segment)	USB channels — see 60 m table below
40 m	7.000–7.300 MHz	7025–7125 kHz (CW/data); 7175–7300 kHz (phone)	LSB	1500 W PEP	Best days & evenings
30 m	10.100–10.150 MHz	10100–10150 kHz: CW & data only (no phone, no image)	—	200 W PEP	CW & data
20 m	14.000–14.350 MHz	14025–14150 kHz (CW/data); 14225–14350 kHz (phone)	USB	1500 W PEP	Best days & nights
17 m	18.068–18.168 MHz	18068–18110 kHz (CW/data); 18110–18168 kHz (phone)	USB	1500 W PEP	Best days & evenings
15 m	21.000–21.450 MHz	21025–21200 kHz (CW/data); 21275–21450 kHz (phone)	USB	1500 W PEP	Best days
12 m	24.890–24.990 MHz	24890–24930 kHz (CW/data); 24930–24990 kHz (phone)	USB	1500 W PEP	Best days
10 m	28.000–29.700 MHz	28000–28300 kHz (CW/data); 28300–29700 kHz (phone)	USB	1500 W PEP	Best days

HF data emissions: No symbol-rate (baud) limit on HF. Data is governed by a **2.8 kHz maximum bandwidth** (FCC 23-93).

Technician on HF: A Technician licensee is limited to **200 W PEP** on any HF band (and to the narrower Technician segments, not shown here).

60 m channel detail

The FCC references 60 m by **channel center frequency**; operators tune **USB 1.5 kHz below center** (the dial frequency). Center frequency is the canonical value; dial is the secondary annotation.

#	Center frequency	USB dial frequency	Max power	Notes
1	5332.0 kHz	5330.5 kHz	100 W ERP	
2	5348.0 kHz	5346.5 kHz	100 W ERP	
3	5373.0 kHz	5371.5 kHz	100 W ERP	
4	5405.0 kHz	5403.5 kHz	100 W ERP	
seg	5351.5–5366.5 kHz (15 kHz wide)	—	9.15 W ERP	All modes, 2.8 kHz max

LF / MF bands — General class

The two long-wave bands carry strict EIRP power caps and require prior UTC notification before first use.

Band	Frequency	Modes	Max power	Notes
2200 m	135.7–137.8 kHz	All modes	1 W EIRP	Prior UTC notification required
630 m	472–479 kHz	All modes	5 W EIRP (1 W EIRP in parts of AK near Russia)	Prior UTC notification required

VHF / UHF / SHF — General class

General, like all licensees Technician and above, runs **1500 W PEP** across these bands (subject to the §97.313(a) "minimum necessary power" rule).

Band	Frequency	Voice	Max power	Notes
6 m	50–54 MHz	USB	1500 W PEP	CW only 50.0–50.1 MHz
2 m	144–148 MHz	USB	1500 W PEP	CW only 144.0–144.1; 600 kHz repeater split
1.25 m	222–225 MHz	USB	1500 W PEP	219–220 MHz point-to-point digital, secondary
70 cm	420–450 MHz	USB	1500 W PEP	"Line A" restriction near Canada; 435–438 satellite; 5 MHz split
33 cm	902–928 MHz	USB	1500 W PEP	Shares 900 MHz ISM (Part 15)
23 cm	1240–1300 MHz	USB	1500 W PEP	Secondary
13 cm	2300–2310 / 2390–2450 MHz	—	1500 W PEP	2390–2450 overlaps 2.4 GHz Wi-Fi
5 cm	5650–5925 MHz	—	1500 W PEP	Overlaps 5 GHz U-NII Wi-Fi
3 cm	10.0–10.5 GHz	—	1500 W PEP	

9 cm (3.3–3.5 GHz): sunseting and omitted here. 3.45–3.5 GHz ceased 14 Apr 2022; 3.3–3.45 GHz is a secondary allocation in active sunset. It does **not** overlap Wi-Fi 5 GHz (that is the 5 cm band above).

Power-limit summary (§97.313): General ceiling is **1500 W PEP** on every band **except** 30 m (**200 W PEP**), 60 m channels (**100 W ERP**) and the 60 m segment (**9.15 W ERP**), 2200 m (**1 W EIRP**), and 630 m (**5 W EIRP**). A Technician is capped at **200 W PEP** on HF.