Aufgaben-Sammlung

MySql / Databases
DDL (ERD → Create / Drop..)

Last Changes: Walter Rothlin / Dec, 24th 2019


Index

DDL (Data Definition Language)	3
Create a model (ERD)	3
Draw a model (ERD)	4
Bedeutung der Konstraints	4
Generate script from ERD-Model	
Use script to create DB Objects	6
Attribute-Types	


DDL (Data Definition Language)

Create a model (ERD)


In Workbench: File → New Model




Draw a model (ERD)



Doppel-Click adressen:



Doppel-Click orte:




File → Save Model As.... Model_hwz_test

Bedeutung der Konstraints

	
PK	Primary Key
NN	NOT NULL
UQ	Unique
В	Binary Data
UN	Unsigned
ZF	Zero Fill (Default O falls Numeric)
Al	Auto Increment
G	Generated


Generate script from ERD-Model

File → Export → Forward Engineer SQL...



<u>B</u>ack <u>N</u>ext

Cancel



Use script to create DB Objects

File → Open SQL script

Execute script and refresh schema view

Attribute-Types

Туре	Storage	Minimum Value	Maximum Value
	(Bytes)	(Signed/Unsigned)	(Signed/Unsigned)
TINYINT	1	-128	127
		0	255
SMALLINT	2	-32768	32767
		0	65535
MEDIUMINT	3	-8388608	8388607
		0	16777215
INT	4	-2147483648	2147483647
		0	4294967295
BIGINT	8	-9223372036854775808	9223372036854775807
		0	18446744073709551615