

Netskope SASE Gateway (NSG) Platform Specifications

Spec Sheet



HARDWARE APPLIANCE	NSG-101	NSG-500	NSG-1500	NSG-2000	NSG-3000
Physical specifications					
LAN/WAN interfaces	4x 1G RJ45	4x 1G RJ45 1x1G SFP ¹ +	2x 1G RJ45/SFP 4x 2.5G RJ45 2x 10G SFP+	2x 1G RJ45/SFP 4x 2.5G RJ45 2x 10G SFP+	6x 1G RJ45 6x 10G SFP+
Wi-Fi	2.4GHz/5GHz 802.11a/b/g/n/ac	Wi-Fi 6 802.11ax	2.4GHz/5GHz 802.11ax	N/A	N/A
LTE	Integrated/USB	USB	USB	USB	N/A
BLE	BLE 5.0	Micro USB	N/A	N/A	N/A
Console Ports	N/A	N/A	RJ-45/Mini USB	RJ-45/Mini USB	RJ45
Serial Port	RS232/485	N/A	N/A	N/A	N/A
External USB	1x USB 3.0	1x USB 3.0	2x USB 3.0	2x USB 3.0	2x USB 3.0
Memory	2 GB	4GB	8GB	16GB	16 GB
Storage	16 GB eMMC	12V DC jack	64GB eMMC	128GB eMMC	128 GB SSD
Size (W x D x H) in mm	125 x 125 x 40	179.5 x 206 x 35	256 x 200 x 44	256 x 200 x 44	437.9 x 455.7 x 44
Mounting	DIN rail, Desktop, Wall & Rack mount	Desktop	Desktop, Wall & Rack mount	Desktop, Wall & Rack mount	Rack mount
Power Input	DC-IN or PoEx1 10- 28V	12V DC jack	12V DC, Single	12V DC, Single	100-264V, Redundant
Operating Conditions (Target)	-30-70 degree C (DC-IN) -30-50 degree C (PoE)	0-40 degree C	0-40 degree C	0-40 degree C	0-40 degree C
Ruggedized	I-Temp	No	No	No	No
Ingress Protection Rating	IP40	N/A	N/A	N/A	N/A
Certifications	FCC,UL,CE, CB, CSA, KC, UKCA, RCM, TELEC,IC VCCI, Anatel, WPC, SRRC, TRA, TRC, EACS+ROHS, NRCS, SUBTEL	FCC, UL, IC, CSA, CE, CB, UKCA, SUBTEL,CRC, ENACOM, NTRC, ASEP, URSEC ,CONATEL, ARCOTEL, TEC	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, TELEC, VCCI, BIS, TRC	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, TELEC, VCCI, BIS, TRC	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, VCCI, Anatel, KC, NRCS, SABS, NOM
Mean Time Between Failure (MTBF) in years	20	70.17	9.92	9.92	22.5

Hardware Appliance	NSG-101	NSG-500	NSG-1500	NSG-2000	NSG-3000
Performance					
Site-to-Site Throughput (1300-byte)	100Mbps	500Mbps	1Gbps	2Gbps	10Gbps
Site-to-Site Throughput (IMIX)	50Mbps	160Mbps	500Mbps	700Mbps	5Gbps
Max Overlay tunnels	50	200	400	800	2400
Max Endpoint SD-WAN tunnels	75	150	600	1200	6000

NSG - Virtual	NSGV ESXi ¹ (2 CORE)	NSGV ESXi ¹ (4 CORE)	NSGV ESXi ² (8 CORE)
Memory	4GB	8GB	16GB
Storage	32GB	32GB	32GB
Site-to-Site throughput (1300-byte)	1Gbps	3Gbps	5Gbps
Site-to-Site throughput (IMIX)	400Mbps	600Mbps	1.5Gbps
Max Overlay tunnels	400	800	2400
Max Endpoint SD-WAN tunnels	600	1200	6000

¹ Performance is based on Intel(R) Xeon(R) Platinum 8358 CPU @ 2.60GHz, VMXNET3

² Performance is based on Intel(R) Xeon(R) Gold 6330 CPU @ 2.00GHz, VMXNET3



Netskope, a global cybersecurity leader, is redefining cloud, data, and network security to help organizations apply Zero Trust principles to protect data. The Netskope Intelligent Security Service Edge (SSE) platform is fast, easy to use, and secures people, devices, and data anywhere they go. Learn how Netskope helps customers be ready for anything, [visit netskope.com](https://www.netskope.com).

©2023 Netskope, Inc. All rights reserved. Netskope is a registered trademark and Netskope Active, Netskope Cloud XD, Netskope Discovery, Cloud Confidence Index, and SkopeSights are trademarks of Netskope, Inc. All other trademarks are trademarks of their respective owners. 06/23 SPEC SHEET-578-5