

Netskope Borderless SD-WAN

Spec Sheet



Netskope SASE Gateway (NSG) Platform Specifications

HARDWARE APPLIANCE	NSG-100	NSG-101	NSG-1500	NSG-2000	NSG-3000
					
Physical specifications					
LAN/WAN interfaces	3x 1G RJ45	4x 1G RJ45	2x 1G RJ45/SFP 4x 2.5G RJ45 2x 10G SFP+	2x 1G RJ45/SFP 4x 2.5G RJ45 2x 10G SFP+	6x 1G RJ45 6x 10G SFP+
Wi-Fi	2.4GHz/5GHz 802.11a/b/g/n/ac	2.4GHz/5GHz 802.11a/b/g/n/ac	2.4GHz/5GHz 802.11a/b/g/n/ac/ax	N/A	N/A
LTE	USB	Integrated/USB	USB	USB	N/A
BLE	N/A	BLE 5.0	N/A	N/A	N/A
Console Ports	Mini USB	Mini USB	RJ-45/Mini USB	RJ-45/Mini USB	RJ45
Serial Port	N/A	RS232/485	N/A	N/A	N/A
External USB	1x USB 3.0 1x USB 2.0	1x USB 3.0	2x USB 3.0	2x USB 3.0	2x USB 3.0
Memory	2 GB	2 GB	8GB	16GB	16 GB
Storage	8 GB eMMC	16 GB eMMC	64GB eMMC	128GB eMMC	128 GB SSD
Size (W x D x H) in mm	110 x 84.6 x 31.75	125 x 125 x 40	256 x 200 x 44	256 x 200 x 44	437.9 x 455.7 x 44
Mounting	Desktop	DIN rail, Desktop, Wall mount, Rack mount	Desktop, Wall mount, Rack mount	Desktop, Wall mount, Rack mount	Rack mount
Power Input	12V DC jack	DC-IN or PoEx1 10-28V	12V DC, Single	12V DC, Single	100-264V, Redundant
Operating Conditions (Target)	0-35 degree C	-30-70 degree C (DC-IN) -30-50 degree C (PoE)	0-40 degree C	0-40 degree C	0-40 degree C
Ruggedized	No	I-Temp	No	No	No
Ingress Protection Rating	N/A	IP40	N/A	N/A	N/A
Certifications	FCC, UL, CE, CB, IC, UKCA, RCM, TELEC, VCCI	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, TELEC, VCCI, Anatel, WPC, SRRC, KC, TRA, EACS+ROHS, NRCS, SUBTEL, TRC	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, TELEC, VCCI, BIS, TRC	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, TELEC, VCCI, BIS, TRC	FCC, UL, CE, CB, IC, CSA, UKCA, RCM, VCCI, Anatel, KC, NRCS, SABS, NOM
Mean Time Between Failure (MTBF) in years	10.6	20	9.92	9.92	22.5

HARDWARE APPLIANCE	NSG-100	NSG-101	NSG-1500	NSG-2000	NSG-3000
Performance					
Max throughput (1300-byte)	100Mbps	100Mbps	1Gbps	2Gbps	5Gbps(Today) 10Gbps*
Max overlay tunnels	50	50	400	800	4000
Max Endpoint SD-WAN tunnels	75	75	600	1200	6000
Flow per second	2400	2400	4800	19200	19200
Max concurrent active flows	240K	240K	480K	1.9M	1.9M
Max number of routes	100K	100K	100K	100K	100K

NSG - VIRTUAL	NSG VIRTUAL (2 CORE)	NSG VIRTUAL (4 CORE)	NSG VIRTUAL (8 CORE)
Max throughput (1300-byte)	1Gbps	2Gbps	4Gbps
Max overlay tunnels	50	800	4000
Max Endpoint SD-WAN tunnels	75	1200	6000
Memory	4GB	8GB	16GB
Storage	32GB	32GB	32GB

*Roadmap



Netskope, a global cybersecurity leader, is redefining cloud, data, and network security to help organizations apply Zero Trust principles to protect data. The Netskope Intelligent Security Service Edge (SSE) platform is fast, easy to use, and secures people, devices, and data anywhere they go. Learn how Netskope helps customers be ready for anything, [visit netskope.com](https://www.netskope.com).