## Homework 9


## DUE WEDNESDAY, MAY 4

- 1. Rotational motion introduces many new terms, and in order to make sense of conversations about rotation, you should be familiar with them. In your own words and using *no mathematics*, define the following and give the dimensions of each of the following:
  - (a) Angular velocity
  - (b) Angular acceleration
  - (c) Tangential velocity
  - (d) Radial acceleration
  - (e) Tangential acceleration
  - (f) Torque
  - (g) Angular momentum
- 2. The CD-ROM drive in a computer accelerates a disk from rest to its full speed of 20000 revolutions per minute; it does so uniformly over 5 seconds. The disk is 6 cm in radius.
  - (a) Is it correct to write  $\alpha = 4000 \text{ rev} \cdot \text{min}^{-1} \cdot \text{s}^{-1}$ ? Explain.
  - (b) What is the maximum angular velocity in our conventional units of radians per second?
  - (c) What is its angular acceleration?
  - (d) How many times does it spin during this interval?
  - (e) After four seconds, what is the tangential velocity of a point along the edge of the disk?
  - (f) After four seconds, what is the angular velocity of a point along the edge of the disk?
  - (g) After four seconds, how many times has the disc rotated?
- 3. Suppose that you want to hold a meter stick horizontal to the ground by touching it with only two fingers. One finger is at the 10 cm mark, while the other finger is at the 20 cm mark. The meter stick has a weight of 1 N. What must you do with your fingers, and what normal forces do they exert on the meter stick? What if your fingers are at the 10 cm and 12 cm marks?

If you are having trouble with this problem, go get a meter stick and physically play with it. We will put a meter stick in the Physics Clinic for people to play with.

4. A construction worker takes a break for lunch, resting on a steel beam.


The steel beam has a mass of 1450 kg, and the construction worker shown has a mass of 80 kg. They sit 3.2 meters from the end of the beam. The cable is rated to transmit a tension of 15 kN.



Should they be worried that the cable might fail?

5. A castle's drawbridge consists of a heavy wooden plank that can be opened or closed using a rope, as shown below:

The rope is attached to the door 4/5 of the way down its length; the left side of the plank is attached to a hinge in the ground. The bridge is left in a partially-raised state by a careless sentry. It makes an angle of 30° with the horizontal; the rope that supports it is perpendicular to the bridge.



If the mass of the door is m, calculate the tension T in the rope in terms of  $\theta$ , m, and g.

6. A person rolls a basketball  $(I = \frac{2}{3}mr^2)$  down a slope; the slope is inclined at an angle  $\theta = 15^{\circ}$ . The basketball rolls without slipping down the slope.


At the same time, another person slides a piece of ice down the slope. There is friction between the ice and the slope – just not very much.

What must the coefficient of kinetic friction  $\mu_k$  between the ice and the slope be such that the piece of ice and the basketball have the same speed when they reach the bottom?

7. A "merry-go-round" is a large horizontal platform for children to play on that can rotate freely.

Imagine a certain merry-go-round has a radius of r=3 m and a mass of 200 kg, and has been constructed out of fancy and well-lubricated bearings so that it rotates freely without friction.

Suppose a child of mass 40 kg runs and jumps on the edge of the platform at 5 m/s; when they land on the edge, they are moving tangent to it. (See the diagram.)



- (a) Once the child jumps on the platform, how will it move?
- (b) Now, imagine that the child walks to the center of the platform. How will it be moving now?
- 8. An large old iron wheel of mass m, still connected to its axle, has been abandoned by a roadside. A person wants to move it, so they tie a rope to the axle, set the wheel up on its edge, and pull horizontally with a tension T. The coefficient of static friction between the wheel and the ground is  $\mu_s$  and the coefficient of kinetic friction is  $\mu_k$ .

They pull gently enough that the wheel rolls without slipping.

- (a) Determine, in terms of m, T, g, and  $\mu$ , the acceleration of the wheel. (Your result may not depend on all of these.)
- (b) Determine, in terms of m, T, g, and  $\mu$ , the frictional force between the wheel and the ground. (Your result may not depend on all of these.)