

# Final Project, K-Means Clustering

Song Liu ([song.liu@bristol.ac.uk](mailto:song.liu@bristol.ac.uk))

GA 18, Fry Building,

Microsoft Teams (search "song liu").

# Clustering

- Clustering is a machine learning task that **groups similar objects together**.
- Given a dataset with  $n$  observations,  $D := \{\mathbf{x}_i\}_{i=1}^n$ , we would like to divide  $D$  into  $K$  disjoint subsets:

$$D = \cup_{i \in \{1 \dots K\}} D_i \text{ and } \cap_{i \in \{1 \dots K\}} D_i = \emptyset,$$

- Such that observations in each subset  $D_i$  **are similar to each other**.

# Clustering Example

- The subsets found by clustering is **not** unique.
  - depending on **how the similarity is defined**, you can get different clustering results.

# Clustering Example

- Clustering of animals: Land vs. Sea.

$$D := \left\{ \begin{array}{ccc} \text{hippo} & \text{jellyfish} & \text{owl} \\ \text{giraffe} & \text{pig} & \text{whale} \end{array} \right\}$$

$$D_1 = \left\{ \text{hippo}, \text{giraffe}, \text{pig}, \text{owl} \right\}$$

$$D_2 = \left\{ \text{whale}, \text{jellyfish} \right\}$$

# Clustering Example, 2

- Clustering of animals: Mammals vs. Non-mammals.

$$D := \left\{ \begin{array}{ccc} \text{hippo} & \text{jellyfish} & \text{owl} \\ \text{giraffe} & \text{pig} & \text{whale} \end{array} \right\}$$

$$D_1 = \left\{ \text{hippo}, \text{giraffe}, \text{pig}, \text{whale} \right\}$$

$$D_2 = \left\{ \text{owl}, \text{jellyfish} \right\}$$

# Similarities

- In mathematics, similarities between objects are usually defined by a metric or distance function.
- One classic choice of distance is Euclidean distances.
- If two objects can be expressed as two points  $\mathbf{a}$  and  $\mathbf{b}$  in a  $d$ -dimensional Euclidean space, the Euclidean distance is

$$\text{dist}(\mathbf{a}, \mathbf{b}) := \sqrt{\sum_{i=1 \dots d} (a_i - b_i)^2}$$

# IRIS dataset

Ronald Fisher created [Iris dataset](#), where he measured the length, width of the sepals and petals 150 iris flowers.

- In this dataset, each flower is a 4-dimensional vector.

```
> iris # load iris dataset in R by typing "iris".  
  Sepal.Length Sepal.Width Petal.Length Petal.Width  
1           5.1           3.5           1.4           0.2  
2           4.9           3.0           1.4           0.2  
3           4.7           x3.2           1.3           0.2  
...
```

# K-Means Clustering Algorithm

Given a dataset and a distance function, how to do clustering?

- **K-means** is a simple and popular choice.
- It computes the similarity between each observation and "centers" of each subset, then assign observations to different subsets.
- After the assignments are made, it updates the centers to be the average of observations in each subset.
- It repeatedly carries out the previous two steps until assignments do not change.



# K-Means Clustering Algorithm

Suppose your dataset  $D$  contains  $n$  observations in  $d$ -dimensional space. Then K-Means divides  $D$  into  $D_1, \dots, D_K$  subsets using the following algorithm.

# K-Means Clustering Algorithm

1. Randomly pick  $K$  observations from your dataset, as  $K$  centers:  $\mathbf{c}_1, \dots, \mathbf{c}_K$

2. For each observation  $\mathbf{x}_i \in D$ ,

i. For each  $k \in \{1 \dots K\}$ , compute the distance

$$d_{i,k} = \text{dist}(\mathbf{x}_i, \mathbf{c}_k)$$

ii. Assign  $\mathbf{x}_i$  to the subset  $D_{k=k'}$ , where

$$k' = \arg \min_k d_{i,k}$$


3. Compute the new centers:  $\mathbf{c}_1, \dots, \mathbf{c}_K$ , where

$$\mathbf{c}_k := \frac{1}{|D_k|} \sum_{\mathbf{x}_j \in D_k} \mathbf{x}_j,$$

i.e., the average of all observations in subset  $D_k$ .


4. Repeat 2 and 3 until the assignment does not change any more.

# K-Means Clustering Algorithm: Demo




# K-Means Clustering Algorithm: Demo

iteration 1 after assignment




# K-Means Clustering Algorithm: Demo




# K-Means Clustering Algorithm: Demo

iteration 2 after assignment




# K-Means Clustering Algorithm: Demo



# K-Means Clustering Algorithm: Demo

iteration 3 after assignment





# K-Means Clustering Algorithm: Demo

The new centers do not lead to a different assignment comparing to iteration 2.

Stop.

## Coursework: Part I (15 points)

The first part of this coursework is generating a toy dataset for our K-means algorithm. Let us assume  $K = 2$  for now.

# Coursework: Part I (15 points)

0. Set the random seed to 1.
1. Generate a dataset  $D$ , containing 100 random observations from two **2-dimensional** normal distribution with **different means**.
  - $D$  can be either a matrix or data frame.
  - You should sample 50 observations from one normal distribution and 50 from the other normal distribution.
2. Create  $C = \{c_1, c_2\}$  by randomly picking **2 centers** from your dataset.
  - The choice of centers needs to be random.
  - You are not allowed to specify centers yourself.

## Coursework: Part I (15 points)

3. Visualize  $D$  using `points` function.

- It is up to you how to visualize your dataset.

## Coursework: Part II (30 points)

- Now, let us write the K-means algorithm and test it on the toy dataset.
- Below is a list of suggested steps of writing your code. However, you can write your code differently.

# Coursework: Part II (30 points)

1. Write a function `dist` that computes the distance  $d_{i,k}$ .
2. Write a function `assign` that assigns  $\mathbf{x}_i$  to  $D_{k=k'}$ .
3. Find a way to apply `assign` to all observations in  $D$ .  
Obtain an 100-dimensional vector `k_prime` whose  $i$ -th component is the  $i$ -th observation's assignment  $k'$ .
4. Write a function `update_centers` that updates centers in  $C$  with the new assignments stored in `k_prime`.
5. Write a function `visualize` that visualizes  $\mathbf{c}_1, \mathbf{c}_2$  and  $D_1, D_2$ .

## Coursework: Part II (30 points)

6. Write a loop that calls `assign`, `update_centers` and `visualize` repeatedly until the elements in `k_prime` do not change any more.

# Coursework: Part III (15 points)

Now, let us apply K-means algorithm to a real-world dataset

`iris` .

- Load iris dataset by typing `iris` and inspect the dataset.
- There are 5 variables in this dataset:
  - Sepal.Length
  - Sepal.Width
  - Petal.Length
  - Petal.Width
  - Species
- The first four variables are the properties of flowers. The fifth variable indicates the types of flowers.



# Coursework: Part III (15 points)

0. Create a new R file.
1. Create a **list of 6 new datasets** from the iris dataset, by picking **every pairs** of variables from the first four variables.
2. Find a way to apply the K-means algorithm you previously wrote to the entire list of iris datasets and perform clustering analysis.
3. Visualize the assignments obtained from the K-means algorithm, and save your plots (6 in total) as 6 png files.

## Coursework: Part III (15 points)

The following code saves a plot to the `points.png` file.

```
#create file
png("./points.png", width = 500, height = 500)
#create the plot
plot(c(-5,5),c(-5,5),type = "n")
points(rnorm(10), rnorm(10), cex = 2)
#close the file
dev.off()
```

# Marking Criteria

- Part I: 15 points
- Part II: 30 points
- Part III: 15 points
- Vectorization and FP: 20 points
  - Your code uses vectorization and does not use unnecessary loops.
  - Your code uses some FP features (not necessarily completely written in FP).
- Coding Style: 20 points.
  - Variable naming, Code formatting, Comments

# DOs and DONTs

- You are encouraged to discuss this coursework with other students.
- All coursework questions should be addressed to the lecturer or TA during lab sessions or using the blackboard forum.
- You are only allowed to use the base R.
- You are not allowed to use external machine learning libraries without the permission from the lecturer.
- You are not allowed to copy other people's work.
  - You are not allowed to pass your work to other students.
- Discuss with others but **write the code by yourself!!**

# Submission

- Deadline: 8th May.
- Submit a zip file containing all your R scripts (Rmd files if you use R markdown).
  - You do not need to submit any data file.
  - You do not need to submit any images your code generate.