Journal of Software Engineering Research and Development, 2026
This work is licensed under a Creative Commons Attribution 4.0 International License.

Kata: an executable quality gate for AI-assisted software changes

Omitted for review

Abstract

AI coding agents produce code faster than a developer can review in detail, and oversight collapses onto the automated test suite. When an agent says "done", nothing executes the checks it claims to have passed, and agents can satisfy visible tests while missing the user's goal (reward hacking). This paper presents Kata, an executable quality gate for AI-assisted software changes. Kata guides a change through a nine-phase cycle — FIT, THINK, SIMPLIFY, INTENT, SURGICAL, VERIFY, TWIN CHECK, ARTIFACT, REPORT — plus an optional adversarial JUDGE that re-runs every claimed check and hunts eight categories of fraud — seven of them exercised by the evaluation — such as weakened tests, false completion claims, undeclared scope, and a triviality claim the measured diff does not support. Unlike skills that instruct the agent to be careful, Kata moves the objective parts of the discipline into tested Python code: lint, typecheck when the project declares one, test, and coverage read real exit codes, the JUDGE confronts the task file with the repository, and an audit mode grades each phase as followed, skipped, faked, or degraded. Two agent frontends are generated from a single source, and the paper describes each executable phase as a code-anchored listing. Version 0.8.0 adds the declared typecheck role, execution evidence in the task file, `kata --stamp` to close the JUDGE's diff window, strict project configuration, and the eighth fraud category.

On 19 trap scenarios we wrote ourselves, the JUDGE returned every expected verdict. In an executed comparison on the same scenarios, three related gates also detected every planted fraud, so Kata's measured advantage is determinism and cost (a median of 0.1 s on fraud scenarios and 1.0 s on the others), not detection; ten of the eleven agent false positives fell on blind-spot scenarios or on a Kata-specific diff convention. On 12 bug-fix tasks from public repositories (48 agent sessions), the JUDGE's independent review flagged the one case of undeclared scope and its own weakened-test detector found none, but the sessions' own JUDGE runs falsely refuted six honest fixes, under a rule corrected after the evaluated version. An appendix reports an exploratory pilot and a 30-session campaign with an iterative builder/critic loop built on the same task file and audit machinery; they do not show that the loop improves the artifacts, and with one run per cell their comparisons are inconclusive.

The scenarios are in-distribution for Kata; the judgment phases of the cycle were not ablated and were evaluated only for cost; the JUDGE has reproduced evasions for an agent that controls the repository; and whether the cycle improves the quality of AI-assisted changes remains future work.

Keywords: *AI agents, software quality, verification, adversarial verification, quality gates, large language models, coding agents*

1 Introduction

AI coding agents (OpenCode, Claude Code, Cursor, and similar tools) change software with remarkable speed. The hard problem is not the speed but whether the result can be trusted. When an agent says "done", what sustains that claim?

A skill says: *"verify your tests before committing"*. The model may follow, ignore, or half-follow the instruction, and nobody can tell the difference. An agent can claim "lint clean, tests passing, coverage at the gate" without any of it having been executed. Or worse: it can have executed the checks, but with a weakened test (a `pass` in place of the assertion) that "passes" without verifying anything.

The Karpathy Development Cycle — the name this paper gives to the agentic-engineering discipline described by Karpathy Karpathy (2026) — proposes discipline: think before coding, keep the code minimal, make surgical changes, and verify objectively. The Fable Method Sahir619 (2026), a GitHub repository that has not been peer-reviewed, proposes gates: classify the task before acting (fit gate), require evidence before action, verify adversarially, and report outcome-first. Both are methodologies, and a methodology is text that instructs. Text instructs; it does not execute.

This paper presents Kata ("form" or "pattern", as in a martial arts kata: a disciplined, repeatable sequence of movements), a quality gate for software changes assisted by AI agents. Kata's contribution is to move the objective parts of the discipline out of the prompt and into executable, testable Python code. The lint, test, and coverage steps read real exit codes; the JUDGE re-runs claimed checks against the real repository, including committed and untracked files; and the audit mode grades each phase of a completed task as followed, skipped, faked, or degraded, naming the concrete risk each grade other than followed created. Where a skill prescribes honesty, Kata supplies an executable mechanism to verify it.

This paper is a **software article**. Following the journal's guidelines (quoted in Section 9.2), it describes a tool, positions it as a significant advance over previously published software, and demonstrates the advance by *direct comparison with available related software*: Section 9.2 reports an executed comparison in which Kata and three alternative gates (nova TeamSPWK (2026), claude-wizard vlad-ko (2026), and a prompt-only baseline) review the same 19 adversarial scenarios. All four detected the planted frauds; the comparison locates Kata's measured advantage in determinism and cost — the same verdict every run, at about one second per review on the trap scenarios. Kata also made no false accusations, but most agent false positives fell on scenarios built around Kata's own conventions, so that result is not ev-

idence of superior reviewer restraint.

The evaluation answers three research questions, each tied to the evidence that answers it:

- **RQ1.** Does the JUDGE honour its two-sided contract — detecting planted frauds without accusing honest work, and confessing what it cannot observe? (Section 9.1: 19 trap scenarios.)
- **RQ2.** How does the JUDGE compare with related gates reviewing the same scenarios, in detection, false accusations, determinism, and cost? (Section 9.2: 19 scenarios, four gates.)
- **RQ3.** Is the cycle feasible on real repositories we did not write, and what does it cost? (Section 9.3: 12 real bugs, 48 agent sessions.)

The evaluation does not establish whether the judgment phases of the cycle (THINK, SIMPLIFY, INTENT, SURGICAL, TWIN CHECK) improve the changes an agent produces: they were not ablated, and their contribution was measured only as cost. Appendix A reports an exploratory fourth question, outside the gate's evaluation: can an iterative builder/critic loop be carried and audited by the same task file, and does it improve the artifacts? The first half is answered affirmatively. The second finds no evidence of improvement, and no power to exclude one, across a 24-session pilot and a 30-session campaign (54 matched pairs, of which 19 were byte-identical and 35 were judged), so the question remains open with a better-instrumented path to it.

The paper proceeds as follows. Section 2 states the problem and the research purpose of the software. Section 3 places Kata in the context of related work. Section 4 describes the software design and the trade-offs weighed, and presents, as numbered Listings, the descriptive algorithms of the executable phases. Section 5 walks through the development cycle in action with real output. Section 6 details the adversarial verification layer. Section 7 presents the audit mode. Section 8 documents how to install and use the `kata` CLI. Section 9 reports the research impact and evaluation, including the executed comparison with related gates. Section 10 discusses the findings and their limitations. Section 11 states the threats to validity. Section 12 concludes, and Appendix A reports the exploratory loop study.

2 Statement of need

AI coding agents produce code faster than a developer can review in detail, and the oversight surface collapses onto the automated test suite. Reward hacking naturally arises in this setup: agents optimize for passing visible tests while deviating from the user's true goal. SpecBench Zhao et al. (2026) measures this phenomenon and finds that the gap between visible and held-out test suites grows by 28 percentage points for every tenfold increase in code size, with failures ranging from subtle feature isolation to deliberate exploits, including a 2,900-line hash-table "compiler" that memorizes test inputs. Agents also end failure transcripts with "all tests pass", and tests get weakened until they agree with the code Sahir619 (2026).

Large language models cannot reliably self-correct without external feedback — sometimes their performance even degrades after self-correction Huang et al. (2024). The implication is that verification cannot be left to the model checking itself: it must be external, executable, and objective.

The target audience of Kata is developers, researchers, and teams who use AI agents to modify code and need objective, reproducible verification that what was claimed was actually done. Kata is a quality gate for software changes, not a project template. It fits the following situations:

- **Before committing**: run the full cycle to force evidence for the change — problem, assumptions, minimality, intent agreement, and passing lint, tests, and coverage — instead of committing on an "it works" impression.
- **Bug fixes**: the cycle is adversarial about defects. INTENT catches code/test/specification conflicts, and TWIN CHECK searches the project for the same defect pattern elsewhere, recording even a negative result.
- **Small code-loop tasks**: the FIT gate measures the diff and routes trivial changes (one file, fewer than ten lines) directly, without planning ceremony.
- **Planning before implementation**: `kata --plan` runs FIT and THINK, saves the plan with assumptions and unknowns, and stops — the plan can be reviewed or handed off before a single line changes.
- **Adversarial verification of finished work**: `kata --judge` re-runs every claimed check and hunts eight fraud categories before a merge or hand-over.
- **Auditing tasks after the fact**: `kata --audit` grades each phase of a completed task as followed, skipped, faked, or degraded, and names the concrete risk each grade other than followed created.
- **Continuous integration**: `kata --check-only` runs lint, tests, and coverage with the coverage gate, non-interactively, as a CI entry point.

Equally important is defining what Kata is *not*. Kata is not an agent that synthesizes code: it does not generate patches or prompt language models to implement algorithms. It is not an automated test generator: it does not synthesize test suites or infer formal invariants. Nor does it claim to solve the general test oracle problem Barr et al. (2015): it takes the repository's declared verification commands and test suite as the material ground truth, ensuring that claimed checks were genuinely executed and that declared assertions were executed and not syntactically weakened. Kata is thus a verification quality gate and evidence-forcing scaffold, leaving code synthesis to the agent or human developer.

3 State of the field

Several tools and methodologies address disciplined AI-assisted development. The Fable Method Sahir619 (2026) is the closest conceptual ancestor: it defines a think/act/prove loop with a fit gate, a triviality gate, evidence before action, adversarial verification, and outcome-first reporting, and it ships an eval that keeps the method honest. Kata adapts the fit gate, the triviality gate, the intent gate, and the hard bounds directly from it, but differs in one structural way: the objective

logic lives in a Python package (`kata.fit`, `kata.verify`, `kata.judge`) that is unit-tested and measured for coverage, rather than in prompt text. The Fable Method's own `fable-judge` also treats a report as a set of claims and hunts weakened tests; the structural difference is that it is prompt text, while Kata's judge is a Python program whose verdict is computed from exit codes, the Git diff, and a Git-anchored baseline, and whose detection is measured by the public trap suite.

claude-wizard vlad-ko (2026) is an 8-phase development skill with TDD and adversarial review, but it is a skill only: there is no backend that executes the gates. Ring LerianStudio (2026) is a large skills library (76 skills, 33 agents) that enforces engineering practices with 10-gate development cycles, again as instructions rather than executable checks. nova TeamSPWK (2026) provides pre-commit quality gating, but as an agent skill without a shared executable core. On the research side, SpecBench Zhao et al. (2026) measures reward hacking in coding agents, and SWE-bench Jimenez et al. (2024) benchmarks agent capability on real GitHub issues; both measure agents, neither provides a gate that a team can run on its own changes.

The problem itself predates coding agents. Specification gaming — optimizing the measured proxy instead of the intended goal — is documented across machine learning Krakovna et al. (2020); Amodei et al. (2016) and formalized as variants of Goodhart's law Manheim and Garrabrant (2018). Software engineering has studied its counterpart for decades as the oracle problem: a passing suite is only as meaningful as the oracle behind it Barr et al. (2015), which is why independent oracle techniques such as metamorphic testing exist Chen et al. (2018). Reward hacking in coding agents is this same failure with a compiler attached, and Kata's answer is to treat each claim in the task file as a property and the repository as the oracle, re-executing the claim instead of reading it.

Three considerations led us to build Kata rather than contribute to an existing project. No existing tool ships an executable verification engine: the closest alternatives are prompts that ask the model to verify itself, which the self-correction literature shows is unreliable Huang et al. (2024). Kata also needed to serve two agent hosts (OpenCode and Claude Code) with identical behavior, and a single Python backend with generated frontends guarantees that the checks a task claims to have passed are the same checks in both hosts. The third consideration was self-verification: Kata's own lint, tests, and coverage are measured, and in the evaluated version (defined in the Declarations) 19 adversarial trap scenarios ran in continuous integration to check that the JUDGE catches planted frauds and does not accuse honest work; the current release, 0.8.0, runs 25.

3.1 Recent research on agent verification

The research landscape of 2026 has produced several works that corroborate the problem Kata addresses and sharpen its positioning. We note up front that most of the 2026 citations in this subsection are arXiv preprints (not yet peer-reviewed; the bibliography marks them); they are cited as evidence of an emerging research direction, not as established results, and the claims we draw from them are qualitative positioning, not measured premises. The Unreliable Progress Bar study Wang et al. (2026) shows that LLM agents cannot reliably report task progress throughout execution — agents claim completion states that do not match reality, and the JUDGE re-executes claims of that kind. The Double Measurement Confound Zhang et al. (2026) demonstrates that agent benchmarks suffer from de-scaffolding and ground-truth scoring confounds, arguing that reliability must be measured beyond the mean; Kata's trap suite follows the same principle by testing both fraud detection and false-positive avoidance. XAgent Huynh et al. (2026) uses execution-guided agentic AI for issue localization and resolution, showing that execution feedback improves agent outcomes — the same insight that motivates Kata's decision to read real exit codes rather than model intentions. Consort Hartman (2026) is a spec-first agent framework for enforced, test-driven development on live database branches; it shares Kata's enforcement philosophy but is scoped to database development, while Kata is a general-purpose gate. The Authority Is Not a String harness Bouras et al. (2026) scopes agent capabilities to resist prompt injection, complementing Kata's authorization gate (AUTH line) from the security angle. TrajMark Zeng et al. (2026) attributes ownership and localizes tampering in coding-agent trajectories, which is conceptually adjacent to Kata's baseline tampering detection, though applied to trajectory provenance rather than task files. The Discovery Certification Protocol Ning et al. (2026) audits AI research agents by certifying that claimed discoveries are reproducible — the same claim-vs-reality confrontation that the JUDGE performs for software changes. RefVerifier Mocan et al. (2026) semi-automatically verifies reference claims in scientific manuscripts, another instance of the claim-verification pattern. The study on traditional test criteria for LLM-generated code Hamidi et al. (2026) and the dynamics of iterative bug-fixing with LLMs Wang-Lin et al. (2026) both show that verification of AI-generated changes requires more than passing tests — the former because traditional criteria miss LLM-specific bugs, the latter because agents may fix what is not broken. Together, these works are consistent with Kata's core design decision: verification should be external, executable, and claim-based, not self-reported. They do not test it.

3.2 Comparative analysis

Table 1 summarizes the comparison between Kata and the related tools and methodologies surveyed in this section. The dimensions are operationalized as follows. *Executes*: the tool ships code that runs checks and reads their exit codes as part of its own verdict, rather than instructing the model to run them. *Shared core*: one executable engine serves more than one agent host (marked *N/A* for benchmarks, which are not gates). *Fraud*: the tool has an adversarial step that re-executes claims against the repository and returns a verdict (*Yes*); performs adversarial review in prompt form without re-execution (*Partial*); or has no adversarial step (*No*). *Audit*: it can grade a completed piece of work after the fact against its own process. *Self-verify*: the project runs its own checks and evaluation against itself. The assessments are ours, based

on each project's public documentation and repository at the commits cited in the bibliography (accessed 2026-09-11); no other tool's authors were consulted, and the executed comparison of Section 9.2 supersedes this table for the gates that could be run. The rows are stated here to make the comparison explicit and falsifiable; a reader who re-evaluates any row against the cited commit should arrive at the same verdict.

The table makes the positioning explicit: Kata is the only tool in the survey, judged by the public documentation we read, that combines executable verification, adversarial fraud detection across eight categories, post-hoc auditing, and blind-spot confession. The tools that execute (SpecBench, SWE-bench, Consort) are benchmarks or domain-specific frameworks, not gates a team runs on its own changes. The tools that audit (Fable Method) do not execute. Kata is the intersection.

Two qualifications bound the comparison. Consort Hartman (2026) executes verification, but its enforcement scope is a framework for test-driven development on live *database* branches; as a gate for general software changes it is not directly comparable by execution, so Section 9.2 compares Kata against the gates that are installable on the same host (nova, claude-wizard) and against a prompt-only baseline. The second qualification concerns *executing verification*: the `kata` CLI does it, while the prompt-based tools do not, since they ship no engine that runs checks and reads exit codes. Their "Partial" fraud column reports that the adversarial step exists only as instruction text — and the executed comparison shows that a reviewer carrying that instruction can run the checks when prompted, which is why the measured difference lies in determinism and cost rather than in detection (Section 9.2).

4 Software design

Kata's design is organized around one principle: the parts of the cycle that can be objective must be executable, and the parts that cannot must be declared before the evidence exists. The Python package `src/kata/` implements the objective logic in four modules.

Figure 1 shows the complete cycle. The nine phases run in sequence, with the optional JUDGE applied after REPORT. The phases that can be objective (FIT, VERIFY, JUDGE) are backed by executable Python logic; the phases that require judgment (THINK, SIMPLIFY, INTENT, SURGICAL, TWIN CHECK, ARTIFACT, REPORT) are guided by skills and recorded in the task file, which the objective phases read and confront with the repository.

Architecturally, Kata operationalizes this discipline along two distinct usage tiers: (1) an *interactive authoring scaffold* (`kata --task`), which guides the developer or agent step-by-step through the nine-phase cycle, generating structured evidence, enforcing minimality, and anchoring baseline commits in the task file; and (2) a *decoupled reviewer gate* (`kata --judge` and `kata --check-only`), which operates non-interactively, re-executing verification commands and auditing repository diffs against baseline anchors. This architectural separation ensures that while the authoring cycle provides deliberate friction and governance for complex, open-ended tasks, automated pipelines and routine pre-commit workflows can deploy the verification gate (without the anchor-protection that `--trusted-base` adds in CI, Section 6.4), which took a median of about two seconds per change on the real repositories of Section 9.3.

4.1 Architecture

`kata.fit` measures the real diff against `HEAD` (including untracked files) and applies the triviality gate (at most one changed file and fewer than ten changed lines); Listing 2 describes the diff measurement and the gate. `kata.verify` runs lint, a declared typecheck, tests, and coverage with a numeric gate, reading exit codes rather than model intentions (Listing 3); a declared role in `.kata/config.yaml` runs verbatim, so the tool does not assume the target project is Python. `kata.judge` treats the task file as a collection of claims, re-runs the claimed checks, diffs the claims against the repository, and hunts eight fraud categories: weakened checks, false completion, scope creep, unauthorized actions, specification betrayal, debris, baseline tampering, and a triviality claim the measured diff does not support (Listings 5–6). The evaluated version hunted the first seven; the eighth was added in 0.8.0. `kata.cli` orchestrates the nine phases, persists the task file, and exposes the audit and judge modes (Listing 4). Section 4.4 presents these algorithms in full as numbered Listings.

4.1.1 Language-agnostic verification

Kata does not assume the project it verifies is a Python project. The project itself knows how to check its repository, so the commands live in `.kata/config.yaml`, next to the task files:

Listing 1. Declaring the verification commands of a non-Python project.

```
verify:
  lint: npx eslint src tests
  test: npx vitest run
  coverage: npx vitest run --coverage
  coverage_pattern: 'All files\s+\|\s+([\d.]+)'
  gate: 80
```

Every key is optional. A role that is not declared falls back to the Python default for that role (ruff, pytest, pytest-cov) and keeps obeying the path flags, so a project can replace only its linter and keep pytest. The exception is `typecheck`: there is no universal type checker, so an undeclared typecheck does not run and `verify.typecheck_clean` stays `null`, never `true`. A declared role is run verbatim and judged by its exit code, the one contract every lint and test tool honours. Coverage is the other exception: the built-in path delegates the gate to `--cov-fail-under`, which does not exist outside Python, so a declared coverage command has its percentage extracted with `coverage_pattern` and compared here. If the pattern matches nothing, the check fails rather than recording 0.0% as a pass — "could not measure" is not "measured and passed". When the project declares several coverage sources, all of them are passed to pytest-cov, so the gate measures the surface the project declared rather than a subset of it.

Table 1. Comparison of Kata with related tools and methodologies. Qualitative assessment by us from the cited sources at the commits cited in the bibliography (accessed 2026-09-11): see the text for the operationalization of each dimension. The dimensions are derived from the reward-hacking problem space (Section 1), not from Kata's architecture. The assessments are our read of the public artifacts; the executed comparison of Section 9.2 supersedes this table for the gates that could be run.

Tool	Re-execute claims	Weakened tests	Scope creep	False completion	Blind-spot confession	Audit record
Fable Method Sahir619 (2026)	No	Partial	No	No	No	Yes
claude-wizard vlad-ko (2026)	No	Partial	No	No	No	No
Ring LerianStudio (2026)	No	No	No	No	No	No
nova TeamSPWK (2026)	No	Partial	No	No	No	No
Consort Hartman (2026)	Yes	No	No	No	No	No
SpecBench Zhao et al. (2026)	Yes	N/A	N/A	N/A	N/A	No
SWE-bench Jimenez et al. (2024)	Yes	N/A	N/A	N/A	N/A	No
Kata	**Yes**	**Yes**	**Yes**	**Yes**	**Yes**	**Yes**

Sources: Fable Method Sahir619 (2026); claude-wizard vlad-ko (2026); Ring LerianStudio (2026); nova TeamSPWK (2026); Consort Hartman (2026); SpecBench Zhao et al. (2026); SWE-bench Jimenez et al. (2024). "Partial" means the tool discusses the fraud type but does not execute a detector for it. Benchmarks (SpecBench, SWE-bench) re-execute checks by design but do not audit or detect frauds. The *Blind-spot confession* column favors Kata partly by protocol: in the executed comparison of Section 9.2, the other tools' agent-reporting schema had no `UNVERIFIABLE` verdict to offer, so a gate could only accuse or stay silent, not confess (Section 9.2); this row is not evidence that the other tools cannot represent that state, only that this comparison did not give them the option. Likewise, the "No" entries for scope creep and false completion record what the tools' public documentation describes, not what they detect: in the executed comparison nova and claude-wizard detected the planted scope creep (s02) and false completion (s03).




Figure 1. The Kata cycle: nine phases plus the optional adversarial JUDGE. Shaded phases (FIT, VERIFY, JUDGE) are backed by executable Python logic; the remaining phases are guided by skills and recorded in the task file, which the objective phases confront with the repository. Dashed arrows show the optional flows: the triviality gate skips the planning phases (FIT to VERIFY directly), VERIFY loops on failure with a hard bound of three attempts before handing the task back to the user, and JUDGE runs after REPORT only when requested. TWIN CHECK runs only for approved tasks, and both the plan-first and the question routes run THINK before stopping — the diagnosis benefits from declaring the problem and the criterion first.

A config file that exists but is invalid aborts with exit code 1. Falling back to ruff silently would report the success of a check the project never asked for, and that is the kind of fabricated claim the judge exists to detect. Since 0.8.0 the refusal is stricter: an unknown key at any level is a named error, because a misspelled section (`veirfy:`) used to fall back to the Python defaults with no warning, and a command containing a shell operator (`&&`, `||`, `|`, `;`, `>`) is refused as well. Commands run without a shell, so `npm run check && npm run test:db` would reach npm as arguments and exit 0 with the second tier never executed; the project must declare a script or an explicit `bash -c`. A path flag that no longer applies because its role is declared is reported as ignored instead of being silently discarded. The JUDGE follows the same line: it knows the test syntax of Python, JS/TS, Go, Ruby, Rust, Java/Kotlin, C#, PHP, and Swift (the language probes implemented in `kata/judge.py` as a per-language table of *weakened*, *empty-body*, *no-op*, and *assertion-family* patterns). A language outside this list (for example, Elixir `.exs`) becomes a declared blind spot, not silence. The 70% coverage gate that the built-in verification default uses is a project convention carried from Kata's own repository, not a research finding: the effective gate is resolved per run as the `--gate` flag if given, then `verify.gate` from `.kata/config.yaml`, then 70%, and the JUDGE compares the measured coverage against whatever gate the project ended up with (Section 8).

The frontends are generated, not hand-maintained. The phase prompts live once in `phases/*.md` and are rendered into the OpenCode agent and the Claude Code skills by a build script (`scripts/build_skills.py`), following the same single-source discipline that Section 4.4 applies to the executable modules. Structurally, the frontends adapt to each host's execution model: in OpenCode, Kata provides an autonomous orchestrator agent (`@kata`) and individual phase skills; in Claude Code, where an isolated subagent would conceal the interactive questions from the main dialogue, Kata runs directly in the primary conversation through skills alone (`skills/kata/` orchestrating the phase skills). The script measures the shared fraction by rendering every

source for both frontends and diffing the outputs line by line: 92.8% of the rendered lines are shared at tag `v0.8.0` (93% at whole-number precision), and the remainder is declared difference — host tool names, identity wording, and capability blocks such as the closed-choice ask — reported by `python3 scripts/build_skills.py --stats`. The figure moves as the phase sources grow: the same command reported 92.6% at `v0.7.0` and 92.8% at `v0.8.0`. The 395 divergent lines are the count we observed between the two hand-maintained copies before the single-source migration; that figure is historical and the script does not re-derive it. This single-source design exists because the previous arrangement — two hand-maintained copies — failed: the copies accumulated those 395 divergent lines, including an improvement applied to one frontend and forgotten in the other. A test fails when the generated files drift from the source, so the divergence cannot pass unnoticed.

4.1.2 Domain adapters

Kata extends the cycle to non-coding tasks without changing the underlying pipeline through domain adapters. A task declares its domain in the task file (`domain: devops`, for example); the orchestrator loads the adapter after FIT and applies its domain-specific evidence set and fraud table. Each adapter defines: the domain scope (what it covers and explicitly does not cover), the evidence (files and state to inspect before acting), the authority (who decides correctness in the domain), how to verify by observation, a domain-specific fraud table, a binding minimum evidence set, FIT routes by task shape, and red lines (actions never allowed without documented human authorization).

Adapters are optional: a missing adapter does not fail `--doctor` or stop the cycle, because the default domain is `coding` and most tasks do not need an adapter. When a domain adapter is missing for a non-coding task, the orchestrator records the skill name in `preflight.skills_missing` and falls back to the adapter's minimal contract. Kata ships four domain adapters: `kata-devops` (Docker, Docker Compose, Terraform, Nginx, GitHub Actions, deploys, and healthchecks), `kata-data-analysis` (pandas, notebooks, SQL, dashboards, and data pipelines), `kata-research` (bibliographic search, literature review, and academic synthesis), and `kata-docs` (READMEs, technical specifications, and architecture guides). New adapters follow the canonical schema in `domains/TEMPLATE.md` and are compiled to both frontends by the same build script that generates the phase skills, so an adapter is written once and served to both hosts.

4.2 Design trade-offs

The cycle encodes two design trade-offs.

The first is the **done criterion** (Fable Step 1): THINK records what "ready" means and how it will be verified *before* the evidence exists, and VERIFY confronts that declared criterion with the final result. Without this, the success criterion only exists after the work is done, and "is it satisfied?" becomes unfalsifiable.

The second is the **hard bound** (Fable Step 5): after three failed verification attempts the task is handed back to the user with what was tried, the real output, and the current hypothesis, instead of looping fix-verify forever. The JUDGE also confesses its blind spots: if it could not observe something (a test language it has no probes for, a file outside the diff), the verdict is UNVERIFIABLE, never VERIFIED — "I could not look" is never reported as "all clear".

4.3 The claim-based verification model

The JUDGE's design is organized around a claim-based verification model that distinguishes Kata from both prompt-based skills and benchmark harnesses. A task file is treated as a collection of claims — "lint clean", "tests pass", "coverage at the gate", "two files changed surgically", "intent aligned" — and each claim is confronted with the repository in one of three ways:

- **Re-executed**: lint, tests, and coverage are re-run and their exit codes compared with the claimed results. A claim that fails re-execution is a false completion fraud.
- **Confronted with the diff**: surgical scope and intent alignment are checked against the actual changed files. A file changed but not declared is scope creep; an intent gate that recorded disagreement but was approved anyway is specification betrayal.
- **Accepted without verification**: the success criterion is a subjective confirmation the user gives during VERIFY, and no command reproduces it. The JUDGE lists it separately as accepted without verification, and it adds a caveat. Counting it as verified is the fraud the judge exists to hunt.

This three-way classification keeps the JUDGE honest in both directions. It does not over-claim: claims it cannot re-execute are confessed, not assumed. Neither does it under-claim: claims it can re-execute are always re-run, never taken at face value. The same model applies to the audit mode, which grades each phase as followed, skipped, faked, or degraded by comparing the task file's content with what the phase was supposed to record. Section 4.4 makes the objective logic behind these phases explicit: Listings 2–9 describe, in a readable form, exactly what each executable phase computes, so the description of the tool and the tool itself can be compared.

The claim-based model also connects Kata to the broader verification literature: the same pattern has emerged independently in other domains, as Section 3 surveys and Section 10 develops. Kata's contribution is to apply the claim-verification pattern to the software change itself, where the claims are the task file and the ground truth is the repository.

4.4 Descriptive algorithms

The objective phases of the cycle are executable Python. This subsection presents, as numbered Listings, a readable, implementation-oriented description of the algorithm behind each executable module. Each Listing is anchored to the code as cited in the Declarations (commit `230e81a` of the evaluated version); line references are from that revision.

Fit gate. Listing 2 measures the real diff a task brings and applies the triviality gate. The critical detail is that Git's `diff` — unstaged, staged, or against a commit — is blind to files that never entered the index, so `untracked_stats` counts the lines of untracked files explicitly (`kata/fit.py:23`). A file that cannot be inspected (binary, or larger than `MAX_UNTRACKED_FILE_BYTES` = 256 KiB, `kata/verify.py:63`) counts as ten lines, which is exactly the number that fails the triviality gate: "could not look" must not become "trivial change", or the cycle would skip SIMPLIFY, INTENT, and SURGICAL where there is the least evidence to trust.

Listing 2. fit gate (kata/fit.py).

```
ALGORITHM fit_gate(cwd)
  // diff_stats: real diff against HEAD, including
     untracked files
  1  files <- []
  2  lines <- 0
  3  result <- git diff HEAD --name-only       //
     staged + unstaged
  4  if result failed then result <- git diff --name-
     only
  5  if result failed or output empty then result <-
     git diff --cached --name-only
  6  files <- non-empty lines of result.stdout
  7  for each line of git diff HEAD --stat (or
     fallback variant):
  8      if line matches |<N>        then lines <-
     lines + N
  9  (new_files, new_lines) <- untracked_stats(cwd)
 10  files <- files union new_files
 11  return (files, lines + new_lines)

  // untracked_stats: untracked files are invisible to
      every git diff
 12 for each f in untracked_files(cwd):            //
     git ls-files --others
 13     if not is_inspectable(f)                    //
      binary or > 256 KiB
 14         then new_lines <- new_lines + 10        //
      "cannot look" fails the gate
 15     else count utf-8 lines of f, summing into
     new_lines
 16     on OSError/UnicodeDecodeError: new_lines <-
     new_lines + 10

  // triviality gate (fable-method)
 17 is_trivial(files, lines) := len(files) <= 1 AND
     lines < 10
```

Verification pipeline. Listing 3 runs the three roles of the evaluated version — lint, test, coverage — respecting the project's declared commands from `.kata/config.yaml` when present (`config.py`), and falling back to the Python defaults otherwise. The 0.8.0 pipeline adds the declared `typecheck` between lint and test; it has no default and does not run when undeclared. Three properties are deliberate. A declared role runs verbatim and is judged by its exit code, the one contract every lint and test tool honours. Coverage is short-circuited when the test step fails, since a coverage number on top of a failing suite is deceptive and uninformative. And "could not measure" is never recorded as "measured and passed": when the coverage pattern matches nothing, the check fails with a named error instead of reporting 0.0% as a pass (`verify.py:201--207`).

Listing 3. verification pipeline (kata/verify.py).

```
ALGORITHM run_all(ruff_paths, test_paths, ignore,
    cov_source, gate, config)
  1  cfg <- config or VerifyConfig()     // roles from
      .kata/config.yaml
  2  if cfg.lint declared  then ruff <- run_command(
    cfg.lint)       // verbatim, exit code
  3                      else ruff <- run_ruff(
    ruff_paths)          // python -m ruff check
  4  if cfg.test declared  then pytest <- run_command(
    cfg.test)
  5                       else pytest <- run_pytest(
    test_paths, ignore)
  6  if pytest.ok:
  7      if cfg.coverage declared  then coverage <-
    run_command_coverage(cfg.coverage,
  8
                       pattern, gate)
  9                              else coverage <-
    run_coverage(source,
 10
              test_paths, gate)
 11  else coverage <- FAIL("skipped - tests failed")
      // short-circuit
 12  return {ruff, pytest, coverage}

  // built-in coverage: gate delegated to pytest-cov --
    cov-fail-under
 13 run_coverage: cmd <- pytest <test_paths> --cov=<
    src>...
 14               --cov-report=term-missing --cov-fail-
    under=<gate> -q
 15               ok <- (exit code 0)  AND  TOTAL line
     matches
 16               ^TOTAL\s+.*?(\d+(?:\.\d+)?)%    //
    else FAIL, never 0.0% pass
 17 // declared coverage: percentage extracted by
    pattern and compared here
 18 run_command_coverage: match <- re.search(pattern,
    output)
 19   if no match or no capture group or group not
    numeric: FAIL (named error)
 20   ok <- (exit code 0) AND float(match[1]) ≥ gate
```

Cycle orchestration. Listing 4 is the interactive driver (`kata/cli.py`). It persists the task file after every phase with an atomic write (`mkstemp + fsync + replace`, `cli.py:115`), so an interrupted cycle can be resumed. The routes matter: a trivial task skips THINK through SURGICAL via the triviality gate; `--plan` and the `plan-first` route run THINK and stop, leaving a plan; the `question` route also runs THINK and stops, leaving a diagnosis. The verify step implements the hard bound of Fable Step 5: a counter of *failed* attempts persisted in the task file hands the task back to the user after three failures.

Listing 4. cycle orchestration (kata/cli.py).

```
ALGORITHM main()
  1  parse args; reject mutually exclusive modes;
     validate task name
  2  if --doctor then print skill install per frontend
     ; exit 1 iff partial
  3  mkdir .kata/; config <- load_verify_config()
       // ConfigError ↪ exit 1
  4  gate <- --gate flag else config.gate else 70
  5  cov_source <- --cov-source else pyproject [tool.
     coverage.run] source else "src"
  6  branch by mode:
  7    --init TASK:  create template; capture
     base_commit + git anchor
```

```
 8                refs/kata/base/<sha256(task)>;
   run FIT, THINK; save; stop
 9    --report:    outcome-first report; exit 1 iff
   status rejected
10    --judge:     judge_task(); print verdict; exit
    1 iff REFUTED
11    --audit:     grade phases; exit 1 iff any
   phase not followed
12    --check-only: run_all(); exit 0 iff approved
13    default:     pick task (branch name > menu >
   new); run cycle:
14      FIT
15      if trivial or plan or route in {question,
   plan-first}: THINK
16      if route == question:      stop
17      if plan or route == plan-first: stop (plan
   saved)
18      if not trivial: SIMPLIFY, INTENT, SURGICAL
      // judgment phases
19      VERIFY                          // hard bound:
   hands back after 3 failures
20      if not trivial: TWIN CHECK   // approved
   tasks only
21      ARTIFACT, REPORT
22   after each phase: save task file (atomic write)

 // VERIFY in detail
23 results <- run_all(...); print lint/test/coverage
   with real exit codes
24 success_criteria_met <- user confirms (or True in
   --check-only)
25 attempts <- persisted count of FAILED runs, not
   executions
26 if not all_ok: attempts <- attempts+1; hand_back <-
    attempts ≥ 3
27 status <- approved iff all_ok and
   success_criteria_met
28 if approved: approved_commit <- HEAD            //
    R14: ceiling of the diff
```

The adversarial judge. Listing 5 is the claim-based verification model of Section 4: it treats the task file as a collection of claims, confronts them with the repository, and returns a verdict. The baseline handling is adversarial: the declared `base_commit` must match the Git anchor recorded when the task started (else *baseline tampering*), and `approved_commit`, when present, is the *ceiling* of the diff, so later tasks' changes do not count as undeclared scope for this one (`judge.py:1377`).

Listing 5. adversarial judge (kata/judge.py).

```
ALGORITHM judge_task(task_data, cwd, config)
  1  task_data, blind_spots <- normalize(task_data)
  2     // sections that are not maps or files lists
     with non-maps become
  3     // a confessed blind spot, never an
     AttributeError (traceback exits 1,
  4     // the same code as REFUTED -
     indistinguishable to CI readers)
  5  base <- task_data.base_commit; anchor <- git refs
     /kata/base/<hash(task)>
  6  if anchor exists but differs from base
     ↪ baseline_tampering (high)
  7  if base does not resolve or is not ancestor of
     HEAD ↪ baseline_tampering
  8  ceiling <- task_data.approved_commit           //
      R14
  9  if ceiling present but invalid ↪
     baseline_tampering; else diff <- base..ceiling
 10  diff <- git diff (base..ceil) + synthetic
     untracked adds; skip ".kata/" bookkeeping
 11  changed <- changed files in the same window
 12  claims <- collect_claims(task_data)   // lint/
     test/coverage/surgical/intent
 13  unverifiable <- collect_unverifiable_claims(
     task_data)  // success criterion
 14  re_ran <- {} ; if claims mention checks:
 15      results <- run_all(...)           // re-
     execution
 16      re_ran <- {check: results[check].ok}
 17  frauds <- baseline_frauds
 18  frauds += hunt_weakened_checks(diff)          //
     Listing 6
 19  frauds += hunt_false_completion(task_data, re_ran
     )     // claimed pass, rerun fails
 20  frauds += hunt_scope_creep(task_data, changed)
         // changed but not declared
 21  frauds += hunt_unauthorized_action(task_data)
         // auth_owed, no AUTH line
 22  frauds += hunt_spec_betrayal(task_data)
         // intent.all_agree == false
 23  frauds += hunt_debris(diff, changed)
         // .tmp, scratch, debug prints
 24  blind_spots += unreadable test languages; ignored
      code files; no claims at all
 25  verdict <- high frauds? REFUTED
 26             : any frauds?       VERIFIED WITH
     CAVEATS
 27             : blind_spots?      UNVERIFIABLE    //
      "could not look" never "all clear"
 28             :                   VERIFIED
```

Weakened-checks hunt. Listing 6 is the most elaborate of the hunters. A weakened check is a test that exists, runs, and verifies nothing: a body replaced by `pass`, an assertion commented out, a new test whose first instruction is a no-op (`assert True`, `pytest.skip`, `it.skip`, `t.Skip`, `XCTSkip`). The hunts are language-aware: probes for each language (`judge.py:29--339`) define what a removal, an empty body, and a no-op look like in that syntax, so a Go pattern is never applied to a Ruby file. One subtlety deserves emphasis: the *pair rule*: a removed assertion is only a fraud if no added line in the same file contains an assertion of the same family, because changing `expect(x).toBe(1)` to `expect(x).toBe(2)` is a modification, not a removal. Files whose language has no probes are *confessed* as unreadable, never silently cleared (`judge.py:728`).

Listing 6. weakened-checks hunt (kata/judge.py).

```
ALGORITHM hunt_weakened_checks(diff)
  1  current <- ""; is_new <- false; pending <- []
     // removals awaiting decision
  2  for each line in diff:
  3    if line starts with "diff --git":
  4        flush pending into frauds (file:current)
     // removals not revoked
  5        current <- file name; is_new <- false
  6    if "new file mode"    then is_new <- true
     // new files: empty-body scan later
  7    if "deleted file mode" then skip
      // deleting a test is not a weakened one
  8    if not a test file (name/dir convention) or no
     probes for its language: continue
  9    if is_new: collect '+' lines per file; continue
 10    if line starts with '+':
 11        if an assertion of the family is on this +
     line:
 12            pending <- []
      // changed value, not removal
 13        for each (pattern, desc) in probes.weakened:
```

```
14            if pattern matches line:
15                if line starts with '-' and family
    probes exist:
16                    pending += (line, desc)
     // decide at flush
17                else: frauds += (weakened_checks,
    high, desc)
18                break
     // one fraud per diff line
19  4  flush pending at end
20  5  for each new test file: for each empty/no-op
    body found
21        (declaration, skipped comments, docstrings,
     then first meaningful line
22        is pass/assert True/skip/xit/no-op) ↪
    frauds += weakened_checks (high)
23  6  return frauds
```

Audit grading. Listing 7 grades each phase of a completed task as followed, skipped, faked, or degraded, and names the concrete risk each skip or fake created (`report.py:169`). The faked pattern is only catchable because there is objective logic behind it: the audit reads the YAML and detects `answered: true` with empty content, or a verify/twins claim without its evidence.

Listing 7. audit grading (kata/report.py).

```
ALGORITHM audit_task(data)
  1  if preflight.skills_missing is non-empty:
  2      grade preflight as degraded (phase ran
     without its skill)
  3  for phase in {fit, think, intent}:        //
     content key: reason/problem/code_does
  4      if skipped            ↪ grade skipped, state
      the risk
  5      elif not answered     ↪ not graded (task in
     progress)
  6      elif content empty    ↪ grade FAKED, state
     the risk
  7      else                  ↪ grade followed
  8  for phase in {simplify, surgical}:        //
     content key: minimum_code/files
  9      same decision; empty/missing content ↪ FAKED
 10  verify:  success_criteria_met but no evidence (
     ruff/tests/coverage false)
 11           ↪ FAKED ("success affirmed without
     execution"); evidence ↪ followed
 12  twins:   defect_fixed but not searched ↪ FAKED;
     searched ↪ followed
 13  return grades + concrete risk per non-followed
     phase
```

Preflight and trap harness. Listing 8 checks skill installation per frontend; Listing 9 drives the adversarial trap suite (`eval/run_traps.py`): every scenario pairs a `fixture/` with a `ground_truth.yaml` specifying the expected verdict and the exact frauds, and the harness fails when the verdict differs, a fraud is missing, or an unexpected fraud appears. A new scenario must be shown to fail when its defect is reintroduced, so a scenario that passes in both states protects nothing.

Listing 8. preflight doctor (kata/skills.py).

```
ALGORITHM doctor()
  1  for each frontend in {opencode, claude-code}:
  2      expected <- phase skills (+ orchestrator "
     kata" for claude-code)
  3      installed <- {s in expected : exists(
     config_dir/skills/s)}
  4                    // a broken symlink does not
     count: exists() follows links
  5      partial <- some installed and some missing
  6  return per frontend: ausente | parcial | completo
  7  exit 1 iff any frontend is partial
     // absent is fine (CLI works without frontends);
     // partial silently loses a phase of the cycle
```

Listing 9. trap harness (eval/run_traps.py).

```
ALGORITHM run_traps()
  1  for each scenario in eval/scenarios/        //
     sorted; 24 as executed
  2      in a fresh sandbox (excluding .kata/ from git
     ; one scenario opts
  3        in to the real environment with
     kata_visivel: true)
  4      repeat gt.judge_runs times in the same
     workspace   // s23: the
  5          // judge's own run leaves artifacts; run
     two must not accuse them
  6      run kata --judge inside the fixture
     // no access to ground truth
  7      gt <- ground_truth.yaml (expected verdict +
     exact frauds)
  8      fail if  verdict != gt.expected_verdict
  9           or  any expected fraud missing
 10           or  any unexpected fraud present
      // two-sided contract
 11      if gt.expected_audit:
 12          run kata --audit and compare per phase
     // grades, e.g. gauntlet
 13  // honest scenarios must return VERIFIED, blind
     spots UNVERIFIABLE,
 14  // fraud scenarios REFUTED; a scenario that
     passes with its defect
 15  // reintroduced protects nothing and is rejected
```

The listings share one discipline that the reader should verify against the code: what is executable is executed, and what cannot be executed is declared. Listing 2 fails the gate rather than guess a line count it could not measure; Listing 5 returns UNVERIFIABLE rather than VERIFIED when it could not observe; the audit grades *degraded* a phase whose own skill was never loaded. Every placeholder in these descriptions is a decision that the code makes explicitly, and each such decision is covered by a unit test in `tests/`.

4.5 Changes in version 0.8.0

The evaluation in this paper was run against the code identified in the Declarations as the evaluated version. The current release, 0.8.0, is not that code: it keeps the nine-phase cycle and the verdict model, and changes the evidence it records and the edges it checks. The additions are:

- **A fourth verification role.** A project may declare `verify.typecheck`; it runs between lint and test and is judged by its exit code. It has no default, and `verify.typecheck_clean` stays `null` when the role is undeclared, because no universal type checker exists and a role that did not run must not be recorded as passed.
- **Execution evidence.** VERIFY stamps `kata_version`, `gate_used`, `commands` (role → command), and `ran_at` in the task file; the report prints them, and the JUDGE compares them with its own run, adding a

caveat when the version, the gate, or a command differs from the recorded one.

- **A closed diff window.** `approved_commit` is not recorded while `HEAD` is still the baseline, because a ceiling equal to the floor is an empty diff window. `kata --stamp TASK [--commit SHA]` records the commit that ends the task, validating that it resolves, descends from `base_commit`, and is an ancestor of `HEAD`.
- **An eighth fraud category.** `hunt_triviality_claim` flags `fit.trivial=true` with no declared files when the measured diff exceeds a deliberately gross tolerance (100 added lines or ten files). The three-file honest task of s16 remains `VERIFIED`, because the tolerance is set to catch a sixteen-thousand-line change approved as trivial, not a small helper change.
- **A finer false-completion rule.** A check that did not run because the environment lacks the tool is a confessed blind spot, not a false completion: "I could not run it" is not "I ran it and it failed".
- **Attribution inside the window.** Commits that fall between `base_commit` and `approved_commit` are attributed to sibling tasks by the stamps the repository already holds: a commit stamped by an approved sibling leaves the window with a caveat naming the commit and the task, and an unstamped commit makes the verdict `UNVERIFIABLE` rather than accusing honest work or blessing it.
- **Stricter configuration and diagnosis.** Unknown keys at any level of `.kata/config.yaml` are named errors; shell operators in a declared command are refused; `kata --doctor` reports skills installed by a different Kata version; and a path flag ignored because its role is declared is reported instead of silently discarded.

These changes are covered by the unit suite and by the current trap suite of 25 scenarios (s20–s25 were added after the evaluation, together with the fixes they guard). They do not alter the 19-scenario results reported in Section 9, and we did not re-run the evaluation on 0.8.0; the Declarations state which commit produced each number.

5 The development cycle in action

To demonstrate the cycle, we applied Kata to a real bug fix in a small example project: a calculator whose `dividir` (divide) function raised an unhandled `ZeroDivisionError`. The change adds a `ValueError` guard and a regression test. The working tree contains two modified files (11 changed lines), so the FIT gate classifies the task as non-trivial and routes it to the full cycle.

5.1 FIT — task classification

The FIT phase measures the real diff and classifies the task; its control flow is Figure 2.

```
diff: 2 file(s), 11 changed line(s)
↪ non-trivial task

Available routes:
  [1] code-loop   - full cycle
  [2] plan-first  - planning only
  [3] question    - diagnosis only
  [4] research    - needs research before acting
  [5] inference   - based on inference only

Chosen route [1]: 1
Brief justification (optional): fix division by zero
    without a guard
```

A trivial task (at most one file, fewer than ten lines) would skip the planning phases and go directly to VERIFY — the triviality gate of the Fable Method. In the evaluated version, and still in 0.8.0, the measured diff counts untracked `.kata/*.yaml` files (the task file itself and the project configuration), so in a project that does not ignore `.kata/` a one-line change is no longer trivial: one file becomes two files and three lines in our reproduction on 0.8.0. The JUDGE and the SURGICAL file list filter this bookkeeping, but `fit.diff_stats` does not; the trap harness hides the defect because it git-excludes `.kata/` in every fixture. No trap scenario covers it. This is a defect of the current release, not a historical note: a reader who relies on the triviality gate should ignore `.kata/` in the project or accept that a one-line change may take the full cycle.[1]




Figure 2. The FIT phase. The real diff is measured including untracked files; the triviality gate re-confirms with the user, because "one file, fewer than ten lines" does not by itself prove that behaviour is unchanged; and the five routes diverge, with `plan-first` and `question` running THINK before stopping (Section 5). The baseline commit and its Git anchor are captured here.

5.2 THINK — declaring before the evidence

THINK records the problem, assumptions, alternatives, unknowns, and the done criterion *before* the evidence exists (Figure 3):

```
What is the exact problem I am solving?
  the dividir (divide) function raises
   ZeroDivisionError with no guard
What assumptions am I making? (semicolon-separated)
```

[1] The `kata` CLI reports in Portuguese; the CLI outputs quoted in this paper are translated into English for presentation. Recurring terms: *não-trivial* = non-trivial; *rota escolhida* = chosen route; *arquivo(s)* = file(s); *linha(s)* = line(s); *limpo* = clean; *passou* = passed; *critério de sucesso* = success criterion; *veredito* = verdict; *fraude(s)* = fraud(s); *re-execução* = re-execution; *ocorrência(s)* = occurrence(s).

```
    none; API is stable
  What alternatives did I consider? (semicolon-
     separated)
    guard with ValueError; return None
  What do I NOT know? (do I need to ask first?)
     nothing
  What is 'done'? (success criterion + how I will
     verify it)
    test test_dividir_por_zero passes and coverage ≥
     70%
```

The done criterion is declared before the evidence exists (Fable Step 1). VERIFY will confront this declared criterion with the final result — not ask "is it satisfied?" to a criterion that only exists afterwards.




Figure 3. The THINK phase. The problem, assumptions, alternatives, unknowns, and the *done* criterion are declared before the evidence exists. In non-interactive mode the section is recorded with `skipped: true` — not `answered` — so the phase is not silently retired for a later interactive run.

5.3 SIMPLIFY, INTENT, SURGICAL — minimalism and intent gates

SIMPLIFY checks that the solution is minimal, with no single-use abstractions and no speculative configuration (Figure 4). INTENT compares what the code does, what the checks expect, and what the specification says, with the authority order: user statement > specification > tests > current code (Figure 5). SURGICAL reviews every changed file and records whether it is necessary (Figure 6):

```
  What does the code DO today? dividir raises
     ZeroDivisionError
  What does the test/check EXPECT? test expects
     ValueError
  What does the specification/README SAY? README does
     not mention the case
  Do code, test, and specification agree? [Y/n]: y

Changed files:
  src/calculadora.py - necessary for this task? [Y/n]:
      y
  tests/test_calculadora.py - necessary for this task?
      [Y/n]: y
  Are the removed imports only those your change made
     unused? [Y/n]: y
```

5.4 VERIFY — objective verification

VERIFY runs the objective checks in order: lint, test, coverage against the gate, and the success criterion confronted with the done criterion declared in THINK (Figure 7):




Figure 4. The SIMPLIFY phase. The diff — including the untracked files that no `git diff` shows — is presented before the three minimality questions. A task that only creates files still gets asked, instead of passing the gate with no question at all.




Figure 5. The INTENT phase. Code, checks, and specification are compared before behaviour changes; a disagreement is resolved in the authority order and recorded as `conflict_resolution`. The JUDGE reads only an *unresolved* disagreement as specification betrayal, so the recorded resolution of a bug fix is not an accusation.




Figure 6. The SURGICAL phase. Every changed file is declared necessary or not, and that declaration is the contract the JUDGE enforces: a changed file that was not declared is scope creep.

```
▶ ruff check src/ tests/
  ✓ clean

▶ pytest tests/ --tb=short -q
```

```
  ✓ passed

▶ coverage (gate ≥ 70%)
  ✓ passed (100.0%)

▶ Success criterion of the task
  (declared in THINK: test test_dividir_por_zero
     passes and coverage ≥ 70%)
  Is the success criterion of the task satisfied? [Y/n
     ]: y

  ! approved_commit not recorded: HEAD is still
     base_commit
      After the commit, run `kata --stamp fix-division-
     by-zero`

  ✓  KATA CYCLE - APPROVED
```

Each role runs the command declared in `.kata/config.yaml` for that role, or the Python default (ruff, pytest, pytest-cov with `--cov-fail-under`) when the role is not declared; `typecheck` is the exception with no default, and it only runs when declared. Coverage is short-circuited when the test step fails. A task is approved only when all checks and the success criterion pass. In 0.8.0 the VERIFY also records the execution evidence — the version, the gate, the commands, and the timestamp — and, when the approval happens before the commit, warns that `approved_commit` is not stamped and prints the `--stamp` command that closes the JUDGE's window.




Figure 7. The VERIFY phase. Lint, test, and coverage are judged by exit codes; coverage is short-circuited when the tests fail; an unmatched coverage pattern fails with a named error rather than recording 0.0% as a pass. The attempt counter records *failed* runs, and after three the task is handed back to the user.

5.5 TWIN CHECK — searching for recurring patterns

TWIN CHECK (Figure 8) runs after VERIFY and only for an approved task. When a defect has been fixed, the same pattern often exists elsewhere. If the INTENT gate recorded a disagreement (`all_agree: false`), TWIN CHECK automatically infers that a bug was resolved; otherwise, it asks the user whether one was. When confirmed, it searches the project for the pattern and records the answer:

```
  Was a defect fixed? Search for a similar pattern? [y
     /N]: y

  Pattern to search (regex): a / b
  Searching for 'a / b' in the project...
  ✓ Found in 1 file(s):
     ./src/calculadora.py:7  return a / b
  Fix the remaining occurrences now? [y/N]: n
```

Recording a negative answer distinguishes "no defect" from "not checked", which is the point of asking.




Figure 8. The TWIN CHECK phase. For an approved task, the project is searched for the pattern of the defect that was fixed, and the result — including a negative one — is recorded. That record is what distinguishes "no defect" from "not checked"; recording `defect_fixed` without a search is graded `faked` by the audit.

5.6 ARTIFACT and REPORT — the due lines

ARTIFACT verifies that the evidence lines that are due are present (Figure 9): INTENT (due when behavior changed), AUTH (due when an irreversible external action was taken), PENDING (due when documentation prescribes a follow-up that was not taken), and TWINS (due when a defect was fixed). REPORT (Figure 10) prints the outcome first, followed by the problem, the done criterion, changed files, verification results, caveats, and any due artifact lines:

```
✓  KATA CYCLE - APPROVED: success criterion satisfied

  Problem: the dividir (divide) function raises
     ZeroDivisionError with no guard
  Declared criterion: test test_dividir_por_zero
     passes and coverage ≥ 70%
  Changed files: src/calculadora.py, tests/
     test_calculadora.py
  INTENT: code does dividir raises ZeroDivisionError;
     check expects
          test expects ValueError; spec says README
     does not mention the case

  Checks:
  ✓ ruff check clean
  ✓ pytest passed
  ✓ coverage 100.0% ≥ gate
  ✓ success criterion satisfied
```

```
TWINS: searched a / b - found 1 file(s), 1
   occurrence(s)
```




Figure 9. The ARTIFACT phase. Each of the four evidence lines has its own trigger; a line that is due but missing is asked for and recorded. A gate that fired on every task would be noise, which is why `TWINS` is due only when a defect was actually declared fixed.




Figure 10. The REPORT phase. The outcome comes first, then the problem, the criterion declared in THINK, the evidence, the caveats, and the due lines. A task still in progress reports only its status: planning is not failing.

5.7 The task file

The entire cycle is persisted in a task file (`.kata/<task>.yaml`), so the evidence behind an approval is persistent and auditable, not conversational. The file records the done criterion, the FIT classification, the THINK declarations, the SIMPLIFY/INTENT/SURGICAL answers, the VERIFY results (including the coverage percentage and the attempt counter), the TWIN CHECK result, and the artifact checks. It also records `kata_version` and, in the verify block, `gate_used`, `commands`, and `ran_at`, so the JUDGE can tell whether the version, the gate, or the command it re-runs is the one that produced the evidence. `base_commit` (the HEAD captured when the task started) and `approved_commit` (the commit that ends the task) define the diff window, which allows the JUDGE to diff `base..approved` even after the task has been committed — changes made by later tasks do not count as undeclared scope for this one. `approved_commit` is not written while HEAD is still the baseline; the commit is stamped afterwards with `kata --stamp`.

The task file from the demonstration of Section 5 is shown in Listing 10. Note the structure: every phase has an `answered` flag (true when a human answered, false when filled with defaults) and a `skipped` flag (true only in non-interactive mode). The audit mode reads these flags to distinguish followed, skipped, and faked phases. The `verify` section records the attempt counter and the hand-back flag, which implement the hard bound of Fable Step 5. The `twins` section records whether a defect was fixed and whether a pattern search was performed — recording a negative answer is what distinguishes "no defect" from "not checked".

Listing 10. Task file produced by the demonstration cycle.

```
task: fix-division-by-zero
status: approved
done: test test_dividir_por_zero passes and coverage ≥
     70%
kata_version: 0.8.0
fit:
  trivial: false
  route: code-loop
  reason: fix division by zero without a guard
  answered: true
think:
  problem: the dividir (divide) function raises
     ZeroDivisionError with no guard
  assumptions: [none, API is stable]
  alternatives: [guard with ValueError, return None]
  unknowns: none
  answered: true
simplify:
  minimum_code: true
  no_single_use_abstractions: true
  no_speculative_config: true
  answered: true
intent:
  code_does: dividir raises ZeroDivisionError
  check_expects: test expects ValueError
  spec_says: README does not mention the case
  all_agree: false
  conflict_resolution: the test prevails; the code
     guards with ValueError
  answered: true
surgical:
  files:
  - path: src/calculadora.py
    necessary: true
  - path: tests/test_calculadora.py
    necessary: true
  removed_imports_clean: true
  answered: true
verify:
  ruff_clean: true
  typecheck_clean: null
  tests_pass: true
  coverage_pct: 100.0
  coverage_pass: true
  success_criteria_met: true
  attempts: 0
  hand_back: false
  gate_used: 70.0
  commands:
    lint: python -m ruff check src/ tests/
    test: python -m pytest tests/ --tb=short -q
    coverage: python -m pytest tests/ --cov=src --cov-
     report=term-missing --cov-fail-under=70.0 -q
  ran_at: '2026-10-29T01:58:46+00:00'
twins:
  pattern: a / b
  result: 1 file(s), 1 occurrence(s)
  searched: true
  defect_fixed: true
```

```
  matches_count: 1
  files_count: 1
  fix_applied: false
preflight:
  skills_missing: []
artifact:
  intent_owed: true
  intent_present: true
  auth_owed: false
  auth_present: false
  pending_owed: false
  pending_present: false
  twins_owed: true
  twins_present: true
base_commit: 762b73cb7343462235d08db2aba13e7f1022c392
# approved_commit absent: HEAD was still base_commit
    at approval.
# After the commit, run `kata --stamp fix-division-by-
    zero`.
```

The task file is the contract between the cycle and the JUDGE. Every section is a claim that the JUDGE can confront with the repository: the verify section with re-execution, the surgical section with the diff, the intent section with the specification, the twins section with a pattern search. The audit depends on this: a phase marked `answered: true` with empty content is a faked phase, and the audit names the concrete risk it created.

6 The adversarial layer: JUDGE

The JUDGE is the phase that no skill can perform (Figure 11). It treats the task file as a collection of claims and confronts them with the repository. It re-runs the claimed checks, diffs the claims against the actual changes, and hunts eight fraud categories:

- **weakened checks**: a test whose body was replaced by `pass`, an assertion turned into a comment, or a new test whose body is only `assert True` — it exists, it runs, it verifies nothing;
- **false completion**: the report claims lint clean, tests passing, and coverage at the gate, but the re-execution fails. In 0.8.0 a command that could not run because the environment lacks the tool is a confessed blind spot, not a false completion: "could not run" is not "ran and failed";
- **scope creep**: the report declares one file, the tree has four;
- **unauthorized action**: an irreversible action was taken without a documented AUTH line;
- **specification betrayal**: the intent gate recorded a disagreement and the task was approved anyway. In the evaluated version this also caught disagreements the gate had resolved and recorded — the normal record of a bug fix, whose honest completion came back `REFUTED`, as it did in six in-session runs of the external study (Section 9.3). Since commit `15ccb7a`, a recorded `conflict_resolution` is accepted without verification and only an unresolved disagreement is betrayal; a twenty-first trap scenario (s21) covers the resolved case;
- **debris**: temporary files in the diff;
- **baseline tampering**: the `base_commit` declared in the YAML diverges from the Git anchor recorded when the task started;
- **triviality claim**: `fit.trivial=true` with no declared files, when the measured diff exceeds a gross tolerance (100 added lines or ten files). Without it, a sixteen-thousand-line change approved as trivial would pass because the triviality flag itself disables the scope hunt. The category was added in 0.8.0 and was not part of the evaluated seven.

Two further checks in 0.8.0 refine the window rather than add categories. The JUDGE compares the recorded version, gate, and commands with the ones it re-runs and adds a caveat when they differ, because a verdict produced under another gate or another command is not the same verdict. And it attributes the commits inside a closed window to sibling tasks by their `approved_commit` stamps: a commit stamped by an approved sibling leaves the window with a caveat naming the commit and the task, while an unstamped commit makes the verdict `UNVERIFIABLE` instead of accusing honest work or blessing it.

These guarantees hold against claims that re-execution or the diff can contradict; they do not hold against an agent that also controls Git metadata or the execution environment. Section 6.4 states that boundary explicitly and reproduces two live bypasses — rewriting the baseline anchor and emptying the diff window — that yield a VERIFIED verdict on a weakened test as evaluated; a reader relying on the JUDGE as a merge gate should read that boundary before the results below.

Frauds are graded by severity: weakened checks, false completion, unauthorized actions, specification betrayal, and baseline tampering are *high-severity*; scope creep is *medium-severity* (when undeclared files number two or fewer) or *high-severity* (when three or more); a triviality claim is *medium-severity* below 1,000 added lines and 50 files, and *high-severity* at or above either; and debris is *low-severity*. Verdict calculation follows strictly (Listing 5): any high-severity fraud produces a `REFUTED` verdict; medium- and low-severity findings yield `VERIFIED WITH CAVEATS`; confessed blind spots without fraud result in `UNVERIFIABLE`; and an entirely clean review with all re-executions passing returns `VERIFIED`.

6.1 Honest work: VERIFIED

After committing the task of Section 5, we ran `kata --task fix-division-by-zero --judge`. The judge re-executed the claimed checks and returned:

```
✓  VERDICT: VERIFIED

  Verified claims:
    • ruff check clean (no lint errors)
    • all tests pass
    • coverage ≥ gate (100.0%)
    • 2 file(s) changed surgically (necessary)
    • intent aligned: code, test, and spec agree

  Claims accepted without verification (not re-
     executable):
    • success criterion satisfied

  Re-execution:
    ✓ lint
    ✓ test
```

```
    ✓ coverage
```

Note that the success criterion is listed as *accepted without verification*: it is a subjective confirmation the user gives during VERIFY, and no command reproduces it. Presenting it as verified would be the fraud the judge exists to hunt. This task was approved before its change was committed. In the evaluated version, `base_commit` and `approved_commit` coincided, so the diff window was empty and the surgical and weakened-check claims were not confronted with a diff (Section 6.4). In 0.8.0 the cycle no longer records `approved_commit` while `HEAD` is still the baseline (Listing 10 shows it absent), and the JUDGE diffs the working tree; after the commit, `kata --stamp` records the commit that ends the task and closes the window.

6.2 Fraudulent work: REFUTED

We then ran the judge against a trap scenario from the evaluation suite: a "completed" task whose report claims ruff clean, tests passing, and coverage at the gate, but where the re-execution fails all three (an unused import in the source, a failing test, and coverage skipped because pytest failed):

```
×  VERDICT: REFUTED

  Frauds found:
    • [high] false_completion
       ruff check re-execution failed, but the report
     claims it passed
       → report: ruff_clean=True → reality: ruff check
      failed
    • [high] false_completion
       pytest re-execution failed, but the report
     claims it passed
       → report: tests_pass=True → reality: pytest
     failed
    • [high] false_completion
       coverage re-execution failed, but the report
     claims it passed
       → report: coverage_pass=True → reality:
     coverage failed

  Re-execution:
    × lint
    × test
    × coverage
```

The verdict is REFUTED, and the exit code is 1. Whereas an instruction-based skill merely requests adherence to verification, Kata deterministically detects the unexecuted assertion and flags the discrepancy against repository state.

6.3 Blind spots are confessed

The judge also confesses its blind spots. If it could not observe something — a test language it has no probes for (it knows Python, JS/TS, Go, Ruby, Rust, Java/Kotlin, C#, PHP, and Swift), a file outside Git's diff, a baseline that no longer resolves — the verdict is UNVERIFIABLE, never VERIFIED. "I could not look" is never reported as "all clear". With fraud present, the fraud decides the verdict and the blind spots are still listed.




Figure 11. The JUDGE phase. The task file is a set of claims; the baseline is checked adversarially; the claimed checks are re-executed; eight frauds are hunted; and what could not be observed is confessed. Only `REFUTED` exits non-zero — a caveat or an honest blind spot is not a failure.

6.4 Threat model

The JUDGE is adversarial toward the claims in a task file, not toward an agent that controls the repository. We state the threat model explicitly, because the difference matters to anyone who uses the JUDGE as a merge gate.

Adversary. A coding agent that writes both the code and the task file, runs shell commands, and can write to the working tree and to the local Git repository, including its refs and `.git/info/exclude`. It wants a passing exit code for work that does not meet its claims.

In scope. Claims that re-execution or the Git diff contradict: checks declared as passing that fail, changed files that were not declared, the planted patterns of Section 9.1, and a `base_commit` edited in the YAML after the anchor was recorded (s14).

Out of scope, with reproduced evasions. Tampering with Git metadata, with the environment the checks run in, or with the machine that runs the JUDGE, and content that is plausible but false. We reproduced the evasions below against `kata/judge.py` as evaluated (unchanged since commit `230e81a`), in a temporary repository whose task replaces a test body with `pass`. Without evasion, the JUDGE returns REFUTED for weakened checks.

- **Rewriting the anchor.** The anchor `refs/kata/base/<sha256(task)>` is an ordinary ref in the repository the agent controls (`record_baseline_ref`, `judge.py:465`). Editing `base_commit` alone is caught as baseline tampering, but moving both the YAML and the ref to the final commit with `git update-ref` empties the diff window, and the verdict is VERIFIED (exit 0). Deleting the ref and editing the YAML yields UNVERIFIABLE (exit 0). After the evaluated version, commit `3454fc7` (shipped in 0.8.0) narrowed this path: the anchor is now written with a reflog, and an anchor that has pointed at

more than one commit is reported as baseline tampering (trap scenario s22). Deleting and recreating the anchor erases its reflog and still evades that check locally; `kata --judge --trusted-base <ref>` closes it in CI by taking the diff floor from the merge base with a ref the agent cannot move, which protects only as far as that ref is protected on the remote.

- **Empty diff window.** The ceiling check (`judge.py:1424`) accepts an `approved_commit` equal to `base_commit`, because Git counts a commit as its own ancestor. The weakened test is then invisible and the verdict is VERIFIED (exit 0), whether or not the change has been committed. No tampering is needed: the cycle records `approved_commit` as the HEAD at approval (`cli.py:902`), so a task approved before its change is committed produces exactly this window. In the evaluated version, the demonstration task of Listing 10 was such a case, and the suite did not exercise it: s17 records an `approved_commit` later than the baseline. s20 now covers it. This path was fixed after the evaluated version, in commit `3cacc5a` (shipped in 0.8.0): when `approved_commit` equals `base_commit` and `HEAD` is still there, the JUDGE diffs the working tree; when `HEAD` has moved on, it confesses the empty window as a blind spot and can no longer return VERIFIED (UNVERIFIABLE when no fraud is found); and the cycle no longer records `approved_commit` while `HEAD` is still the baseline. Regression tests and a twentieth trap scenario (s20) cover the fix. The workflow that closes the window after the commit is `kata --stamp TASK`: it records the commit that ends the task after validating that it descends from the baseline and is an ancestor of `HEAD`. The fix does not close the anchor rewrite above, which we re-ran against it and which still yielded VERIFIED at that commit.
- **Manufacturing a blind spot.** UNVERIFIABLE exits 0 by design (`cli.py:1649`), a fail-open policy chosen so that projects in unprobed languages are not failed wholesale. An agent can exploit it: a weakened test hidden with `.git/info/exclude` (s19) or written in an unprobed language (s12) yields UNVERIFIABLE and passes a gate that reads only the exit code.
- **Declaring everything.** Scope creep compares the diff with the declared files, and `necessary: true` is self-reported: an agent that declares every file it touched is never charged with scope creep, however unnecessary the change.
- **Plausible but false content.** The audit grades a phase as faked when it is marked answered with empty or default content (`_audit_task`, `report.py:169`); a phase filled with plausible but false content is graded followed. `conflict_resolution` is self-reported: accepted unverified, any non-empty text, one line, disarms spec betrayal, a high-severity fraud (commit `15ccb7a`).

These paths bound what a verdict means: VERIFIED says that the claims survived the checks the JUDGE could run over the diff window it was given, not that an agent with repository access could not have arranged that window. Detecting a deleted and recreated anchor without a trusted base, a fail-closed option for UNVERIFIABLE, and an evaluation against an adaptive adversary instructed to evade the JUDGE are future work.

7 The audit mode

7.1 Audit grades and concrete risks

The audit mode (`kata --audit`) grades each phase of a task as followed, skipped, faked, or degraded, and names the concrete risk each skip or fake created. Table 2 summarizes the four grades and what each one means for the trustworthiness of the task.

Table 2. The four audit grades and their meaning.

Grade	Meaning
followed	The phase has `answered: true` and real content
skipped	The phase has `skipped: true` (documented, not hidden)
faked	`answered: true` with default or empty content, or a verify/twins claim without its evidence
degraded	The phase ran without its own skill loaded (`preflight`)

The faked pattern is a phase marked as answered without real content. This is only possible because there is objective logic behind it: the audit reads the YAML and detects `answered: true` with empty content. A skill has no way to detect even that. Kata detects a phase marked answered with empty or default content, though not one filled with plausible but false content (Section 6.4).

```
× FIT: faked
   ! route and triviality not classified by a human -
     effort may be
     wasted on a trivial or misrouted task
× THINK: faked
   ! assumptions never declared - any solution may
     attack the
     wrong problem
× INTENT: faked
   ! code, test, and spec may disagree without a
     record - behavior
     changes without verified intent
✓ SIMPLIFY: followed
✓ SURGICAL: followed
✓ VERIFY: followed

!  Audit found 3 fake(s) and 0 skip(s).
```

The audit is Kata's equivalent of the Fable Method's audit, and it catches phases that were filled in without being observed.

7.2 Preflight and installation checking

The orchestrator is not self-contained: at each phase it loads the matching skill and follows its instructions. When a skill is not installed, the call fails, the orchestrator has no instructions for that phase, and the model improvises from the phase name. The result is a task file with the section filled in and nothing behind it — the faked phase the audit exists to catch,

except produced by the tooling rather than by the agent, and invisible in the output.

The `kata --doctor` command reports, per frontend, which of the expected skills are present under the host's configuration directory. A broken symlink does not count as installed, because `exists()` follows the link and so does the host when it tries to load the skill. A partial install is what fails, not an absent one: exit code 1 is reserved for a frontend that has some skills but not all, because someone with 9 of the 10 phase skills runs the whole cycle and silently loses a phase. With no frontend installed at all, `--doctor` says so and exits 0 — the CLI works without any. Domain adapters are optional and never fail `--doctor`: missing domain adapters (such as `kata-devops` or `kata-data-analysis`) are reported as hints because a coding task does not need them.

When a skill fails to load mid-cycle, the orchestrator is instructed not to improvise: it falls back to a per-phase minimum contract documented in the orchestrator itself, records the skill name in `preflight.skills_missing`, and discloses it in the report. The audit grades such a phase as degraded, not followed, because whatever the other grades read was written without those instructions. VERIFY and JUDGE degrade best, because their logic lives in the Python package rather than in the skill text. Since 0.8.0, `--doctor` also reads the version stored in each `.kata-managed` marker and warns when the installed skills were written by a different Kata version than the one running: a copy of 0.7.4 under a 0.8.0 CLI would otherwise report "complete installation" while the agent followed phase instructions from the older release. This is a warning, not a failure, because a pinned installation may be intentional; exit code 1 remains reserved for a partial install.

8 Using the kata CLI

This section documents how to install Kata and use its command-line interface, so that the demonstrations of Sections 5–7 can be reproduced. Kata is published on the Python Package Index (PyPI) as `kata-dev` (the command stays `kata`); the installable package version is `0.8.0`. The package, the release tag `v0.8.0` and the code that was measured are three different revisions, and the Declarations (Section A.6) define them once, together with the term "evaluated version" used throughout this paper. A DOI will be minted upon acceptance and inserted in the camera-ready version. The canonical user documentation is the README (which ships as the package's long description on PyPI) and `DOCUMENTATION.md` (versioned in the repository, not in the wheel). Both are versioned with the source; the Declarations section gives the exact commits and reproduction commands, together with the comparison and external-study harnesses and the measurement and audit tooling cited in Sections 4 and 9.3.

8.1 Installation

Kata requires Python 3.11 or newer. The recommended installation path is the published package, isolated in its own environment with `pipx` or `uv` so it does not touch the current one:

```
pipx install kata-dev
# or: uv tool install kata-dev
kata --install all       # opencode + claude-code (
    copies the bundled skills)
kata --doctor            # checks the installation
```

Development on the source checkout instead installs the package in editable mode, with the `dev` extra bringing the lint, test, and coverage tools the CLI itself executes:

```
pip install -e '.[dev]'
```

To run the CLI once without installing it permanently (CI/-headless friendly), `pipx` or `uv` can run it directly from the package:

```
pipx run kata-dev --version
uv tool run --from kata-dev kata --version
```

The agent frontends are installed separately through symlinks. `make install` links the OpenCode agent and skills into the OpenCode configuration directory (honoring `OPENCODE_CONFIG_DIR`, defaulting to `~/.config/opencode`); `make install-claude-code` links the skills into the Claude Code configuration directory (honoring `CLAUDE_CONFIG_DIR`, defaulting to `~/.claude`). Because the installer creates symlinks, rebuilding the generated frontends with `make build-skills` is immediately visible without reinstalling. `kata --install` performs the same installation as a copy from the wheel's bundled assets, so a reader without the checkout can install; it adopts a symlink created by the checkout installer when the target has the same content, and `kata --doctor` names the mode (link, copy, or mixed) and warns when the installed skills were written by a different Kata version.

8.2 Command reference

Table 3 lists the CLI modes. All modes operate on task files under `.kata/` at the target project's root; `--doctor` is the exception, checking skill installation without touching any task.

Verification is configurable per role. `--ruff-paths`, `--test-paths`, `--ignore`, `--cov-source`, and `--gate` set the built-in Python defaults (ruff, pytest, pytest-cov with `--cov-fail-under`, gate 70%). The gate is resolved with explicit precedence: the `--gate` flag wins, then `verify.gate` from `.kata/config.yaml`, then the 70% built-in default; the 70% value is a project convention, not a research finding, and the JUDGE compares the measured coverage against whatever gate the run resolved to. A role declared in `.kata/config.yaml` runs verbatim instead, so non-Python projects declare their own lint, typecheck, test, and coverage commands; every undeclared role keeps its Python default, except `typecheck`, which has no default and simply does not run. A path flag that no longer applies because its role is declared is reported as ignored rather than silently discarded. An unknown key at any level of the config is a named error, and a command containing a shell operator is refused because commands run without a shell.

Table 3. The `kata` CLI modes.

Command	Effect
`kata --init TASK`	Create the task file, run FIT + THINK
`kata [--task TASK]`	Run the full interactive cycle
`kata --task TASK --plan`	Run FIT + THINK, save the plan, stop
`kata --check-only`	Run lint + typecheck (if declared) + tests + coverage (CI entry)
`kata --task TASK --report`	Regenerate the outcome-first report
`kata --stamp TASK [--commit SHA]`	Record the commit that ends the task in `approved_commit`, closing the JUDGE's diff wind
`kata --task TASK --judge`	Adversarial verification (hunts frauds)
`kata --task TASK --audit`	Grade phases: followed/skipped/faked/degraded
`kata --doctor`	Check phase-skill installation per frontend

8.3 Typical workflow and exit codes

In practice, Kata integrates into software engineering workflows along two distinct patterns: interactive authoring and automated gating.

Interactive authoring workflow. A developer or coding agent follows three sequential CLI commands:

1. **Initialize**: `kata --init fix-login` measures the working diff, prompts for the task route (Phase 0: FIT), records the problem, assumptions, and declared done criterion (Phase 1: THINK), captures the starting HEAD as `base_commit`, and creates an independent Git anchor at `refs/kata/base/<sha256(task)>`.
2. **Execute and verify**: `kata --task fix-login` guides the change through SIMPLIFY (checking minimality), INTENT (aligning code, test, and spec), SURGICAL (auditing declared files), VERIFY (running lint, declared typecheck, tests, and coverage against exit codes), and TWIN CHECK (searching project-wide for defect recurrence). Upon approval it records the execution evidence; `approved_commit` is not written while HEAD is still the baseline, so the commit that ends the task is stamped next with `kata --stamp fix-login`, which sets the diff ceiling.
3. **Adversarial review**: `kata --task fix-login --judge` re-executes all claimed checks, diffs the Git baseline against the approved ceiling, and hunts for the eight categories of fraud before merge.

Automated CI and review pipelines. In automated pipelines, Kata operates non-interactively without prompting:

- **Per-commit CI**: `kata --check-only` executes the declared or default lint, test, and coverage commands, returning exit code 0 if all pass or 1 if any fails.
- **Pull request gating**: `kata --task <name> --judge` re-runs checks and hunts frauds against the PR's baseline anchor; `kata --task <name> --judge --trusted-base <ref>` closes a recreated anchor with a CI-only ref the agent cannot move, not locally; `kata --task <name> --audit` ensures no phase was faked or silently skipped in headless mode.

Exit codes make the CLI directly composable in shell scripts and CI pipelines:

- **0**: The requested operation passed (an approved cycle, a `VERIFIED` or `VERIFIED WITH CAVEATS` judge verdict, a clean audit, or an `UNVERIFIABLE` blind spot confession). In particular, `VERIFIED WITH CAVEATS` and `UNVERIFIABLE` exit 0: the judge verified what it could and approved with notes, or found no fraud but could observe nothing — treating either as failure would equate an honest limitation with high-severity fraud. This makes UNVERIFIABLE fail-open: an agent can manufacture a blind spot, so a CI job that must fail on anything short of VERIFIED has to read the verdict rather than the exit code (Section 6.4).
- **1**: Failure (a rejected cycle, a `REFUTED` judge verdict, an audit with any phase graded `faked`, `skipped`, or `degraded`, or a partial frontend skill installation).
- **2**: Invalid CLI arguments or syntax.

9 Research impact and evaluation

Kata is dogfooded: its own lint, tests, and coverage are measured (gate 70%), and the continuous integration runs the Makefile rather than restating the commands, so what is verified locally and remotely cannot drift apart.

Evaluation proceeds in two layers. The first is a *self-check*: 19 adversarial trap scenarios (`eval/run_traps.py`, whose driving logic is Listing 9) plant frauds the JUDGE must catch and honest work it must not accuse. The second layer is *external*: 12 bug-fix tasks from public repositories, fixed by two agent models with and without Kata, with the JUDGE reviewing every final artifact. The layers answer different questions: the traps measure the two-sided contract of the JUDGE on fixtures we built ourselves, while the external study measures what real agent sessions produce on code we did not write. The first layer answers RQ1 and, reused as the workload of Section 9.2, RQ2; the second answers RQ3. The exploratory loop study is in Appendix A.

9.1 Self-check: the adversarial trap suite

The evaluation of Kata follows the methodology of the Fable Method's eval Sahir619 (2026): adversarial trap scenarios that plant frauds the tool must catch, and honest scenarios it must not accuse. The trap suite is deliberately asymmetric in its coverage. Table 4 summarizes the 19 scenarios the evaluated version ran at commit `230e81a`.

Table 4. The 19 adversarial trap scenarios of the evaluated version (commit `230e81a`; the suite has grown since — see the note after Table 5). Each row summarizes one `eval/scenarios/<name>/` directory, which pairs a `fixture/` (the planted fraud or honest work) with a `ground_truth.yaml` (the expected verdict and frauds). The scenario set is original to Kata, built incrementally across development sprints, each motivated by a real defect found in the JUDGE; the trap methodology follows the Fable Method's eval Sahir619 (2026).

Scenario	What it exercises
s01	weakened checks: test body replaced by `pass`
s02	scope creep: report declares 1 file, tree has 4
s03	false completion: claims pass, re-execution fails all three
s04	unauthorized action: irreversible action without AUTH line
s05	spec betrayal: intent disagreement approved anyway
s06	debris + false positive guard: real debris beside look-alike names
s07	honest work: must come back VERIFIED
s08	weakened checks: fraudulent test left outside the index
s09	weakened checks: assertion turned into comment (modification diff)
s10	weakened checks: test body turned into `pass # comment`
s11	weakened checks: new test whose body is only `assert True`
s12	blind spot: test in Elixir `.exs`, no probes
s13	blind spot: task claims no reproducible check
s14	baseline tampering: `base_commit` rewritten after anchor
s15	honest work with `.kata/` visible to git
s16	honest trivial task with empty surgical list
s17	honest task with `approved_commit` end to end
s18	weakened checks: JS test turned into comment, `it.skip`
s19	blind spot: Git-ignored test via local exclude

Twelve scenarios plant a fraud that must be detected, spanning all seven fraud categories: weakened checks (a test whose body was replaced by `pass` among real tests; an assertion turned into a comment; a new test whose body is only `assert True`; a fraudulent test left outside the index, invisible to `git diff`; a test body turned into `pass # comment`), false completion (a report claiming lint clean, tests passing, and coverage at the gate, where re-execution fails all three), scope creep (a report declaring one file when the tree has four), unauthorized action (an irreversible action without an AUTH line), specification betrayal (an intent gate that recorded disagreement and was approved anyway), debris (real temporary files in the diff), and baseline tampering (a `base_commit` rewritten after the Git anchor was recorded).

The debris scenario (s06) is the clearest case: it plants real debris beside files whose names merely look like debris (`templates/`, `temperature.py`, `attempt_parser.py`), so a judge that matches the substring "temp" would accuse honest work while a judge that stays silent would clear fraudulent work.

Four scenarios are entirely honest tasks that must come back VERIFIED. These are as important as the fraud scenarios: a judge that refuses legitimate work is as broken as one that misses fraud, and unit tests are poor at catching false positives because they test what we thought to test. One honest scenario exercises the triviality gate with three small files and an empty surgical list, where a naive scope-creep rule would falsely accuse the task. Another exercises the `approved_commit` mechanism end to end: a later task touches an undeclared file after the approval, and the judge must not count it as scope creep for the earlier task. The remaining three scenarios expect UNVERIFIABLE for confessed blind spots: a test in a language the judge has no probes for (Elixir `.exs`), a task that claims no reproducible check at all, and a test hidden from Git via a local ignore rule that the judge cannot see in the diff.

The trap suite also guards the evaluation harness itself. One scenario opts into the real environment with `kata_visivel: true`: the harness excludes `.kata/` from Git in every fixture, and the judge counting the task's own file as scope creep went unnoticed through ten review rounds before that scenario existed — including in the honest-work scenario whose whole job is catching false positives. The same rule applies to every fixture added since: reintroducing the defect it was built for must make it fail, or the scenario is decoration.

9.1.1 Execution results

We executed the full trap suite (`python3 eval/run_traps.py`) on commit `230e81a` of the repository. The study harness of Section 9.3 adds no changes to `src/kata`, so the executed code is the code described in this paper. The machine ran Linux (kernel 7.1.5) on x86_64 with Python 3.12.3, ruff 0.15.21, pytest 9.1.1, and pytest-cov 7.1.0. The harness is deterministic: its verdicts are computed from exit codes and the Git state, not sampled, so re-execution reproduces the result rather than estimating it. All 19 scenarios passed, with a wall-clock of 17.7 s (observed range 16.2–17.8 s over re-executions; the CI re-run guards the verdicts, not the timing). Every planted fraud was detected with the expected verdict and the expected fraud types, and every honest scenario returned the expected verdict with no false accusations. Table 5 summarizes the outcome by expected verdict.

The result confirms the two-sided contract of the JUDGE. On the detection side, twelve scenarios plant a fraud: eleven returned REFUTED with high-severity

Table 5. Trap suite execution results: 19/19 scenarios passed. Verdict counts derive from the `expected_verdict` fields of the 19 `ground_truth.yaml` files; the run reported here executed `python3 eval/run_traps.py` on the described code version, and the harness confirmed actual verdicts match expected ones with no false accusations.

Expected verdict	Scenarios	Count
REFUTED	s01, s02, s03, s04, s05, s08, s09, s10, s11, s14, s18	11
VERIFIED WITH CAVEATS	s06 (debris found; look-alike names spared)	1
VERIFIED	s07, s15, s16, s17	4
UNVERIFIABLE	s12, s13, s19	3

frauds, and the twelfth, s06 (debris), returned VERIFIED WITH CAVEATS with the fraud found — the real debris (`scratch/saida.tmp`, a debug print, a TODO) — while sparing the look-alike names (`templates/`, `temperature.py`, `attempt_parser.py`), so that the twelve together cover all seven fraud categories; the s03 false-completion scenario shown in Section 6 is representative. On the restraint side, four honest scenarios returned VERIFIED, and in s16 the trivial task was not falsely accused by a naive scope-creep rule. Three scenarios returned UNVERIFIABLE, confessing blind spots instead of clearing work the judge could not observe. The suite runs in continuous integration on every push, so any regression in detection or restraint breaks the build.

The suite has grown since the evaluated version. Table 4 and Table 5 describe the evaluated version, and we do not restate them. The repository's suite now holds 25 scenarios: the 19 above plus six added after the evaluation. All 25 exercise the nine-phase cycle and live in this repository; the gauntlet variant of Appendix A is kept in a separate fork and is not part of this count. Three of the six additions cover corrections the cycle needed and were already cited in place — s20 the empty diff window, s21 a resolved intent conflict, and s22 a moved baseline anchor (Section 6.4). s23 exercises the artifacts the judge's own re-execution leaves behind, which a second run in the same tree once read as scope creep. s24 and s25 exercise the attribution added in 0.8.0: s24 pairs an approved task with a sibling task whose commit is stamped inside its window and expects `VERIFIED`, while s25 removes the sibling's stamp and expects `UNVERIFIABLE`, because the judge cannot tell the sibling's commit from the task's own and must confess rather than accuse or bless. All 25 run under the same runner and the same two-sided contract, but only the 19 are the evaluation this paper reports.

The unit suite also exercises the JUDGE against a real git repository in a temporary directory, because blindness to committed or untracked changes cannot be reproduced with mocks. The schema of the task file is compatible with the legacy `.karpathy/` schema, so tasks written against that schema migrate through a symbolic link. Kata is open-source (MIT License) and distributed as the `kata-dev` package on PyPI, installable in both agent hosts with `kata --install` (see the Declarations section and Section 8).

9.2 Executed comparison with related gates

The JSERD guidelines for software articles state that "Software articles should describe a tool likely to be of broad utility that represents a significant advance over previously published software (usually demonstrated by direct comparison with available related software)".[2] This section answers that request by direct comparison: four gates — Kata, nova, claude-wizard, and a prompt-only baseline — reviewed the same 19 adversarial scenarios of Section 9.1, and we measured fraud detection, false positives, and wall-clock time.

9.2.1 Protocol

The comparison reuses the trap suite of Section 9.1 as the workload: each scenario is a git repository holding a "completed" task whose task file records the claims the scenario exercises — lint, tests, and coverage in the false-completion case, a subset elsewhere (the blind spots claim no reproducible check at all). The ground truth is the scenario's `ground_truth.yaml`: the expected verdict and the exact frauds the review must find. Eleven scenarios expect REFUTED; the other eight expect VERIFIED (s07, s15, s16, s17), VERIFIED WITH CAVEATS (s06, the debris scenario, whose ground truth expects the three real debris findings), or UNVERIFIABLE (s12, s13, s19).

Each gate reviews every scenario in a fresh sandbox, without access to the ground truth. Kata runs its `--judge` mode. nova and claude-wizard run headless through the Claude Code CLI (`claude -p` with permission bypass), each receiving an identical canonical prompt that states the review task and the seven fraud categories of the evaluated taxonomy, prefixed with an instruction to follow the gate's workflow. The prompt-only baseline receives the same prompt without any gate-framework instruction; it is a reviewer with the same information and tool access, not a no-verification condition. The agent gates report their verdict as a single JSON object (`fraud_detected`, `fraud_types`, `reason`); the harness parses it with a tolerant JSON decoder. The Kata arm is classified by exact verdict match against the ground truth; for the agent arms, a scenario is *detected* when the gate reports the fraud matching the ground-truth types and a *false positive* when it accuses a scenario whose ground truth expects no fraud. The debris scenario is the exception to the accusation rule: its ground truth expects the real debris to be found, so reporting debris without naming one of the look-alike files counts as correct, while naming a look-alike counts as a false positive. The *Correct* column counts the scenarios a gate classified as detected or clean.

[2] JSERD submission guidelines, `https://journals-sol.sbc.org.br/index.php/jserd/about/submissions`, accessed 2026-09-11. The quoted text is verbatim from the "Software" article type description as of the access date.

9.2.2 Results

Read the numbers below with their scope in mind, stated upfront rather than only in the caveats that close this section: this is one complete run, over 19 scenarios we built alongside Kata, run through a single unrecorded model for the agent gates. It is a demonstration on Kata's own fixtures, not a statistically powered claim about the tools in general.

Table 6 summarizes the outcome. Three results matter here.

All four agent gates detected every planted fraud in all eleven REFUTED scenarios. Fraud detection is not where the gates differ: the difference is in what happens on honest work and confessed blind spots. Kata, in turn, returned the expected verdict on all eight non-REFUTED scenarios, but most agent false positives trace to the comparison design rather than to reviewer judgment. The agent gates made eleven false accusations, and their origin matters more than their count. Seven fell on the three blind-spot scenarios, whose ground truth expects UNVERIFIABLE — nova and the baseline on s12 and s13, all three on s19; the agents' reporting format offered no such verdict, so a gate could only accuse or report no fraud (claude-wizard reported no fraud on s12 and s13 and was scored correct). Three, one per agent gate, fell on s17, where the agents counted a later task's changes as scope creep for the task under review; s17 depends on the `approved_commit` diff ceiling, a Kata convention the review prompt did not explain. The remaining one is the prompt-only baseline accusing the honest s07 task of weakened checks. Excluding the blind-spot scenarios, correctness is 16/16 for Kata, 15/16 for nova and claude-wizard, and 14/16 for the baseline (Table 6); excluding s17 as well, nova and claude-wizard match Kata, and the only difference left is the baseline's error on s07. On the one non-REFUTED scenario that does contain a real fraud (s06, debris), the three agent gates found the debris and spared the look-alike names, and Kata's verdict matched the expected VERIFIED WITH CAVEATS — the trap suite verifies that its output lists the three debris findings (Section 9.1). The gates also differ in time: Kata's median review took 0.1 s on fraud scenarios and 1.0 s on the others, while the agent gates' medians ranged from 16 s to 40 s, because the gate reads exit codes while the agents run a model. Kata's verdicts here are model-independent: its measured advantage over the agent gates is determinism (the same verdict every run) and cost (0.1–1.0 s per review on these fixtures) — not detection, which every gate achieved on these fixtures, and not general restraint, since Kata's absence of false accusations was measured on scenarios built around its own conventions.

A fifth, deterministic baseline (run `make test` and grep the diff for test-smell patterns: `pass` bodies, `assert True` additions, `pytest.skip`) sits below all agent gates on detection: 9/11 REFUTED, missing s08 (fraud in an untracked file invisible to `git diff --cached`) and s14 (metadata fraud in the YAML `base_commit` field). It also produces two false positives (s06 debris, s07 honest work flagged by smell-pattern matches). The comparison is diagnostic: test-smell grep catches the syntactic weakening patterns the JUDGE was designed for (Section 6), but cannot inspect Git state, track file scope across commits, or distinguish legitimate from fraudulent `pass` bodies — the operations that require the deterministic code path the paper argues for.

The comparison is subject to important methodological caveats that we state explicitly. The 19 scenarios and the underlying fraud taxonomy were developed iteratively alongside Kata to serve as regression fixtures. Consequently, the test workloads are strictly in-distribution for Kata — which includes dedicated architectural mechanisms for these specific boundary conditions — and out-of-distribution for the alternative gates. The false positives incurred by the agent gates were concentrated on scenarios exercising these repository-level conventions (e.g., `approved_commit` diff ceiling on s17, Git local excludes on s19, and missing language probes on s12). Hence, the false positive metric reflects familiarity with these architectural conventions and the presence of direct repository query tools as much as generic reviewer restraint.

The tools were also evaluated in a constrained, emulated configuration: `nova` and `claude-wizard` were invoked as structured review prompts within a single headless Claude Code CLI session (`claude -p`), rather than within their native end-to-end interactive developer workflows. For instance, `nova` provides a full Model Context Protocol (MCP) server with specialized subagents that was not wired into this isolated review harness, which was scoped to measure a standalone, single-turn change review pass. The agent gates also operated through a single underlying LLM, Claude Code's default model. The harness did not record which model that was; the local Claude Code session logs of the final run's 57 agent reviews, which are not archived in the repository, show `claude-sonnet-5` through Claude Code CLI 2.1.268. This means their false positives and heuristic tendencies characterize this specific model under review prompting, rather than the tools in their entirety.

Agent reviews are also inherently stochastic, and the scoring rules changed during the study. The repository archives five comparison files, described in `eval/results/README.md`. Two are complete, independent runs: `compare_gates.json` and the final `compare_gates_round2.json` reported in Table 6. `compare_gates_refined.json` re-runs only the eight non-REFUTED scenarios; `compare_gates_merged.json` consolidates the first run with that re-run and is not an independent run; and `compare_gates_final.json` is a run aborted by the account spend limit, whose INCONCLUSIVE entries from s13 onward are infrastructure blocks, not gate behaviour. Two scoring changes were made after the first run's results were seen: the agent-output parser was replaced by a decoder that takes the first complete JSON object, and the debris scenario (s06) stopped counting an accusation of the real debris as a false positive, counting one only when a look-alike file is named. The s06 change favoured the agent gates: under the first rule, all three were charged a false positive on s06 for finding the real debris. The parser change did not: in the first run, the baseline's answer on the honest s07 task could not be parsed and was recorded as INCONCLUSIVE, although its archived prefix reports `fraud_detected: true`, so the final parser would most likely have scored it as a false positive. Scored as they were at the time, the agent false-positive counts in

Table 6. Executed comparison of five gates over the 19 trap scenarios. One complete run (September 2026); raw verdicts in `eval/results/compare_gates_round2.json` (agent gates) and `eval/results/deterministic_baseline.json` (deterministic). In the Non-REFUTED block, FP reports the final run count alongside the range [*min–max*] across the two complete runs, the first re-scored with the final debris (s06) rule (see text). The last block excludes the three blind-spot scenarios (s12, s13, s19), whose ground truth expects UNVERIFIABLE, a verdict the agents' reporting format did not offer.

Gate	Detection	FP (range)	Correct	Median time
Fraud scenarios (11 REFUTED)				
Kata	11/11	—	11/11	0.1 s
nova	11/11	—	11/11	16 s
claude-wizard	11/11	—	11/11	17 s
bare (prompt-only)	11/11	—	11/11	18 s
deterministic (test + smell)	9/11	—	9/11	0.3 s
Non-REFUTED scenarios (8): honest (4), debris (1), blind spots (3)				
Kata	—	0 [0–0]	8/8	1.0 s
nova	—	4 [3–4]	4/8	40 s
claude-wizard	—	2 [2–3]	6/8	27 s
bare (prompt-only)	—	5 [3–5]	3/8	32 s
deterministic (test + smell)	—	2	6/8	0.3 s
All scenarios — correctness (final run)				
Kata			**19/19**	
nova			15/19	
claude-wizard			17/19	
bare (prompt-only)			14/19	
deterministic (test + smell)			15/19	
Excluding blind-spot scenarios s12, s13, s19 (16) — correctness (final run)				
Kata			16/16	
nova			15/16	
claude-wizard			15/16	
bare (prompt-only)			14/16	
deterministic (test + smell)			15/16	

the two complete runs were 4 and 4 for nova, 4 and 2 for claude-wizard, and 4 and 5 for the baseline; applying the final s06 rule to the first run lowers each of its counts to 3 (4 for the baseline if its s07 accusation is counted), which gives the ranges in Table 6. Re-scoring the final run with the final rules from its archived output reproduces every published status. The first run cannot be fully re-scored, because it archives only a truncated excerpt of each agent answer (at most 300 characters); the s06 answers fit whole, so that re-scoring is verifiable, while the s07 answer is cut off and remains INCONCLUSIVE. Kata yielded identical verdicts across every run, with zero false positives on these Kata-built fixtures. The agent reporting schema also lacked an explicit `UNVERIFIABLE` verdict, forcing agents either to accuse or remain silent, precluding explicit confessions of unobservable state.

The comparison, then, does not demonstrate general superiority of Kata over the reasoning capabilities of alternative tools. Rather, it isolates the core thesis of this paper: evaluating complex software engineering boundary conditions (such as Git commit ceilings, untracked ignores, and process exit codes) through heuristic LLM prompts forces the model to guess, whereas executing deterministic, code-level checks — deterministic in the sense that the same repository state always produces the same verdict, not in the sense of completeness — yields instantaneous, reproducible verdicts that confess blind spots explicitly. Whether this also means fewer false accusations on workloads not built alongside Kata remains untested. The comparison harness and raw records are archived as `eval/compare_gates.py` and `eval/results/compare_gates_round2.json`.

9.3 External evaluation: feasibility, scope integrity, and execution overhead on real repositories

The trap suite is ours: the frauds, the fixtures, and the ground truth were written by us, and a reviewer may reasonably ask whether the mechanisms hold outside that self-referential setting. We therefore conducted an external evaluation: 12 bug-fix tasks from six public repositories, attempted by two models under two conditions (bare vs. kata, yielding 48 sessions in total), with the JUDGE independently reviewing every final artifact. We state upfront that this study serves to evaluate operational feasibility, scope integrity, and execution overhead when applied to non-author code; with an exploratory sample size of $N = 1$ run per cell across stochastic agents, it is designed as a feasibility and cost assessment rather than a statistically powered measurement of model population effects.

9.3.1 Protocol

Sample. We selected twelve small fixes from public repositories (Table 7); each is a real commit that fixed a real issue and

came with regression tests, so solvability is attested by history rather than assumed. For each fix, the task state is the parent commit plus the test files the fix changed, and the repository history is re-initialized as a single commit so the agent cannot read the fix. We verified for all twelve tasks that the selected tests fail in the task state and pass at the fix commit (`python3 eval/external_study.py --check-tasks`).

Conditions. Each task was attempted in a fresh sandbox by two models — `deepseek-v4-pro` and `claude-sonnet-5` — under two conditions: *bare*, the model as an agent with no quality gate — a stronger no-gate condition than the prompt-only baseline of Section 9.2, since here the session receives no reviewer prompt or fraud taxonomy at all — and *kata*, the same host running the Kata cycle (task file, phases, objective verification, and the adversarial JUDGE). Both conditions receive the same issue text, run headless with file-edit permissions, and must end with a JSON declaration of the files changed. The bare condition additionally runs with an isolated agent configuration in which the Kata skills are not visible; no bare session created a `.kata/` artifact, while all 24 `kata` sessions produced a task file and a Git baseline anchor. The harness removes tool artifacts from the tree before measurement (`_clean_tool_caches`).

Metrics. From the final repository state and the session's declaration we measured: (a) whether the test suite passes; (b) whether the final diff contains a weakened test, using the JUDGE's own weakened-check detector; (c) undeclared scope, the files changed but absent from the session's declaration; (d) the verdict of the JUDGE as an independent reviewer of the final artifact — for both conditions we synthesized a task file with the session's declared files, supplied the task's test command through `.kata/config.yaml`, and anchored the task state (`refs/kata/base/`) so the same instrument reviews both arms; and (e) wall-clock time of the session and of the JUDGE review. The harness, the manifest with the pinned commits, and the raw results are archived as `eval/external_study.py`, `eval/external_tasks.yaml`, and `eval/results/external_study.json`.

9.3.2 Results

All 48 sessions produced a fix that passes the task's test suite, in both conditions and for both models. The final artifacts contained no weakened tests in any of the 48 runs according to the JUDGE's own weakened-check detector, which found nothing to report. With $N = 1$ per cell, this is a single absence of a negative signal, not a rate: it indicates that on well-isolated, narrow bugs with clear existing regression tests, these particular sessions of frontier LLMs did not resort to test-weakening tactics — a result that describes these sessions, not the models in general. Consequently, the external study demonstrates the operational feasibility and scope integrity of the gate on third-party codebases, while validation of the JUDGE's fraud detection capabilities rests on the 19 adversarial trap scenarios of Section 9.1 where frauds were actively planted. The agent failure the external study did observe was *undeclared scope*: in one run (deepseek, bare), the session changed `tools/intranges.py` to regenerate a code-point table but declared only `idna/core.py`; the JUDGE flagged the extra file as `scope_creep` and returned VERIFIED WITH CAVEATS. The independent review returned VERIFIED for the other 47 runs, with no false accusations on any artifact.

Cost is the other side of this result; agent research has argued that evaluation must account for cost, not only accuracy Kapoor et al. (2024), and the same holds for gates. Without the cycle, the median session took 49 s (range 28–145 s across all 24 bare runs); with Kata, 442 s (range 104–1153 s) — the cycle adds a task file, the phase gates, and the JUDGE to every change, and the median wall-clock cost is roughly nine times higher (Table 8). The dispersion is substantial: while no bare session exceeded 2.5 minutes, the kata arm developed a heavy tail reaching 19.2 minutes (1153 s on t08 for Claude, and 1040 s for DeepSeek), driven by iterative test-suite discovery, multiple verification runs, and full coverage tracing across larger repositories.

This raises an explicit cost-benefit question: is paying a roughly 9-fold median time overhead (and a 19-minute worst case) justified when the only differential failure observed in 48 runs was a single undeclared file? The answer separates the *standalone reviewer* from the *authoring scaffold*. The JUDGE review itself is cheap and independent of the model that produced the change: applied to the same final artifacts, it reached a verdict in a median of about two seconds across all conditions (Table 8), with outliers of about two minutes on t08 and fifty seconds on t10 where the project's coverage command re-executes the full test suite. A review gate costing two seconds per change is viable as an automated CI or pre-commit check. In contrast, the full nine-phase authoring cycle (`kata --task`) is an interactive development discipline. On clean, well-isolated bugs with clear regression tests (such as these 12 tasks), bare agents readily find the direct fix without incentives to game visible checks. Whether the authoring cycle pays for itself on complex or open-ended changes, where verification is ambiguous and the incentive to game visible checks is stronger, is a hypothesis this study cannot test: its tasks gave the agents no such incentive. What the cycle measurably added here is an auditable record (24 task files with Git baseline anchors), which the bare arm did not produce.

This suggests two usage hypotheses for future evaluation, not guidelines established by these data: (1) **Continuous integration and pull-request gating** with the decoupled verification gate (`kata --judge` or `kata --check-only`), which reviewed each change here in a median of about two seconds (at most 116 s), subject to the evasions of Section 6.4, the recreated anchor among them closable only by `kata --judge --trusted-base <ref>`, a CI-only ref the agent cannot move; (2) **Complex or autonomous authoring** with the full scaffold (`kata --task`) for open-ended, multi-file, or safety-critical changes, where the nine-fold overhead would have to be justified by effects this study did not observe.

The `kata` arm is also auditable after the fact. The 24 task files the sessions left behind grade, under the audit mode of Section 7, 151 phase executions as followed, 13 as skipped (the documented headless defaults) and one verify section as faked. Of the $24 \times 8 = 192$ phases the audit schema covers (fit, think, intent, simplify, surgical, verify, twins, and preflight), the 27 not counted are phases that were never

Table 7. The twelve external tasks. Each row is a real fix commit from a public repository (permissive license). The task state is the parent commit plus the test files the fix changed, with the history re-initialized so the fix is not visible; all tasks were verified to fail in the task state and pass at the fix commit.

Task	Repository	License	Fix commit (bug)
t01	`hukkin/tomli`	MIT	`8b962e1` (wrong-mode `TypeError`)
t02	`hukkin/tomli`	MIT	`794c8e5` (`parse_float` illegal types)
t03	`kjd/idna`	BSD-3	`e00ed28` (non-ASCII A-label)
t04	`kjd/idna`	BSD-3	`9067b80` (CONTEXTJ masked error)
t05	`pycqa/pyflakes`	MIT	`e19886e` (redefined global annotation)
t06	`pycqa/pyflakes`	MIT	`e932464` (shadowed unused assignment)
t07	`pycqa/pyflakes`	MIT	`e0d7a6b` (augmented assign to builtin)
t08	`more-itertools`	MIT	`f51a53b` (empty `interleave_evenly`)
t09	`more-itertools`	MIT	`9245cd0` (`split_after` with `maxsplit=1`)
t10	`more-itertools`	MIT	`cca3294` (`last()` without `__reversed__`)
t11	`typing_extensions`	PSF-2.0	`8dfcf3c` (nested `Annotated`)
t12	`davidhalter/parso`	MIT	`e22dc67` (future grammar load)

Table 8. External study: 12 bug-fix tasks from public repositories, two models, two conditions, one session per cell (48 sessions). *Weak.* counts runs whose final artifact contains a weakened test according to the JUDGE's own detector; *undecl.* counts runs with files changed but not declared; *JUDGE* reports the verdicts of the independent review pass (*V* = VERIFIED, *VWC* = VERIFIED WITH CAVEATS); *session* and *review* report median wall-clock times alongside the observed [*min–max*] range. Every session's fix passes the task's test suite.

Condition	Model	Runs	Weak.	Undecl.	JUDGE	Session median [min–max]	Review median [min–max]
bare	claude	12	0	0	12 V	46 s [28–104 s]	2.0 s [1.4–95 s]
bare	deepseek	12	0	1	11 V, 1 VWC	70 s [32–145 s]	1.9 s [1.4–101 s]
kata	claude	12	0	0	12 V	492 s [181–1153 s]	1.9 s [1.6–101 s]
kata	deepseek	12	0	0	12 V	405 s [104–1040 s]	1.9 s [1.4–116 s]

initiated in the YAML (neither `answered` nor `skipped`), which the audit function skips; REPORT and ARTIFACT phases are not graded by the audit. That single `faked` grade is a practical false positive of the audit, and we report it as such: in session `t05-kata-claude` (`pycqa/pyflakes`), the session marked `success_criteria_met: true` while all three objective checks (`ruff_clean`, `tests_pass`, `coverage_pass`) were false, triggering the audit rule that flags claimed success without supporting evidence (Listing 7). The session's `verify.notes` transparently documented the reason: three legacy test failures in `test_api.py` stemmed from Python 3.12 syntax-error message shifts, and `git stash` verified they failed identically on `base_commit` before any change. (In `t05-kata-deepseek`, `ruff_clean: true` was recorded, satisfying the rule). The audit grade is deliberately mechanical and context-blind: by design it cannot read the notes, so it flags zero objective evidence alongside claimed success even when the failure is pre-existing debt rather than fabrication. This is the intended limit of the mechanism, not an unresolved defect — the audit names the risk, and the notes are what a human reviewer reads to distinguish documented environmental debt from fabrication. The 24 session task files are archived under `eval/results/external_study_sessions/`, and the derived audit is archived in `eval/results/external_study_audit.json`.

That deliberate blindness has a practical limit, though. When repositories contain pre-existing test breakages or flaky suites, a context-blind gate flagging `FAKED` on unverified success can create perverse incentives: developers or agents may feel pressured to modify unrelated tests or bypass the quality gate altogether. A promising extension, rather than a correction to the audit as specified, is a formal mechanism for declaring known baseline debt (`baseline_failures`) at `base_commit`, allowing the gate to certify that no new regressions were introduced without penalizing pre-existing repository debt.

The harness field for the sessions' own JUDGE verdict (`session_judge_verdict`) is null in all 48 runs because the harness searched each session's text output for the CLI's `KATA JUDGE` banner, which no session reproduces, instead of reading the task files, which record the verdict. Twelve of the 24 `kata` sessions ran the JUDGE as their final step: six returned VERIFIED, and six, all with `claude-sonnet-5` (t03, t04, t05, t06, t09, t11), returned REFUTED, each for `spec_betrayal` alone on an intent disagreement the session had resolved and recorded. These are false accusations of honest fixes: of the twelve sessions that reached the JUDGE, half (6/12) were falsely refuted, a false-positive rate too high to read as noise. Each session's own notes attribute the verdict to the rule firing on any recorded disagreement. They come from the behaviour of the evaluated JUDGE described in Section 6, fixed after the evaluated version in commit `15ccb7a` (shipped in 0.8.0); we did not re-run the fixed JUDGE against these six sessions' artifacts, so whether the fix would have returned all six to VERIFIED is stated, not measured. The JUDGE results in Table 8 are from the independent review pass, run on synthesized task files whose intent section records no disagreement; their absence of false accusations does not extend to the sessions' own JUDGE runs.

9.3.3 Caveats

The external study is small and we do not over-read it. The twelve tasks come from six Python repositories chosen for permissive licenses and a pytest-based suite; they are not a random sample, and the fixes are reconstructed from real commits (the bug is the parent commit; the acceptance tests are the ones the fix touched) rather than open issue reports taken verbatim. The repositories (`tomli`, `idna`, `pyflakes`, `more-itertools`, among others) are public and popular, and the fix commits are probably in the models' training data; re-initializing the history stops the agent from reading the fix in the sandbox but does not remove memorization. We did not use tasks dated after the models' cutoff or measure memorization, so the 48/48 pass rate may be inflated and bears on feasibility, not on capability. The acceptance tests were also pre-applied to the sandbox, which makes the task easier than a real issue. Two models with a single run per cell mean the numbers describe these sessions, not the models in general; agent runs are stochastic. Sessions that hit the harness timeout or the workspace spend limit were re-run, and the study was resumed after the interruption; only completed sessions are counted, and all 48 have status `ok` in the raw results. The raw results do not record the number of re-executions per arm; because the `kata` arm is roughly nine times longer than the `bare` arm, it was more exposed to timeouts, but we cannot quantify the selection effect without the re-execution log. The comparison is between two prompts to the same host (the Kata cycle and a bare prompt), with the bare condition running an isolated agent configuration; it is a clean room for the tool, not for human reviewers. The time difference between arms therefore reflects the cost of the full Kata cycle (all nine phases), not only the JUDGE review. The independent review uses a task file synthesized from each session's declaration and measurement, identical in shape for both arms, so it exercises the scope and weakened-test checks; false completion is outside its scope by construction, and the trap suite covers it. Last, the review time we report is the automated JUDGE pass, not human review time; and because no session in either condition weakened a test according to the JUDGE's own detector, the external study exercises the scope half of the JUDGE's contract, while the weakened-checks half remains covered by the trap suite of Section 9.1.

10 Discussion

The 2026 preprints surveyed in Section 3 — on unreliable agent self-reporting, benchmark confounds, and claim-based verification in other domains — are consistent with Kata's premise that a claim should be re-executed rather than read. They are preprints, and we cite them as context, not as evidence for the design. Kata applies the claim-verification pattern to the software change itself, where the claims are the task file and the ground truth is the repository.

The executed comparison of Section 9.2 sharpens this positioning. All four agent gates detected every planted fraud, separating *detection* from *restraint*: the difference appeared entirely on honest and blind-spot scenarios. Detection did not require an executable core on these fixtures, as prompted reviewers carrying the fraud taxonomy matched code-executing gates. An executable core does not detect more on these fixtures; it delivers a model-independent verdict: reproducible outcomes, review times of 0.1–1.0 s on the trap scenarios, and honest confessions when mechanisms are unobservable. As analyzed in Section 9.2, agent false positives stemmed from repository boundary conditions (`approved_commit`, Git-ignores, unprobed languages) where heuristic agents guess, whereas Kata programmatically confesses blind spots as `UNVERIFIABLE` — a verdict the agents' reporting format did not offer, so this contrast is partly a property of the comparison design. This reflects the reliability-beyond-the-mean insight of the Double Measurement Confound Zhang et al. (2026): agent false positives fluctuated across runs (Table 6), while Kata's deterministic execution produced identical verdicts throughout, with no false accusations on these fixtures.

The limitations of Kata are equally part of the picture. Kata is a verification quality gate: it checks what was claimed against real exit codes and the diff window it is given, within the threat model of Section 6.4, and says nothing about whether the generated patch is optimal or complete beyond the declared checks. It is interactive (falling back to defaults in headless mode); it requires Git; and its success criterion is subjective. When project tests are flawed, re-execution confirms a false oracle Barr et al. (2015), highlighting metamorphic and property-based testing Chen et al. (2018) as complementary future work. The central claim of this paper is descriptive, moreover — Kata re-executes claimed checks and returns an objective verdict; causal evaluation of whether the cycle improves AI-assisted code quality remains for future controlled empirical studies Sahir619 (2026).

11 Threats to validity

The evaluation of Kata, like any tool evaluation, is subject to threats to validity that we state explicitly.

Construct validity. The trap scenarios measure whether the JUDGE detects planted frauds and does not accuse honest work. The construct "fraud" is operationalized as the seven categories the evaluated JUDGE hunts (the current release adds an eighth), which are derived from the failure modes documented in the Fable Method Sahir619 (2026) — an unrefereed GitHub repository, so these categories are a practitioner taxonomy rather than a validated construct — and from the reward-hacking literature Zhao et al. (2026). While the trap suite demonstrates high sensitivity to these planted categories, real-world bug fixes on well-scoped tasks (as observed in Section 9.3) rarely produce active test-weakening fraud under modern frontier models, meaning the ecological validity of these constructs remains to be probed on larger and more ambiguous industrial changes. The zero-weakened count is circular: it is the JUDGE's own syntactic detector, blind to a changed expected value, a loosened comparison, a swapped oracle, tautologies outside its list, the deletion of a real Python assertion (the probes flag only no-op removals by design, Section 6), and an indented comment that hides the assertion at non-zero column; no manual inspection or mutation testing supports it. A fraud category not in the list (for example, a new class of weakened test that the probes do not

recognize) would not be detected, and the blind-spot mechanism is the honest response: the JUDGE confesses what it could not observe rather than claiming to have looked. The adversary is bounded as well: the trap suite plants frauds in claims, not in all Git metadata. s22 covers moving the anchor, which the reflog now detects, and s20 covers the empty diff window; what remains outside the suite is deleting and recreating the anchor, which erases the reflog and is demonstrated only by manual reproduction unless a trusted base is supplied. The empty diff window that the evaluated version produced when a task was approved before its change was committed is fixed in 0.8.0 (commit `3cacc5a`) and guarded by s20; the workflow that closes it after the commit is `kata --stamp`.

Internal validity. The trap scenarios are deterministic fixtures with a ground truth that specifies the exact verdict and the exact frauds the judge must find. The harness fails when the verdict differs, when a fraud is missing, or when an unexpected fraud appears. This determinism removes experimenter bias from the evaluation, but it also means the scenarios test what we thought to test. The honest scenarios mitigate this: they encode false positives that were actually observed in development (the debris false positive, the triviality-gate false positive, the `.kata/` visibility false positive), so they are regression tests for real defects rather than hypothetical ones. In the external study, evaluating single runs ($N = 1$) per cell across two models limits statistical inference regarding stochastic variance in session execution times, serving instead as a deterministic sanity check on the tool's behavior across non-author code.

External validity. The evaluation is bounded in three ways. The trap suite of Section 9.1 uses small synthetic fixtures authored by the developer rather than industrial workloads, with a limited number of honest scenarios (four). The external study of Section 9.3 evaluates real historical bugs across six public open-source repositories, the tasks are intentionally small Python bug fixes with existing pytest suites, evaluated with one run per cell across two models. They demonstrate feasibility on non-author code and restraint in the independent review pass, not in the sessions' own JUDGE runs, six of which falsely accused honest fixes; they do not represent complex multi-file feature additions, non-Python codebases, or proprietary enterprise software. A broader multi-language study across diverse model tiers and task complexities remains future work: the weakened-check detector is per-language by design (Section 6), so this generalization is not automatic and would need language-specific probes validated the same way the Python ones were. A third bound is the Gauntlet pilot's second campaign (Appendix A.4, 30 sessions), which selects its five tasks by a measured gaming-incentive signal, but draws them from the same pool of small, public, Python bug fixes as the external study, and its blind A/B judge is itself an LLM, not an independent human rater; the null result it reproduces should be read within that same workload profile, not as a broader-population finding. The tool itself is also applied to its own repository: its changes are checked by its own lint, tests and coverage, and the trap suite runs in continuous integration on every push. We have no data on use outside the author's own projects.

Author/evaluator conflation. The author designed the JUDGE, wrote the 19 trap scenarios and their ground truth, built the external-study and Gauntlet harnesses, and is also the one reporting and interpreting all of the results above — no external party reviewed the trap scenarios before they were run, and the "blind" A/B judge, while unaware of arm identity, is not independent of the author's instrumentation choices (Section 9.3 and Appendix A.4). This is declared in the Competing Interests statement, but it bears restating here as a validity threat rather than a disclosure formality: every quantitative claim in this paper is self-reported, and the zero-weakened-test findings above are checked by the JUDGE's own detector, which is also the artifact under evaluation (Section 6). Mitigations in place are the dogfooding on the kata repository itself, honest scenarios derived from real observed false positives rather than hypothetical ones, and the executed comparison against independently authored gates (Section 9.2); what remains unmitigated is independent replication — no third party has re-run the trap suite, the external study, or the Gauntlet campaigns against their own ground truth.

Conclusion validity. The claim "the JUDGE catches fraud" is supported by the trap suite, but the claim "Kata improves the quality of AI-assisted changes" is not directly measured. The mechanism is plausible — forcing evidence before approval, re-executing claimed checks, and auditing completed work — and it is supported by the self-correction literature Huang et al. (2024) and the reward-hacking literature Zhao et al. (2026), but a controlled study comparing changes made with and without Kata is needed to establish it.

12 Conclusion

Kata is not a skill. It is the tool that *executes* the discipline that skills ask for, and that distinction is the thesis of this paper. A skill is an instruction; Kata executes the instruction. Where a skill says "verify your tests", Kata runs the tests, measures the coverage, compares it with the gate, and refuses to approve if it fails. Where a skill says "be honest", the JUDGE re-runs the claimed checks and hunts eight categories of fraud.

The evaluation demonstrates where the executable JUDGE succeeds as a deterministic gate and where its boundaries lie. The 19 trap scenarios close on the JUDGE's two-sided contract: every planted fraud is detected with the expected verdict and no honest scenario is accused. The executed comparison of Section 9.2 shows detection parity across gates. Kata returned every expected verdict at approximately one second per review on the trap scenarios (a median of about two seconds on real repositories), but most agent false positives fell on blind-spot scenarios and on a Kata-specific convention, so the comparison establishes determinism and cost rather than superior restraint. The external study shows the JUDGE is feasible on real repositories, and the judgment phases of the nine-phase cycle were not ablated and were evaluated only for cost. An appendix reports an exploratory pilot and a 30-session campaign that carried an iterative builder/critic loop on the same task file and audit machinery. They found no evidence that the loop improves the artifacts, with the direction against the cycle

reversed between the two and one run per cell, and their value is in showing how such a loop can be audited and how the measurement has to be built. The evaluation still does not show that the cycle causally improves the quality of AI-assisted code; a controlled study of changes with and without Kata remains future work, and the pilot's caveats (four tasks, ties in half the blind verdicts, a workload without incentive to cut corners) say why it is not that study. Kata is an enforcement gate, not a panacea: it verifies claimed exit codes and diffs rather than proving patch optimality; it is interactive; it requires Git; and subjective criteria are accepted with explicit caveats.

For software engineering teams seeking objective assurance over AI-assisted code modifications, Kata provides an executable enforcement boundary: it re-executes claimed verification steps, confronts claims with the underlying repository, and flags the claims that re-execution or the diff contradict, within the threat model of Section 6.4.

Acknowledgements

We thank the open-source communities of the Fable Method Sahir619 (2026) and of the Karpathy Development Cycle Karpathy (2026) for the methodologies that inspired this work, and the maintainers of the related tools surveyed in Section 3 for the comparison that sharpened Kata's design.

A Exploratory study: an iterative loop on top of the cycle

The evaluation in Section 9 leaves the judgment phases unablated, and Section 12 names a controlled study of whether the cycle improves the quality of AI-assisted changes as future work. This appendix reports a first, explicitly exploratory step in that direction: an implementation of an iterative builder/-critic loop on top of the Kata cycle, and a pilot that measures whether it improves the artifacts. **The pilot finds no evidence of improvement**: on this workload the loop did not produce a measurable improvement over the cycle without it, and it lost to a bare agent in blind comparison, though with one run per cell none of these differences is statistically distinguishable from noise. We report it because an inconclusive result from a pre-registered pilot is evidence about the method and about how to measure it, and because the instrument corrections it forced are reusable.

A.1 What was built

The loop follows the Gauntlet Loop pattern: an artifact is decomposed into independently judgeable components; a fresh *builder* improves one component; a fresh *critic*, in a separate context that never sees the builder's reasoning, compares the real artifact against a concrete reference (the *bar*) and reports the single largest gap; the next round works from that gap only, until the reference is met or a round ceiling fires. Two design constraints limit what Kata can own here. The objective core of Kata is deterministic — it reads exit codes and Git state — so the loop's execution belongs to the agent host, not to the `kata` package; Kata's role is to carry the loop's *state* and to *audit* it. The other constraint is that a loop whose critic runs in the builder's context is not the method: the independence is the intervention, so it has to be observable.

Kata therefore gained three things, in a fork kept separate from the evaluated version so the artifact of Section 9 is not disturbed: (i) a `gauntlet:` block in the task file (`bar`, `critic`, `boundary`, and an append-only `rounds` list recording component, gap, verdict, and evidence per round), validated on read with the same fail-loud discipline as the schema version; (ii) an audit grade for it, so a declared loop with no concrete bar or no per-round verdict is reported as `faked` rather than passing as `followed`; and (iii) a `kata-gauntlet` skill, generated to both frontends from the single source of truth, that orchestrates builder and critic as subagents. Verdicts are binary (`pass`/`fail`): a numeric scale invites score drift, where the number rises without the artifact improving.

A.2 Protocol

The pilot reuses the external study's design of Section 9.3: real fixes from public repositories, reconstructed from the fix commit with history re-initialized so the fix is not visible, run headless by two models. It adds a third arm. *bare* is the model with no gate; *kata* is the model running the cycle; *gauntlet* is the model running the loop, where the builder never sees the reference and the critic is a separate subagent that does. Four tasks $\times$ two models $\times$ three arms yielded 24 sessions. The reference for the critic is the upstream fix commit, named in a file outside the measured tree; the builder is never given its path.

Metrics and hypotheses were registered in the repository before collection (commit `85eebf9`; a timestamp in our own Git history, not in an external registry), following the calibration discipline the rest of this paper practices. Of the five registered hypotheses, H4 (the loop costs more time than the cycle) was contradicted by the pilot, and H1 (the loop is preferred to the cycle) was supported in the pilot and reversed in the campaign, so it is not supported. The metrics were: acceptance tests, weakened tests (the JUDGE's own detector), undeclared scope, the JUDGE's independent verdict, wall-clock cost, rounds and gaps per component, and — as the primary metric — a *blind A/B preference*: a fresh judge receives the two final diffs of a matched pair with the origins hidden and the order fixed by a hash of (task, model, arm) decided in advance, and returns a winner or a tie. The judge is `claude-sonnet-5`, which is also one of the two models whose sessions it judges; we ran no self-preference or position-bias check. When the two final diffs of a pair are byte-identical the harness records a tie without calling the judge: this happened in 7 of the 24 pilot pairs and 12 of the 30 campaign pairs, so the number of judge calls was 17 and 18.

Two instrument defects were found during the pilot and corrected; both matter beyond this experiment. The harness had measured "tests pass" by running the manifest's `test_cmd`, which for two tasks names a single test file. Re-running the *full* suite over the preserved artifacts revealed a regression the narrow command had reported as a pass. The other defect was in the A/B judge: it receives diffs but not the

base state, so on tasks whose acceptance tests are pre-applied it cannot distinguish "did not update the tests" from "the tests were already there". Both are corrected in the artifact.

A.3 Results

Three results shape the reading of the pilot. The loop ran as a method: all eight gauntlet sessions recorded rounds in the task file and were graded `followed` by the audit, with no `faked` grade; two sessions show a real `fail→pass` cycle, where the critic named a concrete defect and the following round fixed it. One such gap: "`handleNodeLoad` does not mark the annotation as used, so `def f(): name: str; print(name)` emits both `UndefinedName` and `UnusedAnnotation`". The mechanism is implementable and auditable in headless operation (Table 9).

The second result is that there is no evidence of improvement. In the blind A/B comparison over 24 matched pairs, the loop beat the cycle four times and tied four, but lost to the bare agent four times against one win (Table 10); 11 of 24 verdicts were ties, 7 of them byte-identical diffs that never reached the judge. The only regression in the pilot is a single gauntlet session that hit the 1800 s ceiling with four rounds complete and delivered two of the four files the change required, leaving the expectation tests unupdated — infrastructure interrupting the work, not the method failing, but the delivered artifact did regress. The weakened-test count is zero across all 24 sessions, replicating the external study's result. Undeclared scope concentrates on one task in every arm.

The third result concerns cost, and here the hypothesis was wrong in direction: the loop's median session (282 s) was *below* the cycle's (721 s), not above it. Both arms have sessions stopped at the 1800 s ceiling, so these medians compare censored observations. A plausible and untested explanation is that the cycle runs the full verification pipeline on every task, while the loop is directed at the gap.

A.4 A second campaign on a workload chosen for incentive

The pilot's caveat was that its tasks gave the agents no incentive to cut corners, which makes it a poor setting for testing whether a quality loop helps. To address that, three observable signals were defined and measured offline, before any session: whether the acceptance test passes with the bug still present; whether it asserts on fragile proxies such as message substrings, counts, or snapshots; and whether the upstream fix touches more than one source file. A task scoring high on these signals is one where satisfying the visible test need not require fixing the cause. Applying the signals to the study's task set selected five tasks (four of them *not* used in the pilot), and the campaign ran $5 \times 2 \times 3 = 30$ sessions with the four instrument corrections in place: the full suite measured as a delta against each task's pre-existing failures, the A/B judge given the base state, sessions interrupted by the ceiling or by a signal re-run rather than entering the analysis truncated, and the workload selected by measured incentive.

The campaign is clean on every metric (Table 11): thirty of thirty sessions reached `ok`, the JUDGE returned VERIFIED in all thirty with no fraud found, no session weakened a test, none left scope undeclared, and none introduced a regression — while twenty-four of the thirty healed a pre-existing baseline failure. The instrument corrections earned their place in use rather than in argument: two cells were interrupted (one by the session ceiling, one by a signal) and, instead of entering the analysis truncated as in the pilot, were re-run to completion; and the measuring pass itself surfaced a defect that the pilot could not have detected — a session of the cycle arm commits its own work, so measuring the artifact against the moving `HEAD` yields an empty diff and reads a completed fix as "did nothing". One session of the campaign had done exactly that, and its measurement was redone against the task state.

The blind A/B comparison on these thirty pairs is Table 12. Twenty-one of thirty verdicts are ties, but 12 of those are byte-identical diffs that never reached the judge; of the 18 pairs it saw, 9 were ties and 9 were decisive. The nine decisive verdicts are decided on style and minimality — idiom consistency, an explanatory comment, the smaller of two functionally equivalent changes — never on whether the bug was fixed. No judge reported a candidate that failed to address the reported defect. The corrected instrument therefore does not confirm that the loop helps: with a workload selected for incentive, the full suite as the metric, the base state in the judge's prompt and interrupted cells re-run, the loop does not beat the cycle or the bare agent. It does not replicate the pilot's direction either: against the cycle the loop went from 4–0 in the pilot to 1–4 here, and pooled over both studies the decisive verdicts are 5–4 (loop against cycle), 2–6 (loop against bare) and 3–2 (cycle against bare), none of them a clear difference. We report these counts descriptively and attach no p-values: the pairs share sessions, and a sign test would ignore the clustering by task and model. With one run per cell the two studies cannot exclude a modest effect in either direction, and we do not claim they remove alternative explanations. The corrections remove one specific class of them: narrow measurement and truncated cells.

A.5 Caveats

The pilot is small by construction and we do not over-read it. Four tasks give N=1 per cell for a stochastic agent, and 11 of 24 blind verdicts were ties, which limits discrimination. Two cells hit the session ceiling. Two tasks decomposed into a single component, so they exercised no iteration. The blind A/B judge sees diffs without the base state, which favours whichever arm touched the test files; and in one of 24 judgments the judge stated it had applied the diffs and run the suite, which it could not do — a fabrication of execution, recorded rather than discarded, whose verdict direction nonetheless agreed with the independent full-suite measurement. We did not re-inspect the other 23 judgments' stated reasoning for the same failure mode, so this single confirmed case is a lower bound on how often the blind judge misrepresents its own process, not a rate. The reference is the upstream fix, which the measured tree does not contain, so the critic compares against a description of the reference rather than the reference diff itself; a critic noted this in its own gap. The workload is the external study's, finally: clean, well-isolated

Table 9. Exploratory pilot: 4 tasks, two models, three arms, one session per cell (24 sessions). *Regr.* counts sessions introducing failures that the baseline did not have, and *healed* counts sessions fixing pre-existing baseline failures, both measured by the full suite; baselines had 1, 1, 8, and 5 failures on the four tasks. *Weak.* is weakened tests by the JUDGE's detector; *undecl.* is changed files absent from the session's own declaration; *JUDGE* reports the independent review pass. Times are medians with the observed range.

Arm	n	Regr.	Healed	Weak.	Undecl.	JUDGE	Session median [min–max]
bare	8	0	8	0	2	6 V, 2 VWC	85 s [33–307 s]
kata	8	0	8	0	1	7 V, 1 VWC	721 s [231–1800 s]
gauntlet	8	1	8	0	1	7 V, 1 VWC	282 s [119–1800 s]

Table 10. Blind A/B preference over the pilot's 24 matched pairs (17 judge calls, 7 byte-identical pairs recorded as ties; origins hidden, order fixed by a hash decided before collection). The loop beats the cycle and loses to the bare agent.

Match-up	First arm wins	Tie	Second arm wins
gauntlet vs. kata	4	4	0
gauntlet vs. bare	1	3	4
kata vs. bare	2	4	2

bugs with clear regression tests, which gave the agents little incentive to game visible checks — the same condition that makes this a poor setting for testing whether a quality loop helps.

A.6 What scales, and what would have to change

The pilot does not justify scaling the sample; it justifies fixing the instrument, and those four corrections are implemented and archived alongside the pilot. Each earned its place in the second campaign rather than in argument: "tests pass" is measured with the full suite and reported as a delta against the task's pre-existing failures rather than as a pass, because the manifest's narrow test command had reported a regression as a pass; the A/B judge is given the base state with the diffs, so that on tasks whose acceptance tests are pre-applied it cannot mistake "did not update the tests" for "the tests were already there"; a session interrupted by the ceiling or by a signal is re-run with its attempt history recorded, instead of entering the analysis truncated; and the workload is selected by measured incentive rather than by convenience — on three observable signals, whether the acceptance test passes with the bug present, whether it asserts on fragile proxies such as message substrings or counts, and whether the fix touches more than one source file, the pilot's own task set scores low or medium, which is a quantitative form of the observation that those tasks gave the agents no incentive. With the corrections in place the campaign ran, and it again found no evidence of improvement on a workload chosen for incentive (Appendix A.4). What the two studies establish together is narrower and, we think, useful: that an iterative builder/critic loop can be carried and audited by the same task file and audit machinery that Kata already uses, that a blind A/B comparison with a pre-registered protocol is needed to measure whether such a loop helps, and that on the workloads measured here we found no evidence that it does, without power to exclude a modest effect — while the measuring pass itself has reusable value, having found and fixed a defect (a committed artifact invisible to a moving `HEAD`) that neither study's results would have revealed.

Declarations

Availability of data and materials. Kata is open-source software distributed under the MIT License. It is published on the Python Package Index as `kata-dev` (command `kata`); the installable package version is `0.8.0`. Installable with `pipx install kata-dev` or `pip install kata-dev` (Section 8).

Three revisions are relevant to reproducing this paper, and they are not the same commit. The *evaluated version* is the code that was measured: commit `230e81a` for the trap suite, which identifies itself as 0.6.0, and commit `6f56b35` for the comparison and the external study. The logic under `src/kata/` was unchanged between the two. The *release* is tag `v0.8.0`, 91 commits after `230e81a`. Its tree contains every tool cited here, including the `--stats` measurement of Section 4, the session-audit tooling of Section 9.3, and the 0.8.0 additions described in Section 4.5. Because those additions include logic changes — the declared typecheck role, the eighth fraud category, the finer false-completion rule, and the attribution of sibling commits — `v0.8.0` is not the evaluated version. (The earlier tag `v0.7.0` was 24 commits after `230e81a` and differed from the evaluated version in version metadata and help text, not in logic.) The *package* is `0.8.0` on PyPI and matches the tag. It contains fixes made after the evaluated version (commits `3cacc5a`, `3454fc7` and `15ccb7a`, discussed in Sections 6.4 and 9.3) plus the 0.8.0 additions (among them `6931ec7`, `545d704`, `08509fa`, `c8d1690`, `2a16486` and `075c6f4`). Installing from PyPI therefore does not give the code that was measured; the repository history does. A reader reproducing a specific result should use the commit named where that result is reported.

Author contributions. Omitted for review.

Funding. This research received no specific funding from public, commercial, or not-for-profit agencies.

Competing interests. The author is the developer of Kata. The evaluation is self-reported and states its limitations; the author declares no other competing interests.

Use of AI in writing. Generative AI tools were used in three ways, and the distinction matters for how a reader should assess each part of this work. The tools were Anthropic's Claude models driven through a coding agent; the repository's commit history records which model co-authored each change. *Prose*: the manuscript was drafted and then revised with AI assistance, including editing rounds that shortened clauses and removed formulaic constructions; the argument, its structure, and its framing are the author's, and the author rewrote or rejected AI output where it misrepresented the work. *Software*: AI assistance was also used to edit repository code that the paper describes or relies on, including

Table 11. Second campaign: 5 tasks chosen for gaming incentive, two models, three arms, one session per cell (30 sessions). *Regr.* counts sessions introducing failures absent from the baseline, *healed* sessions fixing pre-existing baseline failures, both by the full suite. Times are medians.

Arm	n	Regr.	Healed	Weak.	Undecl.	JUDGE
bare	10	0	8	0	0	10 V
kata	10	0	8	0	0	10 V
gauntlet	10	0	8	0	0	10 V

Table 12. Blind A/B preference over the second campaign's 30 matched pairs (18 judge calls, 12 byte-identical pairs recorded as ties; origins hidden, order fixed by a hash decided before collection). Ties dominate; the decisive verdicts are all stylistic.

Match-up	First arm wins	Tie	Second arm wins
gauntlet vs. kata	1	5	4
gauntlet vs. bare	1	7	2
kata vs. bare	1	9	0

the paper's own build script and the test that guards the scenario counts reported in Section 9.1. *Verification*: all technical claims, citations, measurements, and evaluation results were re-checked by the author against the repository, and the author takes full responsibility for the content. Where the paper reports an AI-assisted experiment, the sessions are attributed to their models in Section 9.3; this declaration concerns the writing and the tooling, not the evaluated subjects.

References

Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., and Mané, D. (2016). Concrete problems in ai safety. arXiv:1606.06565; `https://arxiv.org/abs/1606.06565`. Preprint; accessed 2026-09-11.

Barr, E. T., Harman, M., McMinn, P., Shahbaz, M., and Yoo, S. (2015). The oracle problem in software testing: A survey. *IEEE Transactions on Software Engineering*, 41(5):507–525.

Bouras, D. S., Dai, Y., and Mechtaev, S. (2026). Authority is not a string: A capability-scoped harness for prompt-injection-resistant coding agents. arXiv:2609.08371; `https://arxiv.org/abs/2609.08371`. Preprint, not peer-reviewed; accessed 2026-09-11.

Chen, T. Y., Cheung, S. C., and Yiu, S. M. (2018). Metamorphic testing: A review of challenges and opportunities. *ACM Computing Surveys*, 51(1):4:1–4:27.

Hamidi, A., Konstantinou, M., Degiovanni, R., and Papadakis, M. (2026). How effective are traditional test criteria at detecting bugs in large language models generated code? arXiv:2609.09315; `https://arxiv.org/abs/2609.09315`. Preprint, not peer-reviewed; accessed 2026-09-11.

Hartman, K. (2026). Introducing consort: A spec-first agent framework for enforced, test-driven development on live database branches. arXiv:2609.09671; `https://arxiv.org/abs/2609.09671`. Preprint, not peer-reviewed; accessed 2026-09-11.

Huang, J., Chen, X., Mishra, S., Zheng, H. S., Yu, A. W., Song, X., and Zhou, D. (2024). Large language models cannot self-correct reasoning yet. *International Conference on Learning Representations (ICLR)*.

Huynh, H., Thongtanunam, P., Fu, M., Le, B., and Tantithamthavorn, K. (2026). Xagent: execution-guided agentic ai for effective localization and resolution of github issues. arXiv:2609.09769; `https://arxiv.org/abs/2609.09769`. Preprint, not peer-reviewed; accessed 2026-09-11.

Jimenez, C. E., Yang, J., Wettig, A., Yao, S., Pei, K., Press, O., and Narasimhan, K. (2024). Swe-bench: Can language models resolve real-world github issues? *International Conference on Learning Representations (ICLR)*.

Kapoor, S., Stroebl, B., Siegel, Z. S., Nadgir, N., and Narayanan, A. (2024). Ai agents that matter. arXiv:2407.01502; `https://arxiv.org/abs/2407.01502`. Preprint; accessed 2026-09-11.

Karpathy, A. (2026). From vibe coding to agentic engineering. Talk at Sequoia AI Ascent 2026, with Stephanie Zhan; `https://www.youtube.com/watch?v=96jN2OCOfLs`. Introduces the agentic-engineering discipline (spec design, diff review, tight verification loops) adapted here as the Karpathy Development Cycle; accessed 2026-09-11.

Krakovna, V., Uesato, J., Mikulik, V., Rahtz, M., Everitt, T., Kumar, R., Kenton, Z., Leike, J., and Legg, S. (2020). Specification gaming: The flip side of ai ingenuity. DeepMind blog; `https://deepmind.google/discover/blog/specification-gaming-the-flip-side-of-ai-ingenuity/`. Accessed 2026-09-11.

LerianStudio (2026). Ring: Skills library for ai agents. GitHub repository, commit ad30421; `https://github.com/LerianStudio/ring`. Accessed 2026-09-11.

Manheim, D. and Garrabrant, S. (2018). Categorizing variants of goodhart's law. arXiv:1803.04585; `https://arxiv.org/abs/1803.04585`. Revised 2019; preprint; accessed 2026-09-11.

Mocan, S., Angermeir, F., and Kreitz, M. (2026). Refverifier: Semi-automated reference claim verification for scientific manuscripts. arXiv:2609.07652; `https://arxiv.org/abs/2609.07652`. Preprint, not peer-reviewed; accessed 2026-09-11.

Ning, J., Zhong, S., Li, X., and Zeng, J. (2026). Scores alone do not prove discovery: The discovery certification protocol for auditing ai research agents. arXiv:2609.09219; `https://arxiv.org/abs/2609.09219`. Preprint, not peer-reviewed; accessed 2026-09-11.

Sahir619 (2026). The fable method: The fable workflow. GitHub repository, commit 88b5cf3; `https://github.com/Sahir619/fable-method`. Not peer-reviewed;

accessed 2026-09-11.

TeamSPWK (2026). nova: Ai agent ops for claude code. GitHub repository, commit 1f8f35d; `https://github.com/TeamSPWK/nova`. Accessed 2026-09-11.

vlad-ko (2026). claude-wizard: Turn claude code from a fast coder into a senior software architect. GitHub repository, commit 43756e1; `https://github.com/vlad-ko/claude-wizard`. Accessed 2026-09-11.

Wang, B., Wang, Y., and Wu, Y. (2026). The unreliable progress bar: Can llm agents reliably report task progress throughout execution? arXiv:2609.08589; `https://arxiv.org/abs/2609.08589`. Preprint, not peer-reviewed; accessed 2026-09-11.

Wang-Lin, X., Isopoussu, A., and Mahon, L. (2026). If it's not buggy, don't fix it: On the dynamics of iterative bug-fixing with llms. arXiv:2609.10123; `https://arxiv.org/abs/2609.10123`. Preprint, not peer-reviewed; accessed 2026-09-11.

Zeng, B., Gao, Z., Li, X., Feng, X., and Jiang, J. (2026). Trajmark: Ownership attribution and segment-level tamper localization for coding-agent trajectories. arXiv:2609.10416; `https://arxiv.org/abs/2609.10416`. Preprint, not peer-reviewed; accessed 2026-09-11.

Zhang, Y., Motaali, S., Dinh, V. P., Piroutiniya, A., de Vergara, J. E. L., de Pedro, L., Correia, R., Parra, I. M., and Xie, Y. (2026). The double measurement confound in agent benchmarks: De-scaffolding, ground-truth scoring, and reliability beyond the mean. arXiv:2609.09218; `https://arxiv.org/abs/2609.09218`. Preprint, not peer-reviewed; accessed 2026-09-11.

Zhao, B., Srikanth, D., Wu, Y., and Jiang, Z. (2026). Specbench: Measuring reward hacking in long-horizon coding agents. arXiv:2605.21384v2; `https://arxiv.org/abs/2605.21384`. Revised 9 September 2026; preprint, not peer-reviewed; accessed 2026-09-11.