



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The organization experienced a security incident in which all network services suddenly became unresponsive. After investigation, the cybersecurity team determined that the disruption was caused by a Distributed Denial-of-Service (DDoS) attack involving a flood of incoming ICMP packets. The team responded by blocking the malicious traffic and temporarily disabling all non-critical services to prioritize the recovery of essential network functions.
Identify	The attack was carried out by a malicious actor who targeted the organization using an ICMP flood technique. This traffic overwhelmed the entire internal network, resulting in widespread service disruption. The immediate priority was to secure critical network resources and restore them to normal operational status as quickly and safely as possible.
Protect	To mitigate the attack, the cybersecurity team implemented a new firewall rule designed to rate-limit incoming ICMP traffic. In addition, an Intrusion Detection and Prevention System (IDS/IPS) was deployed to analyze and filter ICMP packets based on suspicious behavior and known malicious patterns.
Detect	Further strengthening the defenses, the team enabled source IP address

	verification at the firewall level to identify and block spoofed IP packets. They also introduced network monitoring tools to provide continuous visibility into traffic patterns and detect abnormal spikes or unusual activity in real time.
Respond	For future incidents, the cybersecurity team plans to isolate affected systems immediately to limit the spread of disruption across the network. They will prioritize restoring critical services, followed by a structured recovery of remaining systems. Network logs will be thoroughly analyzed to identify indicators of malicious activity, and all incidents will be reported to management and relevant authorities when required.
Recover	To ensure effective recovery from ICMP-based DDoS attacks, the response strategy will include blocking external ICMP flood traffic at the firewall level. Non-essential services will be temporarily disabled to reduce network load, while critical systems will be restored first. Once the attack traffic subsides, the remaining services will be gradually brought back online to return the network to normal functioning.

Reflections/Notes: