

# Quality Control–based Robust LOESS Signal Correction in R

*Wanchang Lin*

2025-04-02

## Contents

0.1	Load libraries . . . . .	2
0.2	Read data. . . . .	2
0.3	Missing value filter and fill . . . . .	2
0.4	Set parameters for QC-RLSC . . . . .	8
0.5	QC outlier detection . . . . .	8
0.6	QC-RLSC . . . . .	9
0.7	Batch shift. . . . .	14
0.8	Save results. . . . .	19
0.9	QC-RLSC wrapper function . . . . .	19

## Quality Control–based Robust LOESS Signal Correction in R

### 0.1 Load libraries

The first step is to load necessary libraries. `mt` is used to plot PCA, PLS and LDA plots to access performance of signal correction. `tictoc` records the running time, especially for the optimisation of LOESS.

```
pkgs <- c("qcrLscR", "mt", "tidyverse", "tictoc")
## install.packages(pkgs)
invisible(lapply(pkgs, library, character.only = TRUE))
```

### 0.2 Read data

The data used is `man_qc` in package `qcrLscR`. This data set is a list of two data frames, `data` and `meta`.

```
names(man_qc)
#> [1] "data" "meta"
t(sapply(man_qc, dim))
#>      [,1] [,2]
#> data  462  656
#> meta   462    2
```

Get meta and data matrix

```
meta <- man_qc$meta
data <- man_qc$data %>%
  mutate_if(is.character, as.numeric)
```

Extract group information of batch and sample types

```
names(meta)
#> [1] "batch" "sample_type"
cls.qc <- factor(meta$sample_type)
table(cls.qc)
#> cls.qc
#>      QC Sample
#>    110    352

cls.bl <- factor(meta$batch)
table(cls.bl)
#> cls.bl
#>    1    2    3    4
#> 119 114 119 110
```

### 0.3 Missing value filter and fill

Check missing value rates

## Quality Control–based Robust LOESS Signal Correction in R

```
tail(sort(mv.perc(data)), 20)
#> V1986 V562 V2098 V1602 V348 V1902 V975 V2017 V2020 V163 V1021 V1676 V1540
#> 0.156 0.158 0.160 0.162 0.165 0.167 0.169 0.169 0.169 0.171 0.171 0.171 0.173
#> V1321 V1935 V1079 V610 V1691 V2077 V926
#> 0.182 0.182 0.190 0.197 0.197 0.197 0.199
```

Filter based on missing values

```
filter_qc <- FALSE      # filter on qc missing values or all missing values
thres <- 0.15           # threshold for filtering

if (filter_qc) {        # filter using all missing values
  ret <- mv.filter(data, thres = thres)
} else {                # filter using qc missing values
  ret <- mv.filter.qc(data, cls.qc, thres = thres)
}
```

Update data matrix

```
dat <- ret$dat
```


Missing values filling for visualisation ('mv.fill' is in R package `mt`)

```
dat_fill <- dat %>% mv.fill(method = "median", ze_ne = T) %>% as_tibble()
```

Data screening before signal correction PCA plot for sample types

```
pcaplot(dat_fill, cls.qc, pcs = c(2, 1), ep = 1)
```


## Quality Control–based Robust LOESS Signal Correction in R



PCA plot for batches

```
pcaplot(dat_fill, cls.bl, pcs = c(2, 1), ep = 1)
```


## Quality Control–based Robust LOESS Signal Correction in R



LDA plot for batches

```
plot(pcalda(dat_fill, cls.bl))
```


## Quality Control–based Robust LOESS Signal Correction in R



LDA plot of batches: LD1 vs LD2 (only for batch groups larger than 2)

```
plot(pcalda(dat_fill, cls.bl), dimen = c(1:2), ep = 2)
```


## Quality Control–based Robust LOESS Signal Correction in R



PLS plot of batches: LC1 vs LC2

```
plot(plslda(dat_fill, cls.bl), dimen = c(1:2), ep = 2)
```

## Quality Control–based Robust LOESS Signal Correction in R



### 0.4 Set parameters for QC-RLSC

```
method <- "subtract" # two methods: "subtract", "divide"
intra <- F           # signal correction within batch or not
opti <- T            # optimise smooth parameter or not
log10 <- T           # log 10 transform data or not
outl <- T            # outlier detect in qc samples or not
shift <- T           # batch shift or not
```

### 0.5 QC outlier detection

log transformation

```
if (log10) {
  dat[dat == 0] <- NA
  dat <- log10(dat)
}
```

outlier detection based on QC



## Quality Control–based Robust LOESS Signal Correction in R

```
if (outl) {
  dat <- sapply(dat, function(x) { #' x <- dat[, 6, drop = T]
    qc_ind <- grepl("qc", cls.qc, ignore.case = TRUE, perl = TRUE)
    ## get median of qc data
    qc_dat <- x[qc_ind]
    qc_median <- median(qc_dat, na.rm = TRUE)
    ## assign other data as NA for QC outlier detection
    tmp <- x
    tmp[!qc_ind] <- NA
    ## QC outlier detection
    out_ind <- outl.det.u(tmp)
    ## assign outlier as qc median
    x[out_ind] <- qc_median
    return(x)
  }) %>% as_tibble()
}
dat
#> # A tibble: 462 x 620
#>       V3    V18    V19    V20    V22    V23    V25    V26    V31    V33    V34    V39    V45
#>   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
#> 1  5.94 NA     NA     NA     NA     NA     NA     NA     NA     NA     NA     NA     5.54
#> 2  6.08 5.74 8.18 5.66 4.97 7.46 4.74 7.28 4.88 6.59 6.88 6.36 5.75
#> 3  5.96 5.70 8.15 5.62 4.96 7.47 NA     7.28 4.87 6.64 6.90 6.38 5.71
#> 4  6.04 5.69 8.12 5.60 4.98 7.48 4.75 7.29 4.89 6.61 6.91 6.39 5.78
#> 5  5.99 5.68 8.14 5.61 4.92 7.45 4.71 7.27 4.72 6.57 6.91 6.39 5.75
#> 6  6.04 5.67 8.13 5.60 4.95 7.47 4.74 7.28 4.75 6.56 6.92 6.41 5.76
#> 7  6.05 5.68 8.13 5.60 4.99 7.47 4.75 7.28 4.78 6.56 6.91 6.37 5.76
#> 8  5.95 5.65 8.09 5.57 4.96 7.46 4.73 7.28 4.71 6.56 6.93 6.40 5.73
#> 9  5.97 5.63 8.10 5.57 4.95 7.47 NA     7.28 4.93 6.61 6.90 6.37 5.75
#> 10 6.02 5.61 8.08 5.54 4.98 7.47 4.73 7.29 4.97 6.65 6.91 6.39 5.76
#> # i 452 more rows
#> # i 607 more variables: V48 <dbl>, V51 <dbl>, V66 <dbl>, V68 <dbl>, V71 <dbl>,
#> #   V72 <dbl>, V73 <dbl>, V74 <dbl>, V104 <dbl>, V106 <dbl>, V112 <dbl>,
#> #   V115 <dbl>, V116 <dbl>, V121 <dbl>, V122 <dbl>, V123 <dbl>, V124 <dbl>,
#> #   V125 <dbl>, V126 <dbl>, V128 <dbl>, V134 <dbl>, V138 <dbl>, V140 <dbl>,
#> #   V142 <dbl>, V147 <dbl>, V149 <dbl>, V157 <dbl>, V158 <dbl>, V159 <dbl>,
#> #   V160 <dbl>, V162 <dbl>, V164 <dbl>, V167 <dbl>, V169 <dbl>, V171 <dbl>, ...
```

### 0.6 QC-RLSC

perform qc-rlsc within each batch or not

```
tic()
if (!intra) {
```

## Quality Control–based Robust LOESS Signal Correction in R


```
res <- qc.rlsc(dat, cls.qc, method = method, opti = opti)
} else { # do signal correction inside each batch
  res <- lapply(levels(cls.bl), function(x) {
    idx <- cls.bl %in% x
    tmp <- qc.rlsc(dat[idx,], cls.qc[idx], method = method, opti = opti)
  })
  res <- bind_rows(res)
}
toc()
#> 17.11 sec elapsed
```

Data visualisation after signal correction

```
res_fill <- res %>% mv.fill(method = "median", ze_ne = T) %>% as_tibble()
```

PCA plot for sample types


```
pcaplot(res_fill, cls.qc, pcs = c(2, 1), ep = 1)
```



PCA plot for batches

## Quality Control–based Robust LOESS Signal Correction in R


```
pcaplot(res_fill, cls.bl, pcs = c(2, 1), ep = 1)
```



LDA plot for batches

```
plot(pcalda(res_fill, cls.bl))
```


## Quality Control–based Robust LOESS Signal Correction in R



LDA plot of batches: LD1 vs LD2 (only for batch groups larger than 2)

```
plot(pcalda(res_fill, cls.bl), dimen = c(1:2), ep = 2)
```


## Quality Control–based Robust LOESS Signal Correction in R



PLS plot of batches: LC1 vs LC2

```
plot(plslda(res_fill, cls.bl), dimen = c(1:2), ep = 2)
```

## Quality Control–based Robust LOESS Signal Correction in R



### 0.7 Batch shift

```
if (shift) {  
  res <- batch.shift(res, cls.bl, overall_average = T) %>% as_tibble()  
}
```


Data visualisation after batch shift

```
res_fill <- res %>% mv.fill(method = "median", ze_ne = T) %>% as_tibble()
```

PCA plot for sample types

```
pcaplot(res_fill, cls.qc, pcs = c(2, 1), ep = 1)
```


## Quality Control–based Robust LOESS Signal Correction in R



PCA plot for batches

```
pcaplot(res_fill, cls.bl, pcs = c(2, 1), ep = 1)
```

## Quality Control–based Robust LOESS Signal Correction in R




LDA plot for batches

```
plot(pcalda(res_fill, cls.bl))
```




## Quality Control–based Robust LOESS Signal Correction in R



LDA plot of batches: LD1 vs LD2 (only for batch groups larger than 2)

```
plot(pcalda(res_fill, cls.bl), dimen = c(1:2), ep = 2)
```


## Quality Control–based Robust LOESS Signal Correction in R



PLS plot of batches: LC1 vs LC2

```
plot(plslda(res_fill, cls.bl), dimen = c(1:2), ep = 2)
```

## Quality Control–based Robust LOESS Signal Correction in R



### 0.8 Save results

inverse log10 transformation

```
res <- 10^res %>% as_tibble()

tmp <- list(data = res, meta = meta)
## write.xlsx(tmp, file = here::here("data", paste0(FILE, "_res.xlsx")),
##           asTable = F, overwrite = T, rowNames = F, colNames = T)
```

### 0.9 QC-RLSC wrapper function

or use wrapper function `qc_rlsc_wrap` directly

```
## res <- qc.rlsc.wrap(dat, cls.qc, cls.bl, method, intra, opti, log10, outl,
##                    shift)
## tmp <- list(data = res, meta = meta)
## write.xlsx(tmp, file = here::here("data", paste0(FILE, "_res.xlsx")),
##           asTable = F, overwrite = T, rowNames = F, colNames = T)
```