

# LoggerStartUp()

## Synopsis

```
int LoggerStartUp()
```

## Description

Initializes internal data structure and starts the logger services.

LoggerStartUp() returns 0 on success and -1 on error.

## Example Usage

This function is failed safe which means when an error occurs the application can continue processing.

```
If( LoggerStartUp() == -1 )
{
    printf("Refer to additional error codes for further details\n");
}
```

## Error Codes

Error codes are written to the following files, where the <cpid> is the application process id number:

- /tmp/<cpid>-LoggerAppsMessage.txt
- \$LOGGER\_HOME\_PATH/LoggerOutput/<cpid>-LoggerAppsMessage.txt

|                                                             |                                                                                                                                 |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| 107, 108, 109, 110, 111                                     | Invalid message grouping id=value pair.                                                                                         |
| 112, 113, 114                                               | Invalid message severity level id=value pair.                                                                                   |
| 118                                                         | Environment variable LOGGER_HOME_PATH is not defined.                                                                           |
| 119                                                         | Failed to create apps message log output file.                                                                                  |
| 120, 130                                                    | Failed to get process executable name.                                                                                          |
| 131                                                         | Failed to determine adjustable configuration data.                                                                              |
| 132, 133, 121, 122,<br>123, 124, 125, 126,<br>127, 128, 129 | Failed to validate LoggerMessageDefines.txt file.                                                                               |
| 134                                                         | Failed to create log file.                                                                                                      |
| 102,<br>101, 103                                            | Only one application instance using the Logger is permitted.<br>Failed to determine if another application is using the Logger. |