Setup definitions in LoggerMessageDefines.txt

Wandi-SASL functions use the logical `message_group` id=value and `severity` id=value pairs defined in $LOGGER_HOME_PATH/LoggerSecureVault/LoggerMessageDefines.txt file.

The logical `message_group` represents groups of related log messages. Log messages can be generated from one or more application functions and/or across multiple application files. For example, defining a logical `message_group` id=value pair as 100=DATABASE and using 100 in the LoggerAppsMsg() will generate the value DATABASE for those log messages.

```
#** Define 1 to 32 unique logical message_group id=value pairs **/
LOGGER_MESSAGE_GROUP_START
100=DATABASE
101=User_Interface
102=Main_routine
LOGGER_MESSAGEGROUP_END
```

The logical `message_group` id integer part must be defined as a unique number (maximum of 32 id=value pairs), and the value part is an alphanumeric text that represents the `message_group` name (maximum of 32 characters).

The `severity` id=value pair represents the importance for log messages. For example, severities for Fatal, Error, and Inform could be represented as 1, 2 and 3 respectively.

```
#** Define from 1 through 4 severity id=value pairs **/
LOGGER_SEVERITY_START
1=FATAL
2=ERROR
3=INFORM
LOGGER_SEVERITY_END
```

The `severity` id integer part must be a unique number from 1 through 4 (maximum of 4 id=value pairs), and the value part is an alphanumeric text that represents a `severity` name (maximum of 16 characters).

Note that lines that start with a "#" sign is treated as a commented line.

During `LoggerStartUp()` these id=value pairs are validated and any error codes are written to the following files (where <cpid> is the application process id number:

- /tmp/<cpid>-LoggerAppsMessage.txt
- $LOGGER_HOME_PATH/LoggerLibApps/LoggerOutput/<cpid>-LoggerAppsMessage.txt