

WandiSSAL_LoggerStartup()

Synopsis

```
#include "WandiSSAL-LoggerLib-2.0.h"
```

```
int WandISSAL_LoggerStartup()
```

Description

Initializes internal data structure and starts the logger services.

WandiSSAL_LoggerStartup() returns 0 on success and -1 on error.

Example Usage

This function is failed safe which means when an error occurs the application can continue processing.

```
If( WandISSAL_LoggerStartup() == -1 )
{
    printf("Refer to additional error codes for further details\n");
}
```

Error Codes

Error codes are written to the following files, where the <cpid> is the application process id number:

- /tmp/<cpid>-LoggerAppsMessage.txt
- \$LOGGER_HOME_PATH/LoggerOutput/<cpid>-LoggerAppsMessage.txt

107, 108, 109, 110, 111	Invalid message grouping id=value pair. Solution: Refer to the LoggerMessageDefines.txt guidelines.
112, 113, 114	Invalid message severity level id=value pair. Solution: Refer to the LoggerMessageDefines.txt guidelines.
118	Environment variable LOGGER_HOME_PATH is not defined or accessible. Solution: Refer to the README for guidelines.
119	Failed to create application message log output file. Solution: Make sure LoggerOutput directory has write permission.
120, 130	Failed to get the application executable name.
132, 133, 121, 122, 123, 124, 125, 126, 127, 128, 129	Failed to validate LoggerMessageDefines.txt file. Solution: Make sure file exists.
134	Failed to create log file. Solution: Make sure LoggerOutput directory has write permission.
102, 101, 103	Only one running application instance is permitted. Failed to determine if another application instance is running. Solution: Make sure LoggerSecureVault has write permission.
145	Invalid PRODUCTION value. Solution: Refer to LoggerMessageDefines.txt guidelines