

How to use Wandi-SSAL Fail-Safe API functions

API capability is integrated with applications when compiled/linked with WandiSSAL-LoggerLib2.0.a library.

- WandiSSAL_LoggerStartUp() initializes internal structures and starts the logger capabilities.
- WandiSSAL_LoggerAppsMsg() generates application log messages.
- WandiSSAL_LoggerShutDown() frees-up internal structures and stops the logger capabilities.

```
#include <stdio.h>

#include "WadniSSAL-LoggerLib-2.0.h"

main()
{
    WandiSSAL_LoggerStartUp();

    ...application code...

    WandiSSAL_LoggerAppsMsg(1,100,3,"Message that generates 1 string and 2
integer arguments [%s], [%d] and [%d]","String Argument", 98,99);

    ...application code...

    WandiSSAL_LoggerShutDown();
}
```

```
02/09/2026 12:01:55 [3650:sample_program] [DATABASE] [INFORMATIONAL] Message
that generates 1 string and 2 integer arguments [String Argument], [98] and
[99]
```

Where:

- "02/09/2026 12:01:55" date and timestamp when the log message was generated.
- "[3650:sample_program]" application process id and name.
- "[DATABASE]" logical message group for related application log messages.
- "[INFORMATIONAL]" severity for log message.
- The remainder of the output is derived from the C-Programming Language printf() format string specification and corresponding string specifier data value.