

Setup definitions in LoggerMessageDefines.txt

Wandi-SSAL API functions use the logical message_group id=value, severity id=value pairs and PRODUCTION value in \$LOGGER_HOME_PATH/LoggerSecureVault/LoggerMessageDefines.txt file.

The logical message_group represents groups of related log messages. Log messages can be generated from one or more application functions and/or across multiple application files. For example, defining a logical message_group id=value pair as 100=DATABASE and using 100 in the LoggerAppsMsg() will generate the value DATABASE for those log messages.

```
*** Define 1 to 32 unique logical message_group id=value pairs **/  
LOGGER_MESSAGE_GROUP_START  
100=DATABASE  
101=User_Interface  
102=Main_routine  
LOGGER_MESSAGE_GROUP_END
```

The logical message_group id integer part must be defined as a unique number (maximum of 32 id=value pairs), and the value part is an alphanumeric text that represents the message_group name (maximum of 16 characters). Do not change keywords LOGGER_MESSAGE_GROUP_START and LOGGER_MESSAGE_GROUP_END.

The severity id=value pair represents the importance for log messages. For example, severities for Fatal, Error, and Inform could be represented as 1, 2 and 3 respectively.

```
*** Define from 1 through 4 severity id=value pairs **/  
LOGGER_SEVERITY_START  
1=FATAL  
2=ERROR  
3=INFORM  
LOGGER_SEVERITY_END
```

The severity id integer part must be a unique number from 1 through 4 (maximum of 4 id=value pairs), and the value part is an alphanumeric text that represents a severity name (maximum of 16 characters). Do not change keywords LOGGER_SEVERITY_START and LOGGER_SEVERITY_END.

```
*** If PRODUCTION=y then only log messages with DevProd=2  
*** will be generated.  
*** If PRODUCTION=n then log messages with both DevProd=1 and  
*** DevProd=2 will be generated.  
LOGGER_LOG_ENV_START  
PRODUCTION=n  
LOGGER_LOG_ENV_END
```

The PRODUCTION value must be 'n' to generate log messages where DevProd parameter is equal to 1 or 2, or must be 'y' to generate log message where DevProd parameter is equal to 2. The 'y' option prevents generating unnecessary development log messages in a production environment.

Note that lines that start with a “#” sign is treated as a commented line.

During LoggerStartUp() these id=value pairs are validated and any error codes are written to the following files (where <cpid> is the application process id number:

- /tmp/<cpid>-LoggerAppsMessage.txt
- \$LOGGER_HOME_PATH/LoggerLibApps/LoggerOutput/<cpid>-LoggerAppsMessage.txt