

Setup definitions in LoggerMessageDefines.txt

Wandi-SSAL API functions use the logical `message_group id=value`, `severity id=value` pairs and `PRODUCTION` value in `$LOGGER_HOME_PATH/LoggerSecureVault/LoggerMessageDefines.txt` file.

The logical `message_group` represents groups of related log messages. Log messages can be generated from one or more application functions and/or across multiple application files. For example, defining a logical `message_group id=value` pair as `100=DATABASE` and using 100 in the `LoggerAppsMsg()` will generate the value `DATABASE` for those log messages.

```
*** Define 1 to 32 unique logical message_group id=value pairs **/  
LOGGER_MESSAGE_GROUP_START  
100=DATABASE  
101=User_Interface  
102=Main_routine  
LOGGER_MESSAGE_GROUP_END
```

The logical `message_group id` integer part must be defined as a unique number (maximum of 32 `id=value` pairs), and the value part is an alphanumeric text that represents the `message_group` name (maximum of 16 characters). Do not change keywords `LOGGER_MESSAGE_GROUP_START` and `LOGGER_MESSAGE_GROUP_END`.

The `severity id=value` pair represents the importance for log messages. For example, severities for Fatal, Error, and Inform could be represented as 1, 2 and 3 respectively.

```
*** Define from 1 through 4 severity id=value pairs **/  
LOGGER_SEVERITY_START  
1=FATAL  
2=ERROR  
3=INFORM  
LOGGER_SEVERITY_END
```

The `severity id` integer part must be a unique number from 1 through 4 (maximum of 4 `id=value` pairs), and the value part is an alphanumeric text that represents a `severity` name (maximum of 16 characters). Do not change keywords `LOGGER_SEVERITY_START` and `LOGGER_SEVERITY_END`.

```
*** If PRODUCTION=y then only log messages with DevProd=2  
*** will be generated.  
*** If PRODUCTION=n then log messages with both DevProd=1 and  
*** DevProd=2 will be generated.  
LOGGER_LOG_ENV_START  
PRODUCTION=n  
LOGGER_LOG_ENV_END
```

The `PRODUCTION` value must be 'n' to generate log messages where `DevProd` parameter is equal to 1 or 2, or must be 'y' to generate log message where `DevProd` parameter is equal to 2. The 'y' option prevents generating unnecessary development log messages in a production environment.

Note that lines that start with a “#” sign is treated as a commented line.

During `LoggerStartUp()` these `id=value` pairs are validated and any error codes are written to the following files (where `<cpid>` is the application process id number:

- `/tmp/<cpid>-LoggerAppsMessage.txt`
- `$LOGGER_HOME_PATH/LoggerLibApps/LoggerOutput/<cpid>-LoggerAppsMessage.txt`