



**GroundWork Monitor
Ganglia Integration Module
System Administrator Guide**

Revision 5.1.0
March 24, 2011

Prepared by: **GroundWork Open Source, Inc.**
139 Townsend Street, Suite 500
San Francisco, CA 94107

Contents

1 Overview.....	3
2 Installation	4
2.1 GroundWork Monitor.....	4
2.2 Fresh Installation of the Ganglia Integration Module.....	4
2.3 Upgrading from a Previous Release of the Ganglia Integration Module.....	6
3 Detailed Description.....	8
3.1 Check Ganglia and Nagios.....	8
3.2 Performance Considerations.....	11
3.3 ganglia Database.....	12
3.3.1 cluster Table.....	12
3.3.2 clusterhost Table.....	12
3.3.3 host Table.....	13
3.3.4 hostinstance Table.....	13
3.3.5 location Table.....	13
3.3.6 metric Table.....	14
3.3.7 metricinstance Table.....	14
3.3.8 metricvalue Table.....	14
3.4 Ganglia Web Interface.....	15
3.4.1 Threshold Configuration.....	15
3.4.2 Access to Ganglia Web Servers.....	15
3.5 Auto-Import.....	16
4 Administration.....	18
4.1 Ganglia-Related Configuration.....	18
4.1.1 Check Ganglia Configuration.....	18
4.1.2 Ganglia Threshold Administration Configuration.....	21
4.1.3 Ganglia Web Server Viewing Configuration.....	22
4.1.4 Ganglia Portal Access Permissions.....	23
4.2 Ganglia Database Administration.....	24
4.2.1 Defining Thresholds.....	24
4.2.2 Validating the Configuration.....	29
4.2.3 Finding and Deleting Hosts.....	29
4.3 Auto-Import Configuration.....	31
Appendix A: Revision History.....	35

1 Overview

This document describes the system administrator tasks required to install and administer the software which integrates GroundWork Monitor with Ganglia, referred to as the *Ganglia Integration Module*. This software allows information gathered by the Ganglia monitoring system to be processed by a GroundWork Monitor system.

Ganglia is an agent-based, cluster-oriented monitoring system. It is useful for large installations with many similar hosts. It is efficient and scalable, and can collect and graph many different metrics. Ganglia, however, does not include threshold values for these metrics, or notifications when these thresholds are violated. Nor does it include reporting. These functions are part of GroundWork Monitor, via the Nagios® monitoring system and GroundWork's user interfaces and databases. This integration module brings these projects together by allowing GroundWork Monitor operator views, dashboards, reports, notifications, and configuration tools to be applied to Ganglia data.

The Ganglia Integration Module has the following features.

- A “collector” gathers information for each host running the Ganglia gmond agent, and relays that information to a GroundWork Monitor host. For each monitored host, selected metrics are compared against warning and critical thresholds. If the thresholds are exceeded for a configured duration, a service alert is generated.
- A web interface called the Ganglia Configuration Administration tool is provided. This interface allows the administrator to:
 - Define Ganglia metrics to monitor (i.e., select a subset of the metrics that Ganglia is collecting, for purposes of watching for extreme values).
 - Define warning, critical, and duration thresholds for the watched metrics.
 - Assign watched-metric thresholds globally (to all Ganglia clusters), to specific Ganglia clusters, or to specific hosts.
 - View the current metric state of certain metrics monitored by the Ganglia interface, for particular hosts.
 - Conveniently access the web pages provided by Ganglia itself.
- An import script that automatically defines the Ganglia hosts to the GroundWork Monitor system is also included. The Monarch Nagios configuration database is updated by the import script, and Monarch procedures are called to automatically commit the changes to Nagios.

The integration module package consists of the following main components:

- Check Ganglia daemon, `check_ganglia.pl`. This module reads a set of Ganglia gmetad and/or gmond XML streams and extracts the metrics for each host. It compares these metrics to the defined watched-metric thresholds to determine if a metric is in violation of its associated thresholds. It then sends passive service check results to the Nagios command pipe. The daemon also updates the `ganglia` database.
- `ganglia` MySQL database. This database contains:
 - The default, per-cluster, and per-host watched-metric thresholds.
 - The current metric measurements for each host.
- Ganglia configuration administration CGI programs, presented as portal applications within GroundWork Monitor Enterprise Edition. The standard security mechanisms available to similar portal applications (e.g., limiting access to only certain Roles) are also available for these portal pages.
- Auto-import script. This script, `autoimport.pl`, queries the `ganglia` MySQL database for hosts reported by the check ganglia daemon. It then queries the monarch database for hosts defined in Nagios, and finds Ganglia hosts that are not in Nagios, which it adds to the monarch database. It applies a default `ganglia` profile to such new hosts, and optionally commits the changes to Nagios.

The detailed design of the system is described below.

2 Installation

The following software prerequisites are required to install the Ganglia Integration Module.

- GroundWork Monitor Enterprise Edition version 6.4.0.
- Ganglia Version 3.0.x or 3.1.X monitoring your infrastructure. Note: it is not necessary to install gmond or gmetad on the GroundWork server, but if you do not, you must ensure that the GroundWork server can access the XML feed on at least one gmond or gmetad instance.

The Ganglia Integration Module is supplied as a set of RPM packages:

- `groundwork-ganglia-integration`
- `groundwork-autoimport`

Multiple RPMs are used to provide appropriate granularity for upgrades as this software and the base product both evolve. Currently, RPMs are provided for Red Hat Enterprise Linux 5 32-bit and Red Hat Enterprise Linux 5 64-bit platforms.

Certain customer-specific extensions may be supplied to those customers as separate RPMs:

- `groundwork-ganglia-customername`
- `groundwork-autoimport-customername`

The `check_ganglia.pl` script which is at the heart of this software runs continually under control of the GroundWork Monitor `gwservices` service. To enable us to automatically install all the software in its intended locations without having it disrupt system operation before it is properly configured, the daemon script looks for the `enable_processing` setting in its configuration file. If the option is turned off, as it is in the default installed configuration file, the script will just emit a log message saying that processing is not enabled, and it will then sleep for a very long time.

To install, you will need to perform the following steps:

- Set up GroundWork Monitor Enterprise Edition.
- Set up Ganglia, and in particular make sure you understand where the gmond and/or gmetad XML feeds are accessible.
- Install the required Ganglia Integration RPM.
- Optionally install the Autoimport RPM.
- Configure and start the software.

The rest of this chapter contains basic instructions for performing these steps.

2.1 GroundWork Monitor

Install GroundWork Monitor according to the standard product installation procedures.

2.2 Fresh Installation of the Ganglia Integration Module

All the Ganglia Integration RPMs get installed on your top-level GroundWork Monitor system, which is where the `check_ganglia.pl` script will run.

Note: Installation of the RPMs will restart both of the `apache` and `gwservices` components of GroundWork Monitor. This will disrupt existing, running sessions where users are accessing GroundWork Monitor. Thus, you may wish to wait until a convenient period of low use to perform these steps.

Install the RPMs for your platform. Here we specify them as individual `rpm` commands, but you may combine them on a single `rpm` command if you wish. The `groundwork-ganglia-customername` and/or `groundwork-autoimport-customername` RPMs will only be installed at particular customer sites.

```
rpm -Uvh groundwork-ganglia-integration-release-build.platform.rpm
rpm -Uvh groundwork-ganglia-customername-release-build.platform.rpm
rpm -Uvh groundwork-autoimport-release-build.platform.rpm
rpm -Uvh groundwork-autoimport-customername-release-build.platform.rpm
```

where `platform` is `i386` for a 32-bit platform, `x86_64` for a 64-bit platform, or `noarch` for either platform.

Once the software is installed, take the following steps:

- Create the ganglia database. This is a destructive operation (it will wipe out any previous database named ganglia). Creating the database is not done automatically during RPM installation because we cannot assume where you want to have this database reside.

```
mysql options < /usr/local/groundwork/core/databases/ganglia_db_create.sql
```

where the *options* are whatever you need to access the proper MySQL instance, such as:

```
mysql -h host -u root -p < ganglia_db_create.sql
```

Note: If you don't have a password for the MySQL root account (definitely not a recommended setup!), just type Return at the password prompt.

- Set up the `/usr/local/groundwork/config/check_ganglia.conf` config file (Section 4.1.1, [Check Ganglia Configuration](#), on page 18). In particular:
 - Check that the `GANGLIA_GMOND_PORT` and `GANGLIA_GMETAD_PORT` definitions match the port numbers in use at your site.
 - Define the hosts and ports at which Ganglia XML streams should be accessed to obtain metric data (`<ganglia_hosts>` section).
 - List the names of the particular Ganglia clusters you wish to monitor (`ganglia_cluster` lines).
 - Adjust the database-access parameters to fit your local site (`dbHost` through `dbPass`).
 - Set `enable_processing = yes` (this parameter appears at the top of the file) once all the other setup in this file is ready.
- Set up the `/usr/local/groundwork/config/GangliaConfigAdmin.conf` config file (Section 4.1.2, [Ganglia Threshold Administration Configuration](#), on page 21). In particular, adjust the database-access parameters to fit your local site (`DatabaseHost` through `DatabasePass`).
- Set up the `/usr/local/groundwork/config/GangliaWebServers.conf` config file (Section 4.1.3, [Ganglia Web Server Viewing Configuration](#), on page 22). In particular, define the hosts and URLs at which your Ganglia Web Server pages are available for viewing (`<ganglia_web_servers>` section).
- Set up the `/usr/local/groundwork/config/autoimport.conf` config file (Section 4.3, [Auto-Import Configuration](#), on page 31). In particular:
 - Check the `commit_changes` value to make sure it will reflect your local usage of auto-import.
 - Check the `process_wg_hostgroups` value to make sure it reflects your local usage. Almost all customers will set this to no.
 - Check the `custom_hostgroup_package` and `custom_hostgroup_package_options` values to make sure they reflect your local usage. Most customers will set the `custom_hostgroup_package` to an empty string; this option must be set properly even if `process_wg_hostgroups` is set to no.
 - Adjust the database-access parameters to fit your local site (`ganglia_database` through `ganglia_dbpwd`, and possibly `cacti_database` through `cacti_dbpwd`).
 - Check the `process_cacti_hosts` value to make sure it reflects your local usage.
- Create various objects within Monarch that will be needed by auto-import. See Section 4.3, [Auto-Import Configuration](#), on page 31 for details.
- Set up a cron job for auto-import, perhaps.
- Kill the `check_ganglia.pl` daemon so it restarts (under control of `gwservices`) using the modified configuration file. Finding the right process to kill is a bit complicated because of the manner in which Perl is installed in GroundWork Monitor. You can either restart all of `gwservices`:

```
service groundwork restart gwservices
```

or target just the `check_ganglia.pl` daemon. This command will do the trick (or complain with a usage message if the daemon is not running):

```
kill `ps -w -w --no-headers -C .perl.bin -o pid,args | fgrep check_ganglia.pl | awk '{print $1}'`
```

Note that all of the configuration files above (`check_ganglia.conf`, `GangliaConfigAdmin.conf`, `GangliaWebServers.conf`, and `autoimport.conf`) have definite controlled ownership (`nagios:nagios`) and permissions (`600`). These settings are not optional; the configuration files are checked for access rights each time the associated program runs, and each program will not run if access to the configuration file is not restricted.

At this point, all of the components are installed and ready to begin collecting data and monitoring your infrastructure. Please read the main body of this document to learn how to get the database populated with your Ganglia-monitored hosts, import them into GroundWork Monitor, set up the thresholds on the metrics, and start getting results.

You may also want to modify the default access controls set up for the Ganglia Integration Module's UI pages. See Section 4.1.4, [Ganglia Portal Access Permissions](#), on page 23 for details.

2.3 Upgrading from a Previous Release of the Ganglia Integration Module

Read through this entire section before beginning. Some steps must be taken manually on the old system to capture configuration data there and transfer it to the new system.

The ganglia database schema and the configuration files for this release are compatible with those from the Ganglia Integration Module version 4.X.X releases. The basic upgrade strategy, therefore, is to save your old database and configuration files, then run the Fresh Installation procedure in the previous section, putting back your old database and configuration files as needed. The following caveats apply:

- You may create the ganglia database as noted under Fresh Installation, but you will then replace its content with that of the old database, to restore the metric thresholds you previously configured.
 - To back up your old database, run a copy of `mysqldump` that knows where your ganglia database is located. For instance, on a GroundWork Monitor 5.1.3 system with the database on the same machine, the command would be:


```
/usr/bin/mysqldump -u root -p ganglia > /tmp/ganglia-db.dump
```
 - To restore the database dump on the upgraded system, after moving it to the `/tmp` directory on your GWME 6.4 system, use the following commands:


```
cd /usr/local/groundwork/mysql/bin
./mysql -h host -u root -p ganglia < /tmp/ganglia-db.dump
```
- The `gangliaconfig.conf` file from the previous release is no longer used.
- Ownership of the `check_cacti.conf` and `GangliaConfigAdmin.conf` files has changed. Keep the setup established by the new release for the ownership (`nagios:nagios`) and permissions (`600`) on these files.
- The `/usr/local/groundwork/etc/check_ganglia.conf` file in the previous releases has been moved. Its new location is listed above, in the Fresh Installation section.
- Certain parameters in the `check_ganglia.conf` file may no longer be relevant in the upgraded environment. In particular:
 - `custom_metrics_package` should be set to `" "` if you will no longer be using a customer-specific package (`groundwork-ganglia-customername` RPM) to process metric data.
 - Database-access parameters are likely to have changed, if only because you most probably will be running the ganglia database on new hardware in conjunction with an upgrade to the GWME 6.4 release.
- The `/usr/local/groundwork/etc/GangliaConfigAdmin.conf` file in the previous releases has been moved. Its new location is listed above, in the Fresh Installation section.
- Certain parameters in the `GangliaConfigAdmin.conf` file may have changed in the upgraded environment. In particular:
 - Database-access parameters are likely to have changed, if only because you most probably will be running the ganglia database on new hardware in conjunction with an upgrade to the GWME 6.4 release.

- The `GangliaWebServers.conf` file is new with the Ganglia Integration Module 5.0.0 release, and must be configured from scratch.
- Certain parameters in the `autoimport.conf` file may have changed in the upgraded environment. In particular:
 - Logging now pays more attention to the configured debug level. For this reason, you probably want to set the `debug_level` to 5 (log statistical data) to capture operational statistics in the log file.
 - The standard logfile path has changed. It is now:

```
# Where to put all the log messages from autoimport processing.  
logfile = "/usr/local/groundwork/nagios/var/log/autoimport.log"
```


(Note that the RPM installation will create a symlink to this path in the `/usr/local/groundwork/logs/` directory, for convenient access.)
 - You may wish to revisit your settings for the `custom_hostgroup_package` and `custom_hostgroup_package_options` options, if you have `process_wg_hostgroups` enabled and there are any recent changes to the packages you have available for assigning hostgroups to hosts.
 - Database-access parameters are likely to have changed, if only because you most probably will be running the `ganglia` and `cacti` databases on new hardware in conjunction with an upgrade to the GWME 6.4 release.

3 Detailed Description

The operation of the Ganglia Integration Module is described in the following sections.

3.1 Check Ganglia and Nagios

The following diagram illustrates the system operation.



Ganglia data for an entire grid or cluster can be queried from the gmond or gmetad agents. The agents output their data in a standard XML stream format, documented in the Ganglia manuals. You can inspect this stream by entering the command “telnet <ganglia host> <port #>” where <ganglia host> is the host name or IP address of the host executing the Ganglia gmond or gmetad agent and <port #> is the TCP port where gmond or gmetad is configured to attach. Typically, this is 8649 for a host running gmond and 8651 for a host running gmetad.

The check_ganglia daemon reads this XML stream to find the metrics for each host. The XML stream describes the cluster-host-metric hierarchy. Be aware that the XML data envelopes do differ between the gmond and gmetad streams. The check_ganglia daemon is capable of interpreting both. In general, if you are running gmetad, you will use that XML data stream.

The check_ganglia daemon is implemented as the check_ganglia.pl script. This is not a Nagios plugin, despite its resident directory and the similar-looking filename. It is not launched as an active check by the Nagios scheduler. Instead, it runs under the supervise director program, which will restart programs under its control. The supervise program is itself run as part of the GroundWork Monitor gwservices component.

The check_ganglia daemon polls every 5 minutes by default, maintaining the current status states and metric values in memory. When it starts, check_ganglia.pl first reads the last state and metric values from the ganglia MySQL database. This initial read of the data allows the daemon to detect state transitions even on the first polling cycle. At the beginning of each polling cycle, the thresholds are read anew from the ganglia database, to pick up any recent changes. After each poll, the daemon compares the last values with the thresholds and sets the state of each metric to either OK, WARNING, or CRITICAL. It then sends these results to Nagios by writing to the Nagios command pipe, located in /usr/local/groundwork/nagios/var/nagios.cmd, or wherever the configuration file specifies. check_ganglia.pl then updates the ganglia database with the latest state and metric values.

The check_ganglia.pl script prints operational statistics in its log file at the end of each polling cycle. The log file can be most easily found through the /usr/local/groundwork/logs/check_ganglia.log symlink.

`check_ganglia.pl` provides for several types of alerting options — value duration, special metrics, and custom metrics.

- To ensure alerts are generated only for consistent problems rather than transient ones, a duration threshold can be specified for each metric. A metric must have exceeded its Warning or Critical threshold continuously (insofar as the periodic `check_ganglia` polling cycles can see) for more than the Duration threshold in order for that state to be set.

For example, if a critical CPU threshold is set for 95% and the duration threshold is 1 hour, the first time the CPU measurement is greater than 95% will NOT set the state to CRITICAL. Each successive poll for the next 1 hour must show the CPU usage greater than 95% before it is set to CRITICAL. A metric is reset to an OK state when a single poll measurement is less than the configured state-recognition threshold.

- Derived metrics are those metrics that do not originate from Ganglia, but are calculated using multiple Ganglia metrics. This feature enables alert thresholds for certain types of conditions to be set more easily.

An example of one such derived metric is `swap_free_percent`. An out-of-the-box Ganglia install gathers metrics for `swap_total` and `swap_free`, but not for `swap_free_percent`. It is not uncommon for clusters and compute grids to contain systems that have varying swap configurations. A derived metric like `swap_free_percent` could prove useful when applying universal thresholds to all machines or to subsets of machines on the grid. Clearly, setting thresholds on a per host basis using the standard Ganglia metrics is tedious in this case. The `check_ganglia` daemon makes this process considerably less painful by actually computing, storing, and alerting on these derived metrics.

As currently written and included in this module, `check_ganglia` supports four derived metrics:

- `mem_cached_percent`
- `mem_free_percent`
- `swap_free_percent`
- `time_since_last_update`

This set can be expanded further by the administrator, though all derived metrics must be directly coded into the `check_ganglia.pl` script. If you do decide to create more special metrics, please contribute your modifications back to GroundWork for folding into future releases.

- Boottime metric. When `check_ganglia` notices that a monitored machine's Ganglia `boottime` metric has changed since the last time the machine's state was checked, a temporary WARNING service state will be generated starting with that polling cycle of that host. The duration of this pulsed state is configured at a global level to reflect site preferences. This state will appear in the Console messages so the operators are able to sense when machines get rebooted even if they are otherwise in an OK state when each state-data polling cycle occurs. The pulse duration allows such conditions to be noticed even when operators are distracted or out of the room for some period.
- Custom metrics. Some customers have specialized needs beyond those which can be handled by the metrics listed above. Certain internal interfaces have been designed to enable call-outs to a external Perl module which can contain arbitrary extensions. Typically, an external module like this is used to adapt to the peculiar environment at the customer site in a manner which is not appropriate for a general product to support. The APIs for these module calls are not currently documented.

Processing of derived, boottime, and custom metrics is controlled via options in the `check_ganglia.conf` configuration file rather than through the threshold-configuration GUI. See Section [4.1.1, Check Ganglia Configuration](#), on page 18 for details.

There are also several options for defining how Nagios integrates with `check_ganglia`. The Nagios system may be set up to have a single service that represents all Ganglia-related metrics for that host, or a separate service for each metric.¹ These options are described below.

The Nagios service detail screen for a single service, named, for example, “ganglia”, would look like this:

The screenshot shows the Nagios web interface. At the top, there's a header with the Nagios logo and a dropdown menu for 'Nagios Destination' set to 'Service Summary'. Below this, on the left, is a box for 'Current Network Status' showing the last update time, update frequency, and login information. To the right of this are two summary tables: 'Host Status Totals' and 'Service Status Totals'. Both tables show counts for Up, Down, Unreachable, Pending, and All Problems. Below these is a table titled 'Service Status Details For Host Group 'New_Ganglia_Hosts'' which lists three hosts with their respective 'ganglia' service status (all OK), last check times, durations, and attempt counts. The status information for each host includes alarm counts and specific metric values like disk_free and swap_free_percent.

Up	Down	Unreachable	Pending
3	0	0	0

Ok	Warning	Unknown	Critical	Pending
3	0	0	0	0

Host	Service	Status	Last Check	Duration	Attempt	Status Information
172.28.112.237	ganglia	OK	10-04-2007 15:29:44	0d 0h 11m 0s	1/3	Alarm Counts:OK (2) OK: disk_free value 3.399 GB. OK: swap_free_percent value 99.99 %.
172.28.112.238	ganglia	OK	10-04-2007 15:29:44	0d 0h 11m 0s	1/3	Alarm Counts:OK (2) OK: disk_free value 4.039 GB. OK: swap_free_percent value 99.44 %.
172.28.112.71	ganglia	OK	10-04-2007 15:29:44	0d 0h 11m 0s	1/3	Alarm Counts:OK (2) OK: disk_free value 0.240 GB. OK: swap_free_percent value 100.00 %.

3 Matching Service Entries Displayed

In this case, if any metric comprising the “ganglia” service for a host goes into the WARNING or CRITICAL state, the service will go into that state. If there are multiple metrics in alert, the state of the service is set to the highest severity. The service text will show the metrics that are in the WARNING or CRITICAL state with the last measurements. The `consolidate_metrics_service_output_detail` option in the `check_ganglia.conf` configuration file controls the level of detail that is displayed in the service output text.

In the above example, a low level of detail is shown — if OK, no metric measurements are shown and if non-OK, only the non-OK metrics and measurements are shown. If the high detail setting is chosen, the state and last value for every metric is shown. A standard, non-GroundWork Nagios configuration will only show 64 characters on the service output text. On a GroundWork Monitor implementation of Nagios, this field has been expanded to 2048 characters to accommodate this option.

The second option is to define a separate service for each metric. In this case, each Ganglia metric is defined as a service under the host, for example, “ganglia_cpu_wio”, “ganglia_cpu_sys”, “ganglia_load_1”, etc. The `check_ganglia.pl` script will send separate passive service results to Nagios for each metric in this case.

When choosing whether to consolidate, or to “roll” or “unroll” the Ganglia service checks in Nagios, note that there is a significant performance impact with unrolling the ganglia checks into multiple Nagios service checks. The next section details this further. Rolling all Ganglia checks into a single Nagios service check allows for simpler configuration and navigation, especially for large data centers. In contrast, using multiple service checks provides for greater granularity during alerting and reporting.

¹ The separate-service model is not supported in the current release of the Ganglia Integration Module (GWMON-5461).

3.2 Performance Considerations

A number of factors influence the performance of the system. The primary driver is the number of Ganglia hosts that need to be monitored by the Nagios system. A corollary to this is the total number of services that the Nagios system needs to support. In testing various configurations, GroundWork has noticed the following potential bottlenecks in Nagios.

1. A large number of services will cause Nagios to take a long time to verify or commit. GroundWork has observed this when the number of services is greater than 20,000.²
2. The Nagios command pipe, `nagios.cmd`, can only read and buffer a limited number of passive service check results at one time. If the internal buffer becomes full and Nagios stops reading the pipe, `check_ganglia` will delay while writing to this pipe. This can be partially remedied by setting a non-default value for the “External command buffer slots” option in Page 2 of the “Configuration → Control → Nagios main configuration” settings. The default value built into Nagios is 4096; a value of 16000 is more suitable for a very large site.
3. Historically, there are other issues with the Nagios handling of a large volume of passive service checks that are outside the scope of this document; customers with a support contract can contact GroundWork for details and a workaround.
4. Nagios can only process a limited number of state changes at any one time. State transitions from OK to CRITICAL appear to be especially problematic. Nagios 3.x will not process any other host or service checks when it is verifying a host alert.³ Depending on the host check command, the number of retries, and the retry interval, this can significantly delay Nagios updates when the number of down hosts is large.

Care must be taken so that passive check result messages do not overload the Nagios command pipe, causing a condition where the number of queued messages keeps increasing. In this case, Nagios may fall behind and never catch up. `check_ganglia` has several features that attempt to avoid this condition. The intent of these features is to minimize the number of service check results that are sent from `check_ganglia` to the Nagios command pipe for each poll, and to optimize the writing of results that do get sent to the command pipe.

1. Passive service checks can be sent on every poll or only when a state has changed. This behavior is controlled by a pair of options in the config file:

```
send_updates_even_when_state_is_persistent
suppress_most_updates_for_persistent_non_okay_states
```

If the first of these options is disabled, either the state is OK or the second option is enabled, and the state has not changed, a passive service check will not be sent. The `maximum_service_non_update_time` parameter can be set so a service can be guaranteed an update within a defined time interval, even when the first and second options are set as described. This allows a periodic passive check to be submitted into Nagios even when the underlying state has not changed. Setting this latter option to less than the Nagios freshness check thresholds will ensure that results are submitted in time to avoid a false positive alarm, and still limit the latency to detect an error condition that prevents the host or service from sending data to Nagios.

2. As stated in the previous section, you can consolidate the metrics into a single service or have a separate service for each metric. Using multiple metrics increases the overall services count and has a tendency to add additional delay into the Nagios verify and startup operations. In addition, multiple metrics also cause more passive results to be written to the Nagios command pipe and thus cause more service state changes to be processed.
3. If the `send_after_each_service` option is set to “yes”, the daemon will write the passive service check results after each service state is processed. If it is set to “no”, it will write all service results at one time. We have found that the write time to the Nagios command pipe is minimized if this is set to “no”.
4. A throttle parameter called `throttle_state_change_threshold` can be set to limit the number of state changes that are sent to Nagios at any one time. If this threshold is reached, `check_ganglia` will break the current batch of state change messages into smaller batches, insert each batch into the Nagios command pipe, wait the number of seconds specified in the `throttle_state_change_threshold_wait` parameter, and then transmit the next batch. This continues until all messages have been sent.

² A variety of performance improvements in the GroundWork and Nagios processing of Commit operations have been made since this original observation. Testing with a current release of the product is in order.

³ That was true for Nagios 2. We need to verify the claim for Nagios 3.

5. The `send_to_foundation` option can be set to send the service check results directly to the Foundation database, avoiding Nagios altogether. Foundation can process state changes more quickly than Nagios, so this can be an option if the operator is using only the GroundWork-specific user interface components (Status Viewer and Event Console). Of course, this will render the Nagios web pages and notification engine unusable for Ganglia service checks, as they will be out of sync with the service checks data stream. Special setup for Nagios would be needed in this case so that Nagios would not feel starved for input on these services.

All of these options and several other operating parameters are documented in the `check_ganglia.conf` configuration file installed by the RPM. The initial settings in this file represent a good starting point and should be checked and adjusted as needed. Before you change values in this file, you may wish to first make a backup copy, to make it easy to refer to the original settings.

3.3 ganglia Database

The ganglia database contains the following tables:

- `cluster` – clusters monitored.
- `clusterhost` – relates clusters to hosts. Populated by configuration, and used for host thresholds.
- `host` – hosts monitored.
- `hostinstance` – relates hosts to clusters. Populated by `check_ganglia`. Has all the hosts Ganglia knows about.
- `location` – locations reference. Used only in limited ways — reserved for future use.
- `metric` – holds abstract metric definitions and default thresholds, to be copied as initial values when these metrics are applied during configuration to specific clusters or hosts.
- `metricinstance` – last metric state and value reported by `check_ganglia`.
- `metricvalue` – stores the actual metric thresholds to be applied, whether they are at the global default level, the cluster level, or the host level.

The `metricvalue` table should have been named `metricthreshold`, to better reflect its actual content. This situation will be corrected in a future update to this package.

Each table's field structure is described below, along with basic data about its indexes.

3.3.1 cluster Table

Field	Type	Null	Key	Default	Extra
ClusterID	int(11) unsigned	NO	PRI	NULL	auto_increment
Name	text	NO			
Description	text	YES		NULL	
Regex	tinyint(1)	YES		NULL	

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
cluster	0	PRIMARY	1	ClusterID	A

3.3.2 clusterhost Table

Field	Type	Null	Key	Default	Extra
ClusterHostID	int(11) unsigned	NO	PRI	NULL	auto_increment
ClusterID	int(11) unsigned	NO	MUL		
HostID	int(11) unsigned	NO	MUL		

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
clusterhost	0	PRIMARY	1	ClusterHostID	A
clusterhost	1	ClusterHost_ClusterFK	1	ClusterID	A
clusterhost	1	ClusterHost_HostFK	1	HostID	A

3.3.3 host Table

Field	Type	Null	Key	Default	Extra
HostID	int(11) unsigned	NO	PRI	NULL	auto_increment
Name	text	NO			
IPAddress	varchar(45)	YES		NULL	
Description	text	YES		NULL	
Regex	tinyint(1)	YES		NULL	

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
host	0	PRIMARY	1	HostID	A

3.3.4 hostinstance Table

Field	Type	Null	Key	Default	Extra
HostInstanceID	int(11) unsigned	NO	PRI	NULL	auto_increment
ClusterID	int(11) unsigned	NO	MUL		
HostID	int(11) unsigned	NO	MUL		
LocationID	int(11) unsigned	NO	MUL		

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
hostinstance	0	PRIMARY	1	HostInstanceID	A
hostinstance	1	HostInstance_ClusterFK	1	ClusterID	A
hostinstance	1	HostInstance_HostFK	1	HostID	A
hostinstance	1	HostInstance_LocationFK	1	LocationID	A

3.3.5 location Table

Field	Type	Null	Key	Default	Extra
LocationID	int(11) unsigned	NO	PRI	NULL	auto_increment
Name	text	NO			
Description	text	YES		NULL	
Regex	tinyint(1)	YES		NULL	

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
location	0	PRIMARY	1	LocationID	A

3.3.6 metric Table

Field	Type	Null	Key	Default	Extra
MetricID	int(11) unsigned	NO	PRI	NULL	auto_increment
Name	text	NO			
Description	text	YES		NULL	
Units	varchar(45)	YES		NULL	
Critical	decimal(64,10)	YES		NULL	
Warning	decimal(64,10)	YES		NULL	
Duration	decimal(64,10)	YES		NULL	

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
metric	0	PRIMARY	1	MetricID	A

3.3.7 metricinstance Table

Field	Type	Null	Key	Default	Extra
MetricInstanceID	int(11) unsigned	NO	PRI	NULL	auto_increment
HostInstanceID	int(11) unsigned	NO	MUL		
MetricID	int(11) unsigned	NO	MUL		
Description	text	YES		NULL	
LastState	text	YES		NULL	
LastUpdateTime	int(11) unsigned	NO			
LastStateChangeTime	int(11) unsigned	NO			
LastValue	text	YES		NULL	

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
metricinstance	0	PRIMARY	1	MetricInstanceID	A
metricinstance	1	MetricInstance_HostInstanceFK	1	HostInstanceID	A
metricinstance	1	MetricInstance_MetricFK	1	MetricID	A

3.3.8 metricvalue Table

Field	Type	Null	Key	Default	Extra
MetricValueID	int(11) unsigned	NO	PRI	NULL	auto_increment
ClusterID	int(11) unsigned	NO	MUL		
HostID	int(11) unsigned	NO	MUL		
LocationID	int(11) unsigned	NO	MUL		
MetricID	int(11) unsigned	NO	MUL		
Description	text	YES		NULL	
Critical	decimal(64,10)	YES		NULL	
Warning	decimal(64,10)	YES		NULL	
Duration	decimal(64,10)	YES		NULL	

Table	Non_unique	Key_name	Seq_in_index	Column_name	Collation
metricvalue	0	PRIMARY	1	MetricValueID	A
metricvalue	1	MetricValue_ClusterFK	1	ClusterID	A
metricvalue	1	MetricValue_HostFK	1	HostID	A
metricvalue	1	MetricValue_LocationFK	1	LocationID	A
metricvalue	1	MetricValue_MetricFK	1	MetricID	A

3.4 Ganglia Web Interface

The Ganglia web interface consists of two parts.

3.4.1 Threshold Configuration

Configuration of thresholds within the ganglia database is controlled by the `GangliaConfigAdmin.cgi` CGI Perl script. Settings for this script are defined in the `GangliaConfigAdmin.conf` file (see Section 4.1.2, [Ganglia Threshold Administration Configuration](#), on page 21). The following functions are available in this interface.

- Define the Ganglia metrics to be monitored, by adding the metric names to the database. Each configured name must exactly match the corresponding Ganglia metric name.
- Define the clusters to be monitored, by adding the cluster names to the database. This setup should match the set of `ganglia_cluster` definitions you specify separately in the `check_ganglia.conf` file.
- Define hosts to be monitored. Hosts are automatically added to the ganglia database by `check_ganglia`. This allows you to modify a host's settings by selecting from a list of existing hosts. `check_ganglia` will also put the host's configuration information in the host description field.
- Define the Warning, Critical, and Duration thresholds for each metric.
 - You *must* define metric thresholds for the "Default" cluster. These are global, default settings which will apply if there are no other settings defined at the cluster or host level.
 - You *may* define metric thresholds for a specific cluster. These settings will override the default cluster settings. These settings are overridden by host metric thresholds, if they exist.
 - You *may* define metric thresholds for a specific host. These settings will override the default or specific cluster settings.
 - Be sure to specify threshold values that make sense for the metric. In some cases, you may want the metric value to normally be above a certain level, and to alert you when it falls below the thresholds you specify. In this case, simply set the Warning threshold higher than the Critical threshold, and this setup will properly analyze the state.
- You may also delete clusters, hosts, or metrics from the ganglia database.⁴ Note that this will not affect Monarch or Nagios, until and unless `autoimport.pl` is run.

3.4.2 Access to Ganglia Web Servers


The Ganglia Integration Module provides a simple way to access the web interface provided by Ganglia itself, without exiting the GroundWork Monitor environment. The Ganglia Views tab presents a list of Ganglia web servers, whose hostnames and access URLs are configured in the `GangliaWebServers.conf` file (see Section 4.1.3, [Ganglia Web Server Viewing Configuration](#), on page 22). The `GangliaWebServers.cgi` script uses this configuration data to present a screen with links to the Ganglia servers; web pages from those servers are presented in a frame beneath these links.

⁴ Inasmuch as hosts known to Ganglia will be automatically added back to the ganglia database when `check_ganglia` runs, it only makes sense to delete hosts after you have either removed them from service or when you stop monitoring the cluster in which they reside. Note that other Ganglia nodes in the cluster will hang on to knowledge about a host for some time after it has gone missing (see, for example, the `host_dmax` and `cleanup_threshold` parameters in `gmond.conf` files).

3.5 Auto-Import

The majority of Ganglia implementations are large. One of the big advantages of Ganglia is its ability to monitor a large infrastructure. Integrating it with Nagios has therefore traditionally been difficult, because of the extremely tedious process of creating all those host and service definitions. One of the great things about GroundWork Monitor, though, is that we can import host definitions and automatically assign service profiles. The auto-import script does that, both for Ganglia and for Cacti, though of course here we are dealing only with Ganglia. You can run the auto-import script as a regularly scheduled (cron) job on the GroundWork server, or as needed, manually.

The auto-import process is shown in the following diagram.



The auto-import script optionally reads the `ganglia` database to find the current hosts that are in the Ganglia XML stream, and optionally reads the `cacti` database to find the current hosts known to Cacti. It also queries the `monarch` database to determine the hosts currently defined in the Nagios system. For hosts in Ganglia but not in Nagios, the script will add the new host to Monarch using the hostname and IP address determined from the Ganglia XML, and matching that stored in the `ganglia` database. A default host profile must be specified in the `autoimport.conf` configuration file. This host profile, which defines the services to be applied to a host, is then applied to each imported host. This host profile must be pre-defined in Monarch. You can easily create this profile via the Monarch GUI. Note that the default host profile must have a one-to-one correspondence with the type of service checks set in the `check_ganglia` configuration — a single service check for all Ganglia metrics, or a separate service check definition for each metric. The auto-import script will also optionally assign the host to a default “New_Ganglia_Hosts” hostgroup.⁵ This host group must also be pre-defined.

If a host known to Ganglia is to be deleted from Nagios with Monarch, it must also be deleted from the `ganglia` database using the Ganglia Threshold Configuration web interface. If not, the host will be added back to Monarch the next time auto-import executes.

If a host is in Monarch, but is no longer in the `ganglia` database, the host is optionally assigned by auto-import to a “deleted hosts” host group.⁶ Collecting all such hosts together in one place this way allows you to manually delete hosts more easily by reviewing the hosts in this host group.

⁵ The name of this hostgroup is configurable in the `autoimport.conf` file.

⁶ The standard name of this hostgroup is `_DELETED_HOSTS`. It is likewise configurable, and whatever the choice of name, this hostgroup must also be pre-defined in Monarch.

Certain special features are configurable in the `autoimport.conf` file (see Section [4.3, Auto-Import Configuration](#), on page [31](#)). These include:

- Assignment of hosts to custom non-default hostgroups, with the assigned hostgroup for each host derived from the host name (and possibly external data, not part of auto-import itself).
- Application of non-default host profiles named after the Ganglia clusters in which the hosts reside, instead of using a single default host profile for all hosts. (This can simplify administration, for instance, if cluster boundaries correspond to functional or machine-type groupings.)
- Selection of whether Ganglia hosts or Cacti hosts (or both) are to be auto-imported. A site would choose to ignore importing from Cacti, for instance, if no Cacti monitoring were configured.

4 Administration

The administration tasks for the Ganglia Integration Module are described in this section.

4.1 Ganglia-Related Configuration

4.1.1 Check Ganglia Configuration

The following parameters control the options in the `check_ganglia.pl` script (see Section 3.1, [Check Ganglia and Nagios](#), on page 8). These are found in the `check_ganglia.conf` file, and represent a common starting point. To configure the `check_ganglia.pl` script, simply edit this file in `/usr/local/groundwork/config/`, and restart `gwservices`.

```
# Configuration file for the check_ganglia.pl script.

#####
#
#   General Program Execution Options
#
#####

# Process Ganglia XML streams? If not, just sleep forever.
# This option is turned off (the value "no", but without quotes) in the default
# configuration file simply so the script can be safely installed before it is
# locally configured. To get the software to run, it must be turned on here
# (the value "yes", but without quotes) once the rest of the setup is correct
# for your site.
enable_processing = no

# Auto-flush the logging output.
# no = normal processing, for efficiency
# yes = autoflush the log output on every single write, for debugging mysterious failures
autoflush_log_output = no

# Global Debug Level Flag; No debug = 0, Statistics = 5, Normal debug = 6,
#                               Detail debug = 7 (gmond XML and metric attribute parsing)
# More precisely, specify one of the following numbers:
# NONE    = 0; turn off all debug info
# FATAL    = 1; the application is about to die
# ERROR    = 2; the application has found a serious problem, but will attempt to recover
# WARNING  = 3; the application has found an anomaly, but will try to handle it
# NOTICE  = 4; the application wants to inform you of a significant event
# STATS    = 5; the application wants to log statistical data for later analysis
# INFO     = 6; the application wants to log a potentially interesting event
# DEBUG    = 7; the application wants to log detailed debugging data
debug_level = 5

# Send to Nagios?
# [yes/no]
send_to_nagios = yes

# Send updates to the database and Nagios even when the state does not change?
# (If not, update in any case on the next iteration after maximum_service_non_update_time.)
# [yes/no]
send_updates_even_when_state_is_persistent = no

# Avoid sending updates to the database and Nagios when the state is not changing?
# (Even if so, send them in any case on the next iteration after maximum_service_non_update_time.)
# [yes/no]
suppress_most_updates_for_persistent_non_okay_states = yes

# Absolute pathname of the Nagios command pipe.
nagios_cmd_pipe = "/usr/local/groundwork/nagios/var/spool/nagios.cmd"

# Consolidate metric results?
# no = send individual metric results
# yes = send all metric results as a single service
consolidate_metrics = yes
```

```

# Service name used for consolidated metrics.
consolidate_metrics_service_name = "ganglia"

# Detail for metric service output.
# [yes/no]; yes = show more detail, no = low detail
consolidate_metrics_service_output_detail = yes

# How to group writes of service results to Nagios.
# no = send all results in a single write
# yes = send to Nagios after each service result
send_after_each_service = no

# How to select the part of a hostname to report out, if the host is not an IP address.
# This pattern must include exactly one part enclosed in parentheses.
# If you don't want any hostname stripping, set this pattern to "".
# For example, to strip the full domain, and only use an unqualified name, use:
# short_hostname_pattern = "(\\S+?)\\."
short_hostname_pattern = ""

# What external package to call to process custom metrics.
# Set to an empty string if you have no such external package.
# If you don't know what these are, set this to "".
custom_metrics_package = ""

# Output a warning if the host has rebooted since the last reporting cycle?
output_reboot_warning = yes

# Set to the number of seconds to continue to report a reboot warning, if $output_reboot_warning is set.
# Anything shorter than the value for cycle_time (below) is effectively equal to zero.
# Simple arithmetic (e.g., 5*60) is allowed in this expression.
output_reboot_warning_duration = 10*60

# Output the mem_free_percent calculated metric?
output_mem_free_percent = no

# Output the mem_cached_percent calculated metric?
output_mem_cached_percent = no

# Output the swap_free_percent calculated metric?
output_swap_free_percent = yes

# Output the time since Ganglia received an update for each host?
output_time_since_last_update = yes

#####
#
#   Performance Throttling Parameters
#
#####

# Time interval for each ganglia poll, in seconds.
# Standard period is 5 minutes.
# Simple arithmetic (e.g., 5*60) is allowed in this expression.
cycle_time = 5*60

# Maximum time interval in seconds between service checks sent to Nagios.
# That is, we will always send a service check result to Nagios on the next
# iteration after this time period has elapsed.
# Simple arithmetic (e.g., 15*60) is allowed in this expression.
maximum_service_non_update_time = 10*60

# Maximum number of state changes that will be sent for each write to Nagios.
# If the number of outstanding state changes is greater than this, check_ganglia
# will wait for throttle_state_change_threshold_wait seconds before sending the
# remaining messages.
throttle_state_change_threshold = 500

```

```

# When throttle_state_change_threshold is exceeded, time in seconds to wait
# before sending the remaining state change message buffer.
# Simple arithmetic (e.g., 2*60) is allowed in this expression.
throttle_state_change_threshold_wait = 6

# The number of slots to pre-allocate for queueing Nagios service messages
# before they are sent to the command pipe. This number should be a little
# more than the total number of hosts in your grid.
initial_bulk_messages_size = 15000

# The number of slots to pre-allocate for queueing metric-instance update rows before
# they are sent to the database. This number should be a little more than the total
# number of metrics you expect to process in each cycle. Bear in mind that you will
# typically have configured at least several metrics to be thresholded per host.
initial_metric_values_size = 100000

# The maximum number of metric value rows you want to have updated in one database
# statement. For efficient updates, it should be at least several thousand.
max_bulk_update_rows = 5000

# The maximum time in seconds to wait for any single write to the output command pipe
# to complete.
max_command_pipe_wait_time = 3*60

# The maximum size in bytes for any single write operation to the output command pipe.
# The value chosen here must be no larger than PIPE_BUF (getconf -a | fgrep PIPE_BUF)
# on your platform, unless you have an absolute guarantee that no other process will
# ever write to the command pipe.
max_command_pipe_write_size = 4096

# Send a check_ganglia service check result at the end of each polling cycle?
# [yes/no]
send_check_ganglia_service_check = yes

#####
#
#   Ganglia Parameters
#
#####

# Where to talk to the Ganglia gmond to fetch node-state data.
# Default gmond port is 8649.
GANGLIA_GMOND_PORT = 8649

# Where to talk to the Ganglia gmetad to fetch node-state data.
# Default gmetad port is 8651.
GANGLIA_GMETAD_PORT = 8651

# List of Ganglia gmond or gmetad hosts to query.
# For convenience, to disable a given entry you need only comment out
# its port definition, not the entire <host ...>/host> block.
# You may also refer to symbols defined above, like $GANGLIA_GMOND_PORT,
# to document your choices.
<ganglia_hosts>

    <host localhost>
        port = $GANGLIA_GMOND_PORT
    </host>
    <host mygmetadhost>
        # port = $GANGLIA_GMETAD_PORT
    </host>
    <host 192.168.1.99>
        # port = 8648
    </host>

</ganglia_hosts>

```

```
# Clusters to monitor.
# Define as many as you need, on separate lines; enclose each value in "double quotes".
# If you define some ganglia_cluster values here, only the clusters listed will be monitored.
# If you don't define any ganglia_cluster values, then all clusters will be monitored.
# Examples:
# ganglia_cluster = "GroundWork Cluster 002"
# ganglia_cluster = "GroundWork Compute Farm"
ganglia_cluster = "GroundWork Cluster 001"

# Ganglia thresholds database connection parameters.
dBHost = "localhost"
dbName = "ganglia"
dBUser = "root"
DBPass = "mysql"

#####
#
#   Foundation Options (used if send_to_foundation=yes)
#
#####

# Send host/service status updates to Foundation?
# [yes/no]
send_to_foundation = no

# This monitoring server name; used as update content (message source).
this_server = "localhost"

# Where to connect to Foundation to send the updates.
# Usual foundation_port is 4913.
foundation_host = "localhost"
foundation_port = 4913
```

4.1.2 Ganglia Threshold Administration Configuration

The following parameters control the options in the GangliaConfigAdmin.cgi script (see Section 3.4.1, [Threshold Configuration](#), on page 15). These are found in the GangliaConfigAdmin.conf file. You will need to adjust the database-access parameters in this file to match your local site. To configure this user interface, simply edit this file in /usr/local/groundwork/config/.

```
# Configuration file for the GangliaConfigAdmin.cgi script.

#####
#
#   General Program Execution Options
#
#####

# Global Debug Level Flag.
# 0 = no debug output
# 1 = Normal debug output
debug_level = 0

# The max number of hosts to process in one DELETE statement. (This just puts a limit on
# a single statement; repeated statements will still be used to process longer lists.)
max_delete_hosts = 1000

# Ganglia thresholds database connection parameters.
DatabaseHost = "localhost"
DatabaseName = "ganglia"
DatabaseUser = "root"
DatabasePass = "mysql"
```

4.1.3 Ganglia Web Server Viewing Configuration

The following parameters control the options in the `GangliaWebServers.cgi` script (see Section 3.4.2, [Access to Ganglia Web Servers](#), on page 15). These are found in the `GangliaWebServers.conf` file. You will need to adjust the set of Ganglia web server hosts and their respective URLs to specify the ones you want to make available through the GroundWork Monitor UI. To configure this user interface, simply edit this file in `/usr/local/groundwork/config/`.

Most likely, you will want to choose one entry as the default Ganglia Web Server, so it shows up automatically when this screen is first displayed. Use the default specification for that, as described in the configuration file comments.

```
# Configuration file for the GangliaWebServers.cgi script.

#####
#
#   General Program Execution Options
#
#####

# Global Debug Level Flag.
# 0 = no debug output
# 1 = Normal debug output
debug_level = 0

# List of Ganglia web servers to allow access to.
#
# For convenience, to disable a given entry you need only comment out
# its url definition, not the entire <host ...></host> block.
#
# If exactly one entry with an active url definition has "default = true" as
# part of its entry, then that entry's Ganglia web server page will appear
# automatically when the screen is first opened. Otherwise, the screen's
# enclosed frame will initially be blank, and the user will need to manually
# select a link for an initial Ganglia web server page to appear.
#
<ganglia_web_servers>

  <host work>
    url = "http://work/ganglia/"
  </host>
  <host geco-15-4>
    url = "http://geco-15-4/ganglia/"
    default = true
  </host>
  <host mygmetadhost>
    # url = "http://mygmetadhost/ganglia/"
  </host>
  <host 192.168.1.99>
    # url = "http://192.168.1.99/ganglia/"
    default = false
  </host>

</ganglia_web_servers>
```


4.1.4 Ganglia Portal Access Permissions

The GroundWork 6.4.0 environment uses the JBoss authentication/authorization facilities for controlling access to the elements within the top-level Ganglia tab within GroundWork Monitor, just as it does for other facilities within the base product. By default, a fresh installation allows access only to users with the GWAdmin role. However, it may be helpful to allow operators (who are not GroundWork Monitor administrators) access to the Ganglia → Ganglia Views page, for quick access to the data the Ganglia web servers can present, while still preventing them from accessing the Ganglia → Ganglia Thresholds page.

The Ganglia Integration Module makes the following objects accessible to an administrator under the Administration tab, for modifying access permissions as needed in the local environment.

- Portal Management → Portal Objects → groundwork-monitor → ganglia-integration
- Portal Management → Portal Objects → groundwork-monitor → ganglia-integration → ganglia-thresholds
- Portal Management → Portal Objects → groundwork-monitor → ganglia-integration → ganglia-views

The following additional objects are provided by the Ganglia Integration Module. Do not change the settings on these objects without first consulting with GroundWork Support.

- Portal Management → Portlet Instances → GWGangliaThresholdsInstance
- Portal Management → Portlet Instances → GWGangliaViewsInstance
- Portal Management → Portlet Definitions → Ganglia Metric Threshold Configuration Portlet
- Portal Management → Portlet Definitions → Ganglia Web Server Views Portlet

The steps needed to modify any of these objects are beyond the scope of this document. For details, see the PORTAL ADMINISTRATION section of the Bookshelf within GroundWork Monitor.

4.2 Ganglia Database Administration

4.2.1 Defining Thresholds

To set up monitoring of Ganglia metrics via thresholds, you will need to:

1. define them, and
2. apply them to the clusters, hosts, and metrics that Ganglia is now collecting for you.

The minimal steps required are:

1. Add a metric name for each metric you want to monitor. If special (derived, boot time, or custom) metrics are defined and enabled, you have to add them as well if you want them to be monitored.
2. Select the Default cluster, which contains the global default threshold settings.
3. Add the metric names you want to monitor to the Default cluster, and define the Warning, Critical, and Duration thresholds for them.

You can also create more specific thresholds which apply to individual clusters and hosts.

1. Add specific clusters.
 - a. Select the cluster, and add the metrics for which you want to override the Default cluster settings for this specific cluster.
 - b. Define the Warning, Critical, and Duration thresholds for each cluster-level override of the global settings.
2. Optionally, add or select specific hosts.
 - a. Select the cluster in which this host is defined (i.e., set the Threshold Cluster for the host) and update the host.
 - b. Add the metrics for which you want to override the Default and specific-cluster settings.
 - c. Define the Warning, Critical, and Duration thresholds for each host-level override of the global and cluster-level settings.

Some things to remember:

- The metric names have to match those from Ganglia exactly. It's a good idea to have the Ganglia web interface up while you work on the thresholds, so you can see the precise format of the metrics and define the thresholds in ways that make sense.⁷ Accessing GroundWork Monitor through several windows in the same browser is supported in current GWME releases. So if you want, you can access the Ganglia Web Server pages through the Ganglia → Ganglia Views screen.
- Warning thresholds and critical thresholds can be high or low, so make sure you see the metric values and alert on them properly. If the warning threshold is less than or equal to the critical threshold, you will get an alarm when the value rises. If the warning threshold is greater than the critical threshold, you will get an alarm when the value falls.
- The units of measure are important for thresholds. For example, the `disk_free` metric is in *gigabytes* by default. If you want an alarm when you have 500 *megabytes* left, set the threshold to 0.5.
- Duration thresholds are specified in seconds.

The remainder of this section walks through setting up thresholds on a few metrics to get you started. There is also help in the form of tool tips and a help page, but it's probably a good idea to read this section first and make sure you understand how to set up thresholds before just diving in. Once you are familiar with the tasks involved, the tool tips will serve to remind you of what to do and how to use the more advanced features.

⁷ Accessing GroundWork Monitor through several windows in the same browser is supported in current GWME releases. So if you want, you can access the Ganglia Web Server pages through the Ganglia → Ganglia Views screen.

The initial screen of the Ganglia threshold-configuration web interface is shown below.

Ganglia Threshold Configuration

Ganglia Configuration Task Selection				
Element	Add	View / Modify / Delete	Bulk Administration	General
Cluster	Add Cluster	-- Select Cluster --	View All Clusters	Help
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB

Your first task is to set up metrics. To define a new metric, select the “Add Metric” button. This will present the following screen.

Ganglia Threshold Configuration

Ganglia Configuration Task Selection				
Element	Add	View / Modify / Delete	Bulk Administration	General
Cluster	Add Cluster	-- Select Cluster --	View All Clusters	Help
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB

Add Metric	
Metric Name	<input type="text" value="cpu_user"/>
Metric Description	<input type="text" value="The percentage of CPU consumed by user jobs."/>
Default Warning Threshold	<input type="text" value="80"/>
Default Critical Threshold	<input type="text" value="99"/>
Default Duration Threshold	<input type="text" value="600"/>
Add Cancel	

Enter the metric name, exactly as defined in Ganglia. The example here is `cpu_user`, a common metric. A free text field is available for the metric description. Also define the default Warning, Critical, and Duration threshold values that will be filled in when this metric is applied to a cluster or host, and click the Add button. After a metric is added, it will appear in the metric drop-down lists.

Once you have at least one metric, it can be applied to a cluster or host. You will probably want to set up several metrics before you proceed to this step.

First, the metric must be applied to the “Default” cluster so that a global default threshold exists for any host. To do this, select the “Default” cluster from the cluster drop down list under View/Modify/Delete. The following page is presented:

Ganglia Threshold Configuration

Ganglia Configuration Task Selection					
Element	Add	View / Modify / Delete	Bulk Administration	General	
Cluster	Add Cluster	Default	View All Clusters	Help	
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration	
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB	

Settings for Cluster ID 1, Name Default	
Name	Default
Description	Default definitions for all clusters.
Update Cluster Delete Cluster Cancel	

Default Metric Thresholds for All Hosts in All Clusters					
Delete	Metric Name	Metric Description	Warning Threshold	Critical Threshold	Duration Threshold
Add New Metric Value to this cluster. -- Select Metric to Add --					
Update Cluster Metric Values Cancel					

By selecting a metric from the “Add New Metric Value to this cluster” drop down, one of the metrics you have defined will be added to the list. If desired, update the metric description, or the Warning, Critical, or Duration thresholds. Continue until all the metrics you wish to monitor are defined and applied to the Default cluster.

Ganglia Threshold Configuration

Ganglia Configuration Task Selection					
Element	Add	View / Modify / Delete	Bulk Administration	General	
Cluster	Add Cluster	Default	View All Clusters	Help	
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration	
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB	

Cluster "Default" has been updated.
Cluster "Default" metric values have been updated.

Settings for Cluster ID 1, Name Default	
Name	Default
Description	Default definitions for all clusters.
Update Cluster Delete Cluster Cancel	

Default Metric Thresholds for All Hosts in All Clusters					
Delete	Metric Name	Metric Description	Warning Threshold	Critical Threshold	Duration Threshold
<input type="checkbox"/>	disk_free	The amount of free disk space in Gigabytes.	0.2	0.1	0
<input type="checkbox"/>	swap_free_percent	swap_free_percent	50	10	900
Add New Metric Value to this cluster. -- Select Metric to Add --					
<div> -- Select Metric to Add -- boottime cpu_user load_one time_since_last_update </div> Metric Values Cancel					

To delete metrics from a cluster, select their Delete checkboxes, then click the “Update Cluster Metric Values” button.

You can also delete definitions for this entire cluster by clicking the “Delete Cluster” button. DO NOT DO THIS for the Default cluster!

After defining the Default cluster, you may click the “Add Cluster” button to define a new cluster, then repeat this process to define metric thresholds for that cluster. Note that if you don’t define a metric for this cluster, it will still be monitored using the thresholds defined and applied to the Default cluster. Those global settings are shown as read-only copies above the per-cluster metric thresholds, as shown in the figure below. This gives you a complete picture of all the thresholds that will be applied to hosts in the cluster, all in one screen. The Source field is a link to the screen where these default settings are established, so these global values can be quickly accessed and adjusted if needed. Only define metric thresholds in a specific cluster if you want to override the settings in the Default cluster. If you do define per-cluster thresholds for some metrics, the display of the corresponding Default cluster thresholds for those metrics will be suppressed, as they will no longer apply to this particular cluster.

Ganglia Threshold Configuration

Ganglia Configuration Task Selection					
Element	Add	View / Modify / Delete	Bulk Administration		General
Cluster	Add Cluster	Compute Farm	View All Clusters		Help
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts		Validate Configuration
Metric	Add Metric	-- Select Metric --	View All Metrics		Back Up DB Restore DB

Settings for Cluster ID 5, Name Compute Farm	
Name	Compute Farm
Description	unspecified
Update Cluster Delete Cluster Cancel	

Default Metric Thresholds for Hosts in the "Compute Farm" Cluster					
Source	Metric Name	Metric Description	Warning Threshold	Critical Threshold	Duration Threshold
Default	cpu_user	The percentage of CPU consumed by user jobs.	80	99	600
Default	disk_free	The amount of free disk space in Gigabytes.	0.2	0.1	0
Delete	swap_free_percent	swap_free_percent	30	5	400
Add New Metric Value to this cluster.			-- Select Metric to Add --		
			Update Cluster Metric Values Cancel		

Generally speaking, you will want to stop at this stage and not go further to define per-host metric thresholds. That's because treating hosts in a grid as individual objects adds complexity to the setup and extra administrative burden to maintain it. Uniformity of monitoring across groups of similar hosts makes the configuration much easier to understand. However, if you do have hosts with particular characteristics that should be monitored in a special way, you can proceed to the next step and set up metric thresholds at the host level.

You may manually define hosts to the ganglia database by selecting “Add Host”, but note that hosts are automatically added to the database by check_ganglia. It is much easier to allow check_ganglia to execute at least once, then select the existing host from the “Modify Host Metric Values” drop-down list and modify its metric settings. You can also use the Find/Delete Multiple Hosts function to generate a list, from which you can click the host name link to reach the particular host's screen. When you select an existing host with one of these methods, the following page appears.

Ganglia Threshold Configuration

Ganglia Configuration Task Selection					
Element	Add	View / Modify / Delete	Bulk Administration	General	
Cluster	Add Cluster	-- Select Cluster --	View All Clusters	Help	
Host	Add Host	compute001	Find/Delete Multiple Hosts	Validate Configuration	
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB	

Settings for Host ID 4, Name compute001

Host Name	compute001
IP Address	172.28.112.71
Description	Cluster Compute Farm, Host compute001, IP 172.28.112.71, machine_type: x86_64, cpu_speed: 2200 MHz, os_name: Linux, mem_total: 1540540 KB, os_release: 2.6.9-42.EL, swap_total: 2031608 KB, cpu_num: 1 CPUs, booted at 00:41:01-2011/01/24
Threshold Cluster	Compute Farm <small>Must be set equal to the Actual Cluster before defining any host-specific thresholds below. See Help.</small>
Actual Cluster	Compute Farm

[Update Host](#) [Delete Host](#) [Cancel](#)

Metric Thresholds That Apply to the "compute001" Host

Source	Metric Name	Metric Description	Warning Threshold	Critical Threshold	Duration Threshold
Default	cpu_user	The percentage of CPU consumed by user jobs.	80	99	600
Default	disk_free	The amount of free disk space in Gigabytes.	0.2	0.1	0
Compute Farm	swap_free_percent	swap_free_percent	30	5	400
Delete	Metric Name	Metric Description	Warning Threshold	Critical Threshold	Duration Threshold
<input type="checkbox"/>	load_one	load_one	2.5	4	600

Add New Metric Value to this host. -- Select Metric to Add --

[Update Host Metric Values](#) [Cancel](#)

To define per-host metric thresholds, first select the Cluster that this host belongs to in the “Threshold Cluster” field, and click the “Update Host” button to add the host to that cluster in the database. This step is necessary since the database is not populated with this information by check_ganglia.⁸

As on the cluster page, you may add metrics and thresholds to this host. These values will override any thresholds for the same metrics specified at the cluster level, as well as the Default-cluster thresholds for those metrics if no cluster-level thresholds are defined. Note that if you don't define a metric for this host, it will still be monitored if it is defined in the Default cluster or this specific cluster. Only define metrics for a host if you want to override the setting in the specific cluster or the Default cluster. The screen for this host shows all the thresholds that apply to this host if the corresponding metrics are sensed by Ganglia, with the source of each threshold clearly identified.

Once you have your thresholds defined, you will begin to receive passive service check results for the services on these hosts in Nagios. You next need to define these hosts and services in Nagios so that you can set up the displays and notifications. The easiest way to do this is with the Auto-Import function, described in a later section.

⁸ Well, it kind of is, but in a different place. That's where the Actual Cluster displayed in the screen comes from. This distinction and the extra manual step involved will be reviewed in a future release.

4.2.2 Validating the Configuration

Certain combinations of settings make little sense, but can be hard to spot when the user interface is presenting only a small portion of the setup in any single screen. To help with this, the threshold configuration UI provides an automated mechanism for digging out certain types of misconfiguration and making them very evident. This facility can be accessed via the “Validate Configuration” button in the top section of the screen.

In the present release, validation runs just one type of sanity check, namely, looking for hosts that belong to more than one cluster, according to the ganglia database. This could cause confusion as to what cluster-level metric thresholds should be applied, so it is a situation to be avoided. If any such hosts are found, they are listed on-screen:

Ganglia Threshold Configuration

Ganglia Configuration Task Selection				
Element	Add	View / Modify / Delete	Bulk Administration	General
Cluster	Add Cluster	-- Select Cluster --	View All Clusters	Help
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB

Hosts that belong to more than one cluster	
Host	Clusters Containing This Host
fileserver001	Research Servers , Production Servers
fileserver002	Research Servers , Production Servers
fileserver003	Research Servers , Production Servers
fileserver004	Research Servers , Production Servers
funknode501	Research Servers , Production Servers
funknode502	Research Servers , Production Servers
funknode503	Research Servers , Production Servers
funknode504	Research Servers , Production Servers
funknode506	Research Servers , Production Servers
testnode501	Research Servers , Production Servers

The host and cluster names are links to the respective pages for those hosts and clusters within the threshold configuration UI, so you can jump immediately to those areas to investigate and make adjustments.

4.2.3 Finding and Deleting Hosts

The threshold configuration tool is designed to make bulk administration of metric thresholds easy. But another aspect of bulk administration comes into play at other times — namely, when you need to find certain hosts, or delete groups of hosts. This is important, for instance, when you take a complete cluster permanently out of service.

Identifying individual hosts or groups of similar hosts can be done via the “Find/Delete Multiple Hosts” capability, accessed via a button in the top section of the screen. It brings up a search template:

Ganglia Threshold Configuration

Ganglia Configuration Task Selection				
Element	Add	View / Modify / Delete	Bulk Administration	General
Cluster	Add Cluster	-- Select Cluster --	View All Clusters	Help
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB

Host Selection Filter		
Actual Cluster	Hostname Pattern	IP Address Pattern
<input type="text"/>	<input type="text"/>	<input type="text"/>
Max Number of Hosts to List	Number of Columns	Search Cancel
<input type="text"/>	<input checked="" type="radio"/> 2 <input type="radio"/> 3 <input type="radio"/> 4 <input type="radio"/> 5	

You can specify a number of criteria to search on, either singly or in combination. If you wave the mouse pointer over the respective heading for each search criterion, a pop-up tooltip will appear that describes acceptable values. (The tooltip will remain steady for you to read its content until either some other tooltip appears, or you click somewhere in the screen to dismiss it.)

The search results look like this:

Ganglia Threshold Configuration

Ganglia Configuration Task Selection				
Element	Add	View / Modify / Delete	Bulk Administration	General
Cluster	Add Cluster	-- Select Cluster --	View All Clusters	Help
Host	Add Host	-- Select Host --	Find/Delete Multiple Hosts	Validate Configuration
Metric	Add Metric	-- Select Metric --	View All Metrics	Back Up DB Restore DB

Host Selection Filter		
Actual Cluster	Hostname Pattern	IP Address Pattern
	geco*	
Max Number of Hosts to List	Number of Columns <input checked="" type="radio"/> 2 <input type="radio"/> 3 <input type="radio"/> 4 <input type="radio"/> 5	Search Cancel

Delete	Hostname	IP Address	Threshold Cluster	Delete	Hostname	IP Address	Threshold Cluster
<input type="checkbox"/>	geco-15-1	172.28.113.76		<input type="checkbox"/>	geco-15-3	172.28.113.78	Compute Farm
<input type="checkbox"/>	geco-15-2	172.28.113.77	Compute Farm	<input type="checkbox"/>	geco-15-4	172.28.113.79	

[Select All Listed Hosts](#) [Deselect All Listed Hosts](#) [Delete Selected Hosts](#) [Cancel](#)

4 hosts match your filter criteria.

Here we see four hosts that matched our specified hostname pattern. Each of their names is a link to the respective host page within the threshold configuration tool. We also see that two of these hosts (geco-15-2 and gecko-15-3) have a Threshold Cluster set, which is a strong indication that host-level metric thresholds are set for these hosts. These cluster names are also links to the respective cluster pages.

Once you have identified an interesting group of hosts this way, you can easily select some or all of them and delete them in bulk from the ganglia database. This is a maintenance step you would typically need to take before running auto-import, so the synchronization of the Monarch and Nagios views of the infrastructure with the Ganglia view will properly reflect the permanent removal of these hosts from your data center.

4.3 Auto-Import Configuration

There are several parameters that control the options in the auto-import script (see Section 3.5, [Auto-Import](#), on page 16). These are found in the `autoimport.conf` file, stored in the `/usr/local/groundwork/config` directory. To configure auto-import, simply edit this file, and create associated objects within Monarch (see below). If the import runs under `cron`, you may wish to kick it off once by hand to ensure the results are what you expect, and that you did not make a mistake editing the file that would prevent the import from functioning. If you are running the import manually, then you will do this anyway.

As always, be sure to make a backup of your monarch database before running any kind of bulk update such as this import script. If it fails for any reason, you should take care not to lose any data.

We present below a listing of the initial configuration file. You should review this file and modify it to meet your needs, then set up the required services, profiles, and host groups in the Monarch GUI. In particular:

- Depending on your configuration of `process_ganglia_hosts` and `process_cacti_hosts`, create and customize services named according to your choices for:
 - `ganglia_svc_name`
 - `cacti_svc_name`
- If the `assign_deleted_hosts_to_hostgroup` option is enabled, create a hostgroup named `_DELETED_HOSTS` (or whatever name you have chosen for the `deleted_hostgroup` option).
- If the `assign_new_hosts_to_hostgroup` option is enabled, create hostgroups named according to your choices for:
 - `new_ganglia_hosts_hostgroup`
 - `new_cacti_hosts_hostgroup`

depending on whether you have `process_ganglia_hosts` and/or `process_cacti_hosts` enabled. (In contrast, hostgroups assigned under the `process_wg_hostgroups` option will be created automatically as needed during auto-import processing.)

- If the `assign_host_profiles_by_ganglia_clusters` option is enabled, create and customize host profiles named after the Ganglia clusters in which your hosts reside.
- Depending on your configuration of `process_ganglia_hosts` and `process_cacti_hosts`, create and customize host and service profiles named according to your choices for:
 - `default_host_profile_ganglia`
 - `default_service_profile_ganglia`
 - `default_host_profile_cacti`
 - `default_service_profile_cacti`

If you enabled `assign_host_profiles_by_ganglia_clusters` but failed to create a host profile named after a particular Ganglia cluster in which a host is found, these Ganglia-related profiles will be used as a fallback.

Then simply run the script from the command line:

```
/usr/local/groundwork/nagios/libexec/autoimport.pl
```

Look in the configured logfile (see below) to see whether any errors occurred, and to examine the operational statistics for each run.

If the script ran without errors, and you did not enable the `commit_changes` option, just open the Monarch (Configuration) GUI, review and adjust the imported hosts, and commit the changes. It's probably a good idea not to enable that option the first time you run the import, just so you can be sure of the results before you go live with the new setup.

You may also want to know which hosts are not being monitored by Ganglia, either because they are being monitored some other way, by Nagios, perhaps, or because they have dropped out of the Ganglia data stream. By default, these hosts will be placed in a new host group you created (e.g., `_DELETED_HOSTS`). Do not worry, the `autoimport` script will not actually delete the hosts it moves there. That is up to you to do on review.

Once you are done importing your hosts and committing your changes, you will be monitoring with Ganglia thresholds under Nagios in GroundWork Monitor. Congratulations!

```
# Configuration file for the autoimport.pl script.

#####
#
#   General Program Execution Options
#
#####

# Global Debug Level (controls the output of messages in the logfile)
# NONE    = 0; turn off all debug info
# FATAL   = 1; the application is about to die
# ERROR    = 2; the application has found a serious problem, but will attempt to recover
# WARNING  = 3; the application has found an anomaly, but will try to handle it
# NOTICE  = 4; the application wants to inform you of a significant event
# STATS    = 5; the application wants to log statistical data for later analysis
# INFO     = 6; the application wants to log a potentially interesting event
# DEBUG    = 7; the application wants to log detailed debugging data
debug_level = 5

# Where to put all the log messages from autoimport processing.
logfile = "/usr/local/groundwork/nagios/var/log/autoimport.log"

# Whether or not to commit a new configuration to Nagios.
# Changes will be committed to the Monarch database regardless.
# [yes/no]
commit_changes = yes

# When defining a monarch host, use the host name instead of the IP address?
# [yes/no]
define_monarch_host_using_dns = yes

# Whether to process WesternGeco-style hostgroups.
# [yes/no]
process_wg_hostgroups = yes

# Whether to use hostgroup_program to classify hosts according to their function.
# If "no", use custom_hostgroup_package instead.
# Used only if process_wg_hostgroups = yes.
# [yes/no]
use_hostgroup_program = no

# A program to classify hosts into hostgroups according to their function.
# Used only if process_wg_hostgroups = yes and use_hostgroup_program = yes.
# The value specified can include initial options beyond just the program name;
# the hostname to be classified will be appended to this full command string.
hostgroup_program = "/usr/local/groundwork/jobs/westerngeco/bin/hosttype -c"

# What Perl package to call to classify hosts into hostgroups according to their function.
# Used only if process_wg_hostgroups = yes and use_hostgroup_program = no.
# For efficiency, the use of a package, if available, is preferred over an external program.
# Set this to an empty string if you have no such package.
custom_hostgroup_package = "WesternGecoHostgroupName"

# What options to initialize the custom_hostgroup_package with.
custom_hostgroup_package_options = "-c"

# Where to find the Nagios log file.
nagioslogfile = "/usr/local/groundwork/nagios/var/nagios.log"

# Ganglia service name to search for in Nagios log file. Hosts with this service will be matched.
ganglia_svc_name = "ganglia"

# Cacti service name to search for in Nagios log file. Hosts with this service will be matched.
cacti_svc_name = "cacti"
```

```

# Assign deleted hosts to the deleted_hostgroup specified below?
# [yes/no]
assign_deleted_hosts_to_hostgroup = yes

# The name of the hostgroup to which deleted hosts will be assigned.
# This hostgroup must already exist in the Monarch database.
deleted_hostgroup = "_DELETED_HOSTS"

# Assign new hosts to the single fixed new hostgroup for the type of node discovered,
# as specified below (new_ganglia_hosts_hostgroup or new_cacti_hosts_hostgroup)?
# [yes/no]
assign_new_hosts_to_hostgroup = no

# Names of hostgroups for newly discovered hosts.
# Used only if assign_new_hosts_to_hostgroup = yes.
new_ganglia_hosts_hostgroup = "New_Ganglia_Hosts"
new_cacti_hosts_hostgroup = "New_Cacti_Hosts"

# For newly discovered Ganglia hosts, assign host profiles named by the Ganglia clusters
# in which the hosts reside? "yes" is only possible if get_ganglia_host_from_ganglia_db
# (below) is "yes".
# If "no", just use the single fixed default_host_profile_ganglia specified below.
# If "yes", the default_host_profile_ganglia host profile will still be used if we find
# no host profile named after a given Ganglia cluster.
# [yes/no]
assign_host_profiles_by_ganglia_clusters = yes

# Note: For newly discovered Cacti hosts, assuming you only use Cacti for network devices,
# using a single host profile (default_host_profile_cacti, specified below) makes sense.
# Within Cacti, you don't have something akin to "Host Groups", though you do have a 'tree'
# structure defined in the database for navigating the devices. If we did want to allow
# alternate host profiles for Cacti devices, then the name of the branch of the tree the
# device is attached to would be the logical candidate. We leave that sort of thing for
# possible future development.

# Default Monarch host and service profiles to be applied to newly discovered hosts.
default_host_profile_ganglia = "ganglia_host"
default_service_profile_ganglia = "Ganglia Hosts"
default_service_profile_ganglia_id = ""
default_host_profile_cacti = "cacti_host"
default_service_profile_cacti = "Cacti Hosts"
default_service_profile_cacti_id = ""

# Process ganglia hosts?
# [yes/no]
process_ganglia_hosts = yes

# Read the Nagios log to pick up the list of Ganglia hosts from service check messages?
# [yes/no]
get_ganglia_host_from_nagios_log = no

# Get the list of ganglia hosts from the Ganglia database?
# Only effective if get_ganglia_host_from_nagios_log = no.
# [yes/no]
get_ganglia_host_from_ganglia_db = yes

# How to access the Ganglia database.
ganglia_database = "ganglia"
ganglia_host = "localhost"
ganglia_dbuser = "root"
ganglia_dbpwd = "mysql"

# Process cacti hosts?
# [yes/no]
process_cacti_hosts = no

```

```
# How to access the Cacti database.  
cacti_database = "cacti"  
cacti_host     = "localhost"  
cacti_dbuser   = "cacti"  
cacti_dbpwd    = "cactipasswd"  
  
# How to access the Monarch database.  
monarch_user_acct = "super_user"
```

Appendix A: Revision History

This manual is expected to be a living document. Future versions may include detail and experience which is not available during the initial development.

The following versions of this document have been issued to date.

Version	Date	Description of Changes
2.0	October 3, 2007	First public release.
3.0	---	Interim internal release.
4.0.5	February 6, 2008	Draft-in-progress of changes to reflect repackaging as RPMs.
5.0.0	February 28, 2011	Revised to reflect installation and running in the GroundWork Monitor Enterprise Edition 6.4 environment. Also edited operational instructions for clarity and to describe new functionality.
5.1.0	March 24, 2011	Extended to: <ul style="list-style-type: none">• Document the default view in the Ganglia Web Server Views screen.• Document additional manual steps needed during initial setup.• Highlight special features briefly mentioned in configuration files.• Provide critical cross-references within this document, for fast access to related info.