

# EE379K Enterprise Network Security Lab 1

## Report

Student: Sean Wang, szw87  
Professor: Mohit Tiwari, Antonio Espinoza  
Department of Electrical & Computer Engineering  
The University of Texas at Austin

September 10, 2019

### Part 1:

#### Step 1:

For step 1, the client and server in C were implemented to closely match the Python versions. For simplicity, the client sends the same hard coded message each time, similar to the Python client. The C client and server were tested with the Python client and server to ensure cross-functionality and that the client implementation in both languages worked almost identically. The only difference between the C client and Python client was the output of the Python client showing

```
From Server: b'INPUT LOWERCASE SENTENCE:'
```

and the C client showing

```
From Server: INPUT LOWERCASE SENTENCE:.
```

To build the server, compile it with:

```
gcc -o server server.c
```

Similarly for the client, compile it with:

```
gcc -o client client.c
```

To run them, simply execute either:

```
./server or ./client
```

## Step 2:

For step 2, the DOS attack was implemented using a command line tool called `hping3` using the options

```
hping3 --count 15000 --destport 12000
--syn --flood --rand-source 127.0.0.2
```

These flags specify to stop sending packets to `127.0.0.2:12000` after sending/receiving 15000 SYN packets, using randomized IP addresses to disguise the actual source and prevent the server's SYN-ACK packets from reaching the actual source. Additionally, the `--flood` option just says to send packets as fast as possible.

As a result, the server receives many requests for establishing a connection, but because the SYN-ACK sent from the server never reaches the actual sender of the initial SYN packet, the 3-way handshake is never completed and the server is left waiting on a response from what it sees as many clients. This can be seen in Figure 1, with some packet details cut out to ensure legibility.

No.	Time	Source	Destination	Protocol	Length	Info
5	0.000339	229.220.168.249	127.0.0.2	TCP	56	2945 → 12000 [SYN] Seq=0 Win=512 Len=0
6	0.000364	127.0.0.2	229.220.168.249	TCP	60	12000 → 2945 [SYN, ACK] Seq=0 Ack=1 Win=65495 Len=0 MSS=65495

Figure 1: An incomplete three-way handshake

Since the server is now swamped with connection requests, the real client (at IP `127.0.0.1`) cannot have its connection request processed by the server and times out, as shown in Figure 2, also with some packet details cut out to ensure legibility.

No.	Time	Source	Destination	Protocol	Length	Info
171837	1.475633	127.0.0.1	127.0.0.2	TCP	76	37564 → 12000 [SYN] Seq=0 Win=65495 Len=0 MSS=
334856	2.490957	127.0.0.1	127.0.0.2	TCP	76	[TCP Retransmission] 37564 → 12000 [SYN] Seq=0
531548	4.511392	127.0.0.1	127.0.0.2	TCP	76	[TCP Retransmission] 37564 → 12000 [SYN] Seq=0

Figure 2: Client's sent SYN packet and client timeout

The rest of the `tcpdump` record of the DOS attack is in `output.pcap` and shows the flood of SYN packets sent to the server at IP `127.0.0.2:12000`.

## Part 2: