


Low capacitance Transil™ arrays for ESD protection

Datasheet - production data



Features

- 2 to 4 unidirectional Transil functions
- Breakdown voltage $V_{BR} = 6.1 \text{ V min}$
- Low leakage current $< 100 \text{ nA}$
- Low diode capacitance (7.5 pF at 3 V)
- Very small PCB area $< 2.6 \text{ mm}^2$

Benefits

- High ESD protection level
- High integration

Complies with the following standards

- IEC 61000-4-2 (exceeds level 4)
 - 20 kV (air discharge)
 - 8 kV (contact discharge)
- MIL STD 883E - Method 3015-7: class 3
 - 25 kV HBM (human body model)

Applications

Where transient overvoltage protection in ESD sensitive equipment is required, such as:

- Automotive applications
- Computers
- Printers
- Communication systems
- Cellular phone handsets and accessories
- Wireline and wireless telephone sets
- Set-top boxes

Description

These devices are monolithic suppressors designed to protect components connected to data and transmission lines against ESD. They clamp the voltage just above the logic level supply for positive transients and to a diode drop below ground for negative transients.

Figure 1: ESDALC6V1P5 functional diagram





Figure 2: ESDALC6V1P6 functional diagram




TM: Transil is a trademark of STMicroelectronics

1 Characteristics

Table 1: Absolute maximum ratings ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Symbol	Parameter		Value	Unit
V_{PP}	Peak pulse voltage	IEC 61000-4-2: Contact discharge Air discharge	8 20	kV
		MIL STD 883G - method 3015-7: Class3	25	
P_{PP}	Peak pulse power	8/20 μ s, T_j initial = T_{amb}	30	W
T_{stg}	Storage temperature range		-55 to +150	$^{\circ}\text{C}$
T_j	Junction temperature		150	
T_L	Maximum lead temperature for soldering during 10 s		260	
T_{op}	Operating temperature range		-40 to +150	

Figure 3: Electrical characteristics (definitions)

Table 2: Electrical characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Order code	V_{BR} at I_R			I_{RM} at V_{RM}			R_d	αT	C
	Min.	Max.		Typ.	Max.		Typ.	Typ.	Typ. at 3 V
	V	V	mA	nA	μ A	V	Ω	$10^{-4}/^{\circ}\text{C}$	pF
ESDALC6V1P5 ESDALC6V1P6	6.1	7.2	1	10	0.1	3	1.5	4.5	7.5

1.1 Characteristics (curves)

Figure 4: Peak pulse power dissipation versus initial junction temperature




Figure 5: Peak pulse power versus exponential pulse duration (T_j initial = 25 °C)




Figure 6: Clamping voltage versus peak pulse current (typical values, rectangular waveform)




Figure 7: Forward voltage drop versus peak forward current (typical values)




Figure 8: Junction capacitance versus reverse applied voltage (typical values)




Figure 9: Relative variation of leakage current versus junction temperature (typical values)







Figure 10: ESD response to IEC 61000-4-2 (air discharge 15 kV positive surge)**Figure 11: Analog crosstalk measurement****Figure 12: Digital crosstalk test measurement**

2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

2.1 SOT-665 package information

Figure 13: SOT-665 package outline





Table 3: SOT-665 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.5		0.62	0.020		0.024
bp	0.17		0.27	0.007		0.011
bp1	0.27		0.34	0.011		0.013
c	0.08		0.18	0.003		0.007
D	1.5		1.7	0.060		0.067
E	1.1		1.3	0.043		0.051
e		1			0.039	
e1		0.5			0.020	
He	1.5		1.7	0.059		0.067
Lp	0.1		0.3	0.004		0.012
Lp1	0.1	0.05		0.004	0.002	
Lp2	0.11		0.26	0.004		0.010

Figure 14: SOT-665 footprint (dimensions in mm)



2.2 SOT-666IP package information

Figure 15: SOT-666IP package outline





Table 4: SOT-666IP package mechanical data

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.45		0.62	0.018		0.024
A3	0.08		0.18	0.003		0.007
b	0.17		0.34	0.007		0.0013
D	1.50		1.70	0.059		0.067
E	1.50		1.70	0.059		0.067
E1	1.10		1.30	0.043		0.051
e		0.5			0.020	
L1		0.19			0.007	
L2	0.1		0.3	0.004		0.012
L3		0.6			0.024	

Figure 16: SOT-666IP footprint (dimensions in mm)



3 Ordering information

Figure 17: Ordering information scheme




Table 5: Ordering information

Order code	Marking ⁽¹⁾	Package	Weight	Base qty.	Delivery mode
ESDALC6V1P5	A1	SOT-665	2.9 mg	3000	Tape and reel
ESDALC6V1P6	D	SOT-666IP			

Notes:

⁽¹⁾The marking can be rotated by multiples of 90° to differentiate assembly location

4 Revision history

Table 6: Document revision history

Date	Revision	Changes
16-Aug-2006	1	ESDALC6V1P3, ESDALC6V1P5, and ESDALC6V1P6 merged and reformatted to current standards.
23-Aug-2006	2	Table 1 on page 2: Temperature range upgraded to $T_{j\max} = 150\text{ °C}$
11-Oct-2006	3	Added values for V_{PP} in Table 1.
23-Apr-2008	4	Reformatted to current standards. Added I_{RM} typical value in Table 2. Update minimum dimension for L2 of SOT-663 in Table 3.
15-Jan-2010	5	Updated Figure 17: SOT-665 footprint (dimensions in mm).
03-Dec-2014	6	Updated SOT-666IP dimension definitions and reformatted to current standard.
17-Mar-2017	7	Removed SOT-663 package. Updated Table 1: "Absolute maximum ratings ($T_{amb} = 25\text{ °C}$)". Updated Table 3: "SOT-665 package mechanical data" and Table 3: "SOT-665 package mechanical data".
03-Aug-2017	8	Updated Section 2.1: "SOT-665 package information" .

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

This datasheet has been downloaded from:

datasheet.eeworld.com.cn

Free Download

Daily Updated Database

100% Free Datasheet Search Site

100% Free IC Replacement Search Site

Convenient Electronic Dictionary

Fast Search System

www.EEworld.com.cn