

第三节:springboot源码解析(王炸篇)

今天内容

1:spring注解 热身

2:springboot 自动装配原理

3:springboot启动原理(jar 包启动)

4:springboot启动原理

5:作业:springboot的自定义启动器

一:spring注解之如何导入Bean的几种方式

- 1) @Bean注解, 不做讲解
- 2) 包扫描来加载Bean 比如标识@Controller @Service @Repository @Component 不做讲解
- 3) @Import几种取值来注册bean
 - ①: 实现ImportSelector接口的类
 - ②: 实现ImportBeanDefinitionRegistrar接口来注册bean
- 4) 实现factoryBean的方式来导入组件 (不做讲解)

1.1)通过@Import注解来导入ImportSelector组件

- ①: 写一个配置类在配置类上标注一个@Import的注解,

```
@Configuration
@Import(value = {TulingSelector.class})
public class TulingConfig {
}
```

- ②: 在@Import注解的value值 写自己需要导入的组件

在selectImports方法中 就是你需要导入组件的全类名

```
public class TulingSelector implements ImportSelector {
    @Override
    public String[] selectImports(AnnotationMetadata annotationMetadata) {
        return new String[]{"com.tuling.service.TulingServiceImpl"};
    }
}
```

核心代码:

```
@RestController
```

```

public class TulingController {

    //自动注入 tulingServiceImpl
    @Autowired
    private TulingServiceImpl tulingServiceImpl;

    @RequestMapping("testTuling")
    public String testTuling() {
        tulingServiceImpl.testService();
        return "tulingOk";
    }
}

```


这里是没有标注其他注解提供给spring包扫描的

```


public class TulingServiceImpl {

    public void testService() {
        System.out.println("我是通过importSelector导入进来的service");
    }
}

```



1.2) 通过@Import导入ImportBeanDefinitionRegistrar 从而进来导入组件



核心代码:

```

public class TulingImportBeanDefinitionRegistrar implements ImportBeanDefinitionRegistrar {
    @Override
    public void registerBeanDefinitions(AnnotationMetadata annotationMetadata, BeanDefinitionRegistry beanDefinitionReg
        //定义一个BeanDefinition
    }
}

```

```

RootBeanDefinition rootBeanDefinition = new RootBeanDefinition(TulingDao.class);
//把自定义的bean定义导入到容器中
beanDefinitionRegistry.registerBeanDefinition("tulingDao",rootBeanDefinition);
}
}

```

通过ImportSelector功能导入进来的

```
public class TulingServiceImpl {
```

```
@Autowired
```

```
private TulingDao tulingDao;
```

```
public void testService() {
```

```
    tulingDao.testTulingDao();
```

```
    System.out.println("我是通过importSelector导入进来的service");
```

```
}
```

```
}
```

通过ImportBeanDefinitionRegistrar导入进来的

```
public class TulingDao {
```


```
public void testTulingDao() {
```

```
    System.out.println("我是通过ImportBeanDefinitionRegistrar导入进来tulingDao组件");
```

```
}
```

```
}
```

测试结果:



1.3)spring底层条件装配的原理@Conditional

应用要求:比如我有二个组件,一个是TulingLog 一个是TulingAspect

而TulingLog 是依赖TulingAspect的 只有容器中有TulingAspect组件才会加载TulingLog

tulingLog组件 依赖TulingAspect组件

```
public class TulingLog {
}
```

tulingAspect组件

```
public class TulingAspect {
}
```

③: 自定义条件组件条件

```
public class TulingConditional implements Condition {  
    @Override  
    public boolean matches(ConditionContext conditionContext, AnnotatedTypeMetadata annotatedTypeMetadata) {  
        // 容器中包含tulingAspect组件才返回True  
        if(conditionContext.getBeanFactory().containsBean("tulingAspect")){  
            return true;  
        }else{  
            return false;  
        }  
    }  
}
```

-----该情况下会加载二个组件-----

```
@Bean  
public TulingAspect tulingAspect() {  
    System.out.println("TulingAspect组件自动装配到容器中");  
    return new TulingAspect();  
}
```

```
@Bean  
@Conditional(value = TulingConditional.class)  
public TulingLog tulingLog() {  
    System.out.println("TulingLog组件自动装配到容器中");  
    return new TulingLog();  
}
```

-----二个组件都不会被加载-----

```
/*@Bean*/  
public TulingAspect tulingAspect() {  
    System.out.println("TulingAspect组件自动装配到容器中");  
    return new TulingAspect();  
}
```


```
@Bean  
@Conditional(value = TulingConditional.class)  
public TulingLog tulingLog() {  
    System.out.println("TulingLog组件自动装配到容器中");  
    return new TulingLog();  
}
```

=====到此结束spring自层注解

=====

二:springboot自动装配原理

2.1)@Springboot注解组合图



根据上面的@SpringBootApplication注解 我们来着重分析如下二个类

①: AutoConfigurationImportSelector.class

②: AutoConfigurationPackages.Registrar.class

先分析AutoConfigurationImportSelector为我们干了什么活??

```
public String[] selectImports(AnnotationMetadata annotationMetadata) {
    if (!isEnabled(annotationMetadata)) {
        return NO_IMPORTS;
    }
    AutoConfigurationMetadata autoConfigurationMetadata = AutoConfigurationMetadataLoader
        .loadMetadata(this.beanClassLoader);
    AnnotationAttributes attributes = getAttributes(annotationMetadata);
    // 获取候选的配置类
    List<String> configurations = getCandidateConfigurations(annotationMetadata,
        attributes);
    // 移除重复的
    configurations = removeDuplicates(configurations);
    Set<String> exclusions = getExclusions(annotationMetadata, attributes);
    checkExcludedClasses(configurations, exclusions);
    configurations.removeAll(exclusions);
    configurations = filter(configurations, autoConfigurationMetadata);
    fireAutoConfigurationImportEvents(configurations, exclusions);
    // 返回出去
    return StringUtils.toStringArray(configurations);
}

// 获取候选的配置类
protected List<String> getCandidateConfigurations(AnnotationMetadata metadata,
    AnnotationAttributes attributes) {
    List<String> configurations = SpringFactoriesLoader.loadFactoryNames(
        getSpringFactoriesLoaderFactoryClass(), getBeanClassLoader());
    Assert.notEmpty(configurations,
        "No auto configuration classes found in META-INF/spring.factories. If you "
        + "are using a custom packaging, make sure that file is correct.");
    return configurations;
}

// 加载配置类
public static List<String> loadFactoryNames(Class<?> factoryClass, @Nullable ClassLoader classLoader) {
    String factoryClassName = factoryClass.getName();
    return loadSpringFactories(classLoader).getOrDefault(factoryClassName, Collections.emptyList());
}
```

```

private static Map<String, List<String>> loadSpringFactories(@Nullable ClassLoader classLoader) {
    MultiValueMap<String, String> result = cache.get(classLoader);
    if (result != null) {
        return result;
    }

    try {

        // "META-INF/spring.factories" 去类路径下该文件中加载 EnableAutoConfiguration.class
        Enumeration<URL> urls = (classLoader != null ?
            classLoader.getResources(FACTORIES_RESOURCE_LOCATION) :
            ClassLoader.getSystemResources(FACTORIES_RESOURCE_LOCATION));
        result = new LinkedMultiValueMap<>();
        // 遍历解析出来的集合
        while (urls.hasMoreElements()) {
            URL url = urls.nextElement();
            UrlResource resource = new UrlResource(url);
            // 放在Properties中
            Properties properties = PropertiesLoaderUtils.loadProperties(resource);
            for (Map.Entry<?, ?> entry : properties.entrySet()) {
                String factoryClassName = ((String) entry.getKey()).trim();
                for (String factoryName : StringUtils.commaDelimitedListToStringArray((String) entry.getValue()))
                    result.add(factoryClassName, factoryName.trim());
            }
        }
        cache.put(classLoader, result);
        // 返回
        return result;
    }
    catch (IOException ex) {
        throw new IllegalArgumentException("Unable to load factories from location [" +
            FACTORIES_RESOURCE_LOCATION + "]", ex);
    }
}

```

主要是扫描spring-boot-autoconfigure\2.0.8.RELEASE\spring-boot-autoconfigure-2.0.8.RELEASE.jar!\META-INF\spring.factories 中EnableAutoConfiguration对应的全类名

```

org.springframework.boot.autoconfigure.EnableAutoConfiguration=\
org.springframework.boot.autoconfigure.admin.SpringApplicationAdminJmxAutoConfiguration,\
org.springframework.boot.autoconfigure.aop.AopAutoConfiguration,\
org.springframework.boot.autoconfigure.amqp.RabbitAutoConfiguration,\
org.springframework.boot.autoconfigure.batch.BatchAutoConfiguration,\
org.springframework.boot.autoconfigure.cache.CacheAutoConfiguration,\
org.springframework.boot.autoconfigure.cassandra.CassandraAutoConfiguration,\
org.springframework.boot.autoconfigure.cloud.CloudAutoConfiguration,\
org.springframework.boot.autoconfigure.context.ConfigurationPropertiesAutoConfiguration,\
org.springframework.boot.autoconfigure.context.MessageSourceAutoConfiguration,\
org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration,\
org.springframework.boot.autoconfigure.couchbase.CouchbaseAutoConfiguration,\
org.springframework.boot.autoconfigure.dao.PersistenceExceptionTranslationAutoConfiguration,\
org.springframework.boot.autoconfigure.data.cassandra.CassandraDataAutoConfiguration,\
org.springframework.boot.autoconfigure.data.cassandra.CassandraReactiveDataAutoConfiguration,\
org.springframework.boot.autoconfigure.data.cassandra.CassandraReactiveRepositoriesAutoConfiguration,\

```

org.springframework.boot.autoconfigure.data.cassandra.CassandraRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.couchbase.CouchbaseDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data.couchbase.CouchbaseReactiveDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data.couchbase.CouchbaseReactiveRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.couchbase.CouchbaseRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.elasticsearch.ElasticsearchAutoConfiguration,\norg.springframework.boot.autoconfigure.data.elasticsearch.ElasticsearchDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data.elasticsearch.ElasticsearchRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.jpa.JpaRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data ldap.LdapDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data ldap.LdapRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.mongo.MongoDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data.mongo.MongoReactiveDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data.mongo.MongoReactiveRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.mongo.MongoRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.neo4j.Neo4jDataAutoConfiguration,\norg.springframework.boot.autoconfigure.data.neo4j.Neo4jRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.solr.SolrRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.redis.RedisAutoConfiguration,\norg.springframework.boot.autoconfigure.data.redis.RedisReactiveAutoConfiguration,\norg.springframework.boot.autoconfigure.data.redis.RedisRepositoriesAutoConfiguration,\norg.springframework.boot.autoconfigure.data.rest.RepositoryRestMvcAutoConfiguration,\norg.springframework.boot.autoconfigure.data.web.SpringDataWebAutoConfiguration,\norg.springframework.boot.autoconfigure.elasticsearch.jest.JestAutoConfiguration,\norg.springframework.boot.autoconfigure.flyway.FlywayAutoConfiguration,\norg.springframework.boot.autoconfigure.freemarker.FreeMarkerAutoConfiguration,\norg.springframework.boot.autoconfigure.gson.GsonAutoConfiguration,\norg.springframework.boot.autoconfigure.h2.H2ConsoleAutoConfiguration,\norg.springframework.boot.autoconfigure.hateoas.HypermediaAutoConfiguration,\norg.springframework.boot.autoconfigure.hazelcast.HazelcastAutoConfiguration,\norg.springframework.boot.autoconfigure.hazelcast.HazelcastJpaDependencyAutoConfiguration,\norg.springframework.boot.autoconfigure.http.HttpMessageConvertersAutoConfiguration,\norg.springframework.boot.autoconfigure.http.codec.CodecsAutoConfiguration,\norg.springframework.boot.autoconfigure.influx.InfluxDbAutoConfiguration,\norg.springframework.boot.autoconfigure.info.ProjectInfoAutoConfiguration,\norg.springframework.boot.autoconfigure.integration.IntegrationAutoConfiguration,\norg.springframework.boot.autoconfigure.jackson.JacksonAutoConfiguration,\norg.springframework.boot.autoconfigure.jdbc.DataSourceAutoConfiguration,\norg.springframework.boot.autoconfigure.jdbc.JdbcTemplateAutoConfiguration,\norg.springframework.boot.autoconfigure.jdbc.JndiDataSourceAutoConfiguration,\norg.springframework.boot.autoconfigure.jdbc.XADataSourceAutoConfiguration,\norg.springframework.boot.autoconfigure.jdbc.DataSourceTransactionManagerAutoConfiguration,\norg.springframework.boot.autoconfigure.jms.JmsAutoConfiguration,\norg.springframework.boot.autoconfigure.jmx.JmxAutoConfiguration,\norg.springframework.boot.autoconfigure.jms.JndiConnectionFactoryAutoConfiguration,\norg.springframework.boot.autoconfigure.jms.activemq.ActiveMQAutoConfiguration,\norg.springframework.boot.autoconfigure.jms.artemis.ArtemisAutoConfiguration,\norg.springframework.boot.autoconfigure.groovy.template.GroovyTemplateAutoConfiguration,\norg.springframework.boot.autoconfigure.jersey.JerseyAutoConfiguration,\norg.springframework.boot.autoconfigure.jooq.JooqAutoConfiguration,\norg.springframework.boot.autoconfigure.jsonb.JsonbAutoConfiguration,\norg.springframework.boot.autoconfigure.kafka.KafkaAutoConfiguration,\norg.springframework.boot.autoconfigure.ldap.embedded.EmbeddedLdapAutoConfiguration,\norg.springframework.boot.autoconfigure.ldap.LdapAutoConfiguration,\norg.springframework.boot.autoconfigure.liquibase.LiquibaseAutoConfiguration,\norg.springframework.boot.autoconfigure.mail.MailSenderAutoConfiguration,\norg.springframework.boot.autoconfigure.mail.MailSenderValidatorAutoConfiguration,\norg.springframework.boot.autoconfigure.mongo.embedded.EmbeddedMongoAutoConfiguration,\norg.springframework.boot.autoconfigure.mongo.MongoAutoConfiguration,\norg.springframework.boot.autoconfigure.mongo.MongoReactiveAutoConfiguration,\norg.springframework.boot.autoconfigure.mustache.MustacheAutoConfiguration,\norg.springframework.boot.autoconfigure.orm.jpa.HibernateJpaAutoConfiguration,\n

```

org.springframework.boot.autoconfigure.quartz.QuartzAutoConfiguration,\
org.springframework.boot.autoconfigure.reactor.core.ReactorCoreAutoConfiguration,\
org.springframework.boot.autoconfigure.security.servlet.SecurityAutoConfiguration,\
org.springframework.boot.autoconfigure.security.servlet.SecurityRequestMatcherProviderAutoConfiguration,\
org.springframework.boot.autoconfigure.security.servlet.UserDetailsServiceAutoConfiguration,\
org.springframework.boot.autoconfigure.security.servlet.SecurityFilterAutoConfiguration,\
org.springframework.boot.autoconfigure.security.reactive.ReactiveSecurityAutoConfiguration,\
org.springframework.boot.autoconfigure.security.reactive.ReactiveUserDetailsServiceAutoConfiguration,\
org.springframework.boot.autoconfigure.sendgrid.SendGridAutoConfiguration,\
org.springframework.boot.autoconfigure.session.SessionAutoConfiguration,\
org.springframework.boot.autoconfigure.security.oauth2.client.OAuth2ClientAutoConfiguration,\
org.springframework.boot.autoconfigure.solr.SolrAutoConfiguration,\
org.springframework.boot.autoconfigure.thymeleaf.ThymeleafAutoConfiguration,\
org.springframework.boot.autoconfigure.transaction.TransactionAutoConfiguration,\
org.springframework.boot.autoconfigure.transaction.jta.JtaAutoConfiguration,\
org.springframework.boot.autoconfigure.validation.ValidationAutoConfiguration,\
org.springframework.boot.autoconfigure.web.client.RestTemplateAutoConfiguration,\
org.springframework.boot.autoconfigure.web.embedded.EmbeddedWebServerFactoryCustomizerAutoConfiguration,\
org.springframework.boot.autoconfigure.web.reactive.HttpHandlerAutoConfiguration,\
org.springframework.boot.autoconfigure.web.reactive.ReactiveWebServerFactoryAutoConfiguration,\
org.springframework.boot.autoconfigure.web.reactive.WebFluxAutoConfiguration,\
org.springframework.boot.autoconfigure.web.reactive.error.ErrorWebFluxAutoConfiguration,\
org.springframework.boot.autoconfigure.web.reactive.function.client.WebClientAutoConfiguration,\
org.springframework.boot.autoconfigure.web.servlet.DispatcherServletAutoConfiguration,\
org.springframework.boot.autoconfigure.web.servlet.ServletWebServerFactoryAutoConfiguration,\
org.springframework.boot.autoconfigure.web.servlet.error.ErrorMvcAutoConfiguration,\
org.springframework.boot.autoconfigure.web.servlet.HttpEncodingAutoConfiguration,\
org.springframework.boot.autoconfigure.web.servlet.MultipartAutoConfiguration,\
org.springframework.boot.autoconfigure.web.servlet.WebMvcAutoConfiguration,\
org.springframework.boot.autoconfigure.websocket.reactive.WebSocketReactiveAutoConfiguration,\
org.springframework.boot.autoconfigure.websocket.servlet.WebSocketServletAutoConfiguration,\
org.springframework.boot.autoconfigure.websocket.servlet.WebSocketMessagingAutoConfiguration,\
org.springframework.boot.autoconfigure.webservices.WebServicesAutoConfiguration

```

上面的一些个 XXXAutoConfiguration都是一个自动配置类

我们就拿二个来分析一下 这些自动配置类是如何工作的???

分析源码1: org.springframework.boot.autoconfigure.data.redis.RedisAutoConfiguration

```

@Configuration 标识是一个配置类
@ConditionalOnClass(RedisOperations.class) 判断是否导入了 redis的jar包
@EnableConfigurationProperties(RedisProperties.class) //开启自动配置属性类加载到容器中
@Import({ LettuceConnectionConfiguration.class, JedisConnectionConfiguration.class })
public class RedisAutoConfiguration {

    //自动配置了一个 redisTemplate 操作对象的
    @Bean
    @ConditionalOnMissingBean(name = "redisTemplate")
    public RedisTemplate<Object, Object> redisTemplate(
        RedisConnectionFactory redisConnectionFactory) throws UnknownHostException {
        RedisTemplate<Object, Object> template = new RedisTemplate<>();
        template.setConnectionFactory(redisConnectionFactory);
        return template;
    }

    操作字符串的
    @Bean
    @ConditionalOnMissingBean
    public StringRedisTemplate stringRedisTemplate(
        RedisConnectionFactory redisConnectionFactory) throws UnknownHostException {

```



```

        StringRedisTemplate template = new StringRedisTemplate();
        template.setConnectionFactory(redisConnectionFactory);
        return template;
    }
}

=====配置jedis 连接工厂配置类=====
@Configuration
@ConditionalOnClass({ GenericObjectPool.class, JedisConnection.class, Jedis.class })
class JedisConnectionFactory extends RedisConnectionFactory {

    private final RedisProperties properties;

    private final List<JedisClientConfigurationBuilderCustomizer> builderCustomizers;

    JedisConnectionFactory(RedisProperties properties,
        ObjectProvider<RedisSentinelConfiguration> sentinelConfiguration,
        ObjectProvider<RedisClusterConfiguration> clusterConfiguration,
        ObjectProvider<List<JedisClientConfigurationBuilderCustomizer>> builderCustomizers) {
        super(properties, sentinelConfiguration, clusterConfiguration);
        this.properties = properties;
        this.builderCustomizers = builderCustomizers
            .getIfAvailable(Collections::emptyList);
    }

    @Bean
    @ConditionalOnMissingBean(RedisConnectionFactory.class)
    public JedisConnectionFactory redisConnectionFactory() throws UnknownHostException {
        return createJedisConnectionFactory();
    }
}

```

我们来看下 `org.springframework.boot.autoconfigure.data.redis.RedisProperties`，这个类是用来什么的？就是我们yml中能配置什么类，在这个类中都会有一个属性一一对应

```

public class RedisProperties {

    /**
     * Database index used by the connection factory.
     */
    private int database = 0;

    /**
     * Connection URL. Overrides host, port, and password. User is ignored. Example:
     * redis://user:password@example.com:6379
     */
    private String url;

    /**
     * Redis server host.
     */
    private String host = "localhost";

    /**
     * Login password of the redis server.
     */
    private String password;
}

```

```

/**
 * Redis server port.
 */
private int port = 6379;

/**
 * Whether to enable SSL support.
 */
private boolean ssl;


/**
 * Connection timeout.
 */
private Duration timeout;

private Sentinel sentinel;

private Cluster cluster;

```

我们对应的配置文件(yml)中就会有对应属性来配置



```


spring:
  redis:
    host: 47.104.128.12
    port: 6379
    password: 123456
  jedis:
    pool:
      max-active: 20
      max-idle: 10
      min-idle: 5

```

以上 就是 AutoConfigurationImportSelector为我们容器中注册了那些组件，然后根据maven依赖导入的jar包，根据条件装配来指定哪些组件

起作用 哪些组件不起作用。

三:上面我们分析了springboot 自动装配原理，接下来我们依靠 自动装配原理来分析出spring Boot的jar包的启动流程。




3.1) 我们先来看springboot 怎么来自动装配tomcat 相关的组件

EmbeddedWebServerFactoryCustomizerAutoConfiguration(内嵌web容器工厂自定义定制器装配类)?

疑问1? : 定制器是用来干什么的?

疑问2? : 定制器何时工作?

类的继承关系



我们就以tomcat 作为内嵌容器来分析

```
@Configuration
@ConditionalOnWebApplication
@EnableConfigurationProperties(ServerProperties.class)
public class EmbeddedWebServerFactoryCustomizerAutoConfiguration {

    //配置tomcat的
    @Configuration
    @ConditionalOnClass({ Tomcat.class, UpgradeProtocol.class })
    public static class TomcatWebServerFactoryCustomizerConfiguration {

        @Bean
        public TomcatWebServerFactoryCustomizer tomcatWebServerFactoryCustomizer(
            Environment environment, ServerProperties serverProperties) {
            return new TomcatWebServerFactoryCustomizer(environment, serverProperties);
        }

    }

    //配置jetty
    @Configuration
    @ConditionalOnClass({ Server.class, Loader.class, WebApplicationContext.class })
    public static class JettyWebServerFactoryCustomizerConfiguration {
```

```

        @Bean
        public JettyWebServerFactoryCustomizer jettyWebServerFactoryCustomizer(
            Environment environment, ServerProperties serverProperties) {
            return new JettyWebServerFactoryCustomizer(environment, serverProperties);
        }
    }

    配置undertow的
    @Configuration
    @ConditionalOnClass({ Undertow.class, SslClientAuthMode.class })
    public static class UndertowWebServerFactoryCustomizerConfiguration {

        @Bean
        public UndertowWebServerFactoryCustomizer undertowWebServerFactoryCustomizer(
            Environment environment, ServerProperties serverProperties) {
            return new UndertowWebServerFactoryCustomizer(environment, serverProperties);
        }
    }
}

```

我们看下tomcat 工厂定制器 是用来修改设置容器的内容的(把serverProperties的属性设置到tomcat的创建工厂中)

```

public class TomcatWebServerFactoryCustomizer implements WebServerFactoryCustomizer<ConfigurableTomcatWebServerFactory> {

    .....其他代码省略。 . . . . .

    @Override
    public void customize(ConfigurableTomcatWebServerFactory factory) {
        ServerProperties properties = this.serverProperties;
        ServerProperties.Tomcat tomcatProperties = properties.getTomcat();
        PropertyMapper propertyMapper = PropertyMapper.get();
        propertyMapper.from(tomcatProperties::getBasedir).whenNonNull()
            .to(factory::setBaseDirectory);
        propertyMapper.from(tomcatProperties::getBackgroundProcessorDelay).whenNonNull()
            .as(Duration::getSeconds).as(Long::intValue)
            .to(factory::setBackgroundProcessorDelay);
        customizeRemotelpValve(factory);
        propertyMapper.from(tomcatProperties::getMaxThreads).when(this::isPositive)
            .to((maxThreads) -> customizeMaxThreads(factory,
                tomcatProperties.getMaxThreads()));
        propertyMapper.from(tomcatProperties::getMinSpareThreads).when(this::isPositive)
            .to((minSpareThreads) -> customizeMinThreads(factory, minSpareThreads));
        propertyMapper.from(() -> determineMaxHttpHeaderSize()).when(this::isPositive)
            .to((maxHttpHeaderSize) -> customizeMaxHttpHeaderSize(factory,
                maxHttpHeaderSize));
        propertyMapper.from(tomcatProperties::getMaxHttpPostSize)
            .when((maxHttpPostSize) -> maxHttpPostSize != 0)
            .to((maxHttpPostSize) -> customizeMaxHttpPostSize(factory,
                maxHttpPostSize));
        propertyMapper.from(tomcatProperties::getAccesslog)
            .when(ServerProperties.Tomcat.Accesslog::isEnabled)
            .to((enabled) -> customizeAccessLog(factory));
        propertyMapper.from(tomcatProperties::getUriEncoding).whenNonNull()
            .to(factory::setUriEncoding);
        propertyMapper.from(properties::getConnectionTimeout).whenNonNull()
            .to((connectionTimeout) -> customizeConnectionTimeout(factory,
                connectionTimeout));
        propertyMapper.from(tomcatProperties::getMaxConnections).when(this::isPositive)
    }
}

```

```

        .to((maxConnections) -> customizeMaxConnections(factory, maxConnections));
    propertyMapper.from(tomcatProperties::getAcceptCount).when(this::isPositive)
        .to((acceptCount) -> customizeAcceptCount(factory, acceptCount));
    customizeStaticResources(factory);
    customizeErrorReportValve(properties.getError(), factory);
}

```

ServletWebServerFactoryAutoConfiguration Servletweb工厂自动配置类

很重要*****: @Import{

ServletWebServerFactoryAutoConfiguration.BeanPostProcessorsRegistrar.class}*****

```

@Configuration
@AutoConfigureOrder(Ordered.HIGHEST_PRECEDENCE)
@ConditionalOnClass(ServletRequest.class)
@ConditionalOnWebApplication(type = Type.SERVLET)
@EnableConfigurationProperties(ServerProperties.class)
@Import({ ServletWebServerFactoryAutoConfiguration.BeanPostProcessorsRegistrar.class,
    ServletWebServerFactoryConfiguration.EmbeddedTomcat.class,
    ServletWebServerFactoryConfiguration.EmbeddedJetty.class,
    ServletWebServerFactoryConfiguration.EmbeddedUndertow.class })
public class ServletWebServerFactoryAutoConfiguration {

    @Bean
    public ServletWebServerFactoryCustomizer servletWebServerFactoryCustomizer(
        ServerProperties serverProperties) {
        return new ServletWebServerFactoryCustomizer(serverProperties);
    }

    @Bean
    @ConditionalOnClass(name = "org.apache.catalina.startup.Tomcat")
    public TomcatServletWebServerFactoryCustomizer tomcatServletWebServerFactoryCustomizer(
        ServerProperties serverProperties) {
        return new TomcatServletWebServerFactoryCustomizer(serverProperties);
    }

}

```

.....ServletWebServerFactoryCustomizer核心代码.....

```

public void customize(ConfigurableServletWebServerFactory factory) {
    PropertyMapper map = PropertyMapper.get().alwaysApplyingWhenNonNull();
    map.from(this.serverProperties::getPort).to(factory::setPort);
    map.from(this.serverProperties::getAddress).to(factory::setAddress);
    map.from(this.serverProperties.getServlet()::getContextPath)
        .to(factory::setContextPath);
    map.from(this.serverProperties.getServlet()::getApplicationDisplayName)
        .to(factory::setDisplayName);
    map.from(this.serverProperties.getServlet()::getSession).to(factory::setSession);
    map.from(this.serverProperties::getSsl).to(factory::setSsl);
    map.from(this.serverProperties.getServlet()::getJsp).to(factory::setJsp);
    map.from(this.serverProperties::getCompression).to(factory::setCompression);
    map.from(this.serverProperties::getHttp2).to(factory::setHttp2);
    map.from(this.serverProperties::getServerHeader).to(factory::setServerHeader);
    map.from(this.serverProperties.getServlet()::getContextParameters)
        .to(factory::setInitParameters);
}

```



```

this.resourceLoader = resourceLoader;
Assert.notNull(primarySources, "PrimarySources must not be null");
//保存主配置类
this.primarySources = new LinkedHashSet<>(Arrays.asList(primarySources));
//保存web应用的类型
this.webApplicationType = WebApplicationType.deduceFromClasspath();
//保存 容器初始化器(ApplicationContextInitializer类型的)
setInitializers((Collection) getSpringFactoriesInstances(
    ApplicationContextInitializer.class));
//把监听器保存到 SpringApplication中[ApplicationListener]
setListeners((Collection) getSpringFactoriesInstances(ApplicationListener.class));
//保存主配置类
this.mainApplicationClass = deduceMainApplicationClass();
}

//还是去META-INF/spring.factories 中获取ApplicationContextInitializer 类型，用于初始化容器
private <T> Collection<T> getSpringFactoriesInstances(Class<T> type,
    Class<?>[] parameterTypes, Object... args) {
    ClassLoader classLoader = Thread.currentThread().getContextClassLoader();
    // Use names and ensure unique to protect against duplicates
    Set<String> names = new LinkedHashSet<>()
        SpringFactoriesLoader.loadFactoryNames(type, classLoader));
    List<T> instances = createSpringFactoriesInstances(type, parameterTypes,
        classLoader, args, names);
    AnnotationAwareOrderComparator.sort(instances);
    return instances;
}

//查找主配置类 查询的依据就是看哪个方法是否有main方法
private Class<?> deduceMainApplicationClass() {
    try {
        StackTraceElement[] stackTrace = new RuntimeException().getStackTrace();
        for (StackTraceElement stackTraceElement : stackTrace) {
            if ("main".equals(stackTraceElement.getMethodName())) {
                return Class.forName(stackTraceElement.getClassName());
            }
        }
    }
    catch (ClassNotFoundException ex) {
        // Swallow and continue
    }
    return null;
}

```

```

▼ names = {LinkedHashSet@1071} size = 6
▶ 0 = "org.springframework.boot.context.ConfigurationWarningsApplicationContextInitializer"
▶ 1 = "org.springframework.boot.context.ContextIdApplicationContextInitializer"
▶ 2 = "org.springframework.boot.context.config.DelegatingApplicationContextInitializer"
▶ 3 = "org.springframework.boot.web.context.ServerPortInfoApplicationContextInitializer"
▶ 4 = "org.springframework.boot.autoconfigure.SharedMetadataReaderFactoryContextInitializer"
▶ 5 = "org.springframework.boot.autoconfigure.logging.ConditionEvaluationReportLoggingListener"

```

```

▶ 0 = {ConfigFileApplicationListener@1224}
▶ 1 = {AnsiOutputApplicationListener@1225}
▶ 2 = {LoggingApplicationListener@1226}
▶ 3 = {ClasspathLoggingApplicationListener@1227}
▶ 4 = {BackgroundPreinitializer@1228}
▶ 5 = {DelegatingApplicationListener@1229}
▶ 6 = {ParentContextCloserApplicationListener@1230}
▶ 7 = {ClearCachesApplicationListener@1231}
▶ 8 = {FileEncodingApplicationListener@1232}
▶ 9 = {LiquibaseServiceLocatorApplicationListener@1233}

```

3)运行SpringbootApplication的运行方法

```

public ConfigurableApplicationContext run(String... args) {
    Stopwatch stopWatch = new Stopwatch();
    stopWatch.start();
    //创建一个 容器对象
    ConfigurableApplicationContext context = null;
    Collection<SpringBootExceptionReporter> exceptionReporters = new ArrayList<>();
    configureHeadlessProperty();
    //去meta-info/spring.factories中获取SpringApplicationRunListener 监听器(事件发布监听器)
    SpringApplicationRunListeners listeners = getRunListeners(args);
    //发布容器 starting事件(通过spring的事件多播器)
    listeners.starting();
    try {
        //封装命令行参数
        ApplicationArguments applicationArguments = new DefaultApplicationArguments(
            args);
        //准备容器环境
        1:获取或者创建环境
        2: 把命令行参数设置到环境中
        3: 通过监听器发布环境准备事件
        ConfigurableEnvironment environment = prepareEnvironment(listeners,
            applicationArguments);
        configureIgnoreBeanInfo(environment);
        //打印springboot的图标
        Banner printedBanner = printBanner(environment);
        //创建容器 根据webApplicationType 来创建容器 通过反射创建
        context = createApplicationContext();
        //去meta-info类中 获取异常报告
        exceptionReporters = getSpringFactoriesInstances(
            SpringBootExceptionReporter.class,
            new Class[] { ConfigurableApplicationContext.class }, context);
        //准备环境
        1: 把环境设置到容器中
        2: 循环调用ApplicationInitializer 进行容器初始化工作
        3:发布容器上下文准备完成事件
        4:注册关于springboot特性的相关单例Bean
        5:发布容器上下文加载完毕事件
        prepareContext(context, environment, listeners, applicationArguments,printedBanner);
        refreshContext(context);
        //运行 ApplicationRunner 和CommandLineRunner
        afterRefresh(context, applicationArguments);
        stopWatch.stop();
        if (this.logStartupInfo) {
            new StartupInfoLogger(this.mainApplicationClass)

```



```

        .logStarted(getApplicationLog(), stopWatch);
    }
    //发布容器启动事件
    listeners.started(context);
    //运行 ApplicationRunner 和CommandLineRunner
    callRunners(context, applicationArguments);
}
catch (Throwable ex) {
    //出现异常; 调用异常分析保护类进行分析
    handleRunFailure(context, ex, exceptionReporters, listeners);
    throw new IllegalStateException(ex);
}

try {
    //发布容器运行事件
    listeners.running(context);
}
catch (Throwable ex) {
    handleRunFailure(context, ex, exceptionReporters, null);
    throw new IllegalStateException(ex);
}
return context;
}

```

5)org.springframework.boot.SpringApplication#refreshContext

6)org.springframework.context.support.AbstractApplicationContext#refresh

7)org.springframework.boot.web.servlet.context.ServletWebServerApplicationContext#onRefresh

8)org.springframework.boot.web.servlet.context.ServletWebServerApplicationContext#createWebServer

8.1)org.springframework.boot.web.servlet.context.ServletWebServerApplicationContext#getWebServerFactory
获取web 服务器工厂

以下是springioc容器启动的核心流程, 在这里不做详细解释,大概步骤为如下:

```

postProcessBeforeInitialization:61, WebServerFactoryCustomizerBeanPostProcessor (org.springframework.boot)
applyBeanPostProcessorsBeforeInitialization:416, AbstractAutowireCapableBeanFactory (org.springframework)
initializeBean:1686, AbstractAutowireCapableBeanFactory (org.springframework.beans.factory.support)
doCreateBean:573, AbstractAutowireCapableBeanFactory (org.springframework.beans.factory.support)
createBean:495, AbstractAutowireCapableBeanFactory (org.springframework.beans.factory.support)
lambda$doGetBean$0:317, AbstractBeanFactory (org.springframework.beans.factory.support)
getObject:-1, 937744315 (org.springframework.beans.factory.support.AbstractBeanFactory$$Lambda$110)
getSingleton:222, DefaultSingletonBeanRegistry (org.springframework.beans.factory.support)
doGetBean:315, AbstractBeanFactory (org.springframework.beans.factory.support)
getBean:204, AbstractBeanFactory (org.springframework.beans.factory.support)

```

.....

8.2)org.springframework.boot.web.server.WebServerFactoryCustomizerBeanPostProcessor#postProcessBeforeInitializati

```

@Override
public Object postProcessBeforeInitialization(Object bean, String beanName) throws BeansException {
    if (bean instanceof WebServerFactory) {
        postProcessBeforeInitialization((WebServerFactory) bean);
    }
    return bean;
}

```

8.3)org.springframework.boot.web.server.WebServerFactoryCustomizerBeanPostProcessor#postProcessBeforeInitializati

```

private void postProcessBeforeInitialization(WebServerFactory webServerFactory) {
    LambdaSafe
        .callbacks(WebServerFactoryCustomizer.class, getCustomizers(),
            webServerFactory)
        .withLogger(WebServerFactoryCustomizerBeanPostProcessor.class)
        .invoke((customizer) -> customizer.customize(webServerFactory));
}

```

8.3.1)WebServerFactoryCustomizerBeanPostProcessor 是一个什么东西？ 在哪里注册到容器中的???

我们往容器中导入了 BeanPostProcessorsRegistrar 他实现了 ImportBeanDefinitionRegistrar

在他的 registerBeanDefinitions注册Bean定义的时候 注册了 webServerFactoryCustomizerBeanPostProcessor

想知道 webServerFactoryCustomizerBeanPostProcessor何时在容器中注册的么????

```

public static class BeanPostProcessorsRegistrar implements ImportBeanDefinitionRegistrar, BeanFactoryAware {

    private ConfigurableListableBeanFactory beanFactory;

    @Override
    public void setBeanFactory(BeanFactory beanFactory) throws BeansException {
        if (beanFactory instanceof ConfigurableListableBeanFactory) {
            this.beanFactory = (ConfigurableListableBeanFactory) beanFactory;
        }
    }

    @Override
    public void registerBeanDefinitions(AnnotationMetadata importingClassMetadata,
        BeanDefinitionRegistry registry) {
        if (this.beanFactory == null) {
            return;
        }
        registerSyntheticBeanIfMissing(registry,
            "webServerFactoryCustomizerBeanPostProcessor",
            WebServerFactoryCustomizerBeanPostProcessor.class);
        registerSyntheticBeanIfMissing(registry,
            "errorPageRegistrarBeanPostProcessor",
            ErrorPageRegistrarBeanPostProcessor.class);
    }
}

```

```
public WebServer getWebServer(ServletContextInitializer... initializers) {
    Tomcat tomcat = new Tomcat();
    File baseDir = (this.baseDirectory != null) ? this.baseDirectory
        : createTempDir("tomcat");
    tomcat.setBaseDir(baseDir.getAbsolutePath());
    Connector connector = new Connector(this.protocol);
    tomcat.getService().addConnector(connector);
    customizeConnector(connector);
    tomcat.setConnector(connector);
    tomcat.getHost().setAutoDeploy(false);
    configureEngine(tomcat.getEngine());
    for (Connector additionalConnector : this.additionalTomcatConnectors) {
        tomcat.getService().addConnector(additionalConnector);
    }
    prepareContext(tomcat.getHost(), initializers);
    return getTomcatWebServer(tomcat);
}

protected TomcatWebServer getTomcatWebServer(Tomcat tomcat) {
    //端口大于0启动启动
    return new TomcatWebServer(tomcat, getPort() >= 0);
}

public TomcatWebServer(Tomcat tomcat, boolean autoStart) {
    Assert.notNull(tomcat, "Tomcat Server must not be null");
    this.tomcat = tomcat;
    this.autoStart = autoStart;
    initialize();
}

tomcat启动流程
private void initialize() throws WebServerException {
    TomcatWebServer.logger
        .info("Tomcat initialized with port(s): " + getPortsDescription(false));
    synchronized (this.monitor) {
        try {
            addInstanceIdToEngineName();

            Context context = findContext();
            context.addLifecycleListener((event) -> {
                if (context.equals(event.getSource())
                    && Lifecycle.START_EVENT.equals(event.getType())) {
                    // Remove service connectors so that protocol binding doesn't
                    // happen when the service is started.
                    removeServiceConnectors();
                }
            });

            // Start the server to trigger initialization listeners
            this.tomcat.start();

            // We can re-throw failure exception directly in the main thread
            rethrowDeferredStartupExceptions();

            try {
                ContextBindings.bindClassLoader(context, context.getNamingToken(),
                    getClass().getClassLoader());
            }
        }
    }
}
```

```

        catch (NamingException ex) {
            // Naming is not enabled. Continue
        }

        // Unlike Jetty, all Tomcat threads are daemon threads. We create a
        // blocking non-daemon to stop immediate shutdown
        startDaemonAwaitThread();
    }
    catch (Exception ex) {
        stopSilently();
        throw new WebServerException("Unable to start embedded Tomcat", ex);
    }
}
}

```

10) 在IOC 容器中的 `org.springframework.context.support.AbstractApplicationContext#refresh` 的 `onRefresh()` 带动tomcat启动

然后在接着执行 ioc容器的其他步骤。

```

}
public void refresh() throws BeansException, IllegalStateException {
    Object var1 = this.startupShutdownMonitor;
    synchronized(this.startupShutdownMonitor) {
        this.prepareRefresh();
        ConfigurableListableBeanFactory beanFactory = this.obtainFreshBeanFactory();
        this.prepareBeanFactory(beanFactory);

        try {
            this.postProcessBeanFactory(beanFactory);
            this.invokeBeanFactoryPostProcessors(beanFactory);
            this.registerBeanPostProcessors(beanFactory);
            this.initMessageSource();
            this.initApplicationEventMulticaster();
            this.onRefresh();
            this.registerListeners();
            this.finishBeanFactoryInitialization(beanFactory);
            this.finishRefresh();
        } catch (BeansException var9) {
            if(this.logger.isWarnEnabled()) {
                this.logger.warn("Exception encountered during context initialization - canceling refresh");
            }
        }

        this.destroyBeans();
    }
}

```

疑问?????

1) `AutoConfigurationImportSelector#selectImports` 的方法是怎么触发的?

```

@Override
public String[] selectImports(AnnotationMetadata annotationMetadata) {
    if (!isEnabled(annotationMetadata)) {
        return NO_IMPORTS;
    }
    AutoConfigurationMetadata autoConfigurationMetadata = AutoConfigurationMetadataLoader
        .loadMetadata(this.beanClassLoader);
    AnnotationAttributes attributes = getAttributes(annotationMetadata);
    List<String> configurations = getCandidateConfigurations(annotationMetadata,
        attributes);
    configurations = removeDuplicates(configurations);
    Set<String> exclusions = getExclusions(annotationMetadata, attributes);
    checkExcludedClasses(configurations, exclusions);
    configurations.removeAll(exclusions);
    configurations = filter(configurations, autoConfigurationMetadata);
    fireAutoConfigurationImportEvents(configurations, exclusions);
    return StringUtils.toStringArray(configurations);
}

```

2) 我们自己定义的一些@Controller @Service 怎么到容器中去的???

接下来 我们就一一解答你们的疑问?还是以debug的方式来为大家解答

1>AbstractApplicationContext#refresh(容器的刷新)

2>AbstractApplicationContext#invokeBeanFactoryPostProcessors 调用bean工厂的后置处理器

3>PostProcessorRegistrationDelegate#invokeBeanDefinitionRegistryPostProcessors

4>ConfigurationClassPostProcessor#postProcessBeanDefinitionRegistry 配置类的后置处理器

5>ConfigurationClassPostProcessor#processConfigBeanDefinitions 处理配置的bean定义

5.1) 找到候选的配置类(tulingvipSpringbootAutoconfigPrincipleApplication)我们自己项目中的配置类

5.2) 创建配置类解析器

6>ConfigurationClassParser#parse 解析我们自己的配置类
(tulingvipSpringbootAutoconfigPrincipleApplication)

7>ConfigurationClassParser#processConfigurationClass处理配置类

7.1)处理配置类上的@PropertySource注解

ConfigurationClassParser#processPropertySource

7.2) 处理@ComponentScan注解的 ComponentScanAnnotationParser#parse

①:创建 类路径下的bean定义扫描器 ClassPathBeanDefinitionScanner

..多个步骤 解析@ComponentScan 注解的属性

②:ClassPathBeanDefinitionScanner#doScan 真正的扫描
(tulingvipSpringbootAutoconfigPrincipleApplication所在的包)

③:返回我们标志了@Controller @Service @Response @compent注解的bean定义

7.3) 处理@Import注解 ConfigurationClassParser#processImports

7.4) 处理@ImportSource注解

7.5) 处理@Bean注解的

8>ConfigurationClassParser#processDeferredImportSelectors 处理实现了
ImportSelectors接口的

9>AutoConfigurationGroup#process (获取 容器中的所有ImportSelector
包含了 AutoConfigurationImportSelector)

调 AutoConfigurationImportSelector.selectImports

11: ConfigurationClassBeanDefinitionReader#loadBeanDefinitions 把解析出来的类的bean
定义 注册到容器中

