ALPHA & OMEGA
SEMICONDUCTOR

AO3402

30V N-Channel MOSFET

General Description

The AO3402 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a load switch or in PWM applications.

Product Summary

V_{DS}	30V
I_D (at V_{GS}=10V)	4A
$R_{DS(ON)}$ (at V_{GS}=10V)	< 52mΩ
$R_{DS(ON)}$ (at V_{GS} =4.5V)	< 65mΩ
$R_{DS(ON)}$ (at V_{GS} =2.5V)	< 85mΩ

Green Product





Absolute Maximum Ratings T_A=25℃ unless otherwise noted				
Parameter		**Symbol**	**Maximum**	**Units**
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current	T_A=25℃	I_D	4	A
	T_A=70℃		3.2	
Pulsed Drain Current [C]		I_{DM}	15	
Power Dissipation [B]	T_A=25℃	P_D	1.4	W
	T_A=70℃		0.9	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	℃

Thermal Characteristics					
Parameter		**Symbol**	**Typ**	**Max**	**Units**
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	70	90	℃/W
Maximum Junction-to-Ambient [A D]	Steady-State		100	125	℃/W
Maximum Junction-to-Lead	Steady-State	$R_{\theta JL}$	63	80	℃/W

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ	Max	Units
STATIC PARAMETERS							
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V		30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=30V, V_{GS}=0V				1	µA
			T_J=55℃			5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±12V				±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250µA		0.5	1	1.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=10V, V_{DS}=5V		15			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=4A			43	52	mΩ
			T_J=125℃		70	84	
		V_{GS}=4.5V, I_D=3A			47	65	mΩ
		V_{GS}=2.5V, I_D=2A			60	85	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=3.6A			14		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V			0.75	1	V
I_S	Maximum Body-Diode Continuous Current					1.5	A
DYNAMIC PARAMETERS							
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=15V, f=1MHz		185	235	285	pF
C_{oss}	Output Capacitance			25	35	45	pF
C_{rss}	Reverse Transfer Capacitance			10	18	25	pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		2.1	4.3	6.5	Ω
SWITCHING PARAMETERS							
Q_g(10V)	Total Gate Charge	V_{GS}=10V, V_{DS}=15V, I_D=4A			10	12	nC
Q_g(4.5V)	Total Gate Charge				4.7		nC
Q_{gs}	Gate Source Charge				0.95		nC
Q_{gd}	Gate Drain Charge				1.6		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=15V, R_L=3.75Ω, R_{GEN}=3Ω			3.5		ns
t_r	Turn-On Rise Time				1.5		ns
$t_{D(off)}$	Turn-Off DelayTime				17.5		ns
t_f	Turn-Off Fall Time				2.5		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=4A, dI/dt=100A/µs			8.5	11	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=4A, dI/dt=100A/µs			2.6	3.5	nC

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A =25° C. The value in any given application depends on the user's specific board design.
B. The power dissipation P_D is based on $T_{J(MAX)}$=150° C, using ≤ 10s junction-to-ambient thermal resistance.
C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150° C. Ratings are based on low frequency and duty cycles to keep initialT_J=25° C.
D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.
E. The static characteristics in Figures 1 to 6 are obtained using <300µs pulses, duty cycle 0.5% max.
F. These curves are based on the junction-to-ambient thermal impedence which is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, assuming a maximum junction temperature of $T_{J(MAX)}$=150° C. The SOA curve provides a single pulse rating.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics (Note E)



Figure 2: Transfer Characteristics (Note E)



Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)



Figure 4: On-Resistance vs. Junction Temperature (Note E)



Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)



Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note F)



Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)



Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms