

手机摄像头 模组规格书

The Embedded Mobile Camera Module
Specification

客户 (Customer): 易 景

产品名称 (Project): LA180

型号 (Model): XCG10017

送样日期(Submission Date):

样品确认 (Approval):

客户确认 (Confirm)	单位 (Department)	外观结构 (Structure)	电子科 (Electric Property)	批准 (Approve)
	签章 (Sign)			
客户意见:				

地址: 湖南省宜章县玉溪镇经济开发区鸿兴路 1 号

电话 (TEL): 0755-28035205

传真 (FAX): 0755-28035200

宜章鑫晨光电子有限公司

YI ZHANG XIN CHEN GUANG OPTOELECTRONIC CO.,LIMITED

内 容 CONTENT			
1. 技术参数 2. 尺寸说明 3. 外观检测 4. 功能测试 5. 包装要求			
版本 Version	填写 Compile	审核 Auditing	批准 Authorize
V1.0			

宜章鑫晨光电子有限公司

YI ZHANG XIN CHEN GUANG OPTOELECTRONIC CO.,LIMITED

一. 技术参数

● 产品介绍.

The BF2557CS is a 1/5-inch 5Mega CMOS Image Sensor which includes CMOS image sensor (CIS) and Sensor control. It is fabricated with the world's most advanced CMOS image sensor process to realize ultra-low dark noise, high sensitivity, high dynamic range and very low power imaging system. The sensor consists of a 2592×1944 pixel array which has an optical format of 1/5 inch. It has integrated noise canceling CDS (Correlated Double Sampling) circuits, analog global gain control, auto black level compensation, on-chip 10-bit ADC. It provides Bayer RGB data with serial MIPI interface. It has a commonly used two-wire serial interface for host to control the operation of the whole sensor.

The product is capable of operating at up to 30 frames per second in 5Mega mode, with complete user control over image. All required sensor control functions, including Exposure control, Gain control, image size and so on, could be programmable through the two-wire serial bus.

● 规格与特性.

总高度: 4.3±0.15mm

基座尺寸: 6.0×6.0mm

影像尺寸: 2MP 格式.

IR 防红外线干扰过滤镜(IR Filter).

● 性能参数

● Optical Format	1/5 inch
● Active pixel array	2592 x 1944
● Pixel size	1.12um x 1.12um
● Sensitivity	0.43 V/Lux-sec
● Dark current	0.2 mV/s at 25°C
● Power supply	VDDIO:1.7~3.1V VDD3A/VDD3C:2.6~3.1V VDDD:1.15~1.35V
● Power consumption	TBD
● Standby current	TBD
● SNR(Max)	37.5 dB
● Dynamic range	64 dB
● Operating temperature	-20~70°C
● Stable Image temperature	0~60°C
● Lens chief ray angle	31.9° (Non-linear)
● Input clock frequency	6~27MH
● Package type	CSP

宜章鑫晨光电子有限公司

YI ZHANG XIN CHEN GUANG OPTOELECTRONIC CO.,LIMITED

三. 外观检测

1	模组外观检测	模组表面不可有毛刺、脏污、划伤。
2	模组尺寸检测	格按照客户图纸控制尺寸与公差。
3	LENS 胶检测	点胶长度为周长的 1/4，点胶量为 2 圈，LENS 胶不可溢到镜头端面 and Holder 上沿。
4	底座胶检测	底座与 FPCB 之间不可有漏缝,不可有胶溢出 FPCB 边缘导致外形尺寸超标的现象。
5	金手指检测	金手指不允许有烧焦、脱皮、桥接、断路、分层、凹凸不平、严重变色等现象。

四. 功能测试

序号	检测项目	标准	1	2	3	4	5	判定	备注
1	PIN 脚定义	样品与图纸相符	√	√	√	√	√	OK	光学测试详细测试条件和标准参考附页
2	点亮	在 DEMO 板上测试有图像	√	√	√	√	√	OK	
3	花屏	在 DEMO 板上测试无花屏现象	√	√	√	√	√	OK	
4	模糊	测试图像中 CHART 是清晰的	√	√	√	√	√	OK	
5	污点	测试图像中无污点	√	√	√	√	√	OK	
6	色点	测试图中无色点色条	√	√	√	√	√	OK	
7	连接器	反复插拔 10 次，无功能不良	√	√	√	√	√	OK	

宜章鑫晨光电子有限公司

YI ZHANG XIN CHEN GUANG OPTOELECTRONIC CO.,LIMITED

五. 包装和运输及注意事项

1. 产品应严格根据产品特点制定相应的包装标准并遵照执行，以保证产品规定使用和储存期内，达到防静电. 防湿. 防震. 防霉等相关保质要求。
2. 产品外包装上应标明：供方名称、标志、产品型号、内装数量、生产日期、批号和订单号。
3. 包装及装箱方案依据客户要求，由双方协商具体细节，以封样为准。

