

```
# Week 8 - Lecture 2, Predictive Policing
```

```
# VIDEO 3 - A Basic Line Plot
```

```
# Load our data:
```

```
mvt = read.csv("mvt.csv", stringsAsFactors=FALSE)
```

```
str(mvt)
```

```
# Convert the Date variable to a format that R will recognize:
```

```
mvt$Date = strptime(mvt$Date, format="%m/%d/%y %H:%M")
```

```
# Extract the hour and the day of the week:
```

```
mvt$Weekday = weekdays(mvt$Date)
```

```
mvt$Hour = mvt$Date$hour
```

```
# Let's take a look at the structure of our data again:
```

```
str(mvt)
```

```
# Create a simple line plot - need the total number of crimes on each  
day of the week. We can get this information by creating a table:
```

```
table(mvt$Weekday)
```

```
# Save this table as a data frame:
```

```
WeekdayCounts = as.data.frame(table(mvt$Weekday))
```

```
str(WeekdayCounts)
```

```
# Load the ggplot2 library:
```

```
library(ggplot2)
```

```
# Create our plot
```

```
ggplot(WeekdayCounts, aes(x=Var1, y=Freq)) + geom_line(aes(group=1))
```

```
#geom_line(aes(group=1), linetype=2) to make the line dashed
```

```
#geom_line(aes(group=1),alpha=0.3) to make the line lighter in color
```

```
# Make the "Var1" variable an ORDERED factor variable
```

```
WeekdayCounts$Var1 = factor(WeekdayCounts$Var1, ordered=TRUE,  
levels=c("Sunday", "Monday", "Tuesday", "Wednesday", "Thursday",  
"Friday", "Saturday"))
```

```
# Try again:
```

```
ggplot(WeekdayCounts, aes(x=Var1, y=Freq)) + geom_line(aes(group=1))
```

```
# Change our x and y labels:
```

```
ggplot(WeekdayCounts, aes(x=Var1, y=Freq)) + geom_line(aes(group=1))  
+ xlab("Day of the Week") + ylab("Total Motor Vehicle Thefts")
```

VIDEO 4 - Adding the Hour of the Day

Create a counts table for the weekday and hour:

```
table(mvt$Weekday, mvt$Hour)
```

Save this to a data frame:

```
DayHourCounts = as.data.frame(table(mvt$Weekday, mvt$Hour))
```

```
str(DayHourCounts)
```

Convert the second variable, Var2, to numbers and call it Hour:

```
DayHourCounts$Hour = as.numeric(as.character(DayHourCounts$Var2))
```

Create out plot:

```
ggplot(DayHourCounts, aes(x=Hour, y=Freq)) +  
geom_line(aes(group=Var1))
```

Change the colors

```
ggplot(DayHourCounts, aes(x=Hour, y=Freq)) +  
geom_line(aes(group=Var1, color=Var1), size=2)
```

Separate the weekends from the weekdays:

```
DayHourCounts$Type = ifelse((DayHourCounts$Var1 == "Sunday") |  
  (DayHourCounts$Var1 == "Saturday"), "Weekend", "Weekday")
```

Redo our plot, this time coloring by Type:

```
ggplot(DayHourCounts, aes(x=Hour, y=Freq)) +  
geom_line(aes(group=Var1, color=Type), size=2)
```

Make the lines a little transparent:

```
ggplot(DayHourCounts, aes(x=Hour, y=Freq)) +  
geom_line(aes(group=Var1, color=Type), size=2, alpha=0.5)
```

Fix the order of the days:

```
DayHourCounts$Var1 = factor(DayHourCounts$Var1, ordered=TRUE,  
  levels=c("Monday", "Tuesday", "Wednesday", "Thursday", "Friday",  
    "Saturday", "Sunday"))
```

Make a heatmap:

```
ggplot(DayHourCounts, aes(x = Hour, y = Var1)) + geom_tile(aes(fill =
```

```
Freq))
```

```
# Change the label on the legend, and get rid of the y-label:
```

```
ggplot(DayHourCounts, aes(x = Hour, y = Var1)) + geom_tile(aes(fill =  
  Freq)) + scale_fill_gradient(name="Total MV Thefts") +  
  theme(axis.title.y = element_blank())
```

```
# Change the color scheme
```

```
ggplot(DayHourCounts, aes(x = Hour, y = Var1)) + geom_tile(aes(fill =  
  Freq)) + scale_fill_gradient(name="Total MV Thefts", low="white",  
  high="red") + theme(axis.title.y = element_blank())
```

```
# VIDEO 5 - Maps
```

```
# Install and load two new packages:
```

```
install.packages("maps")  
install.packages("ggmap")  
library(maps)  
library(ggmap)
```

```
# Load a map of Chicago into R:
```

```
chicago = get_map(location = "chicago", zoom = 11)
```

```
# Look at the map
```

```
ggmap(chicago)
```

```
# Plot the first 100 motor vehicle thefts:
```

```
ggmap(chicago) + geom_point(data = mvt[1:100,], aes(x = Longitude, y  
  = Latitude))
```

```
# Round our latitude and longitude to 2 digits of accuracy, and  
  create a crime counts data frame for each area:
```

```
LatLonCounts = as.data.frame(table(round(mvt$Longitude,2), round(mvt  
  $Latitude,2)))
```

```
str(LatLonCounts)
```

```
# Convert our Longitude and Latitude variable to numbers:
```

```
LatLonCounts$Long = as.numeric(as.character(LatLonCounts$Var1))  
LatLonCounts$Lat = as.numeric(as.character(LatLonCounts$Var2))
```

```
# Plot these points on our map:
```

```
ggmap(chicago) + geom_point(data = LatLonCounts, aes(x = Long, y =  
  Lat, color = Freq, size=Freq))
```

```
# Change the color scheme:
ggmap(chicago) + geom_point(data = LatLonCounts, aes(x = Long, y =
  Lat, color = Freq, size=Freq)) + scale_colour_gradient(low="yellow",
  high="red")
```

```
# We can also use the geom_tile geometry
ggmap(chicago) + geom_tile(data = LatLonCounts, aes(x = Long, y =
  Lat, alpha = Freq), fill="red")
```

VIDEO 6 - Geographical Map on US

```
# Load our data:
murders = read.csv("murder.csv")
```

```
str(murders)
```

```
# Load the map of the US
statesMap = map_data("state")
```

```
str(statesMap)
```

```
# Plot the map:
ggplot(statesMap, aes(x = long, y = lat, group = group)) +
  geom_polygon(fill = "white", color = "black") +
  coord_map("mercator")
```

```
# Create a new variable called region with the lowercase names to
  match the statesMap:
murders$region = tolower(murders$State)
```

```
# Join the statesMap data and the murders data into one dataframe:
murderMap = merge(statesMap, murders, by="region")
str(murderMap)
```

```
# Plot the number of murder on our map of the United States:
ggplot(murderMap, aes(x = long, y = lat, group = group, fill =
  Murders)) + geom_polygon(colour = "black") + scale_fill_gradient(low
  = "black", high = "red", guide = "legend")
```

```
# Plot a map of the population:
ggplot(murderMap, aes(x = long, y = lat, group = group, fill =
  Population)) + geom_polygon(colour = "black") +
  scale_fill_gradient(low = "black", high = "red", guide = "legend")
```

```
# Create a new variable that is the number of murders per 100,000
```

```
population:
murderMap$MurderRate = murderMap$Murders / murderMap$Population *
100000

# Redo our plot with murder rate:
ggplot(murderMap, aes(x = long, y = lat, group = group, fill =
MurderRate)) + geom_polygon(colour = "black") +
scale_fill_gradient(low = "black", high = "red", guide = "legend")

# Redo the plot, removing any states with murder rates above 10:
ggplot(murderMap, aes(x = long, y = lat, group = group, fill =
MurderRate)) + geom_polygon(colour = "black") +
scale_fill_gradient(low = "black", high = "red", guide = "legend",
name = "Murder Rate per 100k", limits = c(0.9,10))
```