Logback

- Maven
- Spring
- logback-spring.xml

Maven

Spring

```
properties:
logging.config=classpath:logback-spring.xml
yaml:
logging:
   config: classpath:logback-spring.xml
```

logback-spring.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration debug="false">
   <conversionRule conversionWord="clr" converterClass="org.springframework.boot.logging.logback.</pre>
ColorConverter" />
   \verb|-conversionRule| conversionWord="wex"| converterClass="org.springframework.boot.logging.logback. |
WhitespaceThrowableProxyConverter" />
   <conversionRule conversionWord="wEx" converterClass="org.springframework.boot.logging.logback.</pre>
ExtendedWhitespaceThrowableProxyConverter" />
    <springProfile name="dev">
        <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
            <filter class="ch.qos.logback.classic.filter.ThresholdFilter">
                <level>DEBUG</level>
            </filter>
            <encoder>
                <pattern>%clr([%p] [%d] [%c.%M] %m%n)</pattern>
                <charset>UTF-8</charset>
            </encoder>
        </appender>
        <!-- debug log-->
        <logger name="com.gdlt.cloud" level="DEBUG"/>
        <logger name="com.github.xiaoymin" level="INFO"/>
                <logger name="com.netflix" level="WARN"/>
        <logger name="org.thymeleaf" level="WARN"/>
        <logger name="org.apache.http" level="INFO"/>
        <le><logger name="com.alibaba.druid" level="INFO"/>
```

```
<le><logger name="org.mybatis" level="INFO"/>
    <logger name="org.hibernate" level="INFO"/>
    <logger name="io.netty" level="INFO"/>
    <logger name="org.redisson" level="INFO"/>
    <logger name="com.baomidou" level="INFO"/>
    <logger name="springfox.documentation" level="WARN"/>
    <logger name="org.springframework" level="INFO"/>
    <logger name="org.apache.commons" level="INFO"/>
    <logger name="druid.sql" level="INFO"/>
           <logger name="java.sql.Connection" level="INFO"/>
            <logger name="java.sql.Statement" level="INFO"/>
            <logger name="java.sql.PreparedStatement" level="DEBUG"/>
   <root level="DEBUG">
       <appender-ref ref="STDOUT" />
    </root>
</springProfile>
<springProfile name="test">
    <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
        <filter class="ch.qos.logback.classic.filter.ThresholdFilter">
            <level>DEBUG</level>
        </filter>
        <encoder>
            <pattern>%clr([%p] [%d] [%c.%M] %m%n)</pattern>
            <charset>UTF-8</charset>
        </encoder>
    </appender>
    <appender name="ROLLING" class="ch.qos.logback.core.rolling.RollingFileAppender">
        <file>center.log</file>
        <rollingPolicy class="ch.qos.logback.core.rolling.TimeBasedRollingPolicy">
            <FileNamePattern>center.%d{yyyy-MM-dd}.log/FileNamePattern>
            <MaxHistory>7</MaxHistory>
        </rellingPolicy>
            <pattern>[%p] [%d] [%c.%M] %m%n</pattern>
            <charset>UTF-8</charset>
        </encoder>
    </appender>
    <!-- debug log-->
    <logger name="com.gdlt.cloud" level="DEBUG"/>
    <le><logger name="com.github.xiaoymin" level="INFO"/>
            <logger name="com.netflix" level="WARN"/>
    <logger name="org.thymeleaf" level="WARN"/>
    <logger name="org.apache.http" level="INFO"/>
    <le><logger name="com.alibaba.druid" level="INFO"/>
    <le><logger name="org.mybatis" level="INFO"/>
    <logger name="org.hibernate" level="INFO"/>
    <logger name="io.netty" level="INFO"/>
    <le><logger name="org.redisson" level="INFO"/>
    <logger name="com.baomidou" level="INFO"/>
    <logger name="springfox.documentation" level="WARN"/>
    <logger name="org.springframework" level="INFO"/>
    <logger name="org.apache.commons" level="INFO"/>
    <logger name="druid.sql" level="INFO"/>
            <logger name="java.sql.Connection" level="INFO"/>
            <logger name="java.sql.Statement" level="INFO"/>
            <logger name="java.sql.PreparedStatement" level="DEBUG"/>
    <root level="DEBUG">
        <appender-ref ref="STDOUT" />
        <appender-ref ref="ROLLING" />
    </root>
</springProfile>
```

```
<springProfile name="prod">
       <appender name="ROLLING" class="ch.qos.logback.core.rolling.RollingFileAppender">
           <file>center.log</file>
           <rollingPolicy class="ch.qos.logback.core.rolling.TimeBasedRollingPolicy">
               <FileNamePattern>center.%d{yyyy-MM-dd}.log</FileNamePattern>
               <MaxHistory>7</MaxHistory>
           </rollingPolicy>
           <encoder>
               <pattern>[%p] [%d] [%c.%M] %m%n</pattern>
               <charset>UTF-8</charset>
           </encoder>
       </appender>
       <root level="WARN">
           <appender-ref ref="ROLLING" />
        </root>
    </springProfile>
</configuration>
```