

一、安装VNC

1. 导入rpm包

百度云下载:

链接: https://pan.baidu.com/s/1v2tyjCvL_UxmyV68blouzw

提取码: lfq8

```
rpm -ivh --nodeps tigervnc-1.8.0-13.el7.x86_64.rpm tigervnc-server-1.8.0-13.el7.x86_64.rpm tigervnc-server-module-1.8.0-17.el7.x86_64.rpm
```

或者

```
yum -y install tigervnc tigervnc-server tigervnc-server-module
```

2. 复制配置文件

```
cp /lib/systemd/system/vncserver@.service  
/lib/systemd/system/vncserver@:1.service
```

3. 修改配置文件

```
vim /lib/systemd/system/vncserver@:1.service
```

```
[Unit]  
Description=Remote desktop service (VNC)  
After=syslog.target network.target  
[Service]  
Type=forking  
# Clean any existing files in /tmp/.X11-unix environment  
ExecStartPre=/bin/sh -c '/usr/bin/vncserver -kill %i > /dev/null 2>&1 || :'  
ExecStart=/usr/sbin/runuser -l root -c "/usr/bin/vncserver %i -geometry 1920x1080"  
PIDFile=/root/.vnc/%H%i.pid  
ExecStop=/bin/sh -c '/usr/bin/vncserver -kill %i > /dev/null 2>&1 || :'  
[Install]  
WantedBy=multi-user.target
```

4. 设置vncserver的密码;

```
vncpasswd root
```

按提示输入密码以及确认密码 5.更新systemctl以使其生效;

```
systemctl daemon-reload
```

6. 启动该服务用来启用vnc的1号窗口;

```
systemctl start vncserver@:1.service
```

关闭1号窗口:

```
systemctl stop vncserver@:1.service
```

查看状态:

```
systemctl status vncserver@:1.service -l
```

7. 设置为开机自动启动

```
systemctl enable vncserver@:1.service
```

8. 修改防火墙

```
systemctl start firewalld      #启动firewalld服务
systemctl status firewalld     #查看运行状态
systemctl enable firewalld     #设置开机启动
systemctl stop firewalld       #关闭firewalld服务
```

首先判断firewalld是否启动, 输入以下命令判断

```
sudo firewall-cmd --state
```

如果启动应该输出

```
running
```

如果是not running, 执行下面命令

```
sudo systemctl start firewalld
```

添加端口号5901-5905

```
sudo firewall-cmd --permanent --zone=public --add-port=5901-5905/tcp
```

重新加载防火墙


```
sudo firewall-cmd --reload
```

可以使用下面命令查看端口号是否被加入

```
firewall-cmd --list-all-zones
```

9. 访问centos7上的vnc

Centos7的ip地址:1 即可访问



10.蓝屏可能是gnome没安造成的,安装GNOME后重启linux

```
yum groupinstall "GNOME Desktop" "Graphical Administration Tools"
reboot
```

11.启动vnc报错：Job for vncserver@:1.service failed because a configured resource limit was exceeded.

执行# systemctl status vncserver@:1.service

发现一条信息：

localhost.localdomain systemd[1]: PID file /root/.vnc/localhost.localdomain:1.pid not readable (yet?) after start.

检查 /root/.vnc/, 发现没有localhost.localdomain:1.pid

解决方法：原来目录/tmp/下有一个/.X11-unix目录会占用这个pid序号资源。把这个目录改名/.X11-unix.bak后，再次执行

```
mv /tmp/.X11-unix /tmp/.X11-unix.bak
systemctl start vncserver@:1.service
```

二、安装DB2




1、下载DB2

百度云下载：

链接：https://pan.baidu.com/s/1I5HEAj4soRjgnV1_-KtO0A

提取码：2614


这里我们下载v10.5的版本。

我的网盘 > 我的资源 > 开发工具、技术文档、jar包等资料 > DB2 > db2v10.5 > 搜索我的网盘文件			
<input type="checkbox"/> 文件名	↑	修改时间	大小
<input type="checkbox"/>  v10.5_linuxx64_expc.tar.gz		2020-05-29 16:31	567.68MB
<input type="checkbox"/>  v10.5_linuxx64_nlpack.tar.gz		2020-05-29 16:31	392.02MB
<input type="checkbox"/>  v10.5fp1_linuxx64_expc.tar.gz		2020-05-29 16:31	559.11MB

2、上传到/home/DB2目录下并解压

```
tar -zxvf v10.5_linuxx64_expc.tar.gz
```

解压后出现如下目录：




3、使用VNC连接服务器，进入可视化界面

```
cd /home/DB2/expc
```


```
root@localhost:/home/DB2/expc



File Edit View Search Terminal Help
[root@localhost ~]# cd /home/DB2/expc/
[root@localhost expc]# ll
total 48
drwxr-xr-x. 6 bin bin   87 Nov 30  2014 db2
-r-xr-xr-x. 1 bin bin 5874 Nov 30  2014 db2ckupgrade
-r-xr-xr-x. 1 bin bin 5789 Nov 30  2014 db2_deinstall
-r-xr-xr-x. 1 bin bin 5659 Nov 30  2014 db2_install
-r-xr-xr-x. 1 bin bin 5623 Nov 30  2014 db2ls
-r-xr-xr-x. 1 bin bin 5633 Nov 30  2014 db2prereqcheck
-r-xr-xr-x. 1 bin bin 5641 Nov 30  2014 db2setup
[root@localhost expc]#
```



4、执行./db2setup,图形化界面安装



5、按照如下的过程进行安装DB2 v10.5数据库







DB2 Setup - DB2 Express-C

1. Introduction
2. Software License Agreement
3. Installation type
4. Installation action
5. Installation directory
6. DAS user
7. Instance setup
8. Instance-owning user
9. Fenced user
10. Summary

Select the installation directory

The DB2 Setup wizard installs DB2 Express-C in the following directory. To select a different directory, type the path or click the ellipsis button and select another directory.

Directory: ...

Space required: 945 MB
Space available: 200071 MB

◀ Back Next ▶ Finish Cancel Help

DB2 Setup - DB2 Express-C

1. Introduction
2. Software License Agreement
3. Installation type
4. Installation action
5. Installation directory
6. DAS user
7. Instance setup
8. Instance-owning user
9. Fenced user
10. Summary

Set user information for the DB2 Administration Server

The DB2 Administration Server (DAS) runs on your computer to provide support required by the DB2 tools. A user with a minimal set of privileges is required to run the DAS. Specify the required user information for the DAS.

☒ New user

User name:

UID: ☒ Use default UID

Group name: 输入密码: 123456

GID: ☒ Use default GID

Password:

Confirm password:

Home directory: ...

☐ Existing user



User name:



☐ Create DAS user later

选择管理用户所在目录

◀ Back Next ▶ Finish Cancel Help

注：选择安装完DB2 再进行创建实例





6、在数据库服务器上创建用户组

创建组db2iadm1（实例管理组）,db2fgrp1（DB2 fencing管理组）和dasadm1（数据库管理员用户组），其中dasadm1组在安装数据库时已经创建，我们只需要创建db2iadm1和db2fgrp组


```
groupadd -g 206 db2iadm1
groupadd -g 203 db2fgrp1
```

7、在数据库服务器上创建用户

创建用户db2inst1(实例管理用户)、db2fenc1(DB2 fencing 管理用户)和dasusr1(数据库管理员用户)，其中dasusr1用户在安装数据库时已经创建，我们只需要创建db2inst1和db2fenc用户

```
useradd -g db2iadml -u 209 -d /home/DB2/db2inst1 db2inst1
useradd -g db2fgrp1 -u 210 -d /home/DB2/db2fenc1 db2fenc1
```

```
[root@localhost ~]# groupadd -g 206 db2iadml
[root@localhost ~]# groupadd -g 203 db2fgrp1
[root@localhost ~]# useradd -g db2iadml -u 209 -d /home/DB2/db2inst1 db2inst1
Creating mailbox file: File exists
[root@localhost ~]# useradd -g db2fgrp1 -u 210 -d /home/DB2/db2fenc1 db2fenc1
Creating mailbox file: File exists
[root@localhost ~]#
```



8、添加用户的密码

添加用户db2inst1(实例管理用户)、db2fenc1(DB2 fencing 管理用户)和dasusr1(数据库管理员用户)的密码，其中dasusr1用户的密码在安装数据库时已经添加，我们只需要添加db2inst1和db2fenc用户的密码。

```
# 添加实例的用户密码
passwd db2inst1
# 123456

# 添加受防护的用户密码
passwd db2fenc1
# 123456
```

```
[root@localhost ~]# passwd db2inst1
Changing password for user db2inst1.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[root@localhost ~]#
[root@localhost ~]# passwd db2fenc1
Changing password for user db2fenc1.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[root@localhost ~]#
```

9、检查用户组和用户是否创建成功

```
# 用户组：
more /etc/group | grep db2
# 用户：
more /etc/passwd | grep db2
```

```
[root@localhost ~]# more /etc/group | grep db2
db2iadml:x:206:
db2fgrp1:x:203:
[root@localhost ~]# more /etc/passwd | grep db2
db2inst1:x:209:206::/home/DB2/db2inst1:/bin/bash
db2fenc1:x:210:203::/home/DB2/db2fenc1:/bin/bash
[root@localhost ~]#
```

10、创建实例

db2icrt创建的是实例，这里db2fenc1指定db2inst1为它的防护用户，而db2inst1为一实例用户。

```
cd /opt/ibm/db2/v10.5/instance/

# 创建DB2实例
./db2icrt -u db2fenc1 db2inst1
```

```
[root@localhost ~]# cd /opt/ibm/db2/V10.5/instance/
[root@localhost instance]#
[root@localhost instance]# ./db2icrt -u db2fenc1 db2inst1
DBI1446I The db2icrt command is running.

DB2 installation is being initialized.

Total number of tasks to be performed: 4
Total estimated time for all tasks to be performed: 309 second(s)

Task #1 start
Description: Setting default global profile registry variables
Estimated time 1 second(s)
Task #1 end

Task #2 start
Description: Initializing instance list
Estimated time 5 second(s)
Task #2 end

Task #3 start
Description: Configuring DB2 instances
Estimated time 300 second(s)
Task #3 end

Task #4 start
Description: Updating global profile registry
Estimated time 3 second(s)
Task #4 end

The execution completed successfully.

For more information see the DB2 installation log at "/tmp/db2icrt.log.17067".
DBI1070I Program db2icrt completed successfully.

[root@localhost instance]#
```

11、配置DB2实例

```
cd /opt/ibm/db2/V10.5/instance/
```

设置DB2自启动(注:依然在root用户下), 设置对db2inst1在Linux启动时自动启动。

```
./db2iauto -on db2inst1
```

修改网络服务端(注:在db2inst1用户下)

修改DB2的服务端口为50000,默认情况下端口也是50000

```
su - db2inst1
```

```
db2 update dbm cfg using SVCENAME 50000
```

修改DB2连接方式为TCP/IP

修改DB2连接方式为TCPIP,然后可通过JDBC、ODBC等访问本DB2服务器上的数据库,安装了DB2客户端的其它机器也可访问数据库

```
db2set DB2COMM=TCPIP
```

```
[root@localhost instance]# ./db2iauto -on db2inst1
[root@localhost instance]# su - db2inst1
Last login: Tue Jun  2 09:14:07 CST 2020 on pts/0
[db2inst1@localhost ~]$ db2 update dbm cfg using SVCENAME 50000
DB20000I  The UPDATE DATABASE MANAGER CONFIGURATION command completed
successfully.
[db2inst1@localhost ~]$ db2set DB2COMM=TCPIP
[db2inst1@localhost ~]$ █
```

12、查看DB2

```
su - db2inst1
```

查看DB2许可证情况

```
db2licm -l
```

查看DB2版本

```
db2level
```

检查相关参数

```
db2set -all
```

```
[db2inst1@localhost ~]$ db2licm -l
Product name:          "DB2 Express-C"
License type:          "Unwarranted"
Expiry date:           "Permanent"
Product identifier:    "db2expc"
Version information:   "10.5"
Max number of CPUs:    "2"
Max amount of memory (GB): "16"
Enforcement policy:    "Soft Stop"
```

```
[db2inst1@localhost ~]$ db2level
DB21085I  This instance or install (instance name, where applicable:
"db2inst1") uses "64" bits and DB2 code release "SQL10055" with level
identifier "0606010E".
Informational tokens are "DB2 v10.5.0.5", "s141128", "IP23633", and Fix Pack
"5".
Product is installed at "/opt/ibm/db2/V10.5".
```

```
[db2inst1@localhost ~]$ db2set -all
[i] DB2COMM=TCPIP
[i] DB2AUTOSTART=YES
[g] DB2_COMPATIBILITY_VECTOR=MYS
[g] DB2SYSTEM=localhost.localdomain
[g] DB2INSTDEF=db2inst1
[g] DB2ADMINSERVER=dasusr1
[db2inst1@localhost ~]$ █
```

13、启动/停止实例

```
su - db2inst1
# 启动
db2start

# 停止
db2stop
# 强制停止
db2stop force

# 停止所有数据库应用程序
db2 force application all
```

14、在数据库服务器上创建数据库 test

```
db2 create database test
```

```
[db2inst1@localhost ~]$ db2start
SQL1063N  DB2START processing was successful.
[db2inst1@localhost ~]$ db2 create database test
DB20000I  The CREATE DATABASE command completed successfully.
```

15、连接数据库test

```
# 指定用户和密码
db2 connect to test user db2inst1 using 123456
```

```
[db2inst1@localhost ~]$ db2 connect to test user db2inst1 using 123456

Database Connection Information

Database server          = DB2/LINUX8664 10.5.5
SQL authorization ID     = DB2INST1
Local database alias     = TEST

[db2inst1@localhost ~]$
```

16、使用DBeaver连接DB2

首先防火墙开启端口50000（上面db2inst1实例指定的端口）

```
# 开放50000端口
firewall-cmd --zone=public --add-port=50000/tcp --permanent

# 开启或关闭端口需要重启，重启后配置立即生效
firewall-cmd --reload


#查看所有开放的端口
firewall-cmd --list-ports

# 查看防火墙状态
```

```
systemctl status firewalld
# 停止防火墙
systemctl stop firewalld
# 开启防火墙
systemctl start firewalld
```

使用DBeaver工具，如下：






注意：需要下载驱动并添加（百度云下载后添加，或者让DBeaver自己下载）

百度云下载：

链接：<https://pan.baidu.com/s/1cM8wiLIDxexMOvujk7f4KQ>

提取码：z162



三、卸载DB2

1、删除db2数据库

```
# Remove DB[首先删除数据库]  
su - db2inst1  
db2start  
db2 list db directory  
db2 drop db <db name>
```

```

[db2inst1@localhost ~]$ db2start
SQL1063N DB2START processing was successful.
[db2inst1@localhost ~]$
[db2inst1@localhost ~]$
[db2inst1@localhost ~]$ ps -ef|grep db2
root      1184   1061   0 16:34 pts/0    00:00:00 su - db2inst1
db2inst1  1185   1184   0 16:34 pts/0    00:00:00 -bash
db2inst1  1327     1   0 16:35 pts/0    00:00:00 /home/DB2/db2inst1/sqllib/bin/db2bp 1185A209 5 A
root      1347     1   0 16:36 pts/0    00:00:00 db2wdog
db2inst1  1349   1347   4 16:36 pts/0    00:00:00 db2sysc
root      1355   1347   0 16:36 pts/0    00:00:00 db2ckpwd
root      1356   1347   0 16:36 pts/0    00:00:00 db2ckpwd
root      1357   1347   0 16:36 pts/0    00:00:00 db2ckpwd
db2inst1  1359   1347   1 16:36 pts/0    00:00:00 db2vend (PD Vendor Process - 1)
db2inst1  1367   1347   3 16:36 pts/0    00:00:00 db2acd  ,0,0,0,1,0,0,0,0002,1,0,995bc4,14,1e014,2,0,1,41fc0,0x210000000,0x210000000,1600000,1800e,2,20012
db2inst1  1371   1185   0 16:36 pts/0    00:00:00 ps -ef
db2inst1  1372   1185   0 16:36 pts/0    00:00:00 grep --color=auto db2
[db2inst1@localhost ~]$
[db2inst1@localhost ~]$
[db2inst1@localhost ~]$ db2 list db directory

System Database Directory

Number of entries in the directory = 1

Database 1 entry:

Database alias           = TEST
Database name            = TEST
Local database directory = /home/DB2/db2inst1
Database release level   = 10.00
Comment                  =
Directory entry type     = Indirect
Catalog database partition number = 0
Alternate server hostname =
Alternate server port number =

[db2inst1@localhost ~]$ db2 drop db TEST
DB20000I The DROP DATABASE command completed successfully.
[db2inst1@localhost ~]$ db2 list db directory
SQL1057W The system database directory is empty.  SQLSTATE=01606

```

2、停止db2数据库并删除db2进程

```

# 查看db2进程
ps -ef|grep db2

```

```

[db2inst1@localhost ~]$ ps -ef|grep db2
root      468     1   0 16:11 pts/0    00:00:00 db2wdog
db2inst1  470   468   0 16:11 pts/0    00:00:03 db2sysc
root      476   468   0 16:11 pts/0    00:00:00 db2ckpwd
root      477   468   0 16:11 pts/0    00:00:00 db2ckpwd
root      478   468   0 16:11 pts/0    00:00:00 db2ckpwd
db2inst1  480   468   0 16:11 pts/0    00:00:00 db2vend (PD Vendor Process - 1)
db2inst1  488   468   0 16:11 pts/0    00:00:00 db2acd  ,0,0,0,1,0,0,0,0002,1,0,995bc4,14,1e014,2,0,1,41fc0,0x210000000,0x210000000,1600000,1003d,2,10039
db2fenc1  653   468   0 16:16 pts/0    00:00:00 db2fmp ( ,1,0,0,0,0,0,0,0002,1,0,995bc4,14,1e014,2,0,1,61fc0,0x210000000,0x210000000,1600000,1003d,2,18040
db2inst1  701  32566   0 16:18 pts/0    00:00:00 ps -ef
db2inst1  702  32566   0 16:18 pts/0    00:00:00 grep --color=auto db2
dasusr1   23648   1   0 16:00 ?        00:00:00 /home/DB2/dasusr1/das/adm/db2dasrmm
root      32565  2492   0 16:08 pts/0    00:00:00 su - db2inst1
db2inst1  32566  32565   0 16:08 pts/0    00:00:00 -bash
db2inst1  32693   1   0 16:08 pts/0    00:00:00 /home/DB2/db2inst1/sqllib/bin/db2bp 32566A209 5 A

```

```

# 切换到db2inst1用户
su - db2inst1

# 停止数据库
db2stop force

# 切换到dasusr1管理用户
su - dasusr1

# 停止DB2管理服务
db2admin stop

```

```

[db2inst1@localhost ~]$ db2stop force
SQL1064N DB2STOP processing was successful.
[db2inst1@localhost ~]$
[db2inst1@localhost ~]$
[db2inst1@localhost ~]$ ps -ef|grep db2
db2inst1  714  32566   0 16:18 pts/0    00:00:00 ps -ef
db2inst1  715  32566   0 16:18 pts/0    00:00:00 grep --color=auto db2
dasusr1   23648   1   0 16:00 ?        00:00:00 /home/DB2/dasusr1/das/adm/db2dasrmm
root      32565  2492   0 16:08 pts/0    00:00:00 su - db2inst1
db2inst1  32566  32565   0 16:08 pts/0    00:00:00 -bash
db2inst1  32693   1   0 16:08 pts/0    00:00:00 /home/DB2/db2inst1/sqllib/bin/db2bp 32566A209 5 A
[db2inst1@localhost ~]$ su - dasusr1
Password:
Last login: Mon Jun  1 16:00:06 CST 2020 on pts/1
[dasusr1@localhost ~]$ db2admin stop
SQL4407W The DB2 Administration Server was stopped successfully.
[dasusr1@localhost ~]$
[dasusr1@localhost ~]$
[dasusr1@localhost ~]$ ps -ef|grep db2
dasusr1    814    717   0 16:20 pts/0    00:00:00 grep --color=auto db2
root       32565  2492   0 16:08 pts/0    00:00:00 su - db2inst1
db2inst1   32566  32565   0 16:08 pts/0    00:00:00 -bash
db2inst1   32693   1   0 16:08 pts/0    00:00:00 /home/DB2/db2inst1/sqllib/bin/db2bp 32566A209 5 A

```

```
# 删除db2进程
su root
kill -9 `ps aux|grep db2 | grep -v 'grep db2' | awk '{print $2}'`
# 查看
ps -ef|grep db2
```

```
[root@localhost db2inst1]# kill -9 `ps aux|grep db2 | grep -v 'grep db2' | awk '{print $2}'`
bash: kill: (1054) - No such process
[root@localhost db2inst1]# Killed
```

```
[root@localhost ~]# ps -ef|grep db2
root      1104   1061   0 16:26 pts/0    00:00:00 grep --color=auto db2
[root@localhost ~]#
```

3、删除实例、das、卸载

```
# Remove Instance【删除实例】
su - root
cd <db2 dir>/instance # 默认/opt/ibm/db2/v10.5/instance/
./db2ilist
./db2idrop <instance name>

# Remove das【删除das】
(1)su - root
(2)cd <db2 dir>/instance # 默认/opt/ibm/db2/v10.5/instance/
(3)./daslist
(4)./dasdrop <das user>

# Uninstall【卸载】
(1)su - root
(2)cd <db2 dir>/install # 默认/opt/ibm/db2/v10.5/install/
(3)./db2_deinstall -a
```

```
[root@localhost instance]# ./db2ilist
db2inst1
[root@localhost instance]# ./db2idrop db2inst1
DBI1446I The db2idrop command is running.

DB2 installation is being initialized.

Total number of tasks to be performed: 2
Total estimated time for all tasks to be performed: 305 second(s)

Task #1 start
Description: Initializing instance list
Estimated time 5 second(s)
Task #1 end

Task #2 start
Description: Configuring DB2 instances
Estimated time 300 second(s)
Task #2 end

The execution completed successfully.

For more information see the DB2 installation log at "/tmp/db2idrop.log.3860".
DBI1070I Program db2idrop completed successfully.

[root@localhost instance]# ./db2ilist
[root@localhost instance]#
```

```
[root@localhost instance]# ./daslist
dasusr1
[root@localhost instance]# ./dasdrop dasusr1
DBI1070I Program dasdrop completed successfully.

[root@localhost instance]# ./daslist
[root@localhost instance]#
```

```
[root@localhost install]# ./db2_deinstall -a
DBI1016I Program db2_deinstall is performing uninstallation. Please
wait.

The execution completed successfully.

For more information see the DB2 uninstallation log at
"/tmp/db2_deinstall.log.9372".
[root@localhost install]#
```

4、删除db2数据库相关文件

```
# 删除db2用户，删除db2相关数据
vim /etc/passwd
# 进入文件后，输入/db2，按enter键查找db2相关配置，按n跳转到下一个
# 删除下图中的三行关于db2的配置
# 选中到某一行，输入dd，即可删除当前行
# 删除成功后，按i键进入输入模式
# 按Esc键后，输入:wq!即可保存退出
```

```
dasusr1:x:1000:101::/home/DB2/dasusr1:/bin/bash
db2inst1:x:209:206::/home/DB2/db2inst1:/bin/bash
db2fenc1:x:210:203::/home/DB2/db2fenc1:/bin/bash
/db2
```

```
# 删除db2组
vim /etc/group
# 操作同上，删除下图中的三行关于db2的配置
```

```
dasadm1:x:101:db2inst1
db2iadm1:x:206:
db2fgrp1:x:203:
/db2
```

```
# 删除db2端口
vim /etc/services
# 操作同上，未找到相关db2配置不做操作
# 按i键进入输入模式，按Esc键后，输入:q!即可不保存退出
```

```
# 删除db2相关用户实例
vim /etc/shadow
# 操作同上，删除下图中的三行关于db2的配置
```

```
dasusr1:05zjTovHJM7BY:18414:0:99999:7:::
db2inst1:$6$VpkowM9b$bv9j4RoGZbbeL7Unx0yUjvs19gh/6g7EBNP9vIgtq4FD2jVTIDVE10jEGHt6PVC/IEfqj3YUzwUT0NLgPaTz5/:18414:0:99999:7:::
db2fenc1:$6$wfbgKht9$HbLCnMlyrqbRX2sa14TJq8s4qc1/7w2xzMyC80Ix4ReDmUz9v7bNt4YHTwL7naNHLwysCHFFxL1.z0NaJYarQ0:18414:0:99999:7:::
/db2
```

```
# 删除db2相关目录
cd /var
ll
rm -rf db2*
```

```
[root@localhost install]# cd /var/
[root@localhost var]# ll
total 20
drwxr-xr-x. 2 root root 18 Jun 1 2020 account
drwxr-xr-x. 2 root root 6 Apr 11 2018 adm
drwxr-xr-x. 13 root root 4096 Jun 1 2020 cache
drwxr-xr-x. 2 root root 6 Apr 2 21:27 crash
drwxr-xr-x. 3 root root 32 May 29 00:43 db
drwxr-xr-x. 2 root root 63 Jun 1 16:48 db2
drwxr-xr-x. 2 root root 17 Apr 11 2018 empty
drwxr-xr-x. 2 root root 6 Apr 11 2018 games
drwxr-xr-x. 2 root root 6 Apr 11 2018 gopher
drwxr-xr-x. 3 root root 17 Apr 1 11:06 kerberos
drwxr-xr-x. 63 root root 4096 Jun 1 2020 lib
drwxr-xr-x. 2 root root 6 Apr 11 2018 local
lrwxrwxrwx. 1 root root 11 May 29 00:20 lock -> ../run/lock
drwxr-xr-x. 19 root root 4096 Jun 1 15:53 log
lrwxrwxrwx. 1 root root 10 May 29 00:43 mail -> spool/mail
drwxr-xr-x. 2 root root 6 Apr 11 2018 nis
drwxr-xr-x. 2 root root 6 Apr 11 2018 opt
drwxr-xr-x. 2 root root 6 Apr 11 2018 preserve
lrwxrwxrwx. 1 root root 6 May 29 00:20 run -> ../run
drwxr-xr-x. 12 root root 4096 Jun 1 2020 spool
drwxr-xr-x. 4 root root 26 Jun 1 2020 target
drwxrwxrwt. 8 root root 4096 Jun 1 15:59 tmp
drwxr-xr-x. 3 root root 16 May 29 00:21 var
drwxr-xr-x. 2 root root 6 Apr 11 2018 yp
[root@localhost var]# rm -rf db2*
```

```
# 删除db2相关文件
cd /tmp
ll
rm -rf db2*
rm -rf dasrct*
```

```
# 删除dasusr1, db2inst1, db2fenc1文件夹
cd /home/DB2
rm -rf dasusr1
rm -rf db2inst1
rm -rf db2fenc1
```

```
[root@localhost tmp]# cd /home/DB2
[root@localhost DB2]#
[root@localhost DB2]#
[root@localhost DB2]# ll
total 4
drwxr-xr-x 5 1000 101 121 Jun 1 16:47 dasusr1
drwx----- 3 210 203 74 Jun 1 16:03 db2fenc1
drwxr-xr-x 8 209 206 140 Jun 1 16:45 db2inst1
drwxr-xr-x. 3 root root 4096 Nov 30 2014 expc
[root@localhost DB2]# rm -rf dasusr1
[root@localhost DB2]# rm -rf db2inst1
[root@localhost DB2]# rm -rf db2fenc1
[root@localhost DB2]# ll
total 4
drwxr-xr-x. 3 root root 4096 Nov 30 2014 expc
[root@localhost DB2]#
```

```
# 删除db2安装目录和rsp文件
```

```
cd /opt
```

```
rm -rf ibm/
```

```
cd /root
```

```
rm -rf db2expc.rsp
```

```
[root@localhost DB2]# cd /opt/
[root@localhost opt]#
[root@localhost opt]# ll
total 0
drwxr-xr-x. 3 root root 16 Jun  1 15:59 ibm
drwxr-xr-x. 2 root root  6 Oct 31  2018 rh
[root@localhost opt]# rm -rf ibm/
[root@localhost opt]# ll
total 0
drwxr-xr-x. 2 root root 6 Oct 31  2018 rh
[root@localhost opt]#
[root@localhost opt]#
[root@localhost opt]# cd /root/
[root@localhost ~]# ll
total 12
-rw-----. 1 root root 1422 May 29 00:23 anaconda-ks.cfg
-rw-r--r--. 1 root root 1607 Jun  1 15:59 db2expc.rsp
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Desktop
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Documents
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Downloads
drwxr-xr-x. 2 root root 23 Jun  1 13:44 isus
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Music
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Pictures
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Public
-rw-----. 1 root root  16 Jun  1  2020 root
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Templates
drwxr-xr-x. 2 root root  6 Jun  1 12:04 Videos
[root@localhost ~]# rm -rf db2expc.rsp
[root@localhost ~]#
```

到这里就卸载成功了，可以重新安装了。