

# 青岛冠宏包装技术有限公司

Metal shielding bag(metal shield) 无尘产品专用  
金属/屏蔽袋出货检验记录

Customer Name: 客户名称:		青岛新核芯科技有限公司	Date/ 检验日期: 2024/10/07	Date/ 生产日期: 2024-9-28	产地: /	订单号 码:	Quantity of order/ 订单(PCS):	
Customer P/N 客户料号: TA03-0015G		Production batch number /生产批号:GH20241008030015G	Shipping date/ 出货日期 2024/10/08	Material type /材质: PET/AL/PE/CPE	Quantity completion /生产数量(PCS): 5000 PCS	Spot-check quantity/抽检数量 (PCS): 200 PCS		
Inspection items/检验项目	Specification/要求		Inspection tools/检验工具	Inspection findings/检验结果		Conclusion/判定		
Material Consistency/规格	confirm to shop order/材质结构与制令 单一致		Visual inspection/目检	OK		OK		
Appearance/外观	no obvious bubbles/无明显气泡		Visual inspection/目检	OK		OK		
	no compound layered/无分层		Visual inspection/目检	OK		OK		
	no obvious folds/无明显折皱		Visual inspection/目检	OK		OK		
	no filth, no foreign matters on surface /表面无脏污、无异物		Visual inspection/目检	OK		OK		
	no scratch, no hole, no breakage/无划 伤、穿孔、破损		Visual inspection/目检	OK		OK		
	No bubble, sealing side is flat /无 气泡、封边平整		Visual inspection/目检	OK		OK		
	printing confirm to CAD drawing(including color, style, situation and so on) 印刷(颜 色、式样、位置)与CAD一致		Visual inspection/目检	/		/		
Size/尺寸 (Overall size/长度、宽 度)	依图纸要求		steel rule/钢尺	MIN	Average	MAX	OK	
				120	120±5	124		
Thickness/厚度	edgescaling width/封边尺寸: 5 mm ±2mm		steel rule/钢尺	230	230±5	235		
	0.12mm ±10%			5	5±2	6	OK	
Anti static 防静电 $\geq \Omega$	1*10Ω6-1*10Ω11		micrometer/千分尺	3.7*10Ω10			OK	
Transverse tensile force 横向拉伸 $\geq N$	130			223.744			OK	
Longitudinal tensile force 纵向拉伸 $\geq N$	120			163.74			OK	
Transverse tensile strength 横向抗拉强度 $\geq Mpa$	44			60.471			OK	
Longitudinal tensile strength 纵向抗拉强度 $\geq Mpa$	40			44.254			OK	
Heat seal capacity/热封 性能, N	90		electronic tensile machine /电子拉力机	159.673			OK	
Vacuum test/真空测试	Vacuum no leakage抽真空无漏气现象			OK			OK	
WVTR/水汽透过率	$\leq 0.002g/100in^2*24h$		dust particle detector/尘 埃粒子测试仪	0.0003g/100in^2*24h			OK	
Electrostatic shielding/静电屏蔽	<20nJ			13.8nJ			OK	
particle/袋内颗粒数 (粒)	0.3um ≤ 150			40			OK	
	0.5um ≤ 80			30			OK	
	1.0um ≤ 50			20			OK	
	5.0um ≤ 5			0			OK	
Sliding sideways experiment/侧漏实验	No sliding sideways/无侧漏现象		Leakage test fluid/测漏液	OK			OK	
Quantity Consistency/数量	confirm to Delivery Order/与送货单 一致		Visual check/目检	OK			OK	
barcode/label Consistency/标签	confirm to real object/与实物一致		Visual check/目检	OK			OK	
Non-conforming description 不良描述	无							
Judgement/判定	<input checked="" type="checkbox"/> Accept			<input type="checkbox"/> Reject				
Checker/检验员:	杜英丹		Audited by/审核:					