CUSTOMER COPY



ROHS)

REV.	DESCRIPTION	BY/DATE	CHECK/DATE	APPROVED/DATE
1.0	Ori.	Jerry Aug,10,05°		



1) Material

Shell: Copper Alloy Contacts : Copper Alloy

Insulator: Thermoplastic, G.F. UL94-V0

2) Environmental

-55℃~+105℃

3) Electrical


Current Rating: 1.0 Amp

Dielectric Strength: 500Vac for 1 minute Insulation Resistance: 500MΩ min. at 500VDC

4) Finish


Refer to Order Information






7.70

7.90





PCB Layout Component side view

General	Tolerance	Angle 1	derance		Octe			
.X	±0.35	×	±1.0°	Jerry /	4 <i>ug</i> ,10,05°	_	OMOSS ELECTRONIC CO., L'	777
_XX	±0.25	XXC	±0.5°	Design	Date	4F., No. 11, Churg-Hain St., ShuLin 238, Taipai, Tairan R.O.C.		
.xxx	±0.15	2000	±0.2°		Aug,10,05'			
SHEET 1/1 FINISH See Notes			CHK Date		USB CONNECTOR			
					USB 6PIN FEMALE NINI & PCB END RIGHT ANGLE DIF			
Scale N/A Unit mm		APPR Date	Date	Dwg. No	A0275	SZE A.		
		•		1		Fort No.	USB-5FCRSXXXXX	EV 1,0

Drawing is subject to change without notice. Any updated information required, please contact with our sales dept.